



Exercise 3.3: Configure Probes

When large datasets need to be loaded or a complex application launched prior to client access, a `readinessProbe` can be used. The pod will not become available to the cluster until a test is met and returns a successful exit code. Both `readinessProbes` and `livenessProbes` use the same syntax and are identical other than the name. Where the `readinessProbe` is checked prior to being ready, then not again, the `livenessProbe` continues to be checked.

There are three types of liveness probes: a command returns a zero exit value, meaning success, an HTTP request returns a response code in the 200 to 399 range, and the third probe uses a TCP socket. In this example we'll use a command, `cat`, which will return a zero exit code when the file `/tmp/healthy` has been created and can be accessed.

1. Edit the YAML deployment file and add the stanza for a `readinessprobe`. Remember that when working with YAML whitespace matters. Indentation is used to parse where information should be associated within the stanza and the entire file. Do not use tabs. If you get an error about validating data, check the indentation. It can also be helpful to paste the file to this website to see how indentation affects the JSON value, which is actually what Kubernetes ingests: <https://www.json2yaml.com/>

```
student@ckad-1:~/app1$ vim simpleapp.yaml
```

YAML

simpleapp.yaml

```
1  ....
2      spec:
3          containers:
4              - image: 10.111.235.60:5000/simpleapp:latest
5                imagePullPolicy: Always
6                name: simpleapp
7                readinessProbe:          #<--This line and next five
8                  periodSeconds: 5
9                  exec:
10                     command:
11                         - cat
12                         - /tmp/healthy
13                 resources: {}
14  ....
```

2. Delete and recreate the `try1` deployment.

```
student@ckad-1:~/app1$ kubectl delete deployment try1
```

```
deployment.extensions "try1" deleted
```

```
student@ckad-1:~/app1$ kubectl create -f simpleapp.yaml
```

```
deployment.extensions/try1 created
```

3. The new `try1` deployment should reference six pods, but show zero available. They are all missing the `/tmp/healthy` file.

```
student@ckad-1:~/app1$ kubectl get deployment
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE
nginx	1/1	1	1	19m
registry	1/1	1	1	19m
try1	0/6	6	0	15s

4. Take a closer look at the pods. Choose one of the try1 pods as a test to create the health check file.

```
student@ckad-1:~/app1$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-g7lnk	1/1	Running	1	40m
registry-795c6c8b8f-7vwdn	1/1	Running	1	40m
try1-9869bdb88-2wfnr	0/1	Running	0	26s
try1-9869bdb88-6bkn1	0/1	Running	0	26s
try1-9869bdb88-786v8	0/1	Running	0	26s
try1-9869bdb88-gmvs4	0/1	Running	0	26s
try1-9869bdb88-lfvlx	0/1	Running	0	26s
try1-9869bdb88-rtchc	0/1	Running	0	26s

5. Run the bash shell interactively and touch the /tmp/healthy file.

```
student@ckad-1:~/app1$ kubectl exec -it try1-9869bdb88-rtchc -- /bin/bash

root@try1-9869bdb88-rtchc:/# touch /tmp/healthy

root@try1-9869bdb88-rtchc:/# exit

exit
```

6. Wait at least five seconds, then check the pods again. Once the probe runs again the container should show available quickly. The pod with the existing /tmp/healthy file should be running and show 1/1 in a READY state. The rest will continue to show 0/1.

```
student@ckad-1:~/app1$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-g7lnk	1/1	Running	1	44m
registry-795c6c8b8f-7vwdn	1/1	Running	1	44m
try1-9869bdb88-2wfnr	0/1	Running	0	4m
try1-9869bdb88-6bkn1	0/1	Running	0	4m
try1-9869bdb88-786v8	0/1	Running	0	4m
try1-9869bdb88-gmvs4	0/1	Running	0	4m
try1-9869bdb88-lfvlx	0/1	Running	0	4m
try1-9869bdb88-rtchc	1/1	Running	0	4m

7. Touch the file in the remaining pods. Consider using a **for** loop, as an easy method to update each pod. Note the > shown in the output represents the secondary prompt, you would not type in that character

```
student@ckad-1:~$ for name in try1-9869bdb88-2wfnr try1-9869bdb88-6bkn1 \
> try1-9869bdb88-786v8 try1-9869bdb88-gmvs4 try1-9869bdb88-lfvlx
> do
> kubectl exec $name touch /tmp/healthy
> done
```

8. It may take a short while for the probes to check for the file and the health checks to succeed.

```
student@ckad-1:~/app1$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-g7lnk	1/1	Running	1	1h
registry-795c6c8b8f-7vwdn	1/1	Running	1	1h
try1-9869bdb88-2wfnr	1/1	Running	0	22m
try1-9869bdb88-6bkn1	1/1	Running	0	22m
try1-9869bdb88-786v8	1/1	Running	0	22m
try1-9869bdb88-gmvs4	1/1	Running	0	22m
try1-9869bdb88-lfvlx	1/1	Running	0	22m
try1-9869bdb88-rtchc	1/1	Running	0	22m

9. Now that we know when a pod is healthy, we may want to keep track that it stays healthy, using a `livenessProbe`. You could use one probe to determine when a pod becomes available and a second probe, to a different location, to ensure ongoing health.

Edit the deployment again. Add in a `livenessProbe` section as seen below. This time we will add a `Sidecar` container to the pod running a simple application which will respond to port 8080. Note that the dash (-) in front of the name. Also `goproxy` is indented the same number of spaces as the - in front of the `image:` line for `simpleapp` earlier in the file. In this example that would be seven spaces

```
student@ckad-1:~/app1$ vim simpleapp.yaml
```



simpleapp.yaml

```
1  ....
2      terminationMessagePath: /dev/termination-log
3      terminationMessagePolicy: File
4      - name: goproxy          #<-- Add lines from here
5        image: k8s.gcr.io/goproxy:0.1
6        ports:
7          - containerPort: 8080
8        readinessProbe:
9          tcpSocket:
10             port: 8080
11             initialDelaySeconds: 5
12             periodSeconds: 10
13        livenessProbe:          #<-- This line is 9 spaces indented, fyi
14          tcpSocket:
15             port: 8080
16             initialDelaySeconds: 15
17             periodSeconds: 20    #<-- to here
18        dnsPolicy: ClusterFirst
19        restartPolicy: Always
20  ....
```

10. Delete and recreate the deployment.

```
student@ckad-1:~$ kubectl delete deployment try1
deployment.extensions "try1" deleted

student@ckad-1:~$ kubectl create -f simpleapp.yaml
deployment.extensions/try1 created
```

11. View the newly created pods. You'll note that there are two containers per pod, and only one is running. The new `simpleapp` containers will not have the `/tmp/healthy` file, so they will not become available until we touch the `/tmp/healthy` file again. We could include a command which creates the file into the container arguments. The output below shows it can take a bit for the old pods to terminate.

```
student@ckad-1:~$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-g7lnk	1/1	Running	1	13h
registry-795c6c8b8f-7vwdn	1/1	Running	1	13h
try1-76cc5ffcc6-4rjvh	1/2	Running	0	3s
try1-76cc5ffcc6-bk5f5	1/2	Running	0	3s
try1-76cc5ffcc6-d8n5q	0/2	ContainerCreating	0	3s
try1-76cc5ffcc6-mm6tw	1/2	Running	0	3s
try1-76cc5ffcc6-r9q5n	1/2	Running	0	3s
try1-76cc5ffcc6-tx4dz	1/2	Running	0	3s
try1-9869bdb88-2wfnr	1/1	Terminating	0	12h

```

try1-9869bdb88-6bkn1      1/1      Terminating      0      12h
try1-9869bdb88-786v8      1/1      Terminating      0      12h
try1-9869bdb88-gmvs4      1/1      Terminating      0      12h
try1-9869bdb88-lfvlx      1/1      Terminating      0      12h
try1-9869bdb88-rtchc      1/1      Terminating      0      12h

```

12. Create the health check file for the readinessProbe. You can use a **for** loop again for each action, with updated pod names. As there are now two containers in the pod, you should include the container name for which one will execute the command. If no name is given, it will default to the first container. Depending on how you edited the YAML file `try1` should be the first pod and `goproxy` the second. To ensure the correct container is updated, add **-c simpleapp** to the **kubectl** command. Your pod names will be different. Use the names of the newly started containers from the **kubectl get pods** command output. Note the `>` character represents the secondary prompt, you would not type in that character.

```

student@ckad-1:~$ for name in try1-76cc5ffcc6-4rjvh \
> try1-76cc5ffcc6-bk5f5 try1-76cc5ffcc6-d8n5q \
> try1-76cc5ffcc6-mm6tw try1-76cc5ffcc6-r9q5n \
> try1-76cc5ffcc6-tx4dz
> do
> kubectl exec $name -c simpleapp touch /tmp/healthy
> done

<output_omitted>

```

13. In the next minute or so the Sidecar container in each pod, which was not running, will change status to Running. Each should show 2/2 containers running.

```

student@ckad-1:~$ kubectl get pods

NAME                                READY   STATUS    RESTARTS   AGE
nginx-6b58d9cdfd-g7lnk             1/1     Running   1          13h
registry-795c6c8b8f-7vwdn         1/1     Running   1          13h
try1-76cc5ffcc6-4rjvh              2/2     Running   0          3s
try1-76cc5ffcc6-bk5f5              2/2     Running   0          3s
try1-76cc5ffcc6-d8n5q              2/2     Running   0          3s
try1-76cc5ffcc6-mm6tw              2/2     Running   0          3s
try1-76cc5ffcc6-r9q5n              2/2     Running   0          3s
try1-76cc5ffcc6-tx4dz              2/2     Running   0          3s

```

14. View the events for a particular pod. Even though both containers are currently running and the pod is in good shape, note the events section shows the issue.

```

student@ckad-1:~/app1$ kubectl describe pod try1-76cc5ffcc6-tx4dz | tail

Normal    SuccessfulMountVolume  9m                                kubelet, ckad-1-lab-x6dj
MountVolume.SetUp succeeded for volume "default-token-jf69w"
Normal    Pulling                9m                                kubelet, ckad-1-lab-x6dj
pulling image "10.108.143.90:5000/simpleapp"
Normal    Pulled                 9m                                kubelet, ckad-1-lab-x6dj
Successfully pulled image "10.108.143.90:5000/simpleapp"
Normal    Created               9m                                kubelet, ckad-1-lab-x6dj
Created container
Normal    Started               9m                                kubelet, ckad-1-lab-x6dj
Started container
Normal    Pulling                9m                                kubelet, ckad-1-lab-x6dj
pulling image "k8s.gcr.io/goproxy:0.1"
Normal    Pulled                 9m                                kubelet, ckad-1-lab-x6dj
Successfully pulled image "k8s.gcr.io/goproxy:0.1"
Normal    Created               9m                                kubelet, ckad-1-lab-x6dj
Created container
Normal    Started               9m                                kubelet, ckad-1-lab-x6dj
Started container
Warning   Unhealthy              4m (x60 over 9m)                 kubelet, ckad-1-lab-x6dj
Readiness probe failed: cat: /tmp/healthy: No such file or directory

```

15. If you look for the status of each container in the pod, they should show that both are Running and ready showing True.

```
student@ckad-1:~/app1$ kubectl describe pod try1-76cc5ffcc6-tx4dz | grep -E 'State|Ready'
```

```
State:      Running
Ready:      True
State:      Running
Ready:      True
Ready:      True
ContainersReady  True
```