



## Exercise 5.4: Rolling Updates and Rollbacks

When we started working with `simpleapp` we used a **Docker** tag called `latest`. While this is the default tag when pulling an image, and commonly used, it remains just a string, it may not be the actual latest version of the image.

1. Make a slight change to our source and create a new image. We will use updates and rollbacks with our application. Adding a comment to the last line should be enough for a new image to be generated.

```
student@ckad-1:~$ cd ~/app1
```

```
student@ckad-1:~/app1$ vim simple.py
```

```
<output_omitted>
```

```
## Sleep for five seconds then continue the loop
```

```
time.sleep(5)
```

```
## Adding a new comment so image is different.
```

2. Build the image again. A new container and image will be created. Verify when successful. There should be a different image ID and a recent creation time.

```
student@ckad-1:~/app1$ sudo docker build -t simpleapp .
```

```
Sending build context to Docker daemon 7.168 kB
```

```
Step 1/3 : FROM python:2
```

```
----> 2863c80c418c
```

```
Step 2/3 : ADD simple.py /
```

```
----> cde8ecf8492b
```

```
Removing intermediate container 3e908b76b5b4
```

```
Step 3/3 : CMD python ./simple.py
```

```
----> Running in 354620c97bf5
```

```
----> cc6bba0ea213
```

```
Removing intermediate container 354620c97bf5
```

```
Successfully built cc6bba0ea213
```

```
student@ckad-1:~/app1$ sudo docker images
```

REPOSITORY		TAG
IMAGE ID	CREATED	SIZE
simpleapp		latest
cc6bba0ea213	8 seconds ago	886 MB
10.105.119.236:5000/simpleapp		latest
15b5ad19d313	4 days ago	886 MB

```
<output_omitted>
```

3. Tag and push the updated image to your locally hosted registry. A reminder your IP address will be different than the example below. Use the tag `v2` this time instead of `latest`.

```
student@ckad-1:~/app1$ sudo docker tag simpleapp \
10.105.119.236:5000/simpleapp:v2
```

```
student@ckad-1:~/app1$ sudo docker push 10.105.119.236:5000/simpleapp:v2
```

```
The push refers to a repository [10.105.119.236:5000/simpleapp]
d6153c8cc7c3: Pushed
ca82a2274c57: Layer already exists
de2fbb43bd2a: Layer already exists
4e32c2de91a6: Layer already exists
6e1b48dc2ccc: Layer already exists
ff57bdb79ac8: Layer already exists
6e5e20cbf4a7: Layer already exists
86985c679800: Layer already exists
8fad67424c4e: Layer already exists
v2: digest: sha256:6cf74051d09463d89f1531fceb9c44cbf99006f8d9b407
dd91d8f07baeee7e9c size: 2218
```

4. Connect to a terminal running on your second node. Pull the latest image, then pull v2. Note the latest did not pull the new version of the image. Again, remember to use the IP for your locally hosted registry. You'll note the digest is different.

```
student@ckad-2:~$ sudo docker pull 10.105.119.236:5000/simpleapp
Using default tag: latest
latest: Pulling from simpleapp
Digest: sha256:cefa3305c36101d32399baf0919d3482ae8a53c926688be33
86f9bbc04e490a5
Status: Image is up to date for 10.105.119.236:5000/simpleapp:latest

student@ckad-2:~$ sudo docker pull 10.105.119.236:5000/simpleapp:v2
v2: Pulling from simpleapp
f65523718fc5: Already exists
1d2dd88bf649: Already exists
c09558828658: Already exists
0e1d7c9e6c06: Already exists
c6b6fe164861: Already exists
45097146116f: Already exists
f21f8abae4c4: Already exists
1c39556edcd0: Already exists
fa67749bf47d: Pull complete
Digest: sha256:6cf74051d09463d89f1531fceb9c44cbf99006f8d9b407dd91d8
f07baeee7e9c
Status: Downloaded newer image for 10.105.119.236:5000/simpleapp:v2
```

5. Use **kubect**l **edit** to update the image for the **try1** deployment to use v2. As we are only changing one parameter we could also use the **kubect**l **set** command. Note that the configuration file has not been updated, so a delete or a replace command would not include the new version. It can take the pods up to a minute to delete and to recreate each pod in sequence.

```
student@ckad-1:~/app1$ kubectl edit deployment try1

....
containers:
- image: 10.105.119.236:5000/simpleapp:v2    #<-- Edit tag
  imagePullPolicy: Always
....
```

6. Verify each of the pods has been recreated and is using the new version of the image. Note some messages will show the scaling down of the old **replicaset**, others should show the scaling up using the new image.

```
student@ckad-1:~/app1$ kubectl get events

42m      Normal      ScalingReplicaSet   Deployment      Scaled up replica set try1-7fdbb5d557 to 6
32s      Normal      ScalingReplicaSet   Deployment      Scaled up replica set try1-7fd7459fc6 to 2
32s      Normal      ScalingReplicaSet   Deployment      Scaled down replica set try1-7fdbb5d557 to 5
32s      Normal      ScalingReplicaSet   Deployment      Scaled up replica set try1-7fd7459fc6 to 3
23s      Normal      ScalingReplicaSet   Deployment      Scaled down replica set try1-7fdbb5d557 to 4
```

```

23s      Normal    ScalingReplicaSet  Deployment  Scaled up replica set try1-7fd7459fc6 to 4
22s      Normal    ScalingReplicaSet  Deployment  Scaled down replica set try1-7fdbb5d557 to 3
22s      Normal    ScalingReplicaSet  Deployment  Scaled up replica set try1-7fd7459fc6 to 5
18s      Normal    ScalingReplicaSet  Deployment  Scaled down replica set try1-7fdbb5d557 to 2
18s      Normal    ScalingReplicaSet  Deployment  Scaled up replica set try1-7fd7459fc6 to 6
8s       Normal    ScalingReplicaSet  Deployment  (combined from similar events):
Scaled down replica set try1-7fdbb5d557 to 0

```

7. View the images of a Pod in the deployment. Narrow the output to just view the images. The goproxy remains unchanged, but the simpleapp should now be v2.

```

student@ckad-1:~/app1$ kubectl describe pod try1-895fccfb-ttqdn |grep Image
Image:          10.105.119.236:5000/simpleapp:v2
Image ID:\
  docker-pullable://10.105.119.236:5000/simpleapp@sha256:6cf74051d09
463d89f1531fceb9c44cbf99006f8d9b407dd91d8f07baeee7e9c
Image:          k8s.gcr.io/goproxy:0.1
Image ID:\
  docker-pullable://k8s.gcr.io/goproxy@sha256:5334c7ad43048e3538775c
b09aaf184f5e8acf4b0ea60e3bc8f1d93c209865a5

```

8. View the update history of the deployment.

```

student@ckad-1:~/app1$ kubectl rollout history deployment try1
deployments "try1"
REVISION  CHANGE-CAUSE
1         <none>
2         <none>

```

9. Compare the output of the **rollout history** for the two revisions. Images and labels should be different, with the image v2 being the change we made.

```

student@ckad-1:~/app1$ kubectl rollout history deployment try1 --revision=1 > one.out
student@ckad-1:~/app1$ kubectl rollout history deployment try1 --revision=2 > two.out

student@ckad-1:~/app1$ diff one.out two.out
1c1
< deployments "try1" with revision #1
---
> deployments "try1" with revision #2
3c3
<   Labels:          pod-template-hash=1509661973
---
>   Labels:          pod-template-hash=45197796
7c7
<   Image:           10.105.119.236:5000/simpleapp:latest
---
>   Image:           10.105.119.236:5000/simpleapp:v2

```

10. View what would be undone using the **-dry-run** option while undoing the rollout. This allows us to see the new template prior to using it.

```

student@ckad-1:~/app1$ kubectl rollout undo --dry-run=true deployment/try1
deployment.apps/try1
Pod Template:
  Labels:          pod-template-hash=1509661973
                  run=try1
  Containers:
    try1:
      Image:        10.105.119.236:5000/simpleapp:latest
      Port:         <none>
<output_omitted>

```

11. View the pods. Depending on how fast you type the try1 pods should be about 2 minutes old.

```
student@ckad-1:~/app1$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-9fnl4	1/1	Running	1	5d
registry-795c6c8b8f-hl5wf	1/1	Running	2	5d
try1-594fbb5fc7-7dl7c	2/2	Running	0	2m
try1-594fbb5fc7-8mxlb	2/2	Running	0	2m
try1-594fbb5fc7-jr7h7	2/2	Running	0	2m
try1-594fbb5fc7-s24wt	2/2	Running	0	2m
try1-594fbb5fc7-xfffg	2/2	Running	0	2m
try1-594fbb5fc7-zfmz8	2/2	Running	0	2m

12. In our case there are only two revisions, which is also the default number kept. Were there more we could choose a particular version. The following command would have the same effect as the previous, without the **-dry-run** option.

```
student@ckad-1:~/app1$ kubectl rollout undo deployment try1 --to-revision=1
deployment.apps/try1
```

13. Again, it can take a bit for the pods to be terminated and re-created. Keep checking back until they are all running again.

```
student@ckad-1:~/app1$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-6b58d9cdfd-9fnl4	1/1	Running	1	5d
registry-795c6c8b8f-hl5wf	1/1	Running	2	5d
try1-594fbb5fc7-7dl7c	2/2	Terminating	0	3m
try1-594fbb5fc7-8mxlb	0/2	Terminating	0	2m
try1-594fbb5fc7-jr7h7	2/2	Terminating	0	3m
try1-594fbb5fc7-s24wt	2/2	Terminating	0	2m
try1-594fbb5fc7-xfffg	2/2	Terminating	0	3m
try1-594fbb5fc7-zfmz8	1/2	Terminating	0	2m
try1-895fccfb-8dn4b	2/2	Running	0	22s
try1-895fccfb-kz72j	2/2	Running	0	10s
try1-895fccfb-rxxtw	2/2	Running	0	24s
try1-895fccfb-srwq4	1/2	Running	0	11s
try1-895fccfb-vkvmb	2/2	Running	0	31s
try1-895fccfb-z46qr	2/2	Running	0	31s