

CS 8790: Report for assignment 7

Chanmann Lim

November 10, 2014

Report:

Appendix:

assignment_7.m

```
% Run filter_7 on Target1.txt with q = 0
filter_7 ('Target1.txt', 0);

% Run filter_7 on Target2.txt with q = 0
filter_7 ('Target2.txt', 0);

% Run filter_7 on Target2.txt with q = 0.15
filter_7 ('Target2.txt', 0.15);

% Run filter_7 on Target2.txt with q = 1
filter_7 ('Target2.txt', 1);
```

filter_7.m

```
function filter_7 (data_file, q)
    % initialize filter
    t = 0;
    x = zeros(4,1);
    P = eye(4) * 10^8; % large covariance P
    result = report();

    % open data file
    fid = fopen(data_file);
    while ~feof(fid)
        tline = fgetl(fid);
        data = sscanf(tline, '%f');

        if ~isempty(data)
            [t_new, z, R] = get_observation(data);
            [t, x, P] = predict(t, x, P, t_new, q);
            [x, P, vx] = update(x, P, z, R);
            result = result.add_data(vx);
        end
    end
    % close file
    fclose(fid);

    result = result.update_estimate(t, x, P);

    result.print_final_estimate();
    result.print_prediction(t + 3600, q);
    result.plot();
    result.print_innovations_percentage();
end
```

get_observation.m

```
function [ t_z, z, R ] = get_observation( data )
%GET_OBSERVATION get observation from data
% data - column vector containing observation data

t_z = data(1);
z = data(2:3);
R = [data(4:5)'; data(5:6)']; % sqrtm(R) not R
R = R * R;
end
```

predict.m

```
function [ t, x, P ] = predict( t, x, P, t_new, q )
%PREDICT - constant velocity precition for (x, P) at time "t_new"
% F : constant velocity transformation matrix respected to "delta_t"
% Q : process noise covariance matrix to ensure that P is conservative

delta_t = (t_new-t);
F = [1 0 delta_t 0; 0 1 0 delta_t; 0 0 1 0; 0 0 0 1];
Q = q * [1 0 0 0; 0 1 0 0; 0 0 0 0; 0 0 0 0] * delta_t; % velocity should not be inflated
% (Fx, FPF' + Q)
t = t_new;
```

```

    x = F * x;
    P = (F * P * F') + Q;
end

```

update.m

```

function [ x, P, vx ] = update( x, P, z, R )
%UPDATE - update sensor estimate
%    incorporate information from new observation (z, R)
%    returns
%        x - updated mean x
%        P - updated covariance P
%        vx - normalized unit innovations

% Use dimensionality transformation matrix H
% to project down the state dimension
% since the observation doesn't come with velocity
H = eye(2, 4);

S = (H * P * H') + R;
W = (P * H') / S;
P = P - (W * S * W');
innovation = (z - H * x);
x = x + W * innovation;

vx = innovation ./ sqrt(S([1;4]));
end

```

report.m

```
classdef report
```

```

    properties
        normalized_unit_innovations;
        running_percentages;
        t;
        x;
        P;
    end

```

```
    methods
```

```

        function obj = report()
            obj.normalized_unit_innovations = [];
            obj.running_percentages = [];
        end

        function obj = add_data(obj, vx)
            % vx - normalized unit innovation vector
            % vs - innovation size
            obj.normalized_unit_innovations(:, end + 1) = vx;
            obj.running_percentages(:, end + 1) = ...
                sum(obj.normalized_unit_innovations < 0, 2) / length(obj.normalized_unit_innovations);
        end

```

```

        function obj = update_estimate(obj, t, x, P)
            obj.t = t;
            obj.x = x;
            obj.P = P;
        end

```

```

        function print_prediction(obj, t, q)
            [~, x_new, P_new] = predict(obj.t, obj.x, obj.P, t, q);
            fprintf('x(%f) = \n\n', t);
            fprintf('%14f\n', x_new);
            fprintf('\n');

            fprintf('P(%f) = \n\n', t);
            fprintf('%14.8f %14.8f %14.8f %14.8f\n', P_new);
            fprintf('\n');
        end

```

```

        function print_final_estimate(obj)

```

```

% print final position
standard_deviation = sqrt(diag(obj.P));
fprintf('The final position of the target with standard deviation=\n');
fprintf('\n%14f, %14f\n%14f, %14f\n%14f, %14f\n%14f, %14f\n', ...
    obj.x(1), standard_deviation(1), ...
    obj.x(2), standard_deviation(2), ...
    obj.x(3), standard_deviation(3), ...
    obj.x(4), standard_deviation(4));
fprintf('\n');

fprintf('x_final=\n\n');
fprintf('%14f\n', obj.x);
fprintf('\n');

fprintf('P_final=\n\n');
fprintf('%14.8f %14.8f %14.8f %14.8f\n', obj.P);
fprintf('\n');
end

function plot(obj)
% plot x innovations
figure;
plot(obj.normalized_unit_innovations(1,:));
ylim([-3, 3]);
title('Normalized x innovations');

figure;
plot(obj.running_percentages(1, :));
ylim([.3, .7]);
title('Running percentage of the x innovations that are less than or equal to 0');

% plot y innovations
figure;
plot(obj.normalized_unit_innovations(2,:));
ylim([-3, 3]);
title('Normalized y innovations');

figure;
plot(obj.running_percentages(2, :));
ylim([.3, .7]);
title('Running percentage of the y innovations that are less than or equal to 0');
end

function print_innovations_percentage(obj)
template = 'Percentage of the innovations that are less than 0 = [%14.2f%%, %14.2f%%]\n';
percent = ...
    sum(obj.normalized_unit_innovations < 0, 2) / length(obj.normalized_unit_innovations);
fprintf(template, percent * 100);
end
end
end

```