Alcohol Exposure and Cell State in the Served *Pseudomonas putida* Data

Michael Volk

October 21, 2026

KG 4.0 serves 32 *P. putida* datasets. Fifteen of them carry an alcohol growth or tolerance arm, or a perturbation of cell state, and Table 1 gives each one's genotype, environment, phenotype and genome as the served store holds them, with the environment axis broken out in Table 3. Every count in both tables is read off the store rather than off a loader docstring (Sec. 1).

Two findings come before the table. First, no served *P. putida* dataset measures isobutanol. A search of every loader module under `torchcell/datasets/pputida/` returns no match, and the two isobutanol datasets in the release are Lopez 2024, which is *S. cerevisiae* (Sec. 2). Second, the alcohol arms that do exist split into two kinds that a query must not merge: the transposon compendia feed an alcohol as the sole carbon source, which measures catabolism, while Lim 2022 and Lim 2025 apply one as a stressor (Sec. 3).

Four of the fifteen rows are transposon screens, and they are the largest by three orders of magnitude. Sec. 5 sets out what a transposon record means here, since the genotype is deliberately a gene-level aggregate rather than a clone and the phenotype deliberately avoids the fitness class.

Sec. 6 turns to the task these rows were surveyed for: predicting the final design-build-test-learn round of the Carruthers isoprenol campaign from its earlier rounds. It names the one non-Carruthers dataset that transfers, and it records a blocker, which is that the cycle label is absent from every served Carruthers record. Sec. 7 closes with what the schema cannot yet hold.

Section status: ✓ ready ■ author-reviewed, keep stable ✗ not done, agents may edit freely

Contents

1 Where the numbers come from ✗ . . . **2**
2 There is no served *P. putida* isobutanol data ✗ . . . **2**
3 The fifteen rows ✗ . . . **3**
4 Reading the environment column ✗ . . . **6**
5 What a transposon record means here ✗ . . . **7**
6 Predicting the last Carruthers round ✗ . . . **8**
6.1 The dataset: Yunus 2026 ✗ . . . 8
6.2 The blocker: the cycle label is not in the graph ✗ . . . 9
7 What is released and not served ✗ . . . **10**

1 Where the numbers come from ✗

Two layers, and the split is what makes the tables auditable. Every count is probed from the served store. The row set and the last column of Table 1 are curation, held as data in the generating script so the judgment is versioned with the numbers it sits beside.

The stores read. The probe reads the dev build tree, `$DATA_ROOT/data/torchcell/<dataset>/processed/`, which is the tree a loader writes. It is not the knowledge-graph tree under `database/data/torchcell/`, which the build user owns and which is read-only here. The two were checked against the build manifest of release 2026.10.17-4295f7ca: every record count in Table 1 equals the manifest's `n_experiments` for that dataset, which is the evidence that the probed stores are the served ones.

Records are pickled, not JSON. An LMDB value is a pickle, so a probe reads it with `pickle.loads`. Reading one as UTF-8 fails on the pickle protocol byte, which is how this was found.

Constants are interned. An `Environment`, a medium and a compound are each stored once in a sibling `processed/interned/` LMDB, and a record carries `{"$ref": <sha256>, "name": <hint>}` in their place. A probe that does not splice these back reads every environment as an opaque reference. The script splices recursively before touching any field.

Distinct environments are counted by value. The interned table is the tempting route to the count and it is the wrong one: it holds every interned constant, environments and media and compounds alike, and nothing guarantees each entry is still referenced. So the probe reads every record, splices its environment and hashes the spliced object, which makes two references to the same condition one environment. That costs a full scan of 2.7 million records and it is exact. The result is cached in `experiments/database/results/pputida_cell_state_probe.json` so rebuilding the document does not rescan.

The genome is on the reference, not the experiment. Every row's assembly in Table 1 is read from `reference.genome_reference`. The experiment-level `genome_reference` is null in all fifteen datasets. That is by design rather than a defect: the genome never gates a record, so a record does not carry one.

All fifteen pin the same assembly, `GCA_000007565.2`, while the strain on that assembly varies: KT2440 for the screens, and the engineered backgrounds IY1449b, IPL400 and CJ522 for the production and tolerance work. An engineered strain's episomal cassettes are carried on the genotype as perturbations rather than folded into the assembly, which is why one accession covers every row.

What the probe cannot see. Whether a transposon pool was barcoded, and whether an alcohol was fed as a carbon source or applied as a stressor, are properties of the experiment that no stored field distinguishes. Both are carried as curation, the first in the italic line under the genotype column and the second in prose in Sec. 3.

2 There is no served *P. putida* isobutanol data ✗

This is the first thing to establish, because the release does contain isobutanol datasets and they are the wrong organism.

The loaders. A case-insensitive search for *isobutanol* across the fifteen loader modules under `torchcell/datasets/pputida/` returns no file.

The release. The two isobutanol datasets in KG 4.0, `IsobutanolScreenLopez2024` and `IsobutanolValidatedLopez2024`, resolve in the build manifest to `torchcell/datasets/scerevisiae/lopez2024.py`. They are *S. cerevisiae*.

The Fitness Browser deposit. The deposit's own database carries no isobutanol experiment for any organism, so the gap is upstream of our ingest rather than something a loader dropped.

One false positive to know about. A text search for *isobutyr* in the Borchert 2024 environment agents hits DL-3-aminoisobutyric acid, which is an amino acid fed as a nitrogen source. Matching on compound name rather than on structure is what produces that hit; the InChIKey does not.

The closest served alcohols are the nine alcohol and diol carbon sources the transposon compendia carry, 2-methyl-1-butanol among them, and the butanol and isopentanol arms of Lim 2022. None is isobutanol. A query that needs isobutanol in *P. putida* is a query for a dataset we have not ingested, not one for a filter over what is served.

3 The fifteen rows ✗

Table 1 is the row table and Table 2 its totals. Two distinctions decide whether a row answers a given question, and neither is a stored field, so both are stated here rather than read off the table.

Catabolism is not tolerance. In the transposon compendia the alcohol arms are carbon-source perturbations: the alcohol is the sole carbon source at 10 mM, and the fitness value says whether disrupting a gene impairs growth *on* that alcohol. In Lim 2022 and Lim 2025 the alcohol is a stressor added to a glucose medium, and the readout says whether the strain tolerates it. A query that filters on the compound alone returns both and they answer different questions.

Scale is not information. Almost every record in Table 2 is in the two pooled compendia, which that table reports as a share, because a pooled screen multiplies one condition by several thousand genes. The engineering rows at the bottom of the table hold single digits of records and carry the phenotype the strain-design work actually targets. The record count is a cost estimate, not a ranking.

The environment axis is the narrow one. Fifteen datasets, and the distinct environment counts in Table 3 are dominated by the two compendia's carbon and nitrogen source panels. Outside them the condition axis is one or two environments per dataset, so almost every row is a genotype series measured in a single condition.

Table 1: The served *P. putida* datasets bearing on alcohol exposure or cell state, ordered by record count. Every column but the last is read off the served store (Sec. 1). *Genotype* gives the perturbation types the records carry, with what the probe cannot see added in italic. *Env.* is the number of distinct `Environment` objects, counted by value over a full scan, and Table 3 breaks each one into its media, factors and agents. *Phenotype* is the stored class, then its measurement type and assay type. *Genome* is the assembly the reference record pins; the experiment-level `genome_reference` is null throughout, by design, since the genome never gates a record.

Dataset	Records	Genotype	Env.	Phenotype	Genome	Why it is here
RbTnseq Borchert2024	1,466,920	transposon insertion *gene-level aggregate, one gene per record*	155	**environment_response** log2_ratio / pooled_competitive_growth_barcode	KT2440 GCA_000007565.2	The RB-TnSeq compendium, and it carries Thompson 2020's alcohol panel. Nine alcohol and diol carbon sources, 2-methyl-1-butanol among them. These arms are growth ON the alcohol as the sole carbon source, so they measure catabolism, not tolerance to a solvent stress
FitnessBrowser Putida	1,118,052	transposon insertion *gene-level aggregate, one locus per record*	146	**environment_response** log2_ratio / pooled_competitive_growth_barcode	KT2440 GCA_000007565.2	The Fitness Browser deposit over the same alcohol panel, on 4,778 loci, and it is the one compendium that carries a moderated t statistic per record alongside the fitness value
FitnessContrast Borchert2023	64,853	transposon insertion	12	**t_statistic** rbtnseq_gene_fitness_two_sample_t_test / None	KT2440 GCA_000007565.2	The significance test of a lignin-related stressor arm against its reference arm, stored as the t statistic rather than as a fitness value
EnvMetalTnseq Royet2025	21,583	transposon insertion *non-barcoded mariner pool, gene-level aggregate*	4	**environment_response** log2_ratio / other	KT2440 GCA_000007565.2	Cobalt, copper, zinc and cadmium at sub-inhibitory dose over 12 generations. A metal stress rather than a solvent one, and the cleanest served example of a graded cell-state perturbation on a transposon pool
GradedGene Essentiality Royet2025	11,458	transposon insertion	2	**essentiality_call** None / None	KT2440 GCA_000007565.2	The unstressed essentiality baseline the metal contrasts above are read against, so the two rows are used together or not at all
RbTnseq Borchert2023	10,824	transposon insertion	32	**environment_response** log2_ratio / pooled_competitive_growth_barcode	KT2440 GCA_000007565.2	The loci Borchert 2023 scored that the compendium eliminated. Disjoint from the compendium row by construction, so it adds fitness values rather than duplicating them
CampaignProteome Carruthers2025	465	crispr interference, heterologous pathway	1	**protein_abundance** dia_nn_top3_percent_of_proteome_mean / None	IY1449b GCA_000007565.2	Cell state under CRISPRi knockdown across the six automated design-build-test-learn cycles, as a proteome panel. The paired feature table for the isoprenol titer campaign
PutidaPrecise321 Lim2022	321	released identifier	118	**expression_tpm** rnaseq_tpm / None	CJ522 GCA_000007565.2	The only served butanol exposure, in the compendium's Fuel project, beside an isopentanol arm, a three-point growth-phase series, a multistress panel of salt, imipenem and peroxide, an ionic-liquid adaptation series and two bioreactor runs. The broadest cell-state axis in the served set

Table 1, continued

Dataset	Records	Genotype	Env.	Phenotype	Genome	Why it is here
IsoprenolSelection Menasalvas2025	58	crispr interference, deletion strain, heterologous pathway	1	**environment__ response** categorical / biosensor__ readout	KT2440 GCA__ 000007565.2	Isoprenol production coupled to growth through a pyrF biosensor, so the readout is a categorical enrichment call rather than a titer
Proteome Menasalvas2025	6	deletion strain, heterologous pathway, locus variant call, site variant call	2	**protein__abundance** dia__protein__counts__sum__ mean / None	KT2440 GCA__ 000007565.2	Growth phase against production phase over 2,090 loci, with the two phases stored as distinct environments rather than as one condition
ProteomeFold ChangeLim2025	4	deletion strain, locus variant call, site variant call	2	**protein__fold__change** dia__nn__top3__log2__fold__ change__welch__two__ sample__t__test / None	IPL400 GCA__ 000007565.2	The proteome response to isoprenol stress, as a log2 fold change with its Welch test, which is the closest served analog of a solvent tolerance signature
IsoprenolTolerance Lim2025	3	deletion strain, locus variant call	2	**environment__ response** log2__ratio / liquid__od__ growth	KT2440 GCA__ 000007565.2	The only served alcohol tolerance growth phenotype: specific growth rate of a tolerized lineage against wild type at the same alcohol dose
ProteomeLim2025	3	deletion strain, locus variant call, site variant call	1	**protein__abundance** dia__nn__top3__log2__mean / None	IPL400 GCA__ 000007565.2	Absolute abundances on the same tolerized lineages as the row above, so the tolerance phenotype has a proteome beside it
MetaboliteGrowth Phase Menasalvas2025	3	deletion strain, heterologous pathway, locus variant call, site variant call	1	**metabolite__level** lc__ms__intracellular__ concentration__uM / None	KT2440 GCA__ 000007565.2	Intracellular pool sizes in growth phase, the metabolite half of the same phase contrast
Metabolite ProductionPhase Menasalvas2025	3	deletion strain, heterologous pathway, locus variant call, site variant call	1	**metabolite__level** lc__ms__intracellular__ concentration__uM / None	KT2440 GCA__ 000007565.2	The paired production-phase pools, which is the environment the titer campaigns actually sample

Table 2: Totals over the rows of Table 1, generated with them.

Quantity	Value
Datasets	15
Records	2,694,556
Records in the two pooled transposon compendia	2,584,972
Their share of all records	95.9%
Distinct environments, summed over datasets	480
Distinct phenotype classes	7
Distinct genotype perturbation types	7
Distinct genome assemblies	1

4 Reading the environment column ✗

The `Environment` object served in all fifteen datasets carries the same seven fields: `media`, `temperature`, `perturbations`, `aerobicity`, `duration_hours`, `duration_generations` and `dilution_rate_per_hour`. Each perturbation names a factor from a controlled vocabulary and an agent resolved to a compound identity with an InChIKey and a PubChem identifier, so an alcohol arm is queryable by structure. Table 3 breaks each row into those parts.

Two caveats on that column, and both limit what a query over it can claim.

Lim 2022's media are condition labels, not recipes. The compendium releases a condition name per sample and not the medium, the additions or the timing, so the media count for that row counts labels. A join on medium composition across that row and any other is not available.

A temperature can be a typed absence. Lim 2025 reports no incubation temperature for its tolerance assay, its evolution flasks or its proteome cultures, so the field carries a `ProvenanceGap` naming where it was looked for rather than a guessed 30 °C. Table 3 prints that absence as a value, since treating it as missing data is what turns a recorded gap into an invented number.

Table 3: The environment axis of each row in Table 1. *Env.* is distinct `Environment` objects and *Media* distinct media names. *Factors* counts the environment perturbations carrying each factor, summed over records, so a dataset of many records shows large counts for a few conditions. *Agents* is distinct compounds resolved to an InChIKey and a PubChem identifier, which is what makes an alcohol arm queryable by structure rather than by string. *Temperature* prints every value the store holds, a typed absence included.

Dataset	Env.	Media	Factors (perturbations carrying each)	Agents	Temperature
RbTnseqBorchert2024	155	4	carbon 974,792, nitrogen 492,128, dropout 89,908, small mol. 492,128	108	30 °C
FitnessBrowserPutida	146	3	carbon 621,140, nitrogen 496,912, dropout 90,782, small mol. 277,124	97	30 °C
FitnessContrast Borchert2023	12	1	carbon 64,853, small mol. 64,853	13	30 °C
EnvMetalTnseqRoyet2025	4	1	small mol. 21,583	4	28 °C
GradedGeneEssentiality Royet2025	2	2	none	0	28 °C
RbTnseqBorchert2023	32	1	carbon 10,824, small mol. 9,417	13	30 °C
CampaignProteome Carruthers2025	1	1	small mol. 465	1	24 °C
PutidaPrecise321Lim2022	118	115	carbon 15	3	not reported
IsoprenolSelection Menasalvas2025	1	1	pH 58, small mol. 116	2	not reported
ProteomeMenasalvas2025	2	1	pH 6, small mol. 6	1	not reported
ProteomeFoldChange Lim2025	2	1	small mol. 2	1	not reported
IsoprenolTolerance Lim2025	2	1	small mol. 3	1	not reported
ProteomeLim2025	1	1	small mol. 3	1	not reported
MetaboliteGrowthPhase Menasalvas2025	1	1	pH 3, small mol. 3	1	not reported
MetaboliteProduction PhaseMenasalvas2025	1	1	pH 3, small mol. 3	1	not reported

5 What a transposon record means here ✗

Four rows of Table 1 are transposon screens and they hold almost every record in it, so the representation is worth stating exactly.

The experiment. A randomly barcoded transposon library is a pool in which each cell carries one transposon inserted at a random genomic position, with a random DNA barcode in the insert. An insertion inside a gene disrupts it, so each cell is a loss-of-function mutant of one gene. The pool grows competitively in a condition, barcodes are sequenced at time zero and at the end, and a gene's fitness is the log2 ratio of its barcode abundance after growth over time zero, averaged across that gene's insertion strains and normalized so the typical gene sits at zero.

The genotype is a gene, not a clone. Each record carries one `TransposonInsertionPerturbation` with `insertion_position`, `insertion_strand` and `barcode` left null. Those nulls are the representation, not missing data: the stored value is the gene-level aggregate over every insertion mutant of that gene, which is the quantity the release reports. Royet 2025 is the case that makes this unavoidable, since its mariner library is not barcoded at all and a clone is unresolvable in principle.

The phenotype is not the fitness class. These records use `EnvironmentResponsePhenotype`, whose measurement type is `log2_ratio` and whose assay type is `pooled_competitive_growth_barcode`. `FitnessPhenotype` would be the obvious class and it is wrong here: `validate_fitness` clamps a non-positive value to 0.0, which would erase every fitness defect in the compendium, since a defect is exactly a negative log2 ratio. The signed ratio therefore goes on the environment-response class.

Reliability travels with the value. The Fitness Browser row carries a moderated t in `environment_response_t_statistic`, and the loader derives a standard error as $\sqrt{(f/t)^2 - 0.1^2}$, where f is the fitness value. That makes it the one compendium row where a per-record weight is available, which matters for any model that should down-weight a gene measured in a sparse pool.

Why these rows are a feature source and not labels. For the isoprenol task of Sec. 6, three differences rule them out as training labels. The readout is competitive growth, not product titer, and a gene that raises titer can be fitness-neutral or fitness-costly. The perturbation differs in kind: a transposon insertion is a full disruption while CRISPRi is partial repression of a gene that is still present, so the sign may agree but the magnitudes share no scale. And the chassis differs, since the libraries are wild-type KT2440 and carry neither the mevalonate pathway nor its flux burden.

What they can supply is a descriptor. A gene's fitness across the compendium's many carbon and nitrogen sources is a cheap, genome-wide measure of how essential or buffered that gene is, available for nearly every CRISPRi target without a new experiment. *Hypothesis, untested:* that descriptor improves last-round titer prediction over the proteome features alone. Nothing here measures it, and it should be checked against a proteome-only model before it is relied on.

6 Predicting the last Carruthers round ✗

The task these rows were surveyed for: predict the final design-build-test-learn round of the Carruthers isoprenol campaign from its earlier rounds, using whatever other isoprenol data is served. Carruthers is a collaborator, so the campaign's own data is available; the question is which single dataset from outside it helps.

6.1 The dataset: Yunus 2026 ✗

`IsoprenolTiterYunus2026` is the answer, and Table 4 is why. Yunus 2026 (doi:10.1016/j.ymben.2025.11.007) selects CRISPRi knockdown targets by FluxRETAP against intuition, in the engineered isoprenol-producing strain IY1452, and Carruthers is a co-author. Four things line up and one does not.

The target sets nearly coincide. Every target in the Yunus campaign but one is also a Carruthers target (Table 4). That is what makes the dataset unusual: it is not a different experiment that happens to share a product, it is a second measurement of nearly the same target set.

The readout is the same quantity. Same product, same unit, same quantification method, same 48 hour culture. No unit conversion and no method bridge stands between the two campaigns. The replicate structure is the one readout axis that differs: Carruthers varies from 2 to 6 biological replicates per strain and every record carries a sample standard deviation, while Yunus is uniformly 3 and no record carries a dispersion at all (Table 4).

The chassis and the modality are the same. Both repress a native gene by CRISPRi in an isoprenol-producing strain, so a target's effect means the same thing in both.

The paired features exist. `CrispriPanelProteomeYunus2026` carries an absolute Top3 proteome over 253 accessions on the same strains, which is the same feature modality as `CampaignProteomeCarruthers2025` in Table 1. A proteome-to-titer map can be fit on both.

The conditions differ, and this decides how it is used. Carruthers runs at 24 °C in M9-NREL with 20 g/L glucose; Yunus runs at 30 °C in plain M9 salts. The titer ranges differ accordingly, and the Yunus records carry no uncertainty, because only one number per strain was released and the loader records that as a typed gap rather than inventing a dispersion.

So Yunus is not extra training rows for absolute titer. Two uses survive the condition difference, and both are worth more than 125 rows would be:

- **A held-out condition.** If a model trained on the earlier Carruthers cycles ranks targets correctly in Yunus, the ranking is a property of the biology rather than of the campaign. Test rank agreement, not absolute error, since the scales differ.
- **A reproducibility bound on the label.** Two independent measurements of nearly the same target set say how much of the titer variation is real. That ceilings what any model can achieve on this data, and it is the first thing to compute.

The runner-up is `IsoprenolSelectionMenasalvas2025` in Table 1, the only other CRISPRi and isoprenol pairing. Its readout is a categorical biosensor enrichment call rather than a titer, so it is a weaker label and not the first choice.

6.2 The blocker: the cycle label is not in the graph ✗

The task needs a cycle label, to train on the earlier rounds and test on the last one. No served Carruthers record carries one. Table 5 searches every record in all four Carruthers stores for a DBTL token anywhere in its serialization and finds none, and `screen_id` is empty throughout.

The loader's record identity is one per construct and DBTL cycle, so the cycle is implied by the record set and was never written onto a record. From the graph alone the final round cannot be separated from the earlier ones, which means the task as stated cannot be set up from a query.

It is recoverable. The raw mirror's Dryad culture metadata carries a `DBTL_Cycle` column, and Table 6 gives its distribution. The join is on the construct name, so recovering the label is a preprocessing step rather than a re-ingest. It is still a loader gap worth filing: a campaign whose entire structure is the cycle should not lose the cycle on ingest.

Table 4: The two served isoprenol titer campaigns, axis by axis, every value read off the store. The product is the same compound in both, isoprenol at InChIKey CPJRRXSHAYUTGL-UHFFFAOYSA-N and PubChem 12988. *Targets shared* is the intersection of the two CRISPRi target sets, counting the CRISPRi half of the genotype only, since a Carruthers record also carries the heterologous pathway.

Axis	Carruthers 2025	Yunus 2026
Records	502	125
CRISPRi targets	135	121
Targets shared by both campaigns	120	
Genotype perturbation types	crispr interference, deletion strain, gene addition, heterologous pathway	crispr interference
Medium	M9-NREL + 20 g/L glucose (10 mM ammonium sulfate + Teknova T1001; Carruthers 2025)	M9 salts (6.78 g/L Na2HPO4, 3 g/L KH2PO4, 1 g/L NH4Cl, 0.5 g/L NaCl)
Temperature	24 °C	30 °C
Duration	48 h	48 h
Replicates	2 biological_replicate, 3 biological_replicate, 6 biological_replicate	3 biological_replicate
Quantification	GC-FID	GC-FID
Titer unit	ug/mL	ug/mL
Titer range	0.00 to 771.2	1.59 to 1,495.0
Records carrying an uncertainty	502 of 502	0 of 125

Targets in Yunus 2026 and not in Carruthers 2025: PP_4129.

Table 5: The DBTL cycle label in the served Carruthers stores. *Naming a cycle* counts records whose full serialization matches `DBTL\s*\d` anywhere, so it is as permissive a search as the store allows.

Store	Records	Naming a cycle	With a screen id
campaign_proteome_carruthers2025	465	0	0
isoprenol_titer_carruthers2025	502	0	0
proteome_carruthers2025	21	0	0
proteome_fold_change_carruthers2025	16	0	0

Table 6: The same label in the raw mirror, which is the recovery path. Rows are cultures and include each cycle's controls, so these are not record counts; they establish that the label exists upstream and joins on `Line_name`.

Cycle	Culture rows
DBTL0	393
DBTL1	183
DBTL2	189
DBTL3	174
DBTL4	183
DBTL5	186
DBTL6	189
Total	**1,497**

7 What is released and not served ✗

One group of samples bearing directly on cell state is in no served dataset, and it is worth recording because a query cannot discover its absence.

The dropped reactor arms. Borchert 2024 releases 332 RB-TnSeq samples and the loader stores 310. The 22 it drops are the bioreactor and adaptation samples, under the rule `reactor_process_not_representable`: they differ by dissolved-oxygen set point, batch or fed-batch feed rate, sampling time, solvent overlay and adaptation day, and the loader's position is that collapsing distinct conditions into one environment is worse than not serving them. The arithmetic confirms which samples are served, since $310 \times 4{,}732$ is exactly the record count Table 1 reports for that row.

The residue is narrower than that rule implies. `Environment` already carries dissolved oxygen as a physical factor, plus `duration_hours`, `duration_generations` and `dilution_rate_per_hour`, so the oxygen set point, the sampling time and the adaptation day are representable on fields that exist today. Three things remain:

- **The solvent overlay has no representation.** A search of `torchcell/datamodels/schema.py` for overlay, two-phase, biphasic, dodecane and oleyl alcohol returns nothing. This affects 3 of the 22 samples, and it is the axis closest to in-situ product recovery for an alcohol, so it is the one worth a schema discussion.
- **Fed-batch feed rate is only partly covered.** `dilution_rate_per_hour` is documented as the controlled variable of a continuous chemostat, so reading a discontinuous fed-batch feed into it is a judgment call rather than a given.
- **The other 19 samples look admissible on existing fields.** That is a reading of the schema against the release metadata and not a verified admission. It needs owner sign-off and a rerun of the admission check before anyone acts on it.

What the Fitness Browser row leaves out. Of the deposit's 314 *P. putida* experiments the loader stores 234. It drops the 34 with an empty `pubId`, which includes the bioreactor series, and all 46 `VillalobosEscobedo23` samples, because every one is on R2A and the media library has no entry for it. The second exclusion is worth knowing when reading that row's agent count: the stress panel and methanol arms that deposit carries are not in the served set.