RSLogix Micro Project Report



Processor Information

Processor Type: Bul.1763 MicroLogix 1100 Series B

Processor Name: UNTITLED

Total Memory Used: 133 Instruction Words Used - 50 Data Table Words Used

Total Memory Left: 6523 Instruction Words Left

Program Files: 5

Data Files: 9

Program ID: 9095

I/O Configuration

)		
L		
2		
3		
1		

Bul.1763

MicroLogix 1100 Series B

Channel Configuration

```
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Edit Resource/Owner Timeout: 60 CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Passthru Link ID: 1
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Write Protected: No
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Comms Servicing Selection: Yes
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Message Servicing Selection: Yes
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex 1st AWA Append Character: \d
  CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex 2nd AWA Append Character: \a
  Source ID: 1 (decimal)
  Baud: 19200
  Parity: NONE
  Control Line : No Handshaking
  Error Detection: CRC
  Embedded Responses: Auto Detect
  Duplicate Packet Detect: Yes
  ACK Timeout (x20 ms): 50
  NAK Retries: 3
  ENQ Retries: 3
CHANNEL 1 (SYSTEM) - Driver: Ethernet
  CHANNEL 1 (SYSTEM) - Driver: Ethernet Edit Resource/Owner Timeout: 60
  CHANNEL 1 (SYSTEM) - Driver: Ethernet Passthru Link ID: 1
  CHANNEL 1 (SYSTEM) - Driver: Ethernet Write Protected: No
  CHANNEL 1 (SYSTEM) - Driver: Ethernet Comms Servicing Selection: Yes
  CHANNEL 1 (SYSTEM) - Driver: Ethernet Message Servicing Selection: Yes
  Hardware Address: 00:00:00:00:00:00
  IP Address: 0.0.0.0
  Subnet Mask: 0.0.0.0
  Gateway Address: 0.0.0.0
  Msg Connection Timeout (x 1mS):
  Msg Reply Timeout (x mS): 3000
  Inactivity Timeout (x Min): 30
  Bootp Enable: Yes
  Dhcp Enable No
  SNMP Enable: No
  HTTP Enable: Yes
  Auto Negotiate Enable: Yes
  Port Speed Enable: 10/100 Mbps Full Duplex/Half Duplex
  Contact:
```

Location:


Program File List

Number	Type	Rungs	Debug	Bytes
0	SYS	0	No	0
1	SYS	0	No	0
2	LADDER	4	No	43
3	LADDER	3	No	48
4	LADDER	5	No	116
	Number 0 1 2 3 4	0 SYS 1 SYS 2 LADDER 3 LADDER	0 SYS 0 1 SYS 0 2 LADDER 4 3 LADDER 3	0 SYS 0 No 1 SYS 0 No 2 LADDER 4 No 3 LADDER 3 No


Data File List


Name	Number	Type	Scope	Debug	Words	Elements	Last	
OUTPUT	0	О	Global	No	12	4	O:3	
INPUT	1	I	Global	No	18	6	I:5	
STATUS	2	S	Global	No	0	66	S:65	
BINARY	3	В	Global	No	1	1	B3:0	
TIMER	4	T	Global	No	6	2	T4:1	
COUNTER	5	C	Global	No	3	1	C5:0	
CONTROL	6	R	Global	No	3	1	R6:0	
INTEGER	7	N	Global	No	1	1	N7:0	
FLOAT	8	F	Global	No	6	3	F8:2	

LAD 2 - MAIN --- Total Rungs in File = 4



LAD 3 - INPUT --- Total Rungs in File = 3





Data File OO (bin) -- OUTPUT

Offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
0:0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
0:0.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
0:0.2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
0:0.3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B

Data File I1 (bin) -- INPUT

Offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0			
I:0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	J	Bul.1763	MicroLogix 1100 Series B
I:0.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	,	Bul.1763	MicroLogix 1100 Series B
I:0.2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	,	Bul.1763	MicroLogix 1100 Series B
I:0.3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	,	Bul.1763	MicroLogix 1100 Series B
I:0.4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	,	Bul.1763	MicroLogix 1100 Series B-Analog
I:0.5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	,	Bul.1763	MicroLogix 1100 Series B-Analog

Data File S2 (hex) -- STATUS

```
Main
Processor Mode S:1/0 - S:1/4 = Remote Program Mode
On Power up Go To Run (Mode Behavior) S:1/12 = 0
First Pass S:1/15 = No
Free Running Clock S:4 = 0000-0000-0000-0000
Proc
OS Catalog Number S:57 = 1100
                                        User Program Type S:63 = 8001h
OS Series S:58 = A
                                        Compiler Revision Number S:64 =
OS FRS S:59 =
Processor Catalog Number S:60 =
Processor Series S:61 = A
Processor FRN S:62 =
Scan Times
Maximum (x10 ms) S:22 = 0
Watchdog (x10 ms) S:3 (high byte) = 10
Last 100 uSec Scan Time S:35 = 0
Scan Toggle Bit S:33/9 = 0
Math
Math Overflow Selected S:2/14 = 0
                                            Math Register (lo word) S:13 = 0
Overflow Trap S:5/0 = 0
                                             Math Register (high word) S:14-S:13 = 0
Carry S:0/0 = 0
                                             Math Register (32 Bit) S:14-S:13 = 0
Overflow S:0/1 = 0
Zero Bit S:0/2 = 0
Sign Bit S:0/3 = 0
Chan 0
Processor Mode S:1/0- S:1/4 = Remote Program Mode
Node Address S:15 (low byte) = 0
                                 Outgoing Msg Cmd Pending S:33/2 = 0
Baud Rate S:15 (high byte) = ?
Channel Mode S:33/3 = 0
Comms Active S:33/4 = 0
Incoming Cmd Pending S:33/0 = 0
Msg Reply Pending S:33/1 = 0
Debug
Suspend Code S:7 = 0
Suspend File S:8 = 0
Errors
Fault Override At Power Up S:1/8 = 0
                                             Fault Routine S:29 = 0
Startup Protection Fault S:1/9 = 0
                                             Major Error S:6 = 0h
Major Error Halt S:1/13 = 0
Overflow Trap S:5/0 = 0
                                             Error Description:
Control Register Error S:5/2 = 0
Major Error Executing User Fault Rtn. S:5/3 = 0
Battery Low S:5/11 = 0
Input Filter Selection Modified S:5/13 = 0
ASCII String Manipulation error S:5/15 = 0
```

Protection

Deny Future Access S:1/14 = No
Data File Overwrite Protection Lost S:36/10 = False

Mem Module

Memory Module Loaded On Boot S:5/8 = 0
Password Mismatch S:5/9 = 0
Load Memory Module On Memory Error S:1/10 = 0
Load Memory Module Always S:1/11 = 0
On Power up Go To Run (Mode Behavior) S:1/12 = 0
Program Compare S:2/9 = 0
Data File Overwrite Protection Lost S:36/10 = 0

Forces

Forces Enabled S:1/5 = Yes Forces Installed S:1/6 = No

Data File B3 (bin) -- BINARY

Offset 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 (Symbol) Description

B3:0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Data File T4 -- TIMER

Offset	EN TT D	N BASE	PRE	ACC	(Symbol) Description
T4:0 T4:1		0 1.0 sec 0 1.0 sec	12 200		Rotameter timer Oil flow timer

Data File C5 -- COUNTER

Offset CU CD DN OV UN UA PRE ACC (Symbol) Description
C5:0 0 0 0 0 0 200 0 Oil flow time

Data File R6 -- CONTROL

Offset EN EU DN EM ER UL IN FD LEN POS (Symbol) Description R6:0 0 0 0 0 0 0 0 0

Data File N7 (dec) -- INTEGER

Offset 0 1 2 3 4 5 6 7 8 9

N7:0 0

Data File F8 -- FLOAT

Offset	0	1	2	3	4
F8:0	0	0	0		

Address/Symbol Database

Address	Symbol	Scope	Description	Sym Group	Dev. Code	ABV	BLW
B3:0/0			Rotameter				
B3:0/1			ONS				
B3:0/2			Running				
B3:0/3			ERROR				
C5:0			Oil flow time				
C5:0.ACC							
F8:0			Flow				
F8:1			K Factor				
F8:2			Arithmetic				
S:0			Arithmetic Flags				
S:0/0			Processor Arithmetic Carry Flag				
S:0/1			Processor Arithmetic Underflow/ Overflow Flag				
S:0/2			Processor Arithmetic Zero Flag				
S:0/3 S:1			Processor Arithmetic Sign Flag Processor Mode Status/ Control				
S:1/0			Processor Mode Bit 0				
S:1/1			Processor Mode Bit 1				
S:1/2			Processor Mode Bit 2				
s:1/3			Processor Mode Bit 3				
S:1/4			Processor Mode Bit 4				
S:1/5			Forces Enabled				
S:1/6			Forces Present				
s:1/7			Comms Active				
S:1/8			Fault Override at Powerup				
S:1/9			Startup Protection Fault				
s:1/10			Load Memory Module on Memory Error				
S:1/11			Load Memory Module Always				
S:1/12			Load Memory Module and RUN				
S:1/13			Major Error Halted				
S:1/14			Access Denied				
S:1/15			First Pass				
S:2/0 S:2/1			STI Pending STI Enabled				
S:2/2			STI Emabled STI Executing				
S:2/2 S:2/3			Index Addressing File Range				
S:2/4			Saved with Debug Single Step				
S:2/5			DH-485 Incoming Command Pending				
S:2/6			DH-485 Message Reply Pending				
S:2/7			DH-485 Outgoing Message Command Pending				
S:2/15			Comms Servicing Selection				
S:3			Current Scan Time/ Watchdog Scan Time				
S:4			Time Base				
S:5/0			Overflow Trap				
S:5/2			Control Register Error				
S:5/3			Major Err Detected Executing UserFault Routine				
S:5/4			M0-M1 Referenced on Disabled Slot				
S:5/8			Memory Module Boot				
S:5/9 S:5/10			Memory Module Password Mismatch STI Overflow				
S:5/10 S:5/11			Battery Low				
S:6			Major Error Fault Code				
s:7			Suspend Code				
S:8			Suspend File				
S:9			Active Nodes				
S:10			Active Nodes				
S:11			I/O Slot Enables				
S:12			I/O Slot Enables				
S:13			Math Register				
S:14			Math Register				
S:15			Node Address/ Baud Rate				
S:16			Debug Single Step Rung				
S:17			Debug Single Step File				
S:18 S:19			Debug Single Step Breakpoint Rung Debug Single Step Breakpoint File				
S:20			Debug Fault/ Powerdown Rung				
S:21			Debug Fault/ Powerdown File				
S:22			Maximum Observed Scan Time				
S:23			Average Scan Time				
S:24			Index Register				
S:25			I/O Interrupt Pending				
S:26			I/O Interrupt Pending				
S:27			I/O Interrupt Enabled				
S:28			I/O Interrupt Enabled				
S:29			User Fault Routine File Number				
s:30			STI Setpoint				
S:31			STI File Number				
S:32			I/O Interrupt Executing				
S:33			Extended Proc Status Control Word				
s:33/0			Incoming Command Pending				
S:33/1			Message Reply Pending				
S:33/2			Outgoing Message Command Pending				
S:33/3			Selection Status User/DF1				
S:33/4			Communicat Active				
S:33/5			Communicat Servicing Selection				
			- -				

Address/Symbol Database

Address	Symbol	Scope	Description	Sym Group	Dev. Code	ABV	BLW
s:33/6			Message Servicing Selection Channel 0				
s:33/7			Message Servicing Selection Channel 1				
s:33/8			Interrupt Latency Control Flag				
S:33/9			Scan Toggle Flag				
S:33/10			Discrete Input Interrupt Reconfigur Flag				
S:33/11			Online Edit Status				
S:33/12			Online Edit Status				
S:33/13 S:33/14			Scan Time Timebase Selection DTR Control Bit				
S:33/14 S:33/15			DTR Force Bit				
S:34			Pass-thru Disabled				
S:34/0			Pass-Thru Disabled Flag				
S:34/1			DH+ Active Node Table Enable Flag				
S:34/2			Floating Point Math Flag Disable, Fl				
s:35			Last 1 ms Scan Time				
S:36			Extended Minor Error Bits				
S:36/8			DII Lost				
S:36/9			STI Lost				
S:36/10			Memory Module Data File Overwrite Protection				
S:37			Clock Calendar Year				
S:38			Clock Calendar Month				
S:39 S:40			Clock Calendar Day Clock Calendar Hours				
S:41			Clock Calendar Minutes				
S:42			Clock Calendar Seconds				
S:43			STI Interrupt Time				
S:44			I/O Event Interrupt Time				
S:45			DII Interrupt Time				
S:46			Discrete Input Interrupt- File Number				
S:47			Discrete Input Interrupt- Slot Number				
S:48			Discrete Input Interrupt- Bit Mask				
S:49			Discrete Input Interrupt- Compare Value				
S:50			Processor Catalog Number				
S:51			Discrete Input Interrupt- Return Number				
S:52			Discrete Input Interrupt- Accumulat				
S:53			Reserved/ Clock Calendar Day of the Week				
S:55			Last DII Scan Time				
S:56 S:57			Maximum Observed DII Scan Time Operating System Catalog Number				
S:58			Operating System Catalog Number Operating System Series				
S:59			Operating System FRN				
S:61			Processor Series				
S:62			Processor Revision				
S:63			User Program Type				
S:64			User Program Functional Index				
S:65			User RAM Size				
S:66			Flash EEPROM Size				
S:67			Channel O Active Nodes				
S:68			Channel O Active Nodes				
S:69			Channel O Active Nodes				
S:70			Channel O Active Nodes				
S:71 S:72			Channel 0 Active Nodes Channel 0 Active Nodes				
S:73			Channel O Active Nodes				
S:74			Channel O Active Nodes				
s:75			Channel O Active Nodes				
S:76			Channel O Active Nodes				
S:77			Channel O Active Nodes				
S:78			Channel O Active Nodes				
S:79			Channel O Active Nodes				
S:80			Channel O Active Nodes				
S:81			Channel O Active Nodes				
S:82			Channel O Active Nodes				
S:83			DH+ Active Nodes				
S:84			DH+ Active Nodes				
S:85			DH+ Active Nodes				
S:86 T4:0			DH+ Active Nodes Rotameter timer				
T4:0 T4:0/DN			Vocameret fillet				
T4:0/DN			Oil flow timer				
T4:1.ACC			OII IIOW CIMCI				
U:3			INPUT				
U:4			CTRL				
U:5			PULSE				

Address Instruction Description

Group_Name Description