

Clearance

1. Frequency

- (1) Missoula Ground: 121.900

2. Procedures

- (1) When appropriate, inform pilots of the current ATIS information prior to contacting ground control.

3. IFR Routing

- (1) Initial Altitude: 14,000
- (2) West Flow
 - (a) Issue the DIDLY SID
- (3) East Flow
 - (a) All RNAV-capable aircraft: issue VICTO SID
 - (b) All Non-RNAV aircraft: issue MZULA SID
- (4) If a pilot cannot accept the above listed procedures:
 - (a) Issue the GRZLY ODP
- (5) If a pilot cannot accept a departure procedure, issue the following headings for radar vectors to their route, per their departure runway:
 - (a) Runway 12, 8 - Heading 160
 - (b) Runway 30, 26 - Heading 280

4. Standard Departure Frequencies

- (1) When appropriate, issue the following frequencies to IFR aircraft:
 - (a) Spokane Approach 124.900
- (2) When appropriate, issue the following frequencies to VFR aircraft requiring radar services after departure:
 - (a) Spokane Approach 124.900

5. VFR Routing

- (1) Not Applicable.

Ground

1. Frequency

- (1) Missoula Ground: 121.900

2. Airspace

- (1) All movement areas with the exception of active runways.

3. Procedures

- (1) Not applicable.

4. Departures

- (1) All aircraft requiring pushback onto the movement area will contact ground prior to pushback and start-up.
- (2) All aircraft will contact ground with position and ATIS prior to being issued taxi instructions.
- (3) During periods of high volumes of traffic, the published Standard Runway Assignments may be used to expedite the flow of departures.
- (4) Standard Runway Assignments
 - (a) East Operations
 - (i) Runway 08: VFR Aircraft.
 - (ii) Runway 12: All departures.
 - (b) West Operations
 - (i) Runway 26: VFR Aircraft.
 - (ii) Runway 30: All departures.

5. Arrivals

- (1) All aircraft will remain on ground frequency until off the movement area.

Local

1. Frequency

- (1) Missoula Tower (Local): 118.400

2. Airspace

- (1) Local: Runways 12/30, 8/26, and MSO Class D airspace.

3. Procedures

- (1) Runway operations

- (a) Use runway 12 (East) during calm wind operations.
 - (b) Use runway 30 (West) when the tailwind component exceeds 5 knots.

- (2) LAHSO

- (a) Not authorized.

- (3) Tower Use of Radar:

- (a) Limited

4. Departures

- (1) Departure Notification / Releases

- (a) Departure Notifications are not required, unless otherwise coordinated by TRACON.
 - (b) Departures are automatically released, unless otherwise coordinated by TRACON.

- (2) IFR Departures

- (a) Ensure aircraft turn to assigned point/heading and altitude reporting is operating prior to handoff to departure.

5. Arrivals

- (1) IFR Arrivals

- (a) N/A

- (2) Missed Approach/Go Around

- (a) Send a Missed Notification (.MA) for the aircraft executing an unplanned Missed Approach/Go Around to the appropriate TRACON sector that will be receiving the aircraft for re-sequencing.
 - (b) VFR aircraft, and/or IFR Category I/II aircraft conducting a visual approach and executing a Go-Around must be instructed to remain in the local pattern, if capable of doing so.

(c) The following is considered Primary Climb-Out procedure and does not require any special coordination with Approach Control or Strip marking (Scratchpad entries) other than the basic Missed Notification. Aircraft must not turn prior to the departure end of the runway. Comm-Change to the appropriate TRACON sector must be completed no later than 1 mile off the departure end of the runway.

(d) CLIMB OUT PROCEDURE:

(i) East Flow: Heading 160, Maintain 9,000.

(ii) West Flow: Heading 290, Maintain 9,000.

(e) VFR traffic join local pattern.

6. VFR Operations

(1) VFR Departures

(a) Depart on-course.

(b) Handoff to departure control as soon as clear of any possible conflicts.

(i) Spokane Approach 124.900

(2) VFR Arrivals

(a) Direct to airport.

(3) VFR Flight Following

(a) Ensure all aircraft requiring flight following have the appropriate scratchpad entry prior to handoff to departure.

TRACON

1. Frequency

(1) Spokane Approach 124.900

2. Airspace

(1) As depicted up to and including 14,000

3. IFR Procedures

(1) East Flow

(a) All arrivals shall be cleared direct MSO VOR or an appropriate IAF.

(2) West Flow

- (a) All arrivals shall be cleared direct MSO VOR or an appropriate IAF.