

RaceDay – API Endpoint Plan

This endpoint plan is designed to cover the required RaceDay functionality: authentication, user profiles, events, categories, event enrolments, and results. The implemented API in Part 2 should follow these routes and request/response structures as closely as possible.

HTTP Method	Route	Description	Role Required	Request Body (if any)	Expected Response
POST	/api/auth/register	Register a new user account.	Public	{"name":"string","email":"string","password":"string","phone":"string"}	201 Created: user details and authentication token; 400 for validation errors; 409 if email already exists.

POST	/api/auth/login	Authenticate an existing user.	Public	{"email":"string","password":"string"}	200 OK: authentication token and user details; 401 for invalid credentials.
GET	/api/users/me	Get the authenticated user profile.	Authenticated	None	200 OK: current user profile; 401 if not authenticated.
PUT	/api/users/me	Update the authenticated user profile.	Authenticated	{"name":"string","email":"string","phone":"string","address":"string"}	200 OK: updated profile; 400 for invalid data; 401 if not authenticated.

GET	/api/events	List available races/events.	Public	None	200 OK: array of events with date, location, entry fee, capacity and status.
GET	/api/events/{eventId}	Get details for one event.	Public	None	200 OK: event details; 404 if event does not exist.

POST	/api/events	Create a new race/event .	Organizer/ Admin	{ "race_name": "string", "description": "string", "race_date": "datetime", "location_id": "integer", "race_type": "string", "entry_fee": "decimal", "capacity": "integer", "status": "string" }	201 Created: created event; 400 for validation errors; 401/403 if role is insufficient .
				tus": "string" }	

PUT	/api/events/{eventId}	Update an existing race/event .	Organizer/Admin	{ "race_name": "string", "description": "string", "race_date": "datetime", "location_id": "integer", "race_type": "string", "entry_fee": "decimal", "capacity": "integer", "status": "string" }	200 OK: updated event; 404 if not found; 403 if not permitted.
				tus": "string"}	
DELETE	/api/events/{eventId}	Cancel/remove an event.	Organizer/Admin	None	204 No Content on success; 404 if not found; 403 if not permitted.

GET	/api/events/{eventId}/categories	List categories for an event.	Public	None	200 OK: array of categories ; 404 if event does not exist.
POST	/api/events/{eventId}/categories	Create a category for an event.	Organizer/Admin	{"category_name":"string","gender_eligibility":"string", "age_from":"integer", "age_to":"integer"}	201 Created: created category; 400 for validation errors; 403 if not permitted.
PUT	/api/categories/{categoryId}	Update an event category.	Organizer/Admin	{"category_name":"string","gender_eligibility":"string", "age_from":"integer", "age_to":"integer"}	200 OK: updated category; 404 if not found; 403 if not permitted.

DELETE	/api/categories/{categoryId}	Delete an event category.	Organizer/Admin	None	204 No Content on success; 404 if not found; 403 if not permitted.
POST	/api/events/{eventId}/enrolments	Enrol/register the authenticated user for an event.	Authenticated	{"category_id":"integer"}	201 Created: enrolment/registration details and bib number/status; 400 if event is full or data is invalid; 409 if already enrolled.

GET	/api/users/ me/enrolments	List the authenticated user's event enrolments.	Authenticated	None	200 OK: array of the user's enrolments with event and category information.
GET	/api/events/{eventId}/enrolments	List enrolments for an event.	Organizer/Admin	None	200 OK: array of enrolments; 403 if role is insufficient.
GET	/api/enrolments/{enrolmentId}	Get one enrolment/registration.	Authenticated	None	200 OK: enrolment details; 403 if the enrolment belongs to another user; 404 if not found.

DELETE	/api/enrolments/{enrolmentId}	Cancel an event enrolment.	Authenticated	None	204 No Content on success; 404 if not found; 403 if not the enrolment owner.
GET	/api/events/{eventId}/results	View results for an event.	Public	None	200 OK: results ordered by finishing position/time; 404 if event does not exist.
GET	/api/results/{resultId}	View a single race result.	Public	None	200 OK: result details including finish time, position and status; 404 if not found.

POST	/api/events/{eventId}/results	Record a result for an enrolled participant .	Organizer/Admin	{"enrolment_id":"integer","finish_time":"datetime","overall_position":"integer","category_position":"integer","chip_time":"datetime","status":"string"}	201 Created: result record; 400 for invalid result/enrolment; 403 if role is insufficient .
PUT	/api/results/{resultId}	Update a recorded result.	Organizer/Admin	{"finish_time":"datetime","overall_position":"integer","category_position":"integer","chip_time":"datetime","status":"string"}	200 OK: updated result; 404 if not found; 403 if not permitted.

Role Definitions

- **Public:** No login required.
- **Authenticated:** Any logged-in user.
- **Organizer/Admin:** User must have an organizer or administrator role.