Question 1

```
#include <iostream>
using namespace std;
int main()
{
cout<<"The Prophet (SallAllahu Alayhi Wa Sallam) said:"<<endl;
cout<<"\"Lying is wrong, except in three things: the lie of a man to his wife to make her content with him; a lie in war, for war is deception; or a lie to settle trouble between people.\"\n[Ahmad, 6.459.H]"<<endl;
return 0;
}
```

Question 2

```
#include <iostream>
using namespace std;
int main()
{
int sum = 0, n = 0, avg =0;
for( int i = 0; i <=500 ; i += 2)
{
   sum += i;
   n = i;
}
avg = sum/250;
cout<<sum <<" " << avg;
return 0;
}
```

Question 3

```
#include <iostream>
using namespace std;

int main() {
        int n;
        cout << "Enter a positive integer: ";
        cin >> n;

        if (n < 0) {
        cout << "Invalid Input" << endl;
        } else {
        int factorial = 1;

        for (int i = 1; i <= n; i++) {
```

```
        factorial *= i;
        }

        cout << n << "! = " << factorial << endl;
        }

        return 0;
}
```

Question 4

```
#include <iostream>
using namespace std;

int main() {
        int num;
        bool isPrime = true;

        cout << "Enter a number: ";
        cin >> num;

        if (num <= 1) {
        isPrime = false;
        } else {
        for (int i = 2; i * i <= num; i++) {
        if (num % i == 0) {
                isPrime = false;
                break;
        }
        }
        }

        if (isPrime) {
        cout << "You have entered a prime number" << endl;
        } else {
        cout << "You have entered a non-prime number" << endl;
        }

        return 0;
}
```

Question 5

```
#include <iostream>
```

```
using namespace std;

int main() {
	int number;

	cout << "Enter a number: ";
	cin >> number;

	cout << "Multiplication table for " << number << ":\n";

	for (int i = 1; i <= 12; i++) {
	cout << number << "x" << i << "=" << number * i << endl;
	}

	return 0;
}
```

Question 6

```
#include <iostream>
using namespace std;

int main() {
	int positiveCount = 0;
	int negativeCount = 0;
	int zeroCount = 0;

	for (int i = 0; i < 10; i++) {
	int value;
	cout << "Enter value " << i + 1 << ": ";
	cin >> value;

	if (value > 0) {
	positiveCount++;
	} else if (value < 0) {
	negativeCount++;
	} else {
	zeroCount++;
	}
	}

	cout << "Total positive numbers: " << positiveCount << endl;
	cout << "Total negative numbers: " << negativeCount << endl;
	cout << "Total zeros: " << zeroCount << endl;
```

```
	return 0;
}
```

Question 7

```
#include <iostream>
using namespace std;

int main() {

	string smiley = ":-)";


	for (int row = 1; row <= 25; row++) {
	for (int col = 1; col <= 80; col++) {
	cout << smiley;
	}
}
	return 0;
}
```

Question 8

```
#include <iostream>
#include <cmath>

using namespace std;

int main() {
	cout << "Armstrong numbers between 99 and 999 are:" << endl;

	for (int num = 99; num <= 999; num++) {
	int originalNum = num;
	int numDigits = 0;
	int armstrongSum = 0;


	int temp = num;
	while (temp != 0) {
	numDigits++;
	temp /= 10;
	}
```

```
        temp = num;


        while (temp != 0) {
        int digit = temp % 10;
        armstrongSum += pow(digit, numDigits);
        temp /= 10;
        }


        if (armstrongSum == originalNum) {
        cout << originalNum << " ";
        }
        }

        cout << endl;

        return 0;
}
```