

The screenshot displays the Postman API client interface. The left sidebar shows the 'My Workspace' with a collection named 'Petstore V3' containing a 'User' folder. The 'User' folder is expanded, showing several endpoints, including 'GET Logs out current logged in u...'. The main panel shows the selected endpoint: 'GET https://petstore.swagger.io/v2/user/logout'. The 'Send' button is visible. Below the URL bar, the 'Query Params' table is empty. The 'Body' tab is selected, showing a JSON response in 'Pretty' format: 

```
1 {
2   "code": 200,
3   "type": "unknown",
4   "message": "ok"
5 }
```

 The status bar at the bottom indicates '200 OK', '567 ms', and '370 B'. The bottom of the interface shows various toolbars including 'Find and replace', 'Console', 'Postbot', 'Runner', 'Start Proxy', 'Cookies', 'Vault', and 'Trash'.

My Workspace

New Import

Overly Petstore V3 POST Create GET Get u GET Logs GET Logs PUT Update

Save Share

GET https://petstore.swagger.io/v2/user/logout

Send

Params Authorization Headers (6) Body Scripts Tests Settings Cookies

Query Params

Key	Value	Description	Bulk Edit
Key	Value	Description	

View more actions

Body Cookies Headers (8) Test Results 200 OK 567 ms 370 B

Pretty Raw Preview Visualize JSON

```
1 {
2   "code": 200,
3   "type": "unknown",
4   "message": "ok"
5 }
```

Online Find and replace Console Postbot Runner Start Proxy Cookies Vault Trash