SpectraPlume

AUTONOMOUS SATELLITE METHANE INTELLIGENCE

Abstract

SpectraPlume is an autonomous AI pipeline detecting and quantifying super-emitter methane (CH4) plumes from NASA EMIT hyperspectral satellite data. Fusing sparsity-constrained matched filtering with a 3D Spatial-Spectral CNN, the system isolates the 2.3 µm absorption band, achieving an F1-score of 0.942, an 85 kg/h detection threshold, and automated flux quantification via Integrated Mass Enhancement.

Introduction

The SpectraPlume Remote Sensing Pipeline: An autonomous satellite intelligence architecture resolving the global super-emitter crisis:

- The 84× Methane Threat: Methane drives 30% of global warming, with 84× the warming power of CO2CO_2CO2 over 20 years.
- Super-Emitter Impact: Point sources (<10% of fossil and waste sites) cause >50% of all methane emissions.
- Monitoring Bottleneck: Manual surveys are slow, while existing satellites suffer high false alarms over bright soil.
- NASA EMIT Advantage: 285 spectral channels (381–2493 nm) on the ISS enable precise short-wave infrared gas detection.

Methods and Materials

- Data Ingestion: Automated harvesting of NASA EMIT Level 1B calibrated radiance cubes (60m GSD).
- Matched Filter (SVD): Covariance decomposition isolating methane column enhancement (Δμ in ppm·m).
- 3D Spatial-Spectral CNN: Attention U-Net modeling fluid plume dispersion and eliminating false alarms.
- Mass Flux Rate (IME): Coupled with ECMWF ERA5 10m wind fields to calculate emission rates in kg/h.


Logos	Name	Purpose	Notes
	NASA EMIT L1B	Hyperspectral Input	285 SWIR bands, 60m resolution
	PyTorch 3D-CNN	Plume Segmentation	Spatial-spectral attention U-Net
	HITRAN Database	Spectroscopy	Methane absorption cross-sections
	ERA5 Wind Model	Meteorological Coupling	10m wind vectors for IME flux rate


Results and data analysis


F1-Score: 0.942 on NASA Data: Validated on 42 verified NASA EMIT super-emitter swaths. SpectraPlume achieved 96.1% precision and 92.4% recall, significantly outperforming traditional 2D matched filters.

85 kg/h Threshold & Terrain Immunity: Detection limit lowered to 85 kg/hkg/hkg/h at 3 m/sm/sm/s wind. The 3D-CNN reduced false alarms over desert sand and urban roofs by 78.4%.

Sub-12 Minute Processing: End-to-end ingestion, atmospheric filtering, segmentation, and GeoJSON plume vectorization executes in <12 minutes per orbit tile for rapid leak notification.







Key Partners

- Space & Science Agencies: NASA JPL (EMIT open data feed), ESA Copernicus (Sentinel-5P), and UNEP IMEO observatory.
- National Energy Operators: Gas transmission companies (EGAS, EGPC) for pipeline mapping and ground-truth telemetry access.

Key Activities

- Autonomous Satellite Ingestion: Automated harvesting and calibration of NASA EMIT L1B SWIR radiance cubes via Earthdata API.
- 3D-CNN Model Inference: Spatial-spectral neural segmentation filtering 78.4% of false alarms over bright desert soil.
- Wind-Coupled Flux Modeling: Coupling 10m ERA5 wind vectors with Integrated Mass Enhancement (IME) to compute hourly kg/h rates.

Key Resources

- Proprietary AI & Physics Core: Pre-trained 3D-Spatial-Spectral Attention U-Net and HITRAN methane absorption cross-section matrix.
- Scalable Cloud Architecture: Elastic serverless GPU compute nodes (NVIDIA Tensor Core) and Cloud-Optimized GeoTIFF storage.
- Open NASA EMIT Archive: Free continuous 285-band spaceborne hyperspectral telemetry from the International Space Station.

Value Propositions

- Zero Orbital CapEx: Exploits existing NASA ISS instruments, delivering global satellite monitoring at zero hardware launch cost.
- Rapid Sub-Hourly Alerts: Compresses leak detection from weeks to <15 minutes post-ingestion, preventing massive gas loss.
- High-Albedo Terrain Immunity: Proprietary physics-AI fusion eliminates false positives across desert sand and industrial metal roofs.

Customer Relationship

- Automated Escalation Alerts: Instant SMS, email, and SCADA-compatible webhook triggers for super-emitter leaks exceeding threshold.
- Transparent Open Verification: Reproducible open-source methodology providing trusted third-party auditability for ESG compliance.

Channels

- Interactive WebGIS Console: Browser dashboard with live plume overlays, wind vectors, time-series history, and GeoJSON export.
- Enterprise SCADA REST API: Direct machine-to-machine telemetry feed into national pipeline control rooms and regulatory systems.

Customer Segments

- National Oil & Gas Operators: Midstream and upstream energy firms seeking immediate fugitive leak mitigation and commodity recovery.
- Municipal Landfill Authorities: Waste management facilities tracking bio-methane emissions to optimize gas-to-energy capture systems.
- Carbon Registries & ESG Regulators: Verification bodies (Verra, Gold Standard) and environmental ministries auditing climate compliance pledges.

Cost Structure

- Cloud GPU Inference OpEx: Serverless inference processing orbital tiles at $0.14 per 1,000 km² (~$180/month national coverage).
- Geospatial Storage & Ingestion: Cloud-Optimized GeoTIFF hosting, automated S3 pipelines, and spatial tile serving (~$45/month).
- Field Ground-Truth Validation: Annual optical gas imaging (OGI) sensor cross-checks and laser sniffing calibration ($1,200/year).

Revenue Streams

- Enterprise SaaS Subscriptions: Tiered 24/7 pipeline network monitoring and SCADA integration ($4,500/month Enterprise Grid Tier).
- Digital MRV Carbon Verification: Certified per-audit proof reports for verified methane capture credit projects ($1,500/audit).
- Commodity Gas Recovery ROI: Stopping a single 1,000 kg/h super-emitter saves ~$18,000/day in recovered natural gas.
- Financial Feasibility Summary: 42-day payback period, 480% first-year ROI, and $1.85/ton CO2e average abatement cost.

Conclusions

SpectraPlume demonstrates that fusing atmospheric physics with 3D Spatial-Spectral AI unlocks automated, real-time super-emitter methane surveillance from open NASA EMIT satellite data. By achieving an 85 kg/h detection threshold and an F1-score of 0.942, the system enables rapid industrial intervention to eliminate high-impact greenhouse gas leaks.

Recommendation

We recommend expanding SpectraPlume to multi-satellite constellations (Sentinel-2 and Landsat-9) for higher temporal revisit rates. Future development will integrate local surface wind sensors, airborne AVIRIS-NG validation flights, and automated SCADA API triggers for immediate industrial valve shutoff upon leak detection.

References

- Thorpe, A. K., et al. (2023). Methane emissions detected by NASA EMIT. Science Advances, 9(32).
- Frankenberg, C., et al. (2016). Airborne methane remote sensing with AVIRIS-NG. Remote Sens. Environ.
- Varon, D. J., et al. (2018). Quantifying methane point sources from satellites. Atmos. Meas. Tech.
- Thompson, D. R., et al. (2015). Real-time spectrometer processing for methane. IEEE TGRS.
- Jacob, D. J., et al. (2022). Quantifying atmospheric methane emissions. Atmos. Chem. Phys.
- Cusworth, D. H., et al. (2021). Intermittent methane emissions from oil and gas. Environ. Sci. Technol. Lett.

Acknowledgement

We sincerely thank Fathallah International Applied Technology School (iATS), the Ministry of Education, and Galaxy for Development. Special thanks to our academic mentors, and to the NASA JPL EMIT Team for open satellite data access :)