## **Day5** Admin Linux

**Create a supplementary (Secondary) group called pgroup with group ID of 30000?** to create new group we can use **groupadd** command and to specify a group id we can use **-g** so the command will be:

sudo groupadd -g 30000 pgroup.

## Lock any user created account so he can't log in?

To lock any user account you can use -l and to unlock -u

sudo passwd -l username sudo passwd -u username

## **Delete user account and group?**

**Sudo userdel username ------** remove user but home still exist **sudo userdel -r username -----** remove user and his home directory **sudeo groupdel groupname -----** → remove group

## State the difference between adduser and useradd with example shown?

Adduser: is like bash script run and has an interactive way to add a new user. Useradd: is a basic command and you have to set this user details manually.

```
muhammed: ~
 nuhammed@muhammed-Inspiron-5570:~$ sudo adduser myuser
[sudo] password for muhammed:
Adding user `myuser'
Adding new group `myuser' (1001) ...
Adding new user `myuser' (1001) with group `myuser' ...
Creating home directory `/home/myuser' ...
Copying files from `/etc/skel' ...
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
Sorry, passwords do not match.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
Changing the user information for myuser
Enter the user information for myuser
Enter the new value, or press ENTER for the default
Full Name []: This is test user
Room Number []: 21
Work Phone []: 01127880767
Home Phone []: 33550146
Other []:
Is the information correct? [Y/n] y
 nuhammed@muhammed-Inspiron-5570:~$
```