Difference Betwee	en \$_SERVER['PHP_SEL	F'] and \$_SER\	VER['REQUEST_URI']			
1. \$_SERVER['PHF	P_SELF']:					
- Returns the path of the current executing PHP file (relative to the root).						
- Does NOT includ	de the query string.					
Example:						
URL: https://example.com/laracast-php/Partials/about.php						
Result: /laracast-php/Partials/about.php						
2. \$_SERVER['REQUEST_URI']:						
- Returns the complete requested URI including query string.						
- More accurate for matching current pages.						
Example:						
URL: https://example.com/laracast-php/Partials/about.php?id=5⟨=en						
Result: /laracast-php/Partials/about.php?id=5⟨=en						
Comparison Table:						
Feature	PHP_SELF	REQUES	T_URI	1		
File path	☐ Yes	🛮 Yes	1			
Includes query s	string 🛘 No	☐ Yes		1		
Use in Navbar active Possible but limited More accurate and preferred [

Starts from root			1

Conclusion:

- Use REQUEST_URI when you need to compare full URL paths or handle active states in navigation.
- PHP_SELF is useful when you only care about the script file path itself.

SERVER['PHP_SELF'] و SERVER['REQUEST_URI'] نىب توافت 1. \$_SERVER['PHP_SELF']: (تیاس هشیر هب تبسن) ار هدشارجا PHP لیاف ریسم -ىمرب .دنادرگ لماش string query ىمن .دوش :لاثم : https://example.com/laracast-php/Partials/about.php امحىتن: /laracast-php/Partials/about.php Y. \$_SERVER['REQUEST_URI']:

- کی کی آرب تساوخرد کی اوخرد کی اوخرد

قىقد

تسا رتهب لاعف کنیل و تاحفص رت. :لاثم https://example.com/laracast-php/Partials/about.php?id=5&lang=en: سردآ امجىتى: /laracast-php/Partials/about.php?id=5&lang=en :ەسىاقم لودج یگژیو | | REQUEST_URI | PHP_SELF |-----| ەلب 🛘 ا الى اف رىسم ا ا الى اف رىسم ا ا ەل ب 🛘 ا دودحم الاعف کانیل یارب بسانم قىقد 🛮 رتەب و رت ەلب 🏾 📗 تىاس ەشىر زا غورش | ەل ب 🛘 ا ەجىتن :یریگ ر گا ىم زا ،دیزاسب ونم رد لاعف کنیل ای دینک یسررب ار URL لماک ریسم دیهاوخ .دىنک ەدافتسا REQUEST_URI

- دیراد زاین ار لیاف ریسم طقف رگا یم

دنک.