Processes

Chapter 3

Process Concept

- An operating system executes a variety of programs:
  - Batch system – jobs
  - Time-shared systems – user programs or tasks
- the terms ***job*** and ***process*** are used almost interchangeably

Process in Memory

- **Process –** a program in execution; process execution must progress in sequential fashion

A process includes:

– program counter
– stack



Two-State Process Model

- Process may be in one of two states
  - Running
  - Not-running



A Five-State Model

- As a process executes, it changes *state*
  - **new**: The process is being created
  - **running**: Instructions are being executed
  - **Waiting (Blocked)**: The process is waiting for some event to occur
  - **ready**: The process is waiting to be assigned to a processor
  - **terminated**: The process has finished execution

Diagram of Process State



Process Description



Operating System Control Structures

- Information about the current status of each process and resource
- Tables are constructed for each entity the operating system manages

Operating System Control Structures (cont.)



User Processes in Virtual Memory



Process Control Block (PCB)

- Information associated with each process
  - Process state
  - Program counter
  - CPU registers
  - CPU scheduling information
  - Memory-management information
  - Accounting information
  - I/O status information



Context Switch

- When CPU switches to another process, the system must save the state of the old process and load the saved state for the new process
- Context-switch time is overhead; the system does no useful work while switching
- Time dependent on hardware support

CPU Switch From Process to Process



The Role of the Process Control Block



Process Scheduling Queues

- **Job queue** – set of all processes in the system
- **Ready queue** – set of all processes residing in main memory, ready and waiting to execute
- **Device queues** – set of processes waiting for an I/O device
- Processes migrate among the various queues

Using Two Queues



Ready Queue And Various I/O Device Queues



Representation of Process Scheduling



Schedulers

- **Long-term scheduler** (or job scheduler) – selects which processes should be brought into the ready queue
- **Short-term scheduler** (or CPU scheduler) – selects which process should be executed next and allocates CPU

Addition of Medium Term Scheduling



Schedulers (Cont.)

- Short-term scheduler is invoked very frequently (milliseconds) $\Rightarrow$ (must be fast)
- Long-term scheduler is invoked very infrequently (seconds, minutes) $\Rightarrow$ (may be slow)
- The long-term scheduler controls the *degree of multiprogramming*

Schedulers (Cont.)

- **I/O-bound process** – spends more time doing I/O than computations, many short CPU bursts
- **CPU-bound process** – spends more time doing computations; few very long CPU bursts

Process Control: Modes of Execution

- User mode
  - Less-privileged mode
  - User programs typically execute in this mode
- System mode, control mode, or kernel mode
  - More-privileged mode
  - Kernel of the operating system

Process Creation

- Parent process create children processes, which, in turn create other processes, forming a tree of processes
- Resource sharing
  - Parent and children share all resources
  - Children share subset of parent's resources
  - Parent and child share no resources

Process Creation (Cont.)

- Execution
  - Parent and children execute concurrently
  - Parent waits until children terminate
- Address space
  - Child duplicate of parent
  - Child has a program loaded into it
- UNIX examples
  - **fork** system call creates new process
  - **exec** system call used after a **fork** to replace the process' memory space with a new program

Process Creation



Process Creation in POSIX

```
#include <sys/types.h>
#include <stdio.h>
#include <unistd.h>

int main()
{
pid_t pid;

    /* fork a child process */
    pid = fork();

    if (pid < 0) { /* error occurred */
       fprintf(stderr, "Fork Failed");
       exit(-1);
    }
    else if (pid == 0) { /* child process */
       execlp("/bin/ls","ls",NULL);
    }
    else { /* parent process */
       /* parent will wait for the child to complete */
       wait(NULL);
       printf("Child Complete");
       exit(0);
    }
}
```

Process Termination

- Process executes last statement and asks the operating system to delete it (**exit**)
  - Output data from child to parent (via **wait**)
  - Process' resources are deallocated by operating system

Process Termination (cont.)

- Parent may terminate execution of children processes (**abort**)
  - Child has exceeded allocated resources
  - Task assigned to child is no longer required
  - If parent is exiting
    - Some operating system do not allow child to continue if its parent terminates
      - All children terminated - ***cascading termination***

Interprocess Communication

Message Passing



Shared Memory



Cooperating Processes

- **Independent** process cannot affect or be affected by the execution of another process
- **Cooperating** process can affect or be affected by the execution of another process
- Advantages of process cooperation
  - Information sharing
  - Computation speed-up
  - Modularity
  - Convenience

Producer-Consumer Problem

- Paradigm for cooperating processes, *producer* process produces information that is consumed by a *consumer* process
  - *unbounded-buffer* places no practical limit on the size of the buffer
  - *bounded-buffer* assumes that there is a fixed buffer size

Bounded-Buffer – Shared-Memory Solution

- Shared data

```
#define BUFFER_SIZE 10
typedef struct {
    . . .
} item;

item buffer[BUFFER_SIZE];
int in = 0;
int out = 0;
```

- Solution is correct, but can only use BUFFER_SIZE-1 elements

Bounded-Buffer – Shared-Memory Solution

```
public interface Buffer
{
   // producers call this method
   public abstract void insert(Object item);

   // consumers call this method
   public abstract Object remove();
}
```

Bounded-Buffer – Shared-Memory Solution

```
public class BoundedBuffer implements Buffer
{
    private static final int BUFFER_SIZE = 5;
    private int count; // number of items in the buffer
    private int in; // points to the next free position
    private int out; // points to the next full position
    private Object[] buffer;

    public BoundedBuffer() {
       // buffer is initially empty
       count = 0;
       in = 0;
       out = 0;

       buffer = new Object[BUFFER_SIZE];
    }

    // producers calls this method
    public void insert(Object item) {
       // Figure 3.16
    }

    // consumers calls this method
    public Object remove() {
       // Figure 3.17
    }
}
```

Bounded-Buffer -- insert() method

```
public void insert(Object item) {
   while (count == BUFFER_SIZE)
        ; // do nothing -- no free buffers

   // add an item to the buffer
   ++count;
   buffer[in] = item;
   in = (in + 1) % BUFFER_SIZE;
}
```

Bounded-Buffer - remove() method

```
public Object remove() {
   Object item;

   while (count == 0)
        ; // do nothing -- nothing to consume

   // remove an item from the buffer
   --count;
   item = buffer[out];
   out = (out + 1) % BUFFER_SIZE;

   return item;
}
```

Interprocess Communication – Message Passing

- Mechanism for processes to communicate and to synchronize their actions
- Message system – processes communicate with each other without resorting to shared variables
- IPC facility provides two operations:
  - **send**(*message*) – message size fixed or variable
  - **receive**(*message*)
- If *P* and *Q* wish to communicate, they need to:
  - establish a *communication link* between them
  - exchange messages via send/receive
- Implementation of communication link
  - physical (e.g., shared memory, hardware bus)
  - logical (e.g., logical properties)

Implementation Questions

- How are links established?
- Can a link be associated with more than two processes?
- How many links can there be between every pair of communicating processes?
- What is the capacity of a link?
- Is the size of a message that the link can accommodate fixed or variable?
- Is a link unidirectional or bi-directional?

Direct Communication

- Processes must name each other explicitly:
  - **send** (*P, message*) – send a message to process P
  - **receive**(*Q, message*) – receive a message from process Q
- Properties of communication link
  - Links are established automatically
  - A link is associated with exactly one pair of communicating processes
  - Between each pair there exists exactly one link
  - The link may be unidirectional, but is usually bi-directional

Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Each mailbox has a unique id
  - Processes can communicate only if they share a mailbox
- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional

Indirect Communication

- Operations
  - create a new mailbox
  - send and receive messages through mailbox
  - destroy a mailbox
- Primitives are defined as:

send(*A, message*) – send a message to mailbox A

receive(*A, message*) – receive a message from mailbox A

Indirect Communication

- Mailbox sharing
  - P_1, P_2, and P_3 share mailbox A
  - P_1, sends; P_2 and P_3 receive
  - Who gets the message?
- Solutions
  - Allow a link to be associated with at most two processes
  - Allow only one process at a time to execute a receive operation
  - Allow the system to select arbitrarily the receiver. Sender is notified who the receiver was.

Synchronization

- Message passing may be either blocking or non-blocking
- **Blocking** is considered **synchronous**
  - **Blocking send** has the sender block until the message is received
  - **Blocking receive** has the receiver block until a message is available
- **Non-blocking** is considered **asynchronous**
  - **Non-blocking** send has the sender send the message and continue
  - **Non-blocking** receive has the receiver receive a valid message or null

Buffering

- Queue of messages attached to the link; implemented in one of three ways
  1. Zero capacity – 0 messages
     Sender must wait for receiver (rendezvous)
  2. Bounded capacity – finite length of *n* messages
     Sender must wait if link full
  3. Unbounded capacity – infinite length
     Sender never waits