

Orca-Tech Website API Specification

Audience: Backend team
Client: Orca-Tech public website (en / ar)
Version: 1.0
Date: 18 September 2026
Status: Ready for implementation

This document is the contract for making site content and forms dynamic. Field names, enums, and validation rules match the current frontend.

1. Overview

Area	Endpoints
Settings	GET /api/settings
About — By the numbers	GET /api/about/stats
Careers	GET /api/careers , GET /api/careers/:id , POST /api/careers/apply
Articles	GET /api/articles , GET /api/articles/:slug
Projects	GET /api/projects , GET /api/projects/:slug
Contact	POST /api/contact

2. Conventions

2.1 Base URL

```
https://{API_HOST}/api
```

All endpoints below are relative to this base.

2.2 Locales

The website is bilingual. **CMS GET responses must return both languages.** Do not localize on the server using `Accept-Language` .

```
LocalizedString = {  
  en: string  
  ar: string  
}
```

2.3 Success envelope (GET)

```
{
  "success": true,
  "data": {}
}
```

2.4 Success envelope (POST)

```
{
  "success": true,
  "message": {
    "en": "Message received.",
    "ar": "تم استلام الرسالة."
  }
}
```

2.5 Validation error

HTTP 400

```
{
  "success": false,
  "errors": {
    "email": ["Enter a valid email."]
  }
}
```

2.6 Not found

HTTP 404

```
{
  "success": false,
  "message": {
    "en": "Not found.",
    "ar": "غير موجود."
  }
}
```

2.7 Shared enums

```
ServiceId =  
  | "ecommerce"  
  | "shopifyWordpress"  
  | "engineering"  
  | "seo"  
  | "ai"  
  | "cloud"  
  | "hosting"  
  | "data"  
  
IndustryId =  
  | "retail"  
  | "fintech"  
  | "healthcare"  
  | "logistics"  
  | "telecom"  
  | "education"  
  | "realEstate"  
  | "hospitality"  
  
ArticleCategory = "tech" | "ai" | "design" | "caseStudies"
```

3. Settings

Used by footer, contact sidebar, SEO, map, and social icons.

GET /api/settings

Response data

```
{
  siteName: string
  legalName: string
  description: LocalizedString
  seo: {
    defaultTitle: LocalizedString
    defaultDescription: LocalizedString
    keywords: LocalizedString
  }
  emails: {
    info: string
    sales: string
  }
  phones: string[]
  address: {
    street: LocalizedString
    locality: LocalizedString
    countryCode: string
    formatted: LocalizedString
  }
  map: {
    lat: number
    lng: number
  }
  social: {
    facebook: string | null
    instagram: string | null
    linkedin: string | null
  }
}
```

Example

```

{
  "success": true,
  "data": {
    "siteName": "Orca-Tech",
    "legalName": "Orca Technology Group",
    "description": {
      "en": "Orca-Tech is a software house building modern platforms, commerce experiences, and intelligent systems for teams that move fast.",
      "ar": "أوركا-تك دار برمجيات تبني منصات حديثة وتجارب تجارة وأنظمة ذكية للفرق السريعة."
    },
    "seo": {
      "defaultTitle": {
        "en": "Orca-Tech – Software Engineering & Digital Products",
        "ar": "أوركا-تك – هندسة البرمجيات والمنتجات الرقمية"
      },
      "defaultDescription": {
        "en": "Orca-Tech is a Dubai software house building e-commerce, mobile apps, SEO, AI products, and cloud platforms for ambitious companies.",
        "ar": "أوركا-تك دار برمجيات في دبي تبني التجارة الإلكترونية وتطبيقات الجوال وتحسين محركات البحث، ومنصات الذكاء الاصطناعي والمنصات السحابية."
      },
      "keywords": {
        "en": "Orca-Tech, software house Dubai, e-commerce development, SEO, React Native, Flutter, AI products, cloud infrastructure, Next.js, Shopify",
        "ar": "أوركا-تك، دار برمجيات دبي، تطوير التجارة الإلكترونية، تحسين محركات البحث، Flutter، React Native، الذكاء الاصطناعي، البنية السحابية، Next.js، Shopify"
      }
    },
    "emails": {
      "info": "info@orcatechltd.com",
      "sales": "sales@orcatechltd.com"
    },
    "phones": ["+971 4 000 0000"],
    "address": {
      "street": { "en": "Port Fouad", "ar": "بورفؤاد" },
      "locality": { "en": "Port Said", "ar": "بورسعيد" },
      "countryCode": "EG",
      "formatted": {
        "en": "Port Fouad, Port Said, Egypt",
        "ar": "بورفؤاد، بورسعيد، مصر"
      }
    },
    "map": {
      "lat": 31.239621138513407,
      "lng": 32.320161845413416
    },
    "social": {
      "facebook": "https://www.facebook.com/",
      "instagram": "https://www.instagram.com/",
      "linkedin": "https://www.linkedin.com/company/orca-techs/"
    }
  }
}

```

Notes

- `phones` is an array so more numbers can be added later.
- Social URLs must be absolute. Use `null` if a platform is not configured; the frontend will hide that icon.
- `map.lat` / `map.lng` drive the contact-page embed.

4. About — By the numbers

Used by the stats row on the About page. The UI animates each `value` and appends `suffix`.

GET `/api/about/stats`

Response `data`

```
{
  title: LocalizedString
  items: Array<{
    id: string
    value: number
    suffix: string
    label: LocalizedString
  }>
}
```

Example

```
{
  "success": true,
  "data": {
    "title": { "en": "By the numbers", "ar": "بالأرقام" },
    "items": [
      {
        "id": "years",
        "value": 12,
        "suffix": "+",
        "label": { "en": "Years of experience", "ar": "سنوات خبرة" }
      },
      {
        "id": "projects",
        "value": 140,
        "suffix": "+",
        "label": { "en": "Projects delivered", "ar": "مشاريع منجزة" }
      },
      {
        "id": "clients",
        "value": 80,
        "suffix": "+",
        "label": { "en": "Clients served", "ar": "عملاء" }
      },
      {
        "id": "team",
        "value": 45,
        "suffix": "+",
        "label": { "en": "Specialists", "ar": "متخصصون" }
      }
    ]
  }
}
```

Notes

- Current UI expects four items.
- `id` should stay stable (`years` , `projects` , `clients` , `team`) if used as a React key.

5. Careers

5.1 Listing — GET /api/careers

Optional query: `department`, `location`, `type`.

An empty `items` array is valid. The careers page already has an empty state that points to a general application.

Response data

```
{
  items: Array<{
    id: string
    title: LocalizedString
    department: LocalizedString
    location: LocalizedString
    type: LocalizedString
    summary: LocalizedString
  }>
}
```

Example item

```
{
  "id": "senior-frontend",
  "title": { "en": "Senior Frontend Engineer", "ar": "مهندس واجهات أول" },
  "department": { "en": "Engineering", "ar": "الهندسة" },
  "location": { "en": "Remote / Dubai", "ar": "عن بُعد / دبي" },
  "type": { "en": "Full-time", "ar": "دوام كامل" },
  "summary": {
    "en": "Lead Next.js and design-system work across client products – performance, accessibility, and production polish.",
    "ar": "وأنظمة التصميم عبر منتجات العملاء – أداء وإتاحة ولمسة إنتاج Next.js قد عمل"
  }
}
```

Current role ids in the site

- `senior-frontend`
- `senior-mobile`
- `product-designer`
- `product-manager`

5.2 Details — GET /api/careers/:id

Return `404` if the role is missing or closed.

Response data

```
{
  id: string
  title: LocalizedString
  department: LocalizedString
  location: LocalizedString
  type: LocalizedString
  summary: LocalizedString
  description: LocalizedString
  responsibilities: LocalizedString[]
  requirements: LocalizedString[]
}
```

`description`, `responsibilities`, and `requirements` are for a richer job page. Listing fields must still be present.

5.3 Apply — `POST /api/careers/apply`

Content-Type: `multipart/form-data` because of the optional CV file.

Request fields

```
{
  name: string
  email: string
  phone: string | null
  role: string
  linkedin: string | null
  portfolio: string | null
  message: string
  cv: File | null
}
```

JSON equivalent (when no file)

```
{
  "name": "Sara Ahmed",
  "email": "sara@example.com",
  "phone": "+20 100 000 0000",
  "role": "senior-frontend",
  "linkedin": "https://linkedin.com/in/sara",
  "portfolio": "https://sara.dev",
  "message": "I have 6 years of Next.js and design-system work across production products."
}
```

Validation

Field	Required	Rules
name	yes	trim, min 2, max 80
email	yes	valid email
phone	no	max 30
role	yes	open job id or "general"
linkedin	no	if present, must start with http:// or https://
portfolio	no	if present, must start with http:// or https://
message	yes	min 10, max 2000
cv	no	.pdf , .doc , .docx ; max 5 MB

Notes

- "general" is a real apply path even when no jobs are open.
- Store the submission and notify HR / info@orcatech1td.com.

6. Articles

6.1 Listing — GET /api/articles

Query

Param	Type	Notes
category	tech ai design caseStudies	optional filter
page	number	default 1
limit	number	default 9

Listing cards use cover, category, title, excerpt, author, date, readTime, and resource links. Do **not** include body or gallery here.

Response data

```

{
  items: Array<{
    slug: string
    category: ArticleCategory
    date: string
    readTime: number
    author: string
    cover: string
    title: LocalizedString
    excerpt: LocalizedString
    links: Array<{
      kind: "linkedin" | "github" | "website"
      href: string
      label: string
    }>
  }>
  pagination: {
    page: number
    limit: number
    total: number
    hasMore: boolean
  }
}

```

Example item

```

{
  "slug": "shipping-headless-commerce",
  "category": "tech",
  "date": "2026-06-12",
  "readTime": 6,
  "author": "Omar Farouk",
  "cover": "https://cdn.example.com/articles/headless-cover.jpg",
  "title": {
    "en": "Shipping headless commerce without losing the checkout",
    "ar": "إطلاق تجارة منفصلة دون فقدان عملية الدفع"
  },
  "excerpt": {
    "en": "A practical path from monolith storefront to headless – and the pitfalls that stall conversions.",
    "ar": "مسار عملي من واجهة متجر أحادية إلى بنية منفصلة – والمزالق التي تعطل التحويل"
  },
  "links": [
    { "kind": "website", "href": "https://shopify.dev", "label": "Shopify.dev" },
    { "kind": "github", "href": "https://github.com/Shopify/hydrogen", "label": "Hydrogen" },
    { "kind": "linkedin", "href": "https://www.linkedin.com/company/shopify", "label": "Shopify" }
  ]
}

```

6.2 Details — GET /api/articles/:slug

Return `404` if the slug does not exist.

Response data

```

{
  slug: string
  category: ArticleCategory
  date: string
  readTime: number
  author: string
  cover: string
  title: LocalizedString
  excerpt: LocalizedString
  links: Array<{
    kind: "linkedin" | "github" | "website"
    href: string
    label: string
  }>
  gallery: Array<{
    src: string
    alt: LocalizedString
  }>
  body: Array<
    | { type: "p"; en: string; ar: string }
    | { type: "h2"; en: string; ar: string }
  >
  related: Array<ArticleListItem>
}

```

`related` is optional. Prefer up to 3 items, same category first. Same shape as listing items (no `body` / `gallery`).

Body blocks

type	Meaning
p	Paragraph
h2	Section heading

`date` is ISO date (YYYY-MM-DD). `readTime` is minutes. `slug` must be URL-safe.

7. Projects

7.1 Listing — GET /api/projects

Optional query: `service` (`ServiceId`), `industry` (`IndustryId`).

Cards use cover, name, tagline, industry, and service.

Response data

```
{
  items: Array<{
    slug: string
    service: ServiceId
    industry: IndustryId
    cover: string
    name: LocalizedString
    tagline: LocalizedString
  }>
}
```

Example item

```
{
  "slug": "ai-powered-marketplace",
  "service": "ecommerce",
  "industry": "retail",
  "cover": "https://cdn.example.com/projects/marketplace-cover.jpg",
  "name": {
    "en": "AI-Powered Multi-Vendor Commerce Platform",
    "ar": "منصة تجارة متعددة البائعين بالذكاء الاصطناعي"
  },
  "tagline": {
    "en": "A feature-rich marketplace combining modern e-commerce, seller operations, platform administration, and practical AI capabilities in one scalable product.",
    "ar": "سوق غني بالميزات يجمع التجارة الحديثة وتشغيل البائعين وإدارة المنصة وقدرات ذكاء اصطناعي عملية.",
    "في منتج واحد قابل للتوسع"
  }
}
```

7.2 Details — GET /api/projects/:slug

Return 404 if the slug does not exist.

Response data

```
{
  slug: string
  service: ServiceId
  industry: IndustryId
  stack: string[]
  tags: LocalizedString[]
  cover: string
  gallery: Array<{
    src: string
    alt: LocalizedString
  }>
  name: LocalizedString
  tagline: LocalizedString
  cta: LocalizedString
  sections: ProjectSection[]
}
```

ProjectSection

```

{
  kicker: LocalizedString
  title: LocalizedString
  intro?: LocalizedString
  cards?: Array<{ title: LocalizedString; body: LocalizedString }>
  notes?: Array<{ title: LocalizedString; body: LocalizedString }>
  steps?: Array<{ title: LocalizedString; body: LocalizedString }>
  modules?: Array<{
    kicker: LocalizedString
    title: LocalizedString
    body: LocalizedString
    bullets: LocalizedString[]
  }>
  layers?: LocalizedString[]
}

```

A section may include any mix of `intro`, `cards`, `notes`, `steps`, `modules`, and `layers`. Omit unused keys.

`cta` is the closing heading on the case-study page, for example: "Building a marketplace, commerce platform, or AI-enabled product?"

8. Contact form

POST `/api/contact`

Content-Type: `application/json`

Request

```

{
  name: string
  email: string
  phone: string | null
  company: string | null
  service: ServiceId
  message: string
}

```

Example

```

{
  "name": "Omar Hassan",
  "email": "omar@company.com",
  "phone": "+971 50 000 0000",
  "company": "Acme",
  "service": "ecommerce",
  "message": "We need a multi-vendor marketplace with AI search and a seller portal."
}

```

Validation

Field	Required	Rules
name	yes	trim, min 2, max 80
email	yes	valid email
phone	no	max 30
company	no	max 80
service	yes	one of ServiceId
message	yes	min 10, max 2000

Success example

```
{
  "success": true,
  "message": {
    "en": "Message received. A producer will follow up shortly.",
    "ar": "تم استلام الرسالة. سيتابع معك أحد المنتجين قريباً."
  }
}
```

Store the lead and notify `info@orcatech1td.com` / sales.

9. Endpoint summary

Method	Path	Auth	Purpose
GET	/api/settings	public	Site-wide settings
GET	/api/about/stats	public	About stats row
GET	/api/careers	public	Job listing
GET	/api/careers/:id	public	Job details
POST	/api/careers/apply	public	Submit application (multipart)
GET	/api/articles	public	Article listing
GET	/api/articles/:slug	public	Article details
GET	/api/projects	public	Project listing
GET	/api/projects/:slug	public	Project details
POST	/api/contact	public	Contact form (JSON)

10. Implementation notes

1. Always return both `en` and `ar` for CMS content.
2. `slug` and `job_id` values must be URL-safe (`ai-powered-marketplace` , `senior-frontend`).
3. Image fields (`cover` , `gallery[].src`) should be absolute CDN URLs, or stable paths the frontend can prefix.
4. Careers apply is `multipart/form-data` . Contact is JSON.
5. Persist contact and application submissions. Send email notifications as needed.
6. `role: "general"` must be accepted even when the jobs list is empty.
7. Listing payloads should stay lean. Full `body` / `sections` / `gallery` belong on detail endpoints only.
8. CORS must allow the Next.js website origin.

11. Suggested HTTP status codes

Code	When
200	Successful GET or POST
400	Validation failed
404	Unknown slug or job id
413	CV file larger than 5 MB
415	CV file type not allowed
429	Rate limit on public POST endpoints
500	Unexpected server error