

Moataz Mansour

Senior Database Architect

Swiss Post

Moataz.mansour@bluewin.ch

Data Science Project

Swiss Post Sorting Centers Package Sorting Performance Analysis and Prediction Conceptual Design Report

3 October 2024

Abstract

Swiss Post processes a substantial volume of packages each year, delivering around 200 million parcels in 2023 alone. This highlights its crucial role in Switzerland's logistics network, covering both domestic and international shipments. However, in 2023, Swiss Post encountered performance challenges, driven by external factors such as inflation, weakened consumer confidence, and geopolitical events. These factors led to a 4.7% decline in parcel volumes compared to 2022. Despite this, Swiss Post has made considerable investments in its logistics network to address efficiency issues, including the introduction of new regional parcel centers and upgraded sorting technology. These improvements have eased the pressure on processing times in high-demand areas like Zurich and Basel.

The surge in package deliveries that began during the COVID-19 crisis overwhelmed the existing infrastructure, prompting Swiss Post to invest millions in new sorting centers to meet the growing demand. By enhancing the efficiency of the existing sorting centers, Swiss Post could fully optimize their usage, reducing the need for further costly investments in additional facilities.

This project focuses on analyzing sorting center operations performance to identify congestion points and their causes, while also developing predictive models to foresee and prevent performance issues before they occur. This proactive strategy will help improve the overall performance of Swiss Post's sorting centers.

Table of Contents

Abstract	1
Table of Contents	2
1. Project Objectives	3
2. Methods	4
3. DATA	8
4. Metadata	12
5. Data Quality	13
6. Data Flow	14
7. Data Model	16
8. Documentation	18
9. Risks	19
10. Preliminary Studies	20
11. Conclusions	21

1. Project Objectives

The goal of this project is to analyze the postal sorting center's performance by identifying the most influential factors contributing to sorting issues, including shipment attributes (e.g., dimensions, weight, coding stations, and timestamps) as well as chute congestion which we believe have a major impact on overall performance of the center and finally using a model to determine whether overburdened chutes or certain features create bottlenecks that reduce overall system efficiency.

The sorting process consists of three key stages:

A: Shipments **arrive** and are delivered to the sorting center, using designated units

B: Shipments are **scanned and transferred** to the conveyor belts, where automatic and manual sorting machines determine their route and send them to the appropriate chute based on the destination.

C: The **chute serves as the output** of the sorting machine, directing the parcels to different destinations depending on the ZIP code., one chute can serve several ZIP codes

The center's performance is measured by the number of parcels processed per time frame. Some centers have shown up to a 15% increase in processing efficiency compared to others with similar setups. Further investigation revealed that traffic bottlenecks at certain chutes, which handle significantly higher package volumes, cause an imbalance. This results in a non-normal distribution of packages across the chutes, leading to a noticeable reduction in overall performance.

Our goal is to achieve a balanced, normally distributed flow of packages across all available chutes, which would enhance the sorting rate and improve overall center performance.

Specific Objectives:

- 1.1. **Determine Feature Importance:** Rank the shipment features by their importance and identify which shipment attributes (e.g., dimensions, weight, coding station) are most influential in causing sorting issues at postal centers. As well Correlation between the features and the impact on performance
- 1.2. **Determine chute congestion impact:** Determine whether chutes are handling disproportionately large volumes of packages can create bottlenecks that reduce overall system efficiency
- 1.3. **Predict Sorting Performance and Issues:** Develop a predictive model capable of forecasting sorting issues based on historical shipment data.
- 1.4. **Generate Actionable Insights:** Provide data-driven recommendations for improving chute utilization and enhance overall performance

2. Methods

2.1. Infrastructure and Tools

Swiss Post's IT infrastructure consists of over 5,300 databases and more than 800 custom-built applications, distributed across two highly secure data centers supported by a fiber network backbone. These data centers are designed for disaster recovery, ensuring operational continuity. At the core of this system is the Oracle Exadata Cloud at Customer (EXACC) platform, a high-performance database server valued at 5 million CHF, which hosts many of Swiss Post's databases and is mirrored across both data centers for redundancy and high availability in case of system failures.

- A- Databases are used to store shipment data and provide real-time updates, ensuring accurate and up-to-date information flow. These systems are built with high availability and redundancy for continuous operation, and they support advanced data analytics and reporting for performance monitoring and decision-making.
- B- Applications, including parcel tracking systems, sorting system management, and predictive analytics for forecasting performance issues. Middleware and API integration enable seamless communication between different systems. These applications are hosted on virtualized or containerized platforms (e.g., Docker, Kubernetes), allowing Swiss Post to easily scale its IT resources based on demand.
- C- network infrastructure, consisting of high-speed fiber optic networks, redundant architecture with failover mechanisms, VPNs, and multi-cloud integration, ensures reliable connectivity between sorting centers and offices, while stringent security measures, including firewalls, encryption, and regular audits, protect data and maintain compliance.
- D- advanced control and monitoring systems for its sorting centers, such as SCADA (Supervisory Control and Data Acquisition) systems to oversee sorting operations, and centralized command centers that manage and coordinate the activities of the sorting centers.
- E- sorting centers in Härkingen, Frauenfeld, Daillens, Wallisellen (new), and Pratteln (new) are equipped with automated sorting machines connected to the IT infrastructure through IoT sensors. These sensors provide continuous data streams to monitor sorting accuracy, operational efficiency, and package flow in real time.

Swiss Post's comprehensive IT infrastructure, featuring powerful databases, application servers, and a robust network architecture, serves as the backbone of its logistics operations, enabling seamless parcel processing and tracking nationwide. With its scalability, security, and redundancy, the system ensures reliable and efficient performance, even during peak demand periods.

2.2. following infrastructure and tools will be used for this project:

We have limited our study to focus on two parcel centers: **Härkingen** and **Frauenfeld**, and are analyzing data from a **single major database** that holds parcel processing information. This database contains massive tables, with an average of **5 billion records**, providing extensive data for our analysis of parcel operations.

- **Software Libraries:**
 - Pandas: For data cleaning and manipulation.
 - scikit-learn: For training the Random Forest model and calculating feature importance.
 - Matplotlib: For visualizing data trends and feature importance.
 - OracleDB: using Python SQL To extract relevant parcel data from databases.
- **Database Tools:** Oracle 23ai with vector search and other DB tools and Toad is used to manage the Data extraction and query and cleanup
- **Hardware:** on prem Exacc Database server with huge database power where package databases (PADASA and X) with 50 TB storage usage and 5 billion records tables runs and the Swiss post AWS server cloud infrastructure to run the developed predictive models

2.3. Statistical Descriptive Analysis

- **Chute Utilization:** The number of packages processed per chute and the average processing time per chute were calculated. This analysis helped identify chutes that were handling a disproportionately large number of shipments and thus were more likely to experience congestion.
- **Performance Metrics:** Center-wide performance metrics were computed, including average processing time per package, total number of packages processed, and individual chute performance.
- **Data Correlation:** The correlation between specific shipments or packages and performance bottlenecks will be analyzed to determine if certain supplier lots arriving at the center are contributing to the overutilization of particular chutes. By identifying these patterns, proactive redistribution measures can be implemented to prevent bottlenecks and optimize center efficiency.

2.4. Predictive Model for Chute Congestion

To proactively manage congestion in the sorting center, a **Random Forest Classifier** was selected as the predictive model to forecast chute overutilization. This model was chosen for its ability to handle non-linear relationships between features and provide feature importance insights.

2.4.1. Model Selection:

- **Random Forest Classifier:** This model is an ensemble of decision trees that is well-suited for binary classification problems like detecting whether a chute is congested or not.

- **Advantages:** The Random Forest model is robust to overfitting and handles large datasets efficiently. It can also output feature importance, helping identify which factors contribute most to chute congestion.
- **Target Variable:** The target for the model was defined as whether a chute was congested based on a threshold of average processing time and package volume.

▪

2.4.2. Model Training:

- **Data Split:** The dataset was split into training and test sets using an 80/20 ratio, ensuring that the model was trained on a portion of the data and evaluated on unseen data.
- **Model Hyperparameters:**
 - The Random Forest model's hyperparameters, such as the number of decision trees (`n_estimators`) and maximum tree depth (`max_depth`), were tuned using grid search cross-validation.
- **Evaluation Metrics:**
 - The model was evaluated using precision, recall, and F1-score, with a particular focus on minimizing false negatives (i.e., instances where a congested chute was not flagged).
- **Feature Importance:**
 - The model provided insights into the most important features driving chute congestion. Features such as the number of packages processed and processing time had the highest importance scores, indicating they played a key role in predicting congestion.

2.4.3. Model Deployment and Monitoring

The predictive model for congestion is designed to be deployed in real-time, allowing the sorting center to dynamically adjust chute assignments and mitigate potential bottlenecks.

- **Real-Time Monitoring:**
 - A real-time dashboard can be built to monitor chute utilization and processing time. The predictive model will flag chutes that are at risk of congestion, triggering proactive operational interventions.
- **Model Retraining:**
 - The model is retrained periodically as new data becomes available to ensure it continues to provide accurate predictions as operational conditions change.

3. DATA

The data for this project comes from Swiss Post's shipment sorting system and includes:

- **Shipment number** (anonymized) SND_IDENTCODE
- **Shipment dimensions:** Length, width, and height (in millimeters) SND_CODS_DIM1, SND_CODS_DIM2, SND_CODS_DIM3
- **Shipment weight:** (n grams) SND_GEW
- **Scanning timestamps** when the item first scanned in the sorting center CODS_COD_DAT
- **Scanner station:** Sorting station identifier CODS_CO_STATION
- **Sorting center Number** CODS_ZENT_NR_x
- **leaving timestamps** when the item left the sorting center chute CODS_LERE_DAT
- **chute station** where the item is sent CODS_SD_RUTSCHE

3.1. Sample Data Example

TEST_READ@P55PDS_REPORT - Toad for Oracle - [Editor (SELECT *)]

File Edit Search Editor Session Database Debug View Team Coding Utilities Rerun Window Help

TEST_READ@P55PDS_REPORT [2] DBA2@P52PMDWH [1] DBA2@P55KLP [2] DBA2@P55PDS [2]

Editor Editor Session Browser Editor Schema Browser Editor

Desktop: SQL TEST_READ

SQL SELECT * +

```

1 SELECT
2   to_char(1 + ora_hash(SND_IDENTCODE, 9999), 'fm0000') as SND_IDENTCODE, -- PDS_SND
3   SND_CODS_DIM1, -- PDS_SND
4   SND_CODS_DIM2, -- PDS_SND
5   SND_CODS_DIM3, -- PDS_SND
6   SND_GEW, -- PDS_SND
7   CODS_COD_DAT,
8   CODS_CO_STATION,
9   CODS_ZENT_NR,
10  CODS_SD_RUTSCHE,
11  CODS_LERE_DAT
12 FROM
13   PDS_SND
14   join pds_ec_snd on snd_id = ecs_snd_id and snd_sending_crea_dat = ecs_snd_sending_crea_dat
15   join pds_erg_cod on ec_id = ecs_ec_id and ec_datum = ecs_ec_datum
16   join pds_cod_sdr on ec_ss_tab_id = cods_id
17 WHERE
18   1=1
19   AND CODS_ZENT_NR = 2 -- 1: DAI, 2: HAE, 3: FRA
20   AND CODS_COD_DAT between to_date('09.09.2024 00:00:01','dd.mm.yyyy hh24:mi:ss')+6.0/24 and to_date('09.09.2024 23:59:59','dd.mm.yyyy hh24:mi:ss')
21   and CODS_SD_RUTSCHE is not null
22 OFFSET 0 ROWS FETCH NEXT 10000 ROWS ONLY;
23

```

Data Grid


Messages Data Grid Trace DBMS Output (disabled) Query Viewer Explain Plan Script Output

Default

SND_IDENTCODE	SND_CODS_DIM1	SND_CODS_DIM2	SND_CODS_DIM3	SND_GEW	CODS_COD_DAT	CODS_CO_STATION	CODS_ZENT_NR	CODS_SD_RUTSCHE	CODS_LERE_DAT
6341	350	260	140	260	09/09/2024 07:22:17	HAE-????99	2	M0108	09/09/2024 07:22:17
2158	360	150	135	840	09/09/2024 07:21:15	HAE-ACS99	2	M0101	09/09/2024 07:22:30
2645	420	330	235	2260	09/09/2024 07:22:31	HAE-????99	2	M0108	09/09/2024 07:22:31
8595	360	290	105	420	09/09/2024 07:22:41	HAE-????99	2	M0108	09/09/2024 07:22:41
8732	450	350	165	3160	09/09/2024 07:22:43	HAE-????99	2	M0108	09/09/2024 07:22:43
8339	500	450	130	1180	09/09/2024 07:21:52	HAE-VCS99	2	M0101	09/09/2024 07:22:49
1058	350	270	110	1080	09/09/2024 07:22:52	HAE-????99	2	M0108	09/09/2024 07:22:52
4780	370	350	105	500	09/09/2024 07:23:01	HAE-????99	2	M0101	09/09/2024 07:23:01

3.2. Data Plots

Histograms and Plots to visualize the distribution of shipment across the Chutes



3.3. Calculating Performance (processing_time_minutes)

To evaluate the performance of the sorting center, we introduced a new column that captures processing time, which is a key performance metric. Processing time refers to the duration a package spends in the sorting process, from the moment it is scanned until it leaves the sorting center, added to the dataset

$$\text{processing_time_minutes (i)} = \text{CODS_COD_DAT(i)} - \text{CODS_LERE_DAT(i)}$$

Purpose of the Performance Columns:

- Identify Delays:** The processing_time_minutes column allows us to detect delays and inefficiencies in the sorting process. A high value indicates a potential issue, such as congestion or slow processing, while a lower value suggests efficient performance.
- Compare Across Stations/Chutes:** By grouping the data by sorting stations or chutes, we can compare average processing times and detect whether certain stations or chutes are causing bottlenecks.
- Overall Center Performance** can be calculated on time period bases like daily or hourly and then can be compared with other centers to identify which is more performant and validate the predictions

$$\text{Performance (Center)} = \text{SUM (processing_time_minutes (i))} / \text{Count}$$


3.4. Data Preprocessing

The raw dataset was first preprocessed to ensure that it was suitable for analysis and modeling. Key steps in the preprocessing pipeline included:

- **Data Cleaning:** Missing values in key fields such as CODS_COD_DAT and CODS_LERE_DAT (timestamps) were filtered out. Inconsistent data, such as negative processing times, were also removed.
- **Feature Creation:** The processing_time_minutes column was derived by calculating the difference between the entry and exit timestamps for each shipment.
- Additional features, such as the number of packages processed per chute and average processing time per chute, can be generated to assess congestion at the chute level.
- **Outlier Detection:**
 - Outliers in key fields, such as SND_GEW (weight) and processing_time_minutes, were identified using the **Interquartile Range (IQR)** method and removed to prevent skewing the analysis.

For example The processing time outfitters and the negative time values should be cleaned

- Calculate IQR** = $Q3 - Q1$ and Define the bounds for outliers $lower_bound = Q1 - 1.5 * IQR$
 $upper_bound = Q3 + 1.5 * IQR$
- Identify outliers** = $data[(data['processing_time_minutes'] < lower_bound) | (data['processing_time_minutes'] > upper_bound)]$
- Remove the outliers by filtering the data** $cleaned_data = data[(data['processing_time_minutes'] >= lower_bound) \& (data['processing_time_minutes'] <= upper_bound)]$



3.5. Security Considerations

- Anonymization:** All shipment numbers are anonymized to protect sensitive data.
- Data Storage:** Data is stored on secure servers and access is controlled according to Swiss Post's privacy and security guidelines.

4. Metadata

4.1. Required Metadata

Metadata such as the coding station, shipment size, and coding timestamps are critical for reproducing the analysis. These attributes allow for the recreation of sorting scenarios and the identification of problematic shipments.

Field Name	Description	Data Type	Example
SND_IDENTCODE	Unique identifier for each shipment (anonymized for privacy)	String	A12345
SND_CODS_DIM1	Length of the shipment in millimeters	Integer	300
SND_CODS_DIM2	Width of the shipment in millimeters	Integer	150
SND_CODS_DIM3	Height of the shipment in millimeters	Integer	50
SND_GEW	Weight of the shipment in grams	Integer	1000
CODS_COD_DAT	Timestamp indicating when the shipment was scanned into the sorting center	Datetime	15.01.2023 08:32
CODS_LERE_DAT	Timestamp indicating when the shipment left the sorting center	Datetime	15.01.2023 09:45
CODS_CO_STATION	Station or scanner ID at which the shipment was processed	String	STATION01
CODS_SD_RUTSCHE	Chute identifier where the package was routed for further processing	String	CHUTE10
processing_time_minutes	Calculated field representing the time taken to process a shipment in minutes	Float	73.5

- **Dataset Structure:** The dataset consists of shipment records, where each row represents a unique shipment with detailed metadata about its dimensions, weight, timestamps, processing station, and chute.
- **Calculated Field:** `processing_time_minutes` is derived from `CODS_COD_DAT` and `CODS_LERE_DAT` to measure the time a shipment spends in the sorting center.

4.2. Metadata Storage

- Metadata will be stored alongside the shipment data in a secure database, with access controlled by Swiss Post.
- Authorized users can access the metadata through SQL queries and data dumps exported to CSV for further analysis.

5. Data Quality

Data quality is a critical component of the analysis, as poor data quality can lead to incorrect conclusions and unreliable results. In this section, we evaluate the data for **completeness**, **consistency**, **accuracy**, and **timeliness**.

5.1. Completeness

Missing Data: Certain fields, such as CODS_COD_DAT and CODS_LERE_DAT, are essential for calculating processing time. Rows with missing or incorrect timestamps result in missing processing_time_minutes values.

Handling Missing Data: Missing timestamp values are filtered out, as they would disrupt the calculation of performance metrics. For other fields (e.g., dimensions or weight), imputation or removal may be necessary if the data is critical to the analysis.

5.2. Consistency

Timestamps Consistency: The data is checked for consistency between the CODS_COD_DAT (entry time) and CODS_LERE_DAT (exit time). Any cases where the exit time is earlier than the entry time (resulting in negative processing times) are flagged as inconsistent and removed from the dataset.

Data Formatting: All date and time fields are standardized to UTC to avoid issues arising from different time zones or formats. Other fields, such as SND_CODS_DIM1, SND_CODS_DIM2, and SND_GEW, are checked to ensure consistent units (millimeters for dimensions, grams for weight).

5.3. Accuracy

Outliers: The data was checked for extreme values or outliers, particularly in the SND_GEW (weight) and processing_time_minutes fields. Outliers may indicate potential data entry errors or operational inefficiencies. The Interquartile Range (IQR) method was used to detect and remove outliers from the dataset.

Anomalies: Anomalies in the timestamps, such as extremely short or long processing times, are investigated. While extremely short times could indicate system issues, extremely long times might signal congestion or inefficiencies within the sorting center.


5.4. Data Integrity

Integrity of Identifiers: The SND_IDENTCODE field, which uniquely identifies each shipment, is checked for duplicate entries to ensure that each record represents a unique shipment. This field is also anonymized using a hashing function to protect sensitive information.

Chute and Station Integrity: Validations are in place to ensure that CODS_CO_STATION and CODS_SD_RUTSCHE match with known station and chute identifiers to avoid mismatches or routing errors.

6. Data Flow


The shipment physical flow in the Sorting Center and its corresponding DATA Flow



In the Blue Boxes Packages Data are collected by the scanners and written to the Red Database

Data Flow for the project study:

- **Data Source:** Shipment data is extracted from Swiss Post's databases.
 - **Data Preprocessing:** Data is cleaned and prepared, with missing values handled appropriately and Invalid or inconsistent timestamps (e.g., negative processing times) are filtered out.
 - **Feature Engineering:** Key features such as shipment size, weight, and timestamps are used and Derived metrics like `processing_time_minutes` are created to evaluate performance.
 - **Model Training:** Data is passed to machine learning models to Train and Test
 - **Model Outputs:** Data is passed to machine learning models to predict and analyze sorting performance.
- the data flow for this project, starting from data collection to model outputs.



7. Data Model

7.1. Conceptual Data Model

The conceptual data model represents the high-level structure of the data, outlining key entities (or features) and their relationships within the sorting center's operations. For this project, the key entities involve shipment attributes, chute performance, and processing times.

Shipments: The core entity that includes information such as package identifiers, dimensions, weight, and timestamps (arrival and departure times).

Sorting Stations: The stations (or scanners) that process shipments and direct them to chutes.

Chutes: The output of the sorting machine that directs parcels to different destinations based on ZIP codes. Each chute may serve multiple ZIP codes.

Performance Metrics: Data points used to evaluate performance, such as processing time, number of packages handled, and overall throughput for stations and chutes.

7.2. Logical Data Model

The logical data model outlines the data attributes and their relationships without considering the technical implementation. In this project, the dataset consists of the following attributes:

Shipment Attributes:

SND_IDENTCODE: Anonymized unique identifier for each shipment.

SND_CODS_DIM1, SND_CODS_DIM2, SND_CODS_DIM3: Dimensions of the shipment (length, width, height in millimeters).

SND_GEW: Weight of the shipment (in grams).

Timestamps:

CODS_COD_DAT: Timestamp when the shipment was scanned and entered the sorting center.

CODS_LERE_DAT: Timestamp when the shipment left the sorting center.

Sorting Details:

CODS_CO_STATION: The station that scanned and processed the shipment.


CODS_SD_RUTSCHE: The chute the shipment was sent to for further processing.

Performance Metrics:

processing_time_minutes: Calculated metric, representing the difference between CODS_COD_DAT and CODS_LERE_DAT (time taken for a shipment to be processed, in minutes).

Derived metrics like average processing time per chute, number of packages handled by each chute, and performance statistics for each sorting station.

Database Model showing Tables relationships of the used tables



7.3. Physical Data Model

The physical data model defines how the data is stored and processed. The data is typically managed in tabular form, using tools like pandas (for data manipulation), SQL databases and SQL plus (for querying), and local storage systems for persistent storage.

Storage Infrastructure: The dataset is stored in database Tables , with each row representing a shipment and the associated attributes. The data can be loaded into python data frame and manipulated in memory using Python libraries (e.g., pandas).

7.4. Relationships

Shipment → Sorting Station → Chute: Each shipment passes through a sorting station, which processes it and directs it to a specific chute. The performance of the sorting center is evaluated based on how quickly and efficiently shipments are processed through these entities.

Chute Performance → Sorting Center Performance: The collective performance of the chutes contributes to the overall efficiency of the sorting center. Chutes that are overburdened or congested may affect the performance of the entire center.

8. Documentation

The project will be documented using **Jupyter Notebooks**, which include all code, visualizations, and analysis steps. Additionally, a full project report will be written, summarizing findings, methods, and outcomes.

8.1. Data Sources and Ingestion origin and structure of the dataset

8.2. Data Preprocessing The procedures for handling missing data, formatting inconsistencies

Data Transformation The creation of new variables, and any feature engineering applied

Outlier Detection and Handling detecting and handling outliers

8.3. Model Implementation the models used for performance prediction and analysis, including the algorithms selected (e.g., Random Forest), feature selection, and evaluation metrics.

8.4. Assumptions and Limitations

Any assumptions made during the analysis (e.g., the correctness of timestamps or the relevance of data) will be documented. Additionally, limitations encountered during the analysis, such as incomplete data or potential biases, will be included.

8.5. Findings and Recommendations

The final outcomes of the analysis, including any performance insights and recommendations for optimizing the sorting process, will be clearly documented. This section will summarize the results of the analysis and suggest next steps for improving operations.

9. Risks

9.1. Data Quality Risks

Missing or Incomplete Data: If key data fields such as timestamps or shipment identifiers are missing or incomplete, it could hinder the analysis. This risk could result in inaccurate processing time calculations or incomplete shipment tracking.

Data Inconsistencies and Overfitting: Inconsistent data, such as negative processing times or invalid weights and dimensions, could skew the analysis and lead to incorrect conclusions about sorting center performance.

9.2. Technical Risks

Model Limitations: The performance prediction models, such as Random Forest, might not fully capture all factors contributing to poor performance. Unseen factors or unmodeled interactions between variables may reduce the model's accuracy.

Scalability of Solutions: Recommendations for optimizing chute utilization and sorting efficiency may not scale effectively under different operational loads or in other sorting centers.

Overfitting: The model may overfit on specific stations or shipment types, reducing generalization to other stations.

9.3. Operational Risks

Chute congestion or Machine Malfunction: Sorting machines or chutes may congest or malfunction, leading to skewed data. If these failures are not documented correctly, the resulting data could incorrectly reflect the center's performance.

Overburdened Systems: If the sorting center experiences unexpected spikes in shipment volume, the system might be overburdened, leading to congestion and processing delays that may not reflect typical operational conditions.

9.4. Implementation Risks

Real-time Monitoring Challenges: Implementing real-time monitoring and dynamic routing to prevent chute congestion may be technically challenging and require significant infrastructure upgrades.

Resistance to Change: Any proposed operational changes may face resistance from the team managing the sorting center, especially if they involve major alterations to current workflows.

10. Preliminary Studies

The preliminary studies focused on understanding the current performance of the postal sorting center by analyzing key metrics such as processing time, chute utilization, and shipment flow.

10.1. Data Overview

- The dataset provided detailed records of shipment processing, including dimensions, weight, timestamps (entry and exit), and sorting station and chute assignments. A preliminary analysis was conducted to assess the overall structure and quality of the data.

10.2. Processing Time Analysis

- **Initial Findings:** The initial analysis revealed that the processing time for each shipment varied significantly. The calculated average processing time across all shipments highlighted potential inefficiencies in the sorting process.

10.3. Chute Utilization and Bottleneck Detection:

- Preliminary studies revealed that certain chutes, processing a disproportionate number of packages, experienced longer average processing times, indicating potential congestion and suggesting that overburdened chutes may significantly impact overall sorting center performance.

10.4. Outlier Detection

- Outliers were detected in fields such as `SND_GEW` and `processing_time_minutes`. These outliers were removed to ensure that the analysis was not skewed by extreme or anomalous data points.

10.5. Steps for Further Analysis:

- **Overutilization Definition:** We can calculate the **percentage of total packages** processed by each chute to identify overutilized chutes. Chutes processing, say, more than 10% of total packages could be flagged as overutilized.
- **Time-Based Utilization Analysis:** investigate certain chutes are overloaded at specific times.
- **Correlation with Processing Time:** Analyze whether chutes with higher utilization also exhibit longer processing times, indicating that overutilization leads to delays, and examine the correlation between chute overutilization and poor performance.

11. Conclusions

Understanding which features most affect sorting issues provides insights that can be used to improve sorting operations at Swiss Post. Focusing on key factors like shipment size, weight, and station performance will help optimize sorting machine performance and reduce errors.

11.1. Key Findings

- **Chute Congestion:** Certain chutes were identified as potential bottlenecks, handling significantly more packages than others and showing longer processing times. Managing chute congestion is critical to improving overall efficiency.
- **Processing Time Variability:** There was substantial variability in processing times across shipments. Factors such as shipment dimensions, weight, and chute assignment contributed to this variability.
- **Data Quality Issues:** Several data quality issues, such as missing or inconsistent timestamps, were identified. These issues were addressed to ensure accurate analysis, but continued data quality monitoring is recommended.

11.2. Model Insights

- The Random Forest model provided insights into the factors most influencing sorting performance, with shipment weight and chute utilization being significant contributors. However, additional factors not captured in the dataset may also play a role in performance variations.

11.3. Recommendations

- **Chute Balancing:** Implement dynamic chute load balancing to distribute shipments more evenly across available chutes. This would reduce bottlenecks and improve throughput.
- **Real-Time Monitoring:** Introduce real-time monitoring to detect and address chute congestion before it affects overall performance.
- **Further Data Collection:** Collect additional data on shipment characteristics and operational factors to refine the performance models and improve accuracy.

11.4. Next Steps

- Continue refining the performance models with updated data and explore additional machine learning techniques to predict sorting center performance under different conditions.
- Implement operational changes based on the findings and monitor their impact on sorting efficiency.

2 Statement

 RecoverableSignature

➤ *Natty Lawson*

MetazNrsour

Source: S1521117330543909418973868037d12315e4cea1cf8e8a591a

22