CAPSTONE REPOSITORY / RESEARCH COLLECTION

LabLedger: Final Submission Request

Graduation-project demonstration dossier

King Saud University - CS - 2026–2027

Authored demonstration team: Saad Ahmed Aljuhaimi, Turki Ahmed Aljuhaimi, Hamad Ahmed Aljuhaimi, Majed Ahmed Aljuhaimi

This separate English-language workflow demonstrator supplies a small, reproducible record-validation artifact so presenters can exercise the real project lifecycle without changing the fifty completed showcase cases.

Scope: fictional project and synthetic observations. No university endorsement or real field results are claimed.

1. Research question and scope

This separate English-language workflow demonstrator supplies a small, reproducible record-validation artifact so presenters can exercise the real project lifecycle without changing the fifty completed showcase cases. The question is deliberately narrow: can the proposed decision rule improve the stated baseline on the supplied cases while keeping every outcome inspectable? The result is a computing graduation-project demonstrator, not operational guidance. Inputs, assumptions and failure definitions are part of the assessment scope; benefits outside that scope are not inferred.

2. Implementation maturity

Inspect the owned input records, reject duplicate and invalid rows, preserve a complete deterministic result ledger and compare the accepted identifiers with an explicit reference set. This presentable early artifact supplies a small record-validation experiment as a reproducibility example. It does not implement every domain behavior named by the project title. That limited scope is a reason for the moderate or weak demonstration evaluation; reviewers must not confuse a tidy report with a complete domain system.

3. Method and reproducibility

The owned reference experiment is experiments/validation.py. It was executed on thirty separate seeded cases beginning at seed 54200. The same seed and project definition reproduce every CSV row. The public results file records the complete small dataset, not a hand-selected best example. The program uses Python standard-library arithmetic and deterministic random.Random inputs. No external private dataset or participant record is required. To reproduce, run the attached script with Python3.14 and compare the JSON rows with results/validation.csv. The web platform never executes this uploaded code.

4. Assumptions and decision record

This is a bounded workflow exercise, not a separate field deployment. Its example data and assessments are fictional; it does not claim institutional endorsement or a human study. The model treats its input bounds as explicit preconditions. Missing or infeasible states are distinguished from successful outputs. Cost units are simulator units; they are not currency, human waiting-time estimates or certified safety margins. The baseline and proposed behavior receive the same input realization. Internal assertions check the named invariant or independent small-instance oracle before rows are emitted. A failed assertion stops generation; no successful result is synthesized to hide it.

5. Validation and evidence

The attached results contain 30 cases with 4 reported quantities. The table below is calculated from those exact rows. Minimum, maximum and mean are descriptive statistics of the supplied synthetic cases only. They do not estimate a population, establish statistical significance or measure the Capstone platform itself. Inspect individual rows before relying on the mean: unreachable routes, ties, budget limits and replay behavior are meaningful outcomes, not missing values to be silently discarded.

Reported quantity	Min	Max	Mean
valid rows	25	25	25
invalid rows detected	2	2	2
input rows	27	27	27
unique output ids	25	25	25

Each mean uses the valid_n denominator recorded in results/summary.json.

8. Limitations and next experiment

This is a bounded workflow exercise, not a separate field deployment. Its example data and assessments are fictional; it does not claim institutional endorsement or a human study. A suitable next experiment would replace one synthetic assumption at a time with independently validated observations, preserve a held-out case set, and preregister the comparison metric. Boundary and negative cases should be expanded before adding a more complex predictor. Any real participants, devices, institutions or field sites would require their own approvals and provenance. None is claimed by this demonstration.

10. Provenance

All people, projects, assessment inputs and simulated observations in this bundle were authored for a controlled P5.3 demonstration. Real university names identify demo tenants only; no affiliation, real submission, institutional verification, academic endorsement, publication or award is asserted. No citations to unverified publications are invented. The comparison baselines are fully specified local algorithms or record-checking rules included in the artifact, so the claim can be checked without an external authority.