

Using Conversion Functions and Conditional Expressions

ORACLE

Copyright © 2019, Oracle and/or its affiliates. All rights reserved.


Objectives

After completing this lesson, you should be able to do the following:

- Describe the various types of conversion functions that are available in SQL
- Use the `TO_CHAR`, `TO_NUMBER`, and `TO_DATE` conversion functions
- Apply conditional expressions in a `SELECT` statement

This lesson focuses on functions that convert data from one type to another (for example, conversion from character data to numeric data) and discusses the conditional expressions in SQL `SELECT` statements.

Conversion Functions



Although implicit data type conversion is available, it is recommended that you do the explicit data type conversion to ensure the reliability of your SQL statements.

ORACLE

In addition to Oracle data types, columns of tables in an Oracle Database can be defined by using the American National Standards Institute (ANSI), DB2, and SQL/DS data types. However, the Oracle server internally converts such data types to Oracle data types.

In some cases, the Oracle server receives data of one data type where it expects data of a different data type. When this happens, the Oracle server can automatically convert the data to the expected data type. This data type conversion can be done *implicitly* by the Oracle server or *explicitly* by the user.

Implicit data type conversions work according to the rules explained in the following slides.

Explicit data type conversions are performed by using the conversion functions. Conversion functions convert a value from one data type to another. Generally, the form of the function names follows the convention *data type TO data type*. The first data type is the input data type and the second data type is the output.

Implicit Data Type Conversion

- Oracle server can automatically perform data type conversion in an expression.
- For example, the expression `hire_date > '01-JAN-90'` results in the implicit conversion from the string `'01-JAN-90'` to a date.
- Therefore, a `VARCHAR2` or `CHAR` value can be implicitly converted to a number or date data type in an expression.
- **Note:** `CHAR` to `NUMBER` conversions succeed only if the character string represents a valid number.

From	To
<code>VARCHAR2</code> or <code>CHAR</code>	<code>NUMBER</code>
<code>VARCHAR2</code> or <code>CHAR</code>	<code>DATE</code>

Implicit Data Type Conversion

- In general, the Oracle server uses the rule for expressions when a data type conversion is needed.
- For example, the expression `grade = 2` results in the implicit conversion of the number 2 to the string "2" because grade is a `CHAR(2)` column.

From	To
NUMBER	VARCHAR2 or CHAR
DATE	VARCHAR2 or CHAR

Using the TO_CHAR Function with Dates

```
TO_CHAR(date[, 'format_model'])
```

The format model:

- Must be enclosed with single quotation marks
- Is case-sensitive
- Can include any valid date format element
- Has an *fm* element to remove padded blanks or suppress leading zeros
- Is separated from the date value by a comma

TO_CHAR converts a datetime data type to a value of VARCHAR2 data type in the format specified by the *format_model*. A format model is a character literal that describes the format of datetime stored in a character string. For example, the datetime format model for the string '11-Nov-2000' is 'DD-Mon-YYYY'. You can use the TO_CHAR function to convert a date from its default format to the one that you specify.

Guidelines

- The format model must be enclosed with single quotation marks and is case-sensitive.
- The format model can include any valid date format element. But be sure to separate the date value from the format model with a comma.
- The names of days and months in the output are automatically padded with blanks.
- To remove padded blanks or to suppress leading zeros, use the fill mode *fm* element.

```
SELECT employee_id, TO_CHAR(hire_date, 'MM/YY') Month_Hired
FROM   employees
WHERE  last_name = 'Higgins';
```

	EMPLOYEE_ID	MONTH_HIRED
1		20506/02

Elements of the Date Format Model

Element	Result
YYYY	Full year in numbers
YEAR	Year spelled out (in English)
MM	Two-digit value for the month
MONTH	Full name of the month
MON	Three-letter abbreviation of the month
DY	Three-letter abbreviation of the day of the week
DAY	Full name of the day of the week
DD	Numeric day of the month

Elements of the Date Format Model

- Time elements format the time portion of the date:

HH24:MI:SS AM	15:45:32 PM
---------------	-------------

- Add character strings by enclosing them with double quotation marks:

DD "of" MONTH	12 of OCTOBER
---------------	---------------

- Number suffixes spell out numbers:

ddspth	fourteenth
--------	------------

Use the formats that are listed in the following tables to display time information and literals, and to change numerals to spelled numbers.

Element	Description
AM or PM	Meridian indicator
A.M. or P.M.	Meridian indicator with periods
HH or HH12	12 hour format
HH24	24 hour format
MI	Minute (0–59)
SS	Second (0–59)
SSSSS	Seconds past midnight (0–86399)

Using the TO_CHAR Function with Dates

```
SELECT last_name,  
       TO_CHAR(hire_date, 'fmDD Month YYYY')  
       AS HIREDATE  
FROM   employees;
```

The hire date appears as 17 June 2003.

```
SELECT last_name,  
       TO_CHAR(hire_date,  
       'fmDdsph "of" Month YYYY fmHH:MI:SS AM')  
       HIREDATE FROM employees;
```

Seventeenth of June 2003 12:00:00 AM

ORACLE

	LAST_NAME	HIREDATE
1	King	Seventeenth of June 2003 12:00:00 AM
2	Kochhar	Twenty-First of September 2005 12:00:00 AM

...

Using the TO_CHAR Function with Numbers

```
TO_CHAR(number [, 'format_model'])
```

These are some of the format elements that you can use with the TO_CHAR function to display a number value as a character:

Element	Result
9	Represents a number
0	Forces a zero to be displayed
\$	Places a floating dollar sign
L	Uses the floating local currency symbol
.	Prints a decimal point
,	Prints a comma as a thousands indicator

When working with number values, such as character strings, you should convert those numbers to the character data type using the TO_CHAR function, which translates a value of NUMBER data type to VARCHAR2 data type. This technique is especially useful with concatenation.

Using the TO_CHAR Function with Numbers

```
SELECT TO_CHAR(salary, '$99,999.00') SALARY  
FROM   employees  
WHERE  last_name = 'Ernst';
```

	 SALARY
1	\$6,000.00

ORACLE

- The Oracle server displays a string of number signs (#) in place of a whole number whose digits exceed the number of digits provided in the format model.
- The Oracle server rounds the stored decimal value to the number of decimal places provided in the format model.

Using the TO_NUMBER and TO_DATE Functions

- Convert a character string to a number format using the TO_NUMBER function:

```
TO_NUMBER(char[, 'format_model'])
```

- Convert a character string to a date format using the TO_DATE function:

```
TO_DATE(char[, 'format_model'])
```

- These functions have an `fx` modifier. This modifier specifies the exact match for the character argument and date format model of a TO_DATE function.

ORACLE

You may want to convert a character string to either a number or a date. To accomplish this task, use the TO_NUMBER or TO_DATE functions. The format model that you select is based on the previously demonstrated format elements.

The `fx` modifier specifies the exact match for the character argument and date format model of a TO_DATE function:

- Punctuation and quoted text in the character argument must exactly match (except for case) the corresponding parts of the format model.
- The character argument cannot have extra blanks. Without `fx`, the Oracle server ignores extra blanks.
- Numeric data in the character argument must have the same number of digits as the corresponding element in the format model. Without `fx`, the numbers in the character argument can omit leading zeros.

ORA-01858: a non-numeric character was found where a numeric was expected
01858. 00000 - "a non-numeric character was found where a numeric was expected"
*Cause: The input data to be converted using a date format model was incorrect. The input data did not contain a number where a number was required by the format model.
*Action: Fix the input data or the date format model to make sure the elements match in number and type. Then retry the operation.

	LAST_NAME	HIRE_DATE
1	Grant	24-MAY-07

Using TO_CHAR and TO_DATE Functions with the RR Date Format

To find employees who were hired before 1990, the RR format can be used. Because the current year is greater than 1999, the RR format interprets the year portion of the date from 1950 to 1999.

```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-YYYY')
FROM employees
WHERE hire_date < TO_DATE('01-Jan-90', 'DD-Mon-RR');
```

LAST_NAME	TO_CHAR(HIRE_DATE,'DD-MON-YYYY')
1 Popp	03-Feb-1989

Alternatively, the following command, results in no rows being selected because the YY format interprets the year portion of the date in the current century (2090).


```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-YYYY')
FROM employees
WHERE TO_DATE(hire_date, 'DD-Mon-yy') < '01-Jan-90' ;
```

ORACLE

To find employees who were hired before 1990, the RR format can be used. Because the current year is greater than 1999, the RR format interprets the year portion of the date from 1950 to 1999.

Alternatively, the following command, results in no rows being selected because the YY format interprets the year portion of the date in the current century (2090).

```
SELECT last_name, TO_CHAR(hire_date, 'DD-Mon-yyyy')
FROM employees
WHERE TO_DATE(hire_date, 'DD-Mon-yy') < '01-Jan-90';
```



The screenshot shows a 'Query Result' window with a toolbar containing icons for save, print, refresh, and SQL. The status bar indicates 'All Rows Fetched: 0 in 0.002 seconds'. The column headers are 'LAST_N...' and 'TO_CH...', which are highlighted with a red box.

Notice that no rows are retrieved from the above query.

General Functions

- These functions work with any data type and pertain to the use of null values in the expression list.
- NVL (expr1, expr2)
- NVL2 (expr1, expr2, expr3)
- NULLIF (expr1, expr2)
- COALESCE (expr1, expr2, ..., exprn)

Function	Description
NVL	Converts a null value to an actual value
NVL2	If <code>expr1</code> is not null, NVL2 returns <code>expr2</code> . If <code>expr1</code> is null, NVL2 returns <code>expr3</code> . The argument <code>expr1</code> can have any data type.
NULLIF	Compares two expressions and returns null if they are equal; returns the first expression if they are not equal
COALESCE	Returns the first non-null expression in the expression list

NVL Function

- To convert a null value to an actual value, use the NVL function.
- Data types that can be used are date, character, and number.
- Data types must match:
 - `NVL(commission_pct,0)`
 - `NVL(hire_date, '01-JAN-97')`
 - `NVL(job_id, 'No Job Yet')`

ORACLE

To convert a null value to an actual value, use the NVL function.

Syntax

`NVL (expr1, expr2)`

In the syntax:

- *expr1* is the source value or expression that may contain a null
- *expr2* is the target value for converting the null

You can use the NVL function with any data type, but the return value is always the same as the data type of *expr1*.

NVL Conversions for Various Data Types

Data Type	Conversion Example
NUMBER	<code>NVL(number_column, 9)</code>
DATE	<code>NVL(date_column, '01-JAN-95')</code>
CHAR or VARCHAR2	<code>NVL(character_column, 'Unavailable')</code>

Using the NVL Function

```
SELECT last name, salary, NVL(commission_pct, 0)
(salary*12) + (salary*12*NVL(commission_pct, 0)) AN_SAL
FROM employees;
```

	LAST_NAME	SALARY	NVL(COMMISSION_PCT,0)	AN_SAL
1	King	24000	0	288000
2	Kochhar	17000	0	204000
3	De Haan	17000	0	204000
4	Hunold	9000	0	108000
5	Ernst	6000	0	72000
6	Lorentz	4200	0	50400
7	Mourgos	5800	0	69600
8	Rajs	3500	0	42000
9	Davies	3100	0	37200
10	Matos	2600	0	31200

...

ORACLE

To calculate the annual compensation of all employees, you need to multiply the monthly salary by 12 and then add the commission percentage to the result:

```
SELECT last_name, salary, commission_pct,
(salary*12) + (salary*12*commission_pct) AN_SAL
FROM employees;
```

	LAST_NAME	SALARY	COMMISSION_PCT	AN_SAL
1	King	24000	(null)	(null)
2	Kochhar	17000	(null)	(null)
...				
14	Taylor	8600	0.2	123840
15	Grant	7000	0.15	96600
16	Whalen	4400	(null)	(null)
17	Hartstein	13000	(null)	(null)
18	Fay	6000	(null)	(null)
19	Higgins	12008	(null)	(null)
20	Gietz	8300	(null)	(null)

Notice that the annual compensation is calculated for only those employees who earn a

commission. If any column value in an expression is null, the result is null. To calculate values for all employees, you must convert the null value to a number before applying the arithmetic operator. In the example in the slide, the `NVL` function is used to convert null values to zero.

Using the NVL2 Function

The NVL2 function examines the first expression.

If the first expression is not null, the NVL2 function returns the second expression.

If the first expression is null, the third expression is returned.

```
SELECT last name, salary, commission_pct  
       NVL2(commission_pct,  
            'SAL+COMM', 'SAL') income  
FROM   employees WHERE department_id IN (50, 80);
```

	LAST_NAME	SALARY	COMMISSION_PCT	INCOME
1	Mourgos	5800	(null)	SAL
2	Rajs	3500	(null)	SAL
3	Davies	3100	(null)	SAL
4	Matos	2600	(null)	SAL
5	Vargas	2500	(null)	SAL
6	Zlotkey	10500	0.2	SAL+COMM
7	Abel	11000	0.3	SAL+COMM
8	Taylor	8600	0.2	SAL+COMM

ORACLE

The NVL2 function examines the first expression. If the first expression is not null, the NVL2 function returns the second expression. If the first expression is null, the third expression is returned.

Syntax

`NVL2(expr1, expr2, expr3)`

In the syntax:

- *expr1* is the source value or expression that may contain a null
- *expr2* is the value that is returned if *expr1* is not null
- *expr3* is the value that is returned if *expr1* is null

In the example shown in the slide, the COMMISSION_PCT column is examined. If a value is detected, the text literal value of SAL+COMM is returned. If the COMMISSION_PCT column contains a null value, the text literal value of SAL is returned.

Note: The argument *expr1* can have any data type. The arguments *expr2* and *expr3* can have any data types except LONG.


Using the NULLIF Function

The NULLIF function compares two expressions.

If they are equal, the function returns null.

If they are not, the function returns *expr1*.

```
SELECT first_name, LENGTH(first_name) "expr1",  
       last_name, LENGTH(last_name) "expr2",  
       NULLIF(LENGTH(first_name), LENGTH(last_name)) result  
FROM employees;
```



	1	FIRST_NAME	2	expr1	3	LAST_NAME	4	expr2	5	RESULT
1	Ellen	5	Abel	4	5					
2	Curtis	6	Davies	6	(null)					
3	Lex	3	De Haan	7	3					
4	Bruce	5	Ernst	5	(null)					
5	Pat	3	Fay	3	(null)					
6	William	7	Gietz	5	7					
7	Kimberely	9	Grant	5	9					
8	Michael	7	Hartstein	9	7					
9	Shelley	7	Higgins	7	(null)					

...

1

2

3

ORACLE

The NULLIF function compares two expressions.

Syntax

```
NULLIF (expr1, expr2)
```

In the syntax:

- NULLIF compares *expr1* and *expr2*. If they are equal, the function returns null. If they are not, the function returns *expr1*. However, you cannot specify the literal NULL for *expr1*.

In the example shown in the slide, the length of the first name in the EMPLOYEES table is compared to the length of the last name in the EMPLOYEES table. When the lengths of the names are equal, a null value is displayed. When the lengths of the names are not equal, the length of the first name is displayed.

Using the COALESCE Function

- The COALESCE function returns the first non-null expression in the list.
- COALESCE (*expr1*, *expr2*, ... *exprn*)
- In the syntax:
 - *expr1* returns this expression if it is not null
 - *expr2* returns this expression if the first expression is null and this expression is not null
 - *exprn* returns this expression if the preceding expressions are null
- Note that all expressions must be of the same data type.

Using the COALESCE Function

```
SELECT last name, employee id,  
COALESCE(TO_CHAR(commission_pct),TO_CHAR(manager_id),  
        'No commission and no manager')  
FROM employees;
```

	LAST_NAME	EMPLOYEE_ID	COALESCE(TO_CHAR(COMMISSION_PCT),TO_CHAR(MANAGER_ID),'NOCOMMISSIONANDNOMANAGER')
1	King	100	No commission and no manager
2	Kochhar	101	100
3	De Haan	102	100
4	Hunold	103	102

...

13	Abel	174	.3
14	Taylor	176	.2
15	Grant	178	.15

If the `manager_id` value is not null, it is displayed.

If the `manager_id` value is null, the `commission_pct` is displayed.

If the `manager_id` and `commission_pct` values are null,
"No commission and no manager" is displayed.

ORACLE

In the example shown in the slide, if the `manager_id` value is not null, it is displayed. If the `manager_id` value is null, the `commission_pct` is displayed. If the `manager_id` and `commission_pct` values are null, "No commission and no manager" is displayed. Note that `TO_CHAR` function is applied so that all expressions are of the same data type.

	LAST_NAME	SALARY	COMMISSION_PCT	New Salary
1	King	24000	(null)	26000
2	Kochhar	17000	(null)	19000
3	De Haan	17000	(null)	19000
4	Hunold	9000	(null)	11000
5	Ernst	6000	(null)	8000
6	Lorentz	4200	(null)	6200
7	Mourgos	5800	(null)	7800
8	Rajs	3500	(null)	5500
9	Davies	3100	(null)	5100
10	Matos	2600	(null)	4600
11	Vargas	2500	(null)	4500
12	Zlotkey	10500	0.2	12600
13	Abel	11000	0.3	14300
14	Taylor	8600	0.2	10320
15	Grant	7000	0.15	8050
16	Whalen	4400	(null)	6400
17	Hartstein	13000	(null)	15000
18	Fay	6000	(null)	8000
19	Higgins	12008	(null)	14008
20	Gietz	8300	(null)	10300

Conditional Expressions

- The two methods that are used to implement conditional processing (`IF-THEN-ELSE` logic) in a SQL statement are the `CASE` expression and the `DECODE` function.
- **Note:** The `CASE` expression complies with the ANSI SQL. The `DECODE` function is specific to Oracle syntax.
- Provide the use of the `IF-THEN-ELSE` logic within a SQL statement.
- Use two methods:
 - `CASE` expression
 - `DECODE` function

CASE Expression

Facilitates conditional inquiries by doing the work of an IF-THEN-ELSE statement:

```
CASE expr WHEN comparison_expr1 THEN return_expr1
        [WHEN comparison_expr2 THEN return_expr2
        WHEN comparison_exprn THEN return_exprn
        ELSE else_expr]
END
```

CASE expressions allow you to use the IF-THEN-ELSE logic in SQL statements without having to invoke procedures.

In a simple CASE expression, the Oracle server searches for the first WHEN ... THEN pair for which `expr` is equal to `comparison_expr` and returns `return_expr`. If none of the WHEN ... THEN pairs meet this condition, and if an ELSE clause exists, the Oracle server returns `else_expr`. Otherwise, the Oracle server returns a null. You cannot specify the literal NULL for all the `return_exprs` and the `else_expr`.

The expressions `expr` and `comparison_expr` must be of the same data type, which can be CHAR, VARCHAR2, NCHAR, or NVARCHAR2, NUMBER, BINARY_FLOAT, or BINARY_DOUBLE or must all have a numeric datatype. All of the return values (`return_expr`) must be of the same data type.

If all expressions have a numeric datatype, then Oracle determines the argument with the highest numeric precedence, implicitly converts the remaining arguments to that datatype, and returns that datatype.

Using the CASE Expression

Facilitates conditional inquiries by doing the work of an IF-THEN-ELSE statement:

```
SELECT last_name, job_id, salary,  
       CASE job_id WHEN 'IT_PROG' THEN 1.10*salary  
                   WHEN 'ST_CLERK' THEN 1.15*salary  
                   WHEN 'SA_REP' THEN 1.20*salary  
       ELSE salary END "REVISED_SALARY"  
FROM employees;
```

	LAST_NAME	JOB_ID	SALARY	REVISED_SALARY
1	King	AD_PRES	24000	24000
...				
4	Hunold	IT_PROG	9000	9900
5	Ernst	IT_PROG	6000	6600
6	Lorentz	IT_PROG	4200	4620
7	Mourgos	ST_MAN	5800	5800
8	Rajs	ST_CLERK	3500	4025
9	Davies	ST_CLERK	3100	3565
10	Matos	ST_CLERK	2600	2990
11	Vargas	ST_CLERK	2500	2875
...				
13	Abel	SA_REP	11000	13200
14	Taylor	SA_REP	8600	10320
15	Grant	SA_REP	7000	8400

ORACLE

In the SQL statement in the slide, the value of `JOB_ID` is decoded. If `JOB_ID` is `IT_PROG`, the salary increase is 10%; if `JOB_ID` is `ST_CLERK`, the salary increase is 15%; if `JOB_ID` is `SA_REP`, the salary increase is 20%. For all other job roles, there is no increase in salary.

The same statement can be written with the `DECODE` function.

The following code is an example of the searched `CASE` expression. In a searched `CASE` expression, the search occurs from left to right until an occurrence of the listed condition is found, and then it returns the return expression. If no condition is found to be true, and if an `ELSE` clause exists, the return expression in the `ELSE` clause is returned; otherwise, a `NULL` is returned.

```
SELECT last_name, salary,  
       (CASE WHEN salary < 5000 THEN 'Low'  
             WHEN salary < 10000 THEN 'Medium'  
             WHEN salary < 20000 THEN 'Good'  
             ELSE 'Excellent'  
       END) qualified_salary  
FROM employees;
```

Another example:

```
SELECT last_name, salary,  
(CASE WHEN salary<5000 THEN 'Low'  
      WHEN salary<10000 THEN 'Medium'  
      WHEN salary<20000 THEN 'Good'  
      ELSE 'Excellent'  
END) qualified_salary  
FROM employees;
```

DECODE Function

- The `DECODE` function decodes an expression in a way similar to the `IF-THEN-ELSE` logic that is used in various languages.
- The `DECODE` function decodes *expression* after comparing it to each *search* value.
- If the expression is the same as *search*, *result* is returned.
- If the default value is omitted, a null value is returned where a search value does not match any of the result values.

```
DECODE(col|expression, search1, result1  
      [, search2, result2,...,]  
      [, default])
```

Using the DECODE Function

```
SELECT last_name, job_id, salary,
       DECODE(job_id, 'IT_PROG', 1.10*salary,
                'ST_CLERK', 1.15*salary,
                'SA_REP', 1.20*salary,
                salary)
       REVISED_SALARY
FROM   employees;
```

	LAST_NAME	JOB_ID	SALARY	REVISED_SALARY
...				
4	Hunold	IT_PROG	9000	9900
5	Ernst	IT_PROG	6000	6600
6	Lorentz	IT_PROG	4200	4620
7	Mourgos	ST_MAN	5800	5800
8	Rajs	ST_CLERK	3500	4025
9	Davies	ST_CLERK	3100	3565
10	Matos	ST_CLERK	2600	2990
11	Vargas	ST_CLERK	2500	2875
12	Zlotkey	SA_MAN	10500	10500
...				
13	Abel	SA_REP	11000	13200
14	Taylor	SA_REP	8600	10320
15	Grant	SA_REP	7000	8400

If JOB_ID is IT_PROG, the salary increase is 10%;

if JOB_ID is ST_CLERK, the salary increase is 15%;

if JOB_ID is SA_REP, the salary increase is 20%.

For all other job roles, there is no increase in salary.

ORACLE

In the SQL statement in the slide, the value of JOB_ID is tested. If JOB_ID is IT_PROG, the salary increase is 10%; if JOB_ID is ST_CLERK, the salary increase is 15%; if JOB_ID is SA_REP, the salary increase is 20%. For all other job roles, there is no increase in salary.

The same statement can be expressed in pseudocode as an IF-THEN-ELSE statement:

```
IF job_id = 'IT_PROG'      THEN salary = salary*1.10
IF job_id = 'ST_CLERK'    THEN salary = salary*1.15
IF job_id = 'SA_REP'      THEN salary = salary*1.20
ELSE salary = salary
```

Using the DECODE Function

Display the applicable tax rate for each employee in department 80 based on the monthly salary:

```
SELECT last name, salary,  
       DECODE (TRUNC(salary/2000, 0),  
               0, 0.00,  
               1, 0.09,  
               2, 0.20,  
               3, 0.30,  
               4, 0.40,  
               5, 0.42,  
               6, 0.44,  
               0.45) TAX_RATE  
FROM   employees  
WHERE  department_id = 80;
```

ORACLE

This slide shows another example using the `DECODE` function. In this example, you determine the tax rate for each employee in department 80 based on the monthly salary.

	LAST_NAME	SALARY	TAX_RATE
1	Zlotkey	10500	0.42
2	Abel	11000	0.42
3	Taylor	8600	0.4

Quiz

The `TO_NUMBER` function converts either character strings or date values to a number in the format specified by the optional format model.

- a. True
- b. False

Answer: b

Summary

In this lesson, you should have learned how to:

- Alter date formats for display using functions
- Convert column data types using functions
- Use `NVL` functions
- Use `IF-THEN-ELSE` logic and other conditional expressions in a `SELECT` statement

Remember the following:

- Conversion functions can convert character, date, and numeric values: `TO_CHAR`, `TO_DATE`, `TO_NUMBER`
- There are several functions that pertain to nulls, including `NVL`, `NVL2`, `NULLIF`, and `COALESCE`.
- The `IF-THEN-ELSE` logic can be applied within a SQL statement by using the `CASE` expression or the `DECODE` function.