

10

Using DDL Statements to Create and Manage Tables

ORACLE®

Copyright © 2007, Oracle. All rights reserved.

Objectives

After completing this lesson, you should be able to do the following:

- Categorize the main database objects
- Review the table structure
- List the data types that are available for columns
- Create a simple table
- Explain how constraints are created at the time of table creation
- Describe how schema objects work

ORACLE

10 - 2

Copyright © 2007, Oracle. All rights reserved.

Objectives

In this lesson, you are introduced to the data definition language (DDL) statements. You are taught the basics of how to create simple tables, alter them, and remove them. The data types available in DDL are shown and schema concepts are introduced. Constraints are discussed in this lesson. Exception messages that are generated from violating constraints during DML operations are shown and explained.

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

Database Objects

Object	Description
Table	Basic unit of storage; composed of rows
View	Logically represents subsets of data from one or more tables
Sequence	Generates numeric values
Index	Improves the performance of some queries
Synonym	Gives alternative name to an object

ORACLE

10 - 4

Copyright © 2007, Oracle. All rights reserved.

Database Objects

The Oracle database can contain multiple data structures. Each structure should be outlined in the database design so that it can be created during the build stage of database development.

- **Table:** Stores data
- **View:** Subset of data from one or more tables
- **Sequence:** Generates numeric values
- **Index:** Improves the performance of some queries
- **Synonym:** Gives alternative name to an object

Oracle Table Structures

- Tables can be created at any time, even when users are using the database.
- You do not need to specify the size of a table. The size is ultimately defined by the amount of space allocated to the database as a whole. It is important, however, to estimate how much space a table will use over time.
- Table structure can be modified online.

Note: More database objects are available, but are not covered in this course.

Naming Rules

Table names and column names:

- Must begin with a letter
- Must be 1–30 characters long
- Must contain only A–Z, a–z, 0–9, _, \$, and #
- Must not duplicate the name of another object owned by the same user
- Must not be an Oracle server–reserved word

ORACLE

10 - 5

Copyright © 2007, Oracle. All rights reserved.

Naming Rules

You name database tables and columns according to the standard rules for naming any Oracle database object:

- Table names and column names must begin with a letter and be 1–30 characters long.
- Names must contain only the characters A–Z, a–z, 0–9, _ (underscore), \$, and # (legal characters, but their use is discouraged).
- Names must not duplicate the name of another object owned by the same Oracle server user.
- Names must not be an Oracle server–reserved word.
 - You may also use quoted identifiers to represent the name of an object. A quoted identifier begins and ends with double quotation marks (“”). If you name a schema object using a quoted identifier, then you must use the double quotation marks whenever you refer to that object. Quoted identifiers can be reserved words, although this is not recommended.

Naming Guidelines

Use descriptive names for tables and other database objects.

Note: Names are not case-sensitive. For example, EMPLOYEES is treated to be the same name as eMPloyees or eMpLOYEES. However, quoted identifiers are case-sensitive.

For more information, see the section on *Schema Object Names and Qualifiers* in the *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

CREATE TABLE Statement

- You must have:
 - CREATE TABLE privilege
 - A storage area

```
CREATE TABLE [schema.]table  
  (column datatype [DEFAULT expr] [, ...]);
```

- You specify:
 - Table name
 - Column name, column data type, and column size



ORACLE

10 - 7

Copyright © 2007, Oracle. All rights reserved.

CREATE TABLE Statement

You create tables to store data by executing the SQL CREATE TABLE statement. This statement is one of the DDL statements that are a subset of the SQL statements used to create, modify, or remove Oracle database structures. These statements have an immediate effect on the database and they also record information in the data dictionary.


To create a table, a user must have the CREATE TABLE privilege and a storage area in which to create objects. The database administrator (DBA) uses data control language (DCL) statements to grant privileges to users.

In the syntax:

<i>schema</i>	Is the same as the owner's name
<i>table</i>	Is the name of the table
DEFAULT <i>expr</i>	Specifies a default value if a value is omitted in the INSERT statement
<i>column</i>	Is the name of the column
<i>datatype</i>	Is the column's data type and length

Referencing Another User's Tables

- Tables belonging to other users are not in the user's schema.
- You should use the owner's name as a prefix to those tables.



ORACLE

10 - 8

Copyright © 2007, Oracle. All rights reserved.

Referencing Another User's Tables

A schema is a collection of logical structures of data or *schema objects*. A schema is owned by a database user and has the same name as that user. Each user owns a single schema.

Schema objects can be created and manipulated with SQL and include tables, views, synonyms, sequences, stored procedures, indexes, clusters, and database links.

If a table does not belong to the user, the owner's name must be prefixed to the table. For example, if there are schemas named USERA and USERB, and both have an EMPLOYEES table, then if USERA wants to access the EMPLOYEES table that belongs to USERB, USERA must prefix the table name with the schema name:

```
SELECT *
FROM   userb.employees;
```

If USERB wants to access the EMPLOYEES table that is owned by USERA, USERB must prefix the table name with the schema name:

```
SELECT *
FROM   usera.employees;
```


DEFAULT Option

- Specify a default value for a column during an insert.

```
... hire_date DATE DEFAULT SYSDATE, ...
```

- Literal values, expressions, or SQL functions are legal values.
- Another column's name or a pseudocolumn are illegal values.
- The default data type must match the column data type.

```
CREATE TABLE hire_dates  
  (id          NUMBER(8) ,  
   hire_date DATE DEFAULT SYSDATE) ;
```

```
CREATE TABLE succeeded.
```

ORACLE

10 - 9

Copyright © 2007, Oracle. All rights reserved.

DEFAULT Option

When you define a table, you can specify that a column should be given a default value by using the **DEFAULT** option. This option prevents null values from entering the columns when a row is inserted without a value for the column. The default value can be a literal, an expression, or a SQL function (such as **SYSDATE** or **USER**), but the value cannot be the name of another column or a pseudocolumn (such as **NEXTVAL** or **CURRVAL**). The default expression must match the data type of the column.

Consider the following examples:

```
INSERT INTO hire_dates values(45, NULL);
```

The above statement will insert the null value rather than the default value.

```
INSERT INTO hire_dates(id) values(35);
```

The above statement will insert **SYSDATE** for the **HIRE_DATE** column.

Note: In SQL Developer, click the Run Script icon or press [F5] to run the DDL statements. The feedback messages will be shown on the Script Output tabbed page.

Creating Tables

- Create the table:

```
CREATE TABLE dept
  (deptno      NUMBER(2) ,
   dname       VARCHAR2(14) ,
   loc         VARCHAR2(13) ,
   create_date DATE DEFAULT SYSDATE) ;
```

```
CREATE TABLE succeeded.
```

- Confirm table creation:

```
DESCRIBE dept
```

DESCRIBE dept		
Name	Null	Type

DEPTNO		NUMBER(2)
DNAME		VARCHAR2(14)
LOC		VARCHAR2(13)
CREATE_DATE		DATE

ORACLE

Creating Tables

The example in the slide creates the DEPT table with four columns: DEPTNO, DNAME, LOC, and CREATE_DATE. The CREATE_DATE column has a default value. If a value is not provided for an INSERT statement, the system date is automatically inserted.

To confirm that the table was created, run the DESCRIBE command.

Because creating a table is a DDL statement, an automatic commit takes place when this statement is executed.

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

Data Types

Data Type	Description
VARCHAR2 (<i>size</i>)	Variable-length character data
CHAR (<i>size</i>)	Fixed-length character data
NUMBER (<i>p</i> , <i>s</i>)	Variable-length numeric data
DATE	Date and time values
LONG	Variable-length character data (up to 2 GB)
CLOB	Character data (up to 4 GB)
RAW and LONG RAW	Raw binary data
BLOB	Binary data (up to 4 GB)
BFILE	Binary data stored in an external file (up to 4 GB)
ROWID	A base-64 number system representing the unique address of a row in its table

ORACLE

10 - 12

Copyright © 2007, Oracle. All rights reserved.

Data Types

When you identify a column for a table, you need to provide a data type for the column. There are several data types available:

Data Type	Description
VARCHAR2 (<i>size</i>)	Variable-length character data (A maximum <i>size</i> must be specified: minimum <i>size</i> is 1; maximum <i>size</i> is 4,000.)
CHAR [(<i>size</i>)]	Fixed-length character data of length <i>size</i> bytes (Default and minimum <i>size</i> is 1; maximum <i>size</i> is 2,000.)
NUMBER [(<i>p</i> , <i>s</i>)]	Number having precision <i>p</i> and scale <i>s</i> (Precision is the total number of decimal digits and scale is the number of digits to the right of the decimal point; precision can range from 1 to 38, and scale can range from –84 to 127.)
DATE	Date and time values to the nearest second between January 1, 4712 B.C., and December 31, 9999 A.D.
LONG	Variable-length character data (up to 2 GB)
CLOB	Character data (up to 4 GB)

Data Types (continued)

Data Type	Description
RAW (<i>size</i>)	Raw binary data of length <i>size</i> (A maximum <i>size</i> must be specified: maximum <i>size</i> is 2,000.)
LONG RAW	Raw binary data of variable length (up to 2 GB)
BLOB	Binary data (up to 4 GB)
BFILE	Binary data stored in an external file (up to 4 GB)
ROWID	A base-64 number system representing the unique address of a row in its table

Guidelines

- A LONG column is not copied when a table is created using a subquery.
- A LONG column cannot be included in a GROUP BY or an ORDER BY clause.
- Only one LONG column can be used per table.
- No constraints can be defined on a LONG column.
- You might want to use a CLOB column rather than a LONG column.

Datetime Data Types

You can use several datetime data types:

Data Type	Description
TIMESTAMP	Date with fractional seconds
INTERVAL YEAR TO MONTH	Stored as an interval of years and months
INTERVAL DAY TO SECOND	Stored as an interval of days, hours, minutes, and seconds



ORACLE

10 - 14

Copyright © 2007, Oracle. All rights reserved.

Datetime Data Types

Data Type	Description
TIMESTAMP	Enables storage of time as a date with fractional seconds. It stores the year, month, day, hour, minute, and the second value of the DATE data type as well as the fractional seconds value There are several variations of this data type such as WITH TIMEZONE, WITH LOCALTIMEZONE.
INTERVAL YEAR TO MONTH	Enables storage of time as an interval of years and months. Used to represent the difference between two datetime values in which the only significant portions are the year and month
INTERVAL DAY TO SECOND	Enables storage of time as an interval of days, hours, minutes, and seconds. Used to represent the precise difference between two datetime values

Note: These datetime data types are available with Oracle9i and later releases. The datetime data types are discussed in detail in the lesson titled “Managing Data in Different Time Zones” in the *Oracle Database 11g: SQL Fundamentals II* course.

Also, for more information about the datetime data types, see the topics *TIMESTAMP Datatype*, *INTERVAL YEAR TO MONTH Datatype*, and *INTERVAL DAY TO SECOND Datatype* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

Including Constraints

- Constraints enforce rules at the table level.
- Constraints prevent the deletion of a table if there are dependencies.
- The following constraint types are valid:
 - NOT NULL
 - UNIQUE
 - PRIMARY KEY
 - FOREIGN KEY
 - CHECK



ORACLE

10 - 16

Copyright © 2007, Oracle. All rights reserved.

Constraints

The Oracle server uses constraints to prevent invalid data entry into tables.

You can use constraints to do the following:

- Enforce rules on the data in a table whenever a row is inserted, updated, or deleted from that table. The constraint must be satisfied for the operation to succeed.
- Prevent the deletion of a table if there are dependencies from other tables.
- Provide rules for Oracle tools, such as Oracle Developer.

Data Integrity Constraints

Constraint	Description
NOT NULL	Specifies that the column cannot contain a null value
UNIQUE	Specifies a column or combination of columns whose values must be unique for all rows in the table
PRIMARY KEY	Uniquely identifies each row of the table
FOREIGN KEY	Establishes and enforces a referential integrity between the column and a column of the referenced table such that values in one table match values in another table.
CHECK	Specifies a condition that must be true

Constraint Guidelines

- You can name a constraint, or the Oracle server generates a name by using the `SYS_Cn` format.
- Create a constraint at either of the following times:
 - At the same time as the creation of the table
 - After the creation of the table
- Define a constraint at the column or table level.
- View a constraint in the data dictionary.

ORACLE

10 - 17

Copyright © 2007, Oracle. All rights reserved.

Constraint Guidelines

All constraints are stored in the data dictionary. Constraints are easy to reference if you give them a meaningful name. Constraint names must follow the standard object-naming rules, except that the name cannot be the same as another object owned by the same user. If you do not name your constraint, the Oracle server generates a name with the format `SYS_Cn`, where *n* is an integer so that the constraint name is unique.

Constraints can be defined at the time of table creation or after the creation of the table. You can define a constraint at the column or table level. Functionally, a table-level constraint is the same as a column-level constraint.

For more information, see the section on “Constraints” in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Defining Constraints

- Syntax:

```
CREATE TABLE [schema.] table
  (column datatype [DEFAULT expr]
   [column_constraint],
   ...
   [table_constraint][, ...]) ;
```

- Column-level constraint syntax:

```
column [CONSTRAINT constraint_name] constraint_type,
```

- Table-level constraint syntax:

```
column, ...
  [CONSTRAINT constraint_name] constraint_type
  (column, ...),
```

ORACLE

10 - 18

Copyright © 2007, Oracle. All rights reserved.

Defining Constraints

The slide gives the syntax for defining constraints when creating a table. You can create constraints at either the column level or table level. Constraints defined at the column level are included when the column is defined. Table-level constraints are defined at the end of the table definition and must refer to the column or columns on which the constraint pertains in a set of parentheses. It is mainly the syntax that differentiates the two; otherwise, functionally, a column-level constraint is the same as a table-level constraint.

NOT NULL constraints must be defined at the column level.

Constraints that apply to more than one column must be defined at the table level.

In the syntax:

schema	Is the same as the owner's name
table	Is the name of the table
DEFAULT expr	Specifies a default value to be used if a value is omitted in the INSERT statement
column	Is the name of the column
datatype	Is the column's data type and length
column_constraint	Is an integrity constraint as part of the column definition
table_constraint	Is an integrity constraint as part of the table definition

Defining Constraints

- Example of a column-level constraint:

```
CREATE TABLE employees(  
  employee_id  NUMBER(6)  
    CONSTRAINT emp_emp_id_pk PRIMARY KEY,  
  first_name   VARCHAR2(20),  
  ...);
```

1

- Example of a table-level constraint:

```
CREATE TABLE employees(  
  employee_id  NUMBER(6),  
  first_name   VARCHAR2(20),  
  ...  
  job_id       VARCHAR2(10) NOT NULL,  
  CONSTRAINT emp_emp_id_pk  
    PRIMARY KEY (EMPLOYEE_ID));
```

2

ORACLE

10 - 19

Copyright © 2007, Oracle. All rights reserved.

Defining Constraints (continued)

Constraints are usually created at the same time as the table. Constraints can be added to a table after its creation and also be temporarily disabled.

Both examples in the slide create a primary key constraint on the `EMPLOYEE_ID` column of the `EMPLOYEES` table.

1. The first example uses the column-level syntax to define the constraint.
2. The second example uses the table-level syntax to define the constraint.

More details about the primary key constraint are provided later in this lesson.

NOT NULL Constraint

Ensures that null values are not permitted for the column:

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	HIRE_DATE	JOB_ID	COMMISSION_PCT
100	Steven	King	SKING	17-JUN-87	AD_PRES	(null)
101	Neena	Kochhar	NKOCHHAR	21-SEP-89	AD_VP	(null)
102	Lex	De Haan	LDEHAAN	13-JAN-93	AD_VP	(null)
103	Alexander	Hunold	AHUNOLD	03-JAN-90	IT_PROG	(null)
104	Bruce	Ernst	BERNST	21-MAY-91	IT_PROG	(null)
107	Diana	Lorentz	DLORENTZ	07-FEB-99	IT_PROG	(null)
124	Kevin	Mourgos	KMOURGOS	16-NOV-99	ST_MAN	(null)
141	Trenna	Rajs	TRAJS	17-OCT-95	ST_CLERK	(null)
142	Curtis	Davies	CDAVIES	29-JAN-97	ST_CLERK	(null)
143	Randall	Matos	RMATOS	15-MAR-98	ST_CLERK	(null)
144	Peter	Vargas	PVARGAS	09-JUL-98	ST_CLERK	(null)
149	Eleni	Zlotkey	EZLOTKEY	29-JAN-00	SA_MAN	0.2
174	Ellen	Abel	EABEL	11-MAY-96	SA_REP	0.3

...

**NOT NULL constraint
(Primary Key enforces
NOT NULL constraint.)**

**NOT NULL
constraint**

**Absence of NOT NULL
constraint (Any row can
contain a null value for
this column.)**


ORACLE

NOT NULL Constraint

The NOT NULL constraint ensures that the column contains no null values. Columns without the NOT NULL constraint can contain null values by default. NOT NULL constraints must be defined at the column level. In the EMPLOYEES table, the EMPLOYEE_ID column inherits a NOT NULL constraint as it is defined as a primary key. Otherwise, the LAST_NAME, EMAIL, HIRE_DATE, and JOB_ID columns have the NOT NULL constraint enforced on them.

Note: Primary key constraint is discussed in detail later in this lesson.

UNIQUE Constraint



ORACLE

10 - 21

Copyright © 2007, Oracle. All rights reserved.

UNIQUE Constraint

A **UNIQUE** key integrity constraint requires that every value in a column or a set of columns (key) be unique—that is, no two rows of a table can have duplicate values in a specified column or a set of columns. The column (or set of columns) included in the definition of the **UNIQUE** key constraint is called the *unique key*. If the **UNIQUE** constraint comprises more than one column, that group of columns is called a *composite unique key*.

UNIQUE constraints enable the input of nulls unless you also define **NOT NULL** constraints for the same columns. In fact, any number of rows can include nulls for columns without the **NOT NULL** constraints because nulls are not considered equal to anything. A null in a column (or in all columns of a composite **UNIQUE** key) always satisfies a **UNIQUE** constraint.

Note: Because of the search mechanism for the **UNIQUE** constraints on more than one column, you cannot have identical values in the non-null columns of a partially null composite **UNIQUE** key constraint.

UNIQUE Constraint

Defined at either the table level or the column level:

```
CREATE TABLE employees (  
    employee_id      NUMBER(6) ,  
    last_name        VARCHAR2(25) NOT NULL ,  
    email            VARCHAR2(25) ,  
    salary           NUMBER(8,2) ,  
    commission_pct   NUMBER(2,2) ,  
    hire_date        DATE NOT NULL ,  
    ...  
    CONSTRAINT emp_email_uk UNIQUE(email));
```

ORACLE

10 - 22

Copyright © 2007, Oracle. All rights reserved.

UNIQUE Constraint (continued)

UNIQUE constraints can be defined at the column level or table level. You define the constraint at the table level when you want to create a composite unique key. A composite key is defined when there is not a single attribute that can uniquely identify a row. In that case, you can have a unique key that is composed of two or more columns, the combined value of which is always unique and can identify rows.

The example in the slide applies the UNIQUE constraint to the EMAIL column of the EMPLOYEES table. The name of the constraint is EMP_EMAIL_UK.

Note: The Oracle server enforces the UNIQUE constraint by implicitly creating a unique index on the unique key column or columns.

PRIMARY KEY Constraint

DEPARTMENTS PRIMARY KEY

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	10	Administration	200	1700
2	20	Marketing	201	1800
3	50	Shipping	124	1500
4	60	IT	103	1400
5	80	Sales	149	2500
6	90	Executive	100	1700
7	110	Accounting	205	1700
8	190	Contracting	(null)	1700

Not allowed
(null value)

↑ INSERT INTO

Public Accounting	124	2500
50 Finance	124	1500

Not allowed
(50 already exists)

ORACLE

10 - 23


Copyright © 2007, Oracle. All rights reserved.

PRIMARY KEY Constraint

A **PRIMARY KEY** constraint creates a primary key for the table. Only one primary key can be created for each table. The **PRIMARY KEY** constraint is a column or a set of columns that uniquely identifies each row in a table. This constraint enforces the uniqueness of the column or column combination and ensures that no column that is part of the primary key can contain a null value.

Note: Because uniqueness is part of the primary key constraint definition, the Oracle server enforces the uniqueness by implicitly creating a unique index on the primary key column or columns.

FOREIGN KEY Constraint



ORACLE

10 - 24

Copyright © 2007, Oracle. All rights reserved.

FOREIGN KEY Constraint

The FOREIGN KEY (or referential integrity) constraint designates a column or a combination of columns as a foreign key and establishes a relationship with a primary key or a unique key in the same table or a different table.

In the example in the slide, DEPARTMENT_ID has been defined as the foreign key in the EMPLOYEES table (dependent or child table); it references the DEPARTMENT_ID column of the DEPARTMENTS table (the referenced or parent table).

Guidelines

- A foreign key value must match an existing value in the parent table or be NULL.
- Foreign keys are based on data values and are purely logical, rather than physical, pointers.

FOREIGN KEY Constraint

Defined at either the table level or the column level:

```
CREATE TABLE employees (  
    employee_id      NUMBER(6),  
    last_name        VARCHAR2(25) NOT NULL,  
    email            VARCHAR2(25),  
    salary           NUMBER(8,2),  
    commission_pct   NUMBER(2,2),  
    hire_date        DATE NOT NULL,  
    ...  
    department_id    NUMBER(4),  
    CONSTRAINT emp_dept_fk FOREIGN KEY (department_id)  
        REFERENCES departments(department_id),  
    CONSTRAINT emp_email_uk UNIQUE(email));
```

ORACLE

10 - 25

Copyright © 2007, Oracle. All rights reserved.

FOREIGN KEY Constraint (continued)

FOREIGN KEY constraints can be defined at the column or table constraint level. A composite foreign key must be created by using the table-level definition.

The example in the slide defines a FOREIGN KEY constraint on the DEPARTMENT_ID column of the EMPLOYEES table, using table-level syntax. The name of the constraint is EMP_DEPT_FK.

The foreign key can also be defined at the column level, provided that the constraint is based on a single column. The syntax differs in that the keywords FOREIGN KEY do not appear. For example:

```
CREATE TABLE employees  
(  
    ...  
    department_id NUMBER(4) CONSTRAINT emp_deptid_fk  
        REFERENCES departments(department_id),  
    ...  
)
```

FOREIGN KEY Constraint: Keywords

- **FOREIGN KEY:** Defines the column in the child table at the table-constraint level
- **REFERENCES:** Identifies the table and column in the parent table
- **ON DELETE CASCADE:** Deletes the dependent rows in the child table when a row in the parent table is deleted
- **ON DELETE SET NULL:** Converts dependent foreign key values to null

ORACLE

10 - 26

Copyright © 2007, Oracle. All rights reserved.

FOREIGN KEY Constraint: Keywords

The foreign key is defined in the child table and the table containing the referenced column is the parent table. The foreign key is defined using a combination of the following keywords:

- **FOREIGN KEY** is used to define the column in the child table at the table-constraint level.
- **REFERENCES** identifies the table and the column in the parent table.
- **ON DELETE CASCADE** indicates that when a row in the parent table is deleted, the dependent rows in the child table are also deleted.
- **ON DELETE SET NULL** indicates that when a row in the parent table is deleted, the foreign key values are set to null.

The default behavior is called the *restrict rule*, which disallows the update or deletion of referenced data.

Without the **ON DELETE CASCADE** or the **ON DELETE SET NULL** options, the row in the parent table cannot be deleted if it is referenced in the child table.

CHECK Constraint

- Defines a condition that each row must satisfy
- The following expressions are not allowed:
 - References to CURRVAL, NEXTVAL, LEVEL, and ROWNUM pseudocolumns
 - Calls to SYSDATE, UID, USER, and USERENV functions
 - Queries that refer to other values in other rows

```
..., salary NUMBER(2)
      CONSTRAINT emp_salary_min
      CHECK (salary > 0),...
```

ORACLE

10 - 27

Copyright © 2007, Oracle. All rights reserved.

CHECK Constraint

The CHECK constraint defines a condition that each row must satisfy. The condition can use the same constructs as the query conditions, with the following exceptions:

- References to the CURRVAL, NEXTVAL, LEVEL, and ROWNUM pseudocolumns
- Calls to SYSDATE, UID, USER, and USERENV functions
- Queries that refer to other values in other rows

A single column can have multiple CHECK constraints that refer to the column in its definition. There is no limit to the number of CHECK constraints that you can define on a column.

CHECK constraints can be defined at the column level or table level.

```
CREATE TABLE employees
(
  ...
  salary NUMBER(8,2) CONSTRAINT emp_salary_min
                        CHECK (salary > 0),
  ...
)
```

CREATE TABLE: Example

```
CREATE TABLE employees
( employee_id      NUMBER(6)
  CONSTRAINT emp_employee_id PRIMARY KEY
, first_name       VARCHAR2(20)
, last_name        VARCHAR2(25)
  CONSTRAINT emp_last_name_nn NOT NULL
, email            VARCHAR2(25)
  CONSTRAINT emp_email_nn    NOT NULL
  CONSTRAINT emp_email_uk    UNIQUE
, phone_number     VARCHAR2(20)
, hire_date        DATE
  CONSTRAINT emp_hire_date_nn NOT NULL
, job_id           VARCHAR2(10)
  CONSTRAINT emp_job_nn      NOT NULL
, salary           NUMBER(8,2)
  CONSTRAINT emp_salary_ck   CHECK (salary>0)
, commission_pct   NUMBER(2,2)
, manager_id       NUMBER(6)
  CONSTRAINT emp_manager_fk REFERENCES
    employees (employee_id)
, department_id    NUMBER(4)
  CONSTRAINT emp_dept_fk    REFERENCES
    departments (department_id));
```

ORACLE

10 - 28

Copyright © 2007, Oracle. All rights reserved.

CREATE TABLE: Example

The example in the slide shows the statement that is used to create the EMPLOYEES table in the HR schema.

Violating Constraints

```
UPDATE employees
SET   department_id = 55
WHERE department_id = 110;
```

Error starting at line 1 in command:

```
UPDATE employees
SET   department_id = 55
WHERE department_id = 110
```

Error report:

```
SQL Error: ORA-02291: integrity constraint (ORA16.EMP_DEPT_FK) violated - parent key not found
02291. 00000 - "integrity constraint (%s.%s) violated - parent key not found"
*Cause:      A foreign key value has no matching primary key value.
*Action:     Delete the foreign key or add a matching primary key.
```

Department 55 does not exist.

ORACLE

10 - 29

Copyright © 2007, Oracle. All rights reserved.

Violating Constraints

When you have constraints in place on columns, an error is returned if you try to violate the constraint rule. For example, if you try to update a record with a value that is tied to an integrity constraint, an error is returned.

In the example in the slide, department 55 does not exist in the parent table, DEPARTMENTS, and so you receive the “parent key not found” violation ORA-02291.

Violating Constraints

You cannot delete a row that contains a primary key that is used as a foreign key in another table.

```
DELETE FROM departments
WHERE department_id = 60;
```

Error starting at line 1 in command: DELETE FROM departments WHERE department_id = 60 Error report: SQL Error: ORA-02292: integrity constraint (ORA16.EMP_DEPT_FK) violated - child record found 02292. 00000 - "integrity constraint (%s.%s) violated - child record found" *Cause: attempted to delete a parent key value that had a foreign dependency. *Action: delete dependencies first then parent or disable constraint.	
---	--

ORACLE

10 - 30

Copyright © 2007, Oracle. All rights reserved.

Violating Constraints (continued)

If you attempt to delete a record with a value that is tied to an integrity constraint, an error is returned.

The example in the slide tries to delete department 60 from the DEPARTMENTS table, but it results in an error because that department number is used as a foreign key in the EMPLOYEES table. If the parent record that you attempt to delete has child records, then you receive the “child record found” violation ORA-02292.

The following statement works because there are no employees in department 70:

```
DELETE FROM departments
WHERE department_id = 70;
```

```
1 rows deleted
```

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- **Creating a table using a subquery**
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

Creating a Table Using a Subquery

- Create a table and insert rows by combining the `CREATE TABLE` statement and the `AS subquery` option.

```
CREATE TABLE table
      [(column, column...)]
AS subquery;
```

- Match the number of specified columns to the number of subquery columns.
- Define columns with column names and default values.

ORACLE

10 - 32

Copyright © 2007, Oracle. All rights reserved.

Creating a Table Using a Subquery

A second method for creating a table is to apply the `AS subquery` clause, which both creates the table and inserts rows returned from the subquery.

In the syntax:

table is the name of the table

column is the name of the column, default value, and integrity constraint

subquery is the `SELECT` statement that defines the set of rows to be inserted into the new table

Guidelines

- The table is created with the specified column names, and the rows retrieved by the `SELECT` statement are inserted into the table.
- The column definition can contain only the column name and default value.
- If column specifications are given, the number of columns must equal the number of columns in the subquery `SELECT` list.
- If no column specifications are given, the column names of the table are the same as the column names in the subquery.
- The column data type definitions and the `NOT NULL` constraint are passed to the new table. Note that only the explicit `NOT NULL` constraint will be inherited. The `PRIMARY KEY` column will not pass the `NOT NULL` feature to the new column. Any other constraint rules are not passed to the new table. However, you can add constraints in the column definition.

Creating a Table Using a Subquery

```
CREATE TABLE dept80
AS
  SELECT  employee_id, last_name,
          salary*12 ANNSAL,
          hire_date
  FROM    employees
  WHERE   department_id = 80;
```

```
CREATE TABLE succeeded.
```

```
DESCRIBE dept80
```

Name	Null	Type
EMPLOYEE_ID		NUMBER(6)
LAST_NAME	NOT NULL	VARCHAR2(25)
ANNSAL		NUMBER
HIRE_DATE	NOT NULL	DATE

ORACLE

10 - 33

Copyright © 2007, Oracle. All rights reserved.

Creating a Table Using a Subquery (continued)

The example in the slide creates a table named DEPT80, which contains details of all the employees working in department 80. Notice that the data for the DEPT80 table comes from the EMPLOYEES table.

You can verify the existence of a database table and check the column definitions by using the DESCRIBE command.

However, be sure to provide a column alias when selecting an expression. The expression SALARY*12 is given the alias ANNSAL. Without the alias, the following error is generated:

```
Error starting at line 1 in command:
CREATE TABLE    dept80
AS SELECT  employee_id, last_name,
salary*12,
hire_date FROM employees WHERE   department_id = 80
Error at Command Line:3 Column:6
Error report:
SQL Error: ORA-00998: must name this expression with a column alias
00998. 00000 - "must name this expression with a column alias"
*Cause:
*Action:
```

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

ALTER TABLE Statement

Use the ALTER TABLE statement to:

- Add a new column
- Modify an existing column definition
- Define a default value for the new column
- Drop a column
- Rename a column
- Change table to read-only status

ORACLE

10 - 35

Copyright © 2007, Oracle. All rights reserved.

ALTER TABLE Statement

After you create a table, you may need to change the table structure for any of the following reasons:

- You omitted a column.
- Your column definition or its name needs to be changed.
- You need to remove columns.
- You want to put the table into the read-only mode

You can do this by using the ALTER TABLE statement.

Read-Only Tables

Use the `ALTER TABLE` syntax to put a table into the read-only mode:

- Prevents DDL or DML changes during table maintenance
- Change it back into read/write mode

```
ALTER TABLE employees READ ONLY;

-- perform table maintenance and then
-- return table back to read/write mode

ALTER TABLE employees READ WRITE;
```

ORACLE

10 - 36

Copyright © 2007, Oracle. All rights reserved.

Read-Only Tables

With Oracle Database 11g, you can specify `READ ONLY` to place a table in the read-only mode. When the table is in the `READ-ONLY` mode, you cannot issue any DML statements that affect the table or any `SELECT ... FOR UPDATE` statements. You can issue DDL statements as long as they do not modify any data in the table. Operations on indexes associated with the table are allowed when the table is in the `READ ONLY` mode.

Specify `READ/WRITE` to return a read-only table to the read/write mode.

Note: You can drop a table that is in the `READ ONLY` mode. • `DROP` `//` `✓` `●` `]` `•` `?`
`]` `//` `]` `▼` `▲` `]` `//` `●` `○` `//` `•` `●` `▲` `•` `]` `▼` `▲` `]` `•` `▲` `•` `//` `○` `✓` `×` `//` `?` `//`
`✓` `]` `]` `?` `?` `▲` `//` `▲` `•` `]` `▲` `✓` `✓` `○` `]` `//` `●` `▲` `]` `●` `▲` `?` `•` `?` `●` `//` `▲`
`×` `]` `-` `▼` `•` `×` `]` `•` `]` `?` `//` `✓` `]` `]` `▼` `?` `]` `]` `✓` `//` `▲` `•` `]` `▲` `✓` `✓` `○` `]` `◄` `•` `○` `○`
`●` `//` `▲` `✓` `]` `×` `]` `○` `✓` `•` `○` `]` `▼` `●` `▲` `•` `○` `▲` `•` `]` `▲` `✓` `✓` `○` `]` `?` `//` `✓` `]` `]` `•` `?`
`○` `✓` `]` `]` `×` `]` `✓` `]` `◄` `×` `•` `▲` `]` `✓` `■` `✓` `•` `●` `✓` `●` `]` `▲` `•` `]` `●` `▲` `•` `]` `×` `]` `-` `▼` `•` `×` `]`
`]` `•` `✓` `●` `■` `]` `?` `]` `✓` `●` `✓` `]` `○` `✓` `]` `▲` `//` `▲` `•` `]` `✓` `○` `//` `]` `?` `]` `■` `]` `○` `▲`
`•` `]` `✓` `]` `]` `×` `?` `✓` `●` `]` `?` `//` `//` `●`

For information about the `ALTER TABLE` statement, see the course titled *Oracle Database 10g SQL Fundamentals II*.

Lesson Agenda

- Database objects
 - Naming rules
- CREATE TABLE statement:
 - Access another user's tables
 - DEFAULT option
- Data types
- Overview of constraints: NOT NULL, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE
 - Read-only tables
- DROP TABLE statement

ORACLE

Dropping a Table

- Moves a table to the recycle bin
- Removes the table and all its data entirely if the `PURGE` clause is specified
- Invalidates dependent objects and removes object privileges on the table

```
DROP TABLE dept80;
```

```
DROP TABLE dept80 succeeded.
```

ORACLE

10 - 38

Copyright © 2007, Oracle. All rights reserved.

Dropping a Table

The `DROP TABLE` statement moves a table to the recycle bin or removes the table and all its data from the database entirely. Unless you specify the `PURGE` clause, the `DROP TABLE` statement does not result in space being released back to the tablespace for use by other objects, and the space continues to count towards the user's space quota. Dropping a table invalidates the dependent objects and removes object privileges on the table.

When you drop a table, the database loses all the data in the table and all the indexes associated with it.

Syntax

```
DROP TABLE table [PURGE]
```

In the syntax, *table* is the name of the table.

Guidelines

- All the data is deleted from the table.
- Any views and synonyms remain, but are invalid.
- Any pending transactions are committed.
- Only the creator of the table or a user with the `DROP ANY TABLE` privilege can remove a table.

Note: Use the `FLASHBACK TABLE` statement to restore a dropped table from the recycle bin. This is discussed in detail in the course titled *Oracle Database 11g: SQL Fundamentals II*.

Summary

In this lesson, you should have learned how to use the `CREATE TABLE` statement to create a table and include constraints:

- Categorize the main database objects
- Review the table structure
- List the data types that are available for columns
- Create a simple table
- Explain how constraints are created at the time of table creation
- Describe how schema objects work

ORACLE

10 - 39

Copyright © 2007, Oracle. All rights reserved.

Summary

In this lesson, you should have learned how to do the following:

CREATE TABLE

- Use the `CREATE TABLE` statement to create a table and include constraints.
- Create a table based on another table by using a subquery.

DROP TABLE

- Remove rows and a table structure.
- When executed, this statement cannot be rolled back.