

[View on GitHub](#)[Getting started](#)[Layout](#)[Content](#)[Components](#)[Utilities](#)[Borders](#)[Clearfix](#)[Close icon](#)[Colors](#)[Display](#)[Embed](#)[Flex](#)[Float](#)[Image replacement](#)[Interactions](#)[Overflow](#)[Position](#)[Screen readers](#)[Shadows](#)[Sizing](#)[Spacing](#)[Stretched link](#)[Text](#)[Vertical align](#)[Visibility](#)[Extend](#)[Migration](#)[About](#)

Interactions

Utility classes that change how users interact with the contents of a website.



Get 10 Free Images From
Adobe Stock. Start Now.
ads via Carbon

Text selection

Change how the content is selected when the user interacts with it. Note that Internet Explorer and Legacy Edge have no support for the `all` value for `user-select`, and as such, **`.user-select-all` is not supported by either browser.**

This paragraph will be entirely selected when clicked by the user.

This paragraph has the default select behavior.

This paragraph will not be selectable when clicked by the user.

[Copy](#)

```
<p class="user-select-all">This paragraph will be entirely selected when clicked by the user.</p>
<p class="user-select-auto">This paragraph has the default select behavior.</p>
<p class="user-select-none">This paragraph will not be selectable when clicked by the user.</p>
```

Customize the available classes by changing the `$user-selects` Sass list in `_variables.scss`.