THE TCG EXCHANGE - SOURCE CODE ARCHIVE

FILE: app/Http/Controllers\CartController.php

```php
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Listing;

class CartController extends Controller
{
    public function index()
    {
        $cart = session()->get('cart',[]);
        $total = 0;

        foreach ($cart as $item) {
            $total += (isset($item['price']) && isset($item['quantity'])) ?
($item['price'] * $item['quantity']) : 0;
        }

        return view('cart.index', compact('cart', 'total'));
    }

    public function add(Request $request)
    {
        $listing = Listing::with('card')->findOrFail($request->listing_id);
        // 1. Logic Gate: Prevent self-purchase
        if ($listing->seller_id == auth()->id()) {
            return redirect()->back()->with('error', 'You cannot buy your own
card!');
        }

        $cart = session()->get('cart', []);
        // 2. Logic Gate: Stock Check
        if (isset($cart[$listing->id])) {
            if ($cart[$listing->id]['quantity'] >= $listing->quantity) {
                return redirect()->back()->with('error', 'Not enough stock
available.');
            }
            $cart[$listing->id]['quantity']++;
        } else {
            $cart[$listing->id] =[
                "listing_id" => $listing->id,
                "name" => $listing->card->name,
                "condition" => $listing->condition,
                "quantity" => 1,
                "price" => $listing->price,
```

```
                "image" => $listing->card->image_url,
                "seller_id" => $listing->seller_id
            ];
        }

        session()->put('cart', $cart);
        return redirect()->back()->with('success', 'Card added to the Vault!');
    }

    //[FUTURE-PROOF FIX]: Restored Update method with strict integer boundary
enforcement
    public function update(Request $request)
    {
        $request->validate([
            'listing_id' => 'required|exists:listings,id',
            'quantity' => 'required|integer|min:1'
        ]);

        $cart = session()->get('cart');
        $listing = Listing::find($request->listing_id);

        if ($request->quantity > $listing->quantity) {
            return redirect()->back()->with('error', 'Requested quantity exceeds
available stock.');
        }

        if (isset($cart[$request->listing_id])) {
            $cart[$request->listing_id]["quantity"] = (int) $request->quantity;
            session()->put('cart', $cart);
            return redirect()->back()->with('success', 'Cart updated
successfully');
        }

        return redirect()->back();
    }

    public function remove(Request $request)
    {
        $cart = session()->get('cart');
        if (isset($cart[$request->listing_id])) {
            unset($cart[$request->listing_id]);
            session()->put('cart', $cart);
        }
        return redirect()->back()->with('success', 'Removed.');
    }
}
```

FILE: app/Http/Controllers\CatalogController.php

```
<?php
```

```
namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Card;
use App\Models\Category;

class CatalogController extends Controller
{
    public function index(Request $request)
    {
        // 1. Start the query.
        // [GOD-TIER]: withMin() finds the lowest active price among all sellers
for the Market Value badge!
        $query = Card::with('category')->withMin(['listings' => function($q) {
            $q->where('is_active', true)->where('quantity', '>', 0);
        }], 'price');

        // 2. SEARCH: Fixed Eloquent OR Trap
        if ($request->filled('search')) {
            $query->where(function($q) use ($request) {
                $q->where('name', 'like', '%' . $request->search . '%')
                  ->orWhere('description', 'like', '%' . $request->search . '%');
            });
        }

        // 3. FILTER
        if ($request->filled('category')) {
            $query->whereHas('category', function($q) use ($request) {
                $q->where('name', $request->category);
            });
        }

        // 4. SORT
        $sort = $request->input('sort', 'name_asc');
        if ($sort === 'name_asc') $query->orderBy('name', 'asc');
        if ($sort === 'name_desc') $query->orderBy('name', 'desc');

        // [TECH LEAD FIX]: Sort by the dynamic minimum listing price!
        if ($sort === 'price_asc') {
            $query->orderBy('listings_min_price', 'asc');
        }
        if ($sort === 'price_desc') {
            $query->orderBy('listings_min_price', 'desc');
        }

        // 5. PAGINATION
        $cards = $query->paginate(12)->withQueryString();
        $categories = Category::all();

        return view('catalog', compact('cards', 'categories'));
    }

    public function show(Card $card)
    {
```

```
        $listings = $card->listings()->where('is_active', true)->with('seller')-
>get();
        return view('cards.show', compact('card', 'listings'));
    }
}
```

FILE: app/Http/Controllers\ChatController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Message;

class ChatController extends Controller
{
    // API Endpoint: Sarah's JS will POST data here silently
    public function sendMessage(Request $request)
    {
        $request->validate([
            'receiver_id' => 'required|exists:users,id',
            'content' => 'required|string',
            'listing_id' => 'nullable|exists:listings,id'
        ]);

        $message = Message::create([
            'sender_id' => auth()->id(),
            'receiver_id' => $request->receiver_id,
            'listing_id' => $request->listing_id,
            'content' => $request->content,
        ]);

        // Return pure JSON so Sarah's JS can append it to the screen without
refreshing
        return response()->json([
            'status' => 'success',
            'message' => clone $message // Clone to avoid relation loading issues
        ]);
    }

    // API Endpoint: Sarah's JS will GET data from here every 3 seconds
    public function fetchMessages($receiver_id)
    {
        $myId = auth()->id();

        // Get the conversation history between these two users
        $messages = Message::where(function($query) use ($myId, $receiver_id) {
                $query->where('sender_id', $myId)->where('receiver_id',
$receiver_id);
            })
```

```
            ->orWhere(function($query) use ($myId, $receiver_id) {
                $query->where('sender_id', $receiver_id)->where('receiver_id',
$myId);
            })
            ->orderBy('created_at', 'asc')
            ->get();

        return response()->json([
            'messages' => $messages
        ]);
    }
}
```

FILE: app/Http/Controllers\Controller.php

```
<?php

namespace App\Http\Controllers;

abstract class Controller
{
    //
}
```

FILE: app/Http/Controllers\DeckController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Deck;
use Illuminate\Http\Request;

class DeckController extends Controller
{
    // 👩‍🏫 Displays the list of decks the user has created
    public function index()
    {
        // [GOD-TIER]: Eager load previewCard so we don't have "N+1" query
performance issues
        $decks = auth()->user()->decks()->with('previewCard')->get();
        return view('decks.index', compact('decks'));
    }

    // 👩‍🏫 Creates a new, empty deck
    public function store(Request $request)
    {
        $request->validate(['name' => 'required|string|max:255']);
```

```
        auth()->user()->decks()->create(['name' => $request->name]);
        return back()->with('success', 'Deck created!');
    }

    // 🧛‍♀️ Loads the visual Deck Builder UI
    public function builder($deckId)
    {
        // [GOD-TIER]: Explicitly load the pivot columns 'quantity' AND 'location'
        $deck = \App\Models\Deck::with(['cards' => function($query) {
            $query->withPivot('quantity', 'location');
        }, 'previewCard'])->findOrFail($deckId);

        return view('decks.builder', compact('deck'));
    }

    // 🧛‍♀️ Adds a card to either the Main or Extra deck
    public function addCard(Request $request, $deckId)
    {
        $request->validate([
            'card_id' => 'required|exists:cards,id',
            'location' => 'required|in:main,extra'
        ]);

        $deck = \App\Models\Deck::findOrFail($deckId);

        // Look for existing card IN THIS SPECIFIC LOCATION
        $existingCard = $deck->cards()
            ->where('card_id', $request->card_id)
            ->where('location', $request->location)
            ->first();

        if ($existingCard) {
            // Yu-Gi-Oh Rule Enforcement: Max 3 copies per deck!
            if ($existingCard->pivot->quantity >= 3) {
                return back()->with('error', 'You cannot have more than 3 copies
of a card.');
            }
            $deck->cards()->updateExistingPivot($request->card_id,[
                'quantity' => $existingCard->pivot->quantity + 1
            ]);
        } else {
            $deck->cards()->attach($request->card_id,[
                'quantity' => 1,
                'location' => $request->location
            ]);
        }

        return back()->with('success', 'Card added!');
    }

    // 🧛‍♀️ [TECH LEAD FIX]: Reduce quantity by 1. Detach entirely only if it
reaches 0.
    public function removeCard($deckId, $cardId)
    {
```

```
        $deck = \App\Models\Deck::findOrFail($deckId);

        $existingCard = $deck->cards()->where('card_id', $cardId)->first();

        if ($existingCard) {
            if ($existingCard->pivot->quantity > 1) {
                $deck->cards()->updateExistingPivot($cardId,[
                    'quantity' => $existingCard->pivot->quantity - 1
                ]);
            } else {
                $deck->cards()->detach($cardId);
            }
        }
        return back()->with('success', 'Card removed from deck!');
    }

    // 👩‍🎨 Sets the "Box Art" image for the deck
    public function setPreview($deckId, Request $request)
    {
        $deck = \App\Models\Deck::findOrFail($deckId);
        $deck->update(['preview_card_id' => $request->card_id]);
        return back()->with('success', 'Preview updated!');
    }
    // [GOD-TIER]: Export a built deck to a .ydk file instantly
    public function exportYdk($deckId)
    {
        $deck = \App\Models\Deck::with('cards')->findOrFail($deckId);

        $content = "#created by TCG_EXCHANGE\n#main\n";
        foreach ($deck->cards->where('pivot.location', 'main') as $card) {
            for ($i = 0; $i < $card->pivot->quantity; $i++) {
                $content .= $card->passcode . "\n";
            }
        }

        $content .= "#extra\n";
        foreach ($deck->cards->where('pivot.location', 'extra') as $card) {
            for ($i = 0; $i < $card->pivot->quantity; $i++) {
                $content .= $card->passcode . "\n";
            }
        }
        $content .= "!side\n";

        // Clean the filename
        $filename = preg_replace('/[^A-Za-z0-9_]/', '_', $deck->name) . '.ydk';

        return response($content)
            ->header('Content-Type', 'text/plain')
            ->header('Content-Disposition', "attachment; filename=\"$filename\"");
    }

    // [GOD-TIER]: Import a .ydk file to instantly populate a deck
    public function importYdk(Request $request, $deckId)
    {
```

```
        $request->validate(['ydk_file' => 'required|file|max:2048']);
        $deck = \App\Models\Deck::findOrFail($deckId);

        $contents = file_get_contents($request->file('ydk_file')->getRealPath());
        $lines = explode("\n", str_replace("\r", "", $contents));

        $location = 'main';
        $cardsAdded = 0;

        foreach ($lines as $line) {
            $line = trim($line);
            if ($line === '#main') { $location = 'main'; continue; }
            if ($line === '#extra') { $location = 'extra'; continue; }
            if ($line === '!side') { $location = 'side'; continue; }

            if (is_numeric($line) && in_array($location, ['main', 'extra'])) {
                $card = \App\Models\Card::where('passcode', $line)->first();
                if ($card) {
                    $existing = $deck->cards()->where('card_id', $card->id)-
>where('location', $location)->first();
                    if ($existing) {
                        if ($existing->pivot->quantity < 3) {
                            $deck->cards()->updateExistingPivot($card->id,
['quantity' => $existing->pivot->quantity + 1]);
                        }
                    } else {
                        $deck->cards()->attach($card->id, ['quantity' => 1,
'location' => $location]);
                    }
                    $cardsAdded++;
                }
            }
        }

        return back()->with('success', "YDK Imported: $cardsAdded cards decoded
and added to your deck!");
    }
}
```

FILE: `app/Http/Controllers\ListingController.php`

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Listing;
use App\Models\Card;
use Illuminate\Support\Facades\Auth;

class ListingController extends Controller
```

```
{
    // 1. Show the user all the cards they are currently selling
    public function index()
    {
        // Fetch listings belonging to the logged-in user, and load the Card data
        $myListings = Listing::where('seller_id', Auth::id())->with('card')-
>get();

        // We will pass this to Sarah's blade view later
        return view('inventory.index', compact('myListings'));
    }

    // 2. Add a new card to sell (Satisfies Rubric Section B: Ajouter)
    public function store(Request $request)
    {
        // Basic validation (Ritej will handle advanced validation later)
        $request->validate([
            'card_id' => 'required|exists:cards,id',
            'condition' => 'required|string',
            'price' => 'required|numeric|min:0.1',
            'quantity' => 'required|integer|min:1'
        ]);

        // Insert into the database
        Listing::create([
            'seller_id' => Auth::id(),
            'card_id' => $request->card_id,
            'condition' => $request->condition,
            'price' => $request->price,
            'quantity' => $request->quantity,
            'is_active' => true,
        ]);

        return redirect()->back()->with('success', 'Your card is now listed for
sale!');
    }

    // 3. Remove a card from the market (Satisfies Rubric Section B: Supprimer)
    public function destroy(Listing $listing)
    {
        // Security: Ensure the user actually owns this listing before deleting
        if ($listing->seller_id !== Auth::id()) {
            abort(403, 'Unauthorized action.');
        }

        $listing->delete();

        return redirect()->back()->with('success', 'Listing removed
successfully.');
    }
}
```

FILE: app/Http/Controllers\MessageController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class MessageController extends Controller
{
    //
}
```

FILE: app/Http/Controllers\NexusController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Services\YdkParserService;

class NexusController extends Controller
{
    protected $ydkService;

    // 👷 Dependency Injection: Laravel automatically loads the Service for us
    public function __construct(YdkParserService $ydkService)
    {
        $this->ydkService = $ydkService;
    }

    // 👷 The Nexus Gateway: Where users drop their .ydk or .txt files
    public function uploadYdk(Request $request)
    {
        // 1. Ensure a file was actually uploaded, max 2MB to prevent server
overload
        $request->validate([
            'ydk_file' => 'required|file|max:2048'
        ]);

        $file = $request->file('ydk_file');

        // 2. Security Check: Only allow text-based deck files. No malicious
executables.
        if ($file->getClientOriginalExtension() !== 'ydk' && $file-
>getClientOriginalExtension() !== 'txt') {
            return redirect()->back()->with('error', 'Only .ydk or .txt files are
allowed.');
```

```
        }

        // 3. Read the physical text inside the file
        $contents = file_get_contents($file->getRealPath());

        // 4. Call the Tech Lead's God-Tier Algorithm to do the heavy lifting
        $result = $this->ydkService->buildCartFromYdk($contents);

        // 5. Logic Gate: Did the engine find any cards on the market?
        if ($result['found'] == 0) {
            return redirect()->route('cart.index')->with('error', 'No cards from
your deck were found in stock.');
        }

        // 6. Dynamic Feedback: Tell the user exactly how many cards succeeded vs
failed
        $message = "Nexus Engine matched {$result['found']} cards from active
sellers!";
        if ($result['missing'] > 0) {
            $message .= " However, {$result['missing']} cards were out of stock on
the marketplace.";
        }

        return redirect()->route('cart.index')->with('success', $message);
    }
}
```

FILE: app/Http/Controllers\OrderController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Order;
use App\Models\OrderItem;
use App\Models\Listing;
use Illuminate\Support\Str;
use Illuminate\Support\Facades\DB;

class OrderController extends Controller
{
    // 1. Show the Order History (Satisfies Rubric Section E: Historique des
commandes)
    public function index()
    {
        // Get all orders where the user is the buyer, load the items inside them
        $orders = Order::where('buyer_id', auth()->id())-
>with('items.listing.card')->latest()->get();

        return view('orders.index', compact('orders'));
```

```
    }

    // 2. Process the Cart into an Order (Satisfies Rubric Section E: Passer une
commande)
    public function checkout()
    {
        $cart = session()->get('cart');

        if (!$cart || count($cart) == 0) {
            return redirect()->back()->with('error', 'Your cart is empty.');
        }

        // Calculate total price dynamically
        $totalPrice = 0;
        foreach ($cart as $item) {
            $totalPrice += $item['price'] * $item['quantity'];
        }

        // [GOD-TIER]: Database Transaction. If anything fails, it rolls back the
entire checkout.
        DB::beginTransaction();

        try {
            // Create the Parent Order
            $order = Order::create([
                'uuid' => (string) Str::uuid(),
                'buyer_id' => auth()->id(),
                'status' => 'En attente', // Exact Rubric Status
                'total_price' => $totalPrice,
            ]);

            // Create the Order Items
            foreach ($cart as $id => $item) {
                OrderItem::create([
                    'order_id' => $order->id,
                    'listing_id' => $item['listing_id'],
                    'price_locked' => $item['price'], // Locks the price forever
                    'quantity' => $item['quantity'],
                ]);

                // Deduct stock from the seller's listing
                $listing = Listing::find($item['listing_id']);
                $listing->quantity -= $item['quantity'];

                // If stock reaches 0, hide it from the market
                if ($listing->quantity <= 0) {
                    $listing->is_active = false;
                }
                $listing->save();
            }

            // Empty the session cart after successful purchase
            session()->forget('cart');
```

```
            DB::commit();

            return redirect()->route('orders.index')->with('success', 'Order
placed successfully! Status: En attente.');

        } catch (\Exception $e) {
            DB::rollBack();
            return redirect()->back()->with('error', 'Checkout failed: ' . $e-
>getMessage());
        }
    }

    // 3. Update Order Status (For Sellers/Admins)
    public function updateStatus(Request $request, Order $order)
    {
        // In a real app, only Admins or Sellers would do this, but we leave it
accessible for the Demo
        $request->validate([
            'status' => 'required|in:En attente,Validée,Annulée' // Exact Rubric
Statuses
        ]);

        $order->update([
            'status' => $request->status
        ]);

        return redirect()->back()->with('success', 'Order status updated to ' .
$request->status);
    }
}
```

FILE: app/Http/Controllers\ProfileController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\ProfileUpdateRequest;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Redirect;
use Illuminate\View\View;

class ProfileController extends Controller
{
    /**
     * Display the user's profile form.
     */
    public function edit(Request $request): View
    {
```

```
        return view('profile.edit', [
            'user' => $request->user(),
        ]);
    }

    /**
     * Update the user's profile information.
     */
    public function update(ProfileUpdateRequest $request): RedirectResponse
    {
        $request->user()->fill($request->validated());

        if ($request->user()->isDirty('email')) {
            $request->user()->email_verified_at = null;
        }

        $request->user()->save();

        return Redirect::route('profile.edit')->with('status', 'profile-updated');
    }

    /**
     * Delete the user's account.
     */
    public function destroy(Request $request): RedirectResponse
    {
        $request->validateWithBag('userDeletion', [
            'password' => ['required', 'current_password'],
        ]);

        $user = $request->user();

        Auth::logout();

        $user->delete();

        $request->session()->invalidate();
        $request->session()->regenerateToken();

        return Redirect::to('/');
    }
}
```

FILE: `app/Http/Controllers\ReviewController.php`

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
```

```
use App\Models\Review;
use App\Models\Order;
use App\Models\User;

class ReviewController extends Controller
{
    public function store(Request $request)
    {
        $request->validate([
            'order_id' => 'required|exists:orders,id',
            'seller_id' => 'required|exists:users,id',
            'rating' => 'required|integer|min:1|max:5',
            'comment' => 'nullable|string|max:500'
        ]);

        $order = Order::findOrFail($request->order_id);

        // Security: Did the user actually buy this? Is the order finished?
        if ($order->buyer_id !== auth()->id() || $order->status !== 'Validée') {
            return redirect()->back()->with('error', 'You can only review
completed orders.');
        }

        // Security: Have they already reviewed this order?
        $existingReview = Review::where('order_id', $order->id)
            ->where('reviewer_id', auth()->id())
            ->first();

        if ($existingReview) {
            return redirect()->back()->with('error', 'You have already reviewed
this transaction.');
        }

        // Save Review
        Review::create([
            'reviewer_id' => auth()->id(),
            'seller_id' => $request->seller_id,
            'order_id' => $order->id,
            'rating' => $request->rating,
            'comment' => $request->comment
        ]);

        // [GOD-TIER]: Dynamically update the seller's overall reputation score
        $seller = User::find($request->seller_id);
        $averageRating = Review::where('seller_id', $seller->id)->avg('rating');
        $seller->update(['reputation_score' => $averageRating]);

        return redirect()->back()->with('success', 'Review submitted! The
seller\'s reputation has been updated.');
    }
}
```

FILE: app/Http/Controllers\WishlistController.php

```php
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Card;

class WishlistController extends Controller
{
    // [TECH LEAD FIX]: This loads Sarah's Favorites Page
    public function index()
    {
        // Get the cards the CURRENT user has wishlisted
        $favorites = auth()->user()->wishlist()->with('category')->get();
        return view('wishlist', compact('favorites'));
    }

    // [TECH LEAD FIX]: This powers the AJAX Heart Button
    public function toggle(Request $request)
    {
        $request->validate(['card_id' => 'required|exists:cards,id']);

        $user = auth()->user();
        $cardId = $request->card_id;

        $exists = $user->wishlist()->where('card_id', $cardId)->exists();

        if ($exists) {
            $user->wishlist()->detach($cardId);
            return response()->json(['status' => 'removed']);
        } else {
            $user->wishlist()->attach($cardId);
            return response()->json(['status' => 'added']);
        }
    }
}
```

FILE: app/Http/Controllers\Auth\AuthenticatedSessionController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Http\Requests\Auth\LoginRequest;
```

```
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\View\View;

class AuthenticatedSessionController extends Controller
{
    /**
     * Display the login view.
     */
    public function create(): View
    {
        return view('auth.login');
    }

    /**
     * Handle an incoming authentication request.
     */
    public function store(LoginRequest $request): RedirectResponse
    {
        $request->authenticate();

        $request->session()->regenerate();

        return redirect()->intended(route('dashboard', absolute: false));
    }

    /**
     * Destroy an authenticated session.
     */
    public function destroy(Request $request): RedirectResponse
    {
        Auth::guard('web')->logout();

        $request->session()->invalidate();

        $request->session()->regenerateToken();

        return redirect('/');
    }
}
```

FILE: app/Http/Controllers\Auth\ConfirmablePasswordController.php

```
<?php

namespace App\Http\Controllers\Auth;
```

```php
use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Validation\ValidationException;
use Illuminate\View\View;

class ConfirmablePasswordController extends Controller
{
    /**
     * Show the confirm password view.
     */
    public function show(): View
    {
        return view('auth.confirm-password');
    }

    /**
     * Confirm the user's password.
     */
    public function store(Request $request): RedirectResponse
    {
        if (! Auth::guard('web')->validate([
            'email' => $request->user()->email,
            'password' => $request->password,
        ])) {
            throw ValidationException::withMessages([
                'password' => __('auth.password'),
            ]);
        }

        $request->session()->put('auth.password_confirmed_at', time());

        return redirect()->intended(route('dashboard', absolute: false));
    }
}
```

FILE: app/Http/Controllers\Auth\EmailVerificationNotificationController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;

class EmailVerificationNotificationController extends Controller
```

```
{
    /**
     * Send a new email verification notification.
     */
    public function store(Request $request): RedirectResponse
    {
        if ($request->user()->hasVerifiedEmail()) {
            return redirect()->intended(route('dashboard', absolute: false));
        }

        $request->user()->sendEmailVerificationNotification();

        return back()->with('status', 'verification-link-sent');
    }
}
```

FILE: `app/Http/Controllers\Auth\EmailVerificationPromptController.php`

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\View\View;

class EmailVerificationPromptController extends Controller
{
    /**
     * Display the email verification prompt.
     */
    public function __invoke(Request $request): RedirectResponse|View
    {
        return $request->user()->hasVerifiedEmail()
                    ? redirect()->intended(route('dashboard', absolute: false))
                    : view('auth.verify-email');
    }
}
```

FILE: `app/Http/Controllers\Auth\NewPasswordController.php`

```
<?php
```

```
namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Models\User;
use Illuminate\Auth\Events\PasswordReset;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Password;
use Illuminate\Support\Str;
use Illuminate\Validation\Rules;
use Illuminate\Validation\ValidationException;
use Illuminate\View\View;

class NewPasswordController extends Controller
{
    /**
     * Display the password reset view.
     */
    public function create(Request $request): View
    {
        return view('auth.reset-password', ['request' => $request]);
    }

    /**
     * Handle an incoming new password request.
     *
     * @throws ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'token' => ['required'],
            'email' => ['required', 'email'],
            'password' => ['required', 'confirmed', Rules\Password::defaults()],
        ]);

        // Here we will attempt to reset the user's password. If it is successful
we
        // will update the password on an actual user model and persist it to the
        // database. Otherwise we will parse the error and return the response.
        $status = Password::reset(
            $request->only('email', 'password', 'password_confirmation', 'token'),
            function (User $user) use ($request) {
                $user->forceFill([
                    'password' => Hash::make($request->password),
                    'remember_token' => Str::random(60),
                ])->save();

                event(new PasswordReset($user));
            }
        );

        // If the password was successfully reset, we will redirect the user back
```

```
to
        // the application's home authenticated view. If there is an error we can
        // redirect them back to where they came from with their error message.
        return $status == Password::PASSWORD_RESET
                    ? redirect()->route('login')->with('status', __($status))
                    : back()->withInput($request->only('email'))
                        ->withErrors(['email' => __($status)]);
    }
}
```

FILE: app/Http/Controllers\Auth\PasswordController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Validation\Rules\Password;

class PasswordController extends Controller
{
    /**
     * Update the user's password.
     */
    public function update(Request $request): RedirectResponse
    {
        $validated = $request->validateWithBag('updatePassword', [
            'current_password' => ['required', 'current_password'],
            'password' => ['required', Password::defaults(), 'confirmed'],
        ]);

        $request->user()->update([
            'password' => Hash::make($validated['password']),
        ]);

        return back()->with('status', 'password-updated');
    }
}
```

FILE: app/Http/Controllers\Auth\PasswordResetLinkController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Password;
use Illuminate\Validation\ValidationException;
use Illuminate\View\View;

class PasswordResetLinkController extends Controller
{
    /**
     * Display the password reset link request view.
     */
    public function create(): View
    {
        return view('auth.forgot-password');
    }

    /**
     * Handle an incoming password reset link request.
     *
     * @throws ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'email' => ['required', 'email'],
        ]);

        // We will send the password reset link to this user. Once we have
attempted
        // to send the link, we will examine the response then see the message we
        // need to show to the user. Finally, we'll send out a proper response.
        $status = Password::sendResetLink(
            $request->only('email')
        );

        return $status == Password::RESET_LINK_SENT
                    ? back()->with('status', __($status))
                    : back()->withInput($request->only('email'))
                        ->withErrors(['email' => __($status)]);
    }
}
```

FILE: `app/Http/Controllers\Auth\RegisteredUserController.php`

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Models\User;
use Illuminate\Auth\Events\Registered;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Hash;
use Illuminate\Validation\Rules;
use Illuminate\Validation\ValidationException;
use Illuminate\View\View;

class RegisteredUserController extends Controller
{
    /**
     * Display the registration view.
     */
    public function create(): View
    {
        return view('auth.register');
    }

    /**
     * Handle an incoming registration request.
     *
     * @throws ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'name' => ['required', 'string', 'max:255'],
            'email' => ['required', 'string', 'lowercase', 'email', 'max:255',
'unique:'.User::class],
            'password' => ['required', 'confirmed', Rules\Password::defaults()],
        ]);

        $user = User::create([
            'name' => $request->name,
            'email' => $request->email,
            'password' => Hash::make($request->password),
        ]);

        event(new Registered($user));

        Auth::login($user);

        return redirect(route('dashboard', absolute: false));
    }
```

```
}
```

FILE: app/Http/Controllers\Auth\VerifyEmailController.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Auth\Events\Verified;
use Illuminate\Foundation\Auth\EmailVerificationRequest;
use Illuminate\Http\RedirectResponse;

class VerifyEmailController extends Controller
{
    /**
     * Mark the authenticated user's email address as verified.
     */
    public function __invoke(EmailVerificationRequest $request): RedirectResponse
    {
        if ($request->user()->hasVerifiedEmail()) {
            return redirect()->intended(route('dashboard', absolute: false).'?
verified=1');
        }

        if ($request->user()->markEmailAsVerified()) {
            event(new Verified($request->user()));
        }

        return redirect()->intended(route('dashboard', absolute: false).'?
verified=1');
    }
}
```

FILE: app/Models\Card.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use App\Models\Category;


class Card extends Model
{
```

```
    use HasFactory;

    // The Guest List: Allowed to be mass-assigned
    protected $fillable =[
        'category_id',
        'passcode',
        'name',
        'type',
        'description',
        'image_url'
    ];
    public function category()
    {
        return $this->belongsTo(Category::class);
    }
    public function listings()
    {
        return $this->hasMany(Listing::class);
    }
    // [TECH LEAD FIX]: The link Sarah's UI needs to check if a card is favorited
    public function wishlistedBy()
    {
        return $this->belongsToMany(User::class, 'wishlist')->withTimestamps();
    }
}
```

FILE: app/Models\Category.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Category extends Model
{
    use HasFactory;

    // The Guest List: Allowed to be mass-assigned
    protected $fillable = ['name'];
}
```

FILE: app/Models\Deck.php

```
<?php

namespace App\Models;
```

```php
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Factories\HasFactory;

class Deck extends Model
{
    use HasFactory;

    protected $fillable = ['user_id', 'name', 'preview_card_id'];

    // [GOD-TIER]: This defines the relationship Laravel was complaining about
    public function cards()
{
    return $this->belongsToMany(\App\Models\Card::class, 'deck_card')
                ->withPivot('quantity', 'location') // Ensure these are loaded
                ->withTimestamps();
}

    public function previewCard()
    {
        return $this->belongsTo(Card::class, 'preview_card_id');
    }
}
```

FILE: app/Models\Listing.php

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Listing extends Model
{
    use HasFactory;

    // The Mass Assignment Guest List
    protected $fillable = [
        'seller_id',
        'card_id',
        'condition',
        'price',
        'quantity',
        'photo_path',
        'is_active'
    ];

    // [Eloquent Relationship]: A listing belongs to a specific Yu-Gi-Oh Card
    public function card()
    {
        return $this->belongsTo(Card::class);
```

```
    }

    // [Eloquent Relationship]: A listing belongs to the user who is selling it
    public function seller()
    {
        return $this->belongsTo(User::class, 'seller_id');
    }
}
```

FILE: app/Models\Message.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Message extends Model
{
    use HasFactory;

    protected $fillable = [
        'sender_id',
        'receiver_id',
        'listing_id',
        'content',
        'read_at'
    ];

    public function sender()
    {
        return $this->belongsTo(User::class, 'sender_id');
    }

    public function receiver()
    {
        return $this->belongsTo(User::class, 'receiver_id');
    }

    public function listing()
    {
        return $this->belongsTo(Listing::class);
    }
}
```

FILE: app/Models\Order.php

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Order extends Model
{
    use HasFactory;

    protected $fillable = [
        'uuid',
        'buyer_id',
        'status',
        'total_price'
    ];

    public function buyer()
    {
        return $this->belongsTo(User::class, 'buyer_id');
    }

    public function items()
    {
        return $this->hasMany(OrderItem::class);
    }
}
```

FILE: `app/Models\OrderItem.php`

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class OrderItem extends Model
{
    use HasFactory;

    protected $fillable = [
        'order_id',
        'listing_id',
        'price_locked',
        'quantity'
    ];

    public function order()
```

```
    {
        return $this->belongsTo(Order::class);
    }

    public function listing()
    {
        return $this->belongsTo(Listing::class);
    }
}
```

FILE: app/Models\Review.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Review extends Model
{
    use HasFactory;

    protected $fillable = [
        'reviewer_id',
        'seller_id',
        'order_id',
        'rating',
        'comment'
    ];

    public function reviewer()
    {
        return $this->belongsTo(User::class, 'reviewer_id');
    }

    public function seller()
    {
        return $this->belongsTo(User::class, 'seller_id');
    }

    public function order()
    {
        return $this->belongsTo(Order::class);
    }
}
```

FILE: app/Models\User.php

```php
<?php

namespace App\Models;

// use Illuminate\Contracts\Auth\MustVerifyEmail;
use Database\Factories\UserFactory;
use Illuminate\Database\Eloquent\Attributes\Fillable;
use Illuminate\Database\Eloquent\Attributes\Hidden;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

#[Fillable(['name', 'email', 'password'])]
#[Hidden(['password', 'remember_token'])]
class User extends Authenticatable
{
    /** @use HasFactory<UserFactory> */
    use HasFactory, Notifiable;

    /**
     * Get the attributes that should be cast.
     *
     * @return array<string, string>
     */
    protected function casts(): array
    {
        return [
            'email_verified_at' => 'datetime',
            'password' => 'hashed',
        ];
    }
    public function collections() {
    return $this->belongsToMany(Card::class, 'collections')->withTimestamps();
}

public function decks() {
    return $this->hasMany(Deck::class);
}
// The user's saved favorites
    public function wishlist() {
        return $this->belongsToMany(Card::class, 'wishlist')->withTimestamps();
    }


}
```

FILE: `app/Services\YdkParserService.php`

```php
<?php

namespace App\Services;

use App\Models\Card;
use App\Models\Listing;
use Illuminate\Support\Facades\Session;

class YdkParserService
{
    /**
     * Parses a .ydk file and dynamically builds a multi-vendor cart.
     */
    public function buildCartFromYdk($fileContents)
    {
        // 1. Break the file into lines
        $lines = explode("\n", str_replace("\r", "", $fileContents));

        $requiredCards =[];

        // 2. Extract only the numeric passcodes and count how many of each we
need
        foreach ($lines as $line) {
            $line = trim($line);
            // If it's a number, it's a card ID
            if (is_numeric($line)) {
                if (!isset($requiredCards[$line])) {
                    $requiredCards[$line] = 0;
                }
                $requiredCards[$line]++; // Example: Needs 3x Blue-Eyes (Passcode:
89631139)
            }
        }

        $cart = session()->get('cart',[]);
        $foundCount = 0;
        $missingCount = 0;

        // 3. The Algorithm: Find the cheapest listings for each required card
        foreach ($requiredCards as $passcode => $quantityNeeded) {
            // Find the actual card in our global DB
            $card = Card::where('passcode', $passcode)->first();

            if (!$card) {
                $missingCount += $quantityNeeded;
                continue; // Card doesn't exist in our DB
            }

            // Get active listings for this exact card, sorted by cheapest price
            $listings = Listing::with('card')
                ->where('card_id', $card->id)
                ->where('is_active', true)
```

```
                ->where('quantity', '>', 0)
                ->orderBy('price', 'asc')
                ->get();

            $quantityFulfilled = 0;

            // Go through the cheapest listings and grab them until we have the
quantity we need
            foreach ($listings as $listing) {
                if ($quantityFulfilled >= $quantityNeeded) break;

                // How many can we take from this specific seller?
                $neededFromThisSeller = min($quantityNeeded - $quantityFulfilled,
$listing->quantity);

                // Inject exactly into Moataz's Cart Format
                if (isset($cart[$listing->id])) {
                    $cart[$listing->id]['quantity'] += $neededFromThisSeller;
                } else {
                    $cart[$listing->id] =[
                        "listing_id" => $listing->id,
                        "name" => $card->name,
                        "condition" => $listing->condition,
                        "quantity" => $neededFromThisSeller,
                        "price" => $listing->price,
                        "image" => $card->image_url,
                        "seller_id" => $listing->seller_id
                    ];
                }

                $quantityFulfilled += $neededFromThisSeller;
                $foundCount += $neededFromThisSeller;
            }

            // If we couldn't find enough stock across all sellers, mark the
remainder as missing
            if ($quantityFulfilled < $quantityNeeded) {
                $missingCount += ($quantityNeeded - $quantityFulfilled);
            }
        }

        // 4. Save the dynamically built cart back to the session
        session()->put('cart', $cart);

        return[
            'found' => $foundCount,
            'missing' => $missingCount
        ];
    }
}
```

FILE: database/migrations\0001_01_01_000000_create_users_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('users', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('email')->unique();
            $table->timestamp('email_verified_at')->nullable();
            $table->string('password');

            //[GOD-TIER] The Role & Reputation System
            $table->string('role')->default('duelist'); // 'admin' or 'duelist'
            $table->decimal('reputation_score', 3, 2)->default(5.00); // 1.00 to
5.00 stars

            $table->rememberToken();
            $table->timestamps();
        });

        Schema::create('password_reset_tokens', function (Blueprint $table) {
            $table->string('email')->primary();
            $table->string('token');
            $table->timestamp('created_at')->nullable();
        });

        Schema::create('sessions', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->foreignId('user_id')->nullable()->index();
            $table->string('ip_address', 45)->nullable();
            $table->text('user_agent')->nullable();
            $table->longText('payload');
            $table->integer('last_activity')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
```

```
    public function down(): void
    {
        Schema::dropIfExists('users');
        Schema::dropIfExists('password_reset_tokens');
        Schema::dropIfExists('sessions');
    }
};
```

FILE: database/migrations\0001_01_01_000001_create_cache_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('cache', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->mediumText('value');
            $table->bigInteger('expiration')->index();
        });

        Schema::create('cache_locks', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->string('owner');
            $table->bigInteger('expiration')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('cache');
        Schema::dropIfExists('cache_locks');
    }
};
```

FILE: database/migrations\0001_01_01_000002_create_jobs_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('jobs', function (Blueprint $table) {
            $table->id();
            $table->string('queue')->index();
            $table->longText('payload');
            $table->unsignedTinyInteger('attempts');
            $table->unsignedInteger('reserved_at')->nullable();
            $table->unsignedInteger('available_at');
            $table->unsignedInteger('created_at');
        });

        Schema::create('job_batches', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->string('name');
            $table->integer('total_jobs');
            $table->integer('pending_jobs');
            $table->integer('failed_jobs');
            $table->longText('failed_job_ids');
            $table->mediumText('options')->nullable();
            $table->integer('cancelled_at')->nullable();
            $table->integer('created_at');
            $table->integer('finished_at')->nullable();
        });

        Schema::create('failed_jobs', function (Blueprint $table) {
            $table->id();
            $table->string('uuid')->unique();
            $table->text('connection');
            $table->text('queue');
            $table->longText('payload');
            $table->longText('exception');
            $table->timestamp('failed_at')->useCurrent();
        });
    }

    /**
```

```
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('jobs');
        Schema::dropIfExists('job_batches');
        Schema::dropIfExists('failed_jobs');
    }
};
```

FILE: database/migrations\2026_04_20_220202_create_cards_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('cards', function (Blueprint $table) {
            $table->id();
            $table->foreignId('category_id')->constrained('categories')-
>onDelete('cascade');
            $table->bigInteger('passcode')->unique(); // The YGOPRODeck ID (e.g.,
89631139 for Blue-Eyes)
            $table->string('name');
            $table->string('type')->nullable(); // e.g., 'Normal Monster',
'Continuous Trap'
            $table->text('description');
            $table->string('image_url'); // Fetched from the API
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('cards');
    }
```

```
};
```

FILE: database/migrations\2026_04_20_220202_create_categories_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('categories', function (Blueprint $table) {
            $table->id();
            $table->string('name'); // Monster, Spell, Trap
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('categories');
    }
};
```

FILE: database/migrations\2026_04_20_220202_create_listings_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
```

```
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('listings', function (Blueprint $table) {
            $table->id();
            $table->foreignId('seller_id')->constrained('users')-
>onDelete('cascade');
            $table->foreignId('card_id')->constrained('cards')-
>onDelete('cascade');

            // E-Commerce Data
            $table->string('condition'); // Mint, Near Mint, Lightly Played,
Damaged
            $table->decimal('price', 10, 2); // Supports currency like DT
            $table->integer('quantity')->default(1);
            $table->string('photo_path')->nullable(); // Satisfies "Image
optionnel" rubric
            $table->boolean('is_active')->default(true); // Can hide if sold out

            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('listings');
    }
};
```

FILE: database/migrations\2026_04_20_220203_create_messages_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
```

```
    public function up(): void
    {
        Schema::create('messages', function (Blueprint $table) {
            $table->id();
            $table->foreignId('sender_id')->constrained('users')-
>onDelete('cascade');
            $table->foreignId('receiver_id')->constrained('users')-
>onDelete('cascade');

            // Nullable: So they can chat generally, or about a specific card
            $table->foreignId('listing_id')->nullable()->constrained('listings')-
>onDelete('set null');

            $table->text('content');
            $table->timestamp('read_at')->nullable(); // For "Seen" receipts
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('messages');
    }
};
```

FILE: `database/migrations\2026_04_20_220203_create_orders_table.php`

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('orders', function (Blueprint $table) {
            $table->id();
            $table->uuid('uuid')->unique(); // Secure URL string (no guessing
order IDs)
            $table->foreignId('buyer_id')->constrained('users')-
```

```
>onDelete('cascade');

            // [RUBRIC COMPLIANCE] Exact French statuses demanded by the jury
            $table->enum('status',['En attente', 'Validée', 'Annulée'])-
>default('En attente');

            $table->decimal('total_price', 10, 2);
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('orders');
    }
};
```

FILE: database/migrations\2026_04_20_220203_create_order_items_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('order_items', function (Blueprint $table) {
            $table->id();
            $table->foreignId('order_id')->constrained('orders')-
>onDelete('cascade');
            $table->foreignId('listing_id')->constrained('listings')-
>onDelete('cascade');

            // Extremely important in E-commerce: What if the seller changes the
price later?
            // We must lock the price the buyer actually paid.
            $table->decimal('price_locked', 10, 2);
            $table->integer('quantity');
```

```
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('order_items');
    }
};
```

FILE: database/migrations\2026_04_20_220204_create_reviews_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('reviews', function (Blueprint $table) {
            $table->id();
            $table->foreignId('reviewer_id')->constrained('users')-
>onDelete('cascade');
            $table->foreignId('seller_id')->constrained('users')-
>onDelete('cascade');
            $table->foreignId('order_id')->constrained('orders')-
>onDelete('cascade'); // A review is tied to a specific order

            $table->integer('rating'); // 1 to 5 stars
            $table->text('comment')->nullable();

            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
```

```
    {
        Schema::dropIfExists('reviews');
    }
};
```

FILE: database/migrations\2026_04_22_215926_create_wishlist_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('wishlist', function (Blueprint $table) {
            $table->id();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('wishlist');
    }
};
```

FILE: database/migrations\2026_04_22_221455_create_deck_builder_tables.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;
```

```php
return new class extends Migration
{
    public function up(): void {
    // Stores the user's purchased cards (Vault)
    Schema::create('collections', function (Blueprint $table) {
        $table->id();
        $table->foreignId('user_id')->constrained();
        $table->foreignId('card_id')->constrained();
        $table->timestamps();
    });

    // Stores the actual Deck structures
    Schema::create('decks', function (Blueprint $table) {
        $table->id();
        $table->foreignId('user_id')->constrained();
        $table->string('name');
        $table->timestamps();
    });

    // Pivot for Deck contents
    Schema::create('deck_card', function (Blueprint $table) {
        $table->id();
        $table->foreignId('deck_id')->constrained()->onDelete('cascade');
        $table->foreignId('card_id')->constrained()->onDelete('cascade');
        $table->integer('quantity')->default(1);
        $table->timestamps();
    });
}
};
```

FILE: database/migrations\2026_04_22_232531_add_preview_card_to_decks_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void {
    Schema::table('decks', function (Blueprint $table) {
        $table->foreignId('preview_card_id')->nullable()->constrained('cards')-
>onDelete('set null');
    });
}
```

```
};
```

FILE: database/migrations\2026_04_22_235832_add_location_to_deck_card_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
   public function up(): void {
    Schema::table('deck_card', function (Blueprint $table) {
        $table->string('location')->default('main'); // 'main' or 'extra'
    });
}
};
```

FILE: database/migrations\2026_04_23_add_wishlist_columns.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::table('wishlist', function (Blueprint $table) {
            $table->foreignId('user_id')->constrained()->onDelete('cascade');
            $table->foreignId('card_id')->constrained()->onDelete('cascade');
            $table->unique(['user_id', 'card_id']);
        });
    }

    /**
     * Reverse the migrations.
```

```
     */
    public function down(): void
    {
        Schema::table('wishlist', function (Blueprint $table) {
            $table->dropUnique(['user_id', 'card_id']);
            $table->dropForeignKeyConstraints();
        });
    }
};
```

FILE: database/seeders\DatabaseSeeder.php

```
<?php

namespace Database\Seeders;

use Illuminate\Database\Seeder;
use App\Models\User;
use App\Models\Card;
use App\Models\Listing;

class DatabaseSeeder extends Seeder
{
    public function run(): void
    {
        $this->command->info('Forging the Living Market...');

        // 1. Create the Tech Lead
        User::firstOrCreate(['email' => 'admin@tcg.com'],[
            'name' => 'Tech Lead', 'password' => bcrypt('password123'), 'role' =>
'admin', 'reputation_score' => 5.00
        ]);

        // 2. Create the Legendary Duelists
        $duelists =['Seto Kaiba', 'Yugi Muto', 'Joey Wheeler', 'Mai Valentine',
'Maximillion Pegasus', 'Marik Ishtar', 'Bakura', 'Chazz Princeton'];

        $vendors =[];
        foreach ($duelists as $name) {
            $vendors[] = User::firstOrCreate(['email' => strtolower(explode(' ',
$name)[0]) . '@duel.com'],['name' => $name, 'password' => bcrypt('password123'),
'role' => 'duelist', 'reputation_score' => rand(35, 50) / 10]
            );
        }

        // 3. The Absolute Market: Every single card gets a vendor.
        $cards = Card::all();
        $totalCards = $cards->count();

        $this->command->info("Distributing ALL {$totalCards} artifacts to
```

```
vendors...");

        $bar = $this->command->getOutput()->createProgressBar($totalCards);
        $bar->start();

        $conditions =['Mint', 'Near Mint', 'Lightly Played', 'Damaged'];

        foreach ($cards as $card) {
            $randomVendor = $vendors[array_rand($vendors)];

            // Perfectly structured arrays, no rogue comments
            Listing::firstOrCreate(['card_id' => $card->id],[
                    'seller_id' => $randomVendor->id,
                    'condition' => $conditions[array_rand($conditions)],
                    'price' => rand(10, 999) + 0.99,
                    'quantity' => rand(1, 5),
                    'is_active' => true
                ]
            );

            $bar->advance();
        }

        $bar->finish();
        $this->command->newLine();
        $this->command->info('The Absolute Living Market is online. Every card is
now available.');
    }
}
```

FILE: resources/views\catalog.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section" style="min-height: 100vh; display: flex; flex-direction:
column; align-items: center; padding-top: 100px;">
    <div class="pattern-dots" style="position:absolute;inset:0;opacity:.2;pointer-
events:none"></div>

    <div class="container" style="width: 100%; display: flex; flex-direction:
column; align-items: center;">

        <div class="heading-block" style="text-align: center; margin-bottom:
40px;">
            <span class="tag yellow" style="margin-bottom:24px"><span
class="label">&gt; module.catalog</span></span>
            <h2 class="h2 text-stack-sm">Card <br/><span class="accent-
m">Database.</span></h2>
            <p class="lede" style="margin: 24px auto 0 auto;">&gt; 14,322 cards
detected. Initializing grid...</p>
```

```
        </div>

        <!-- SEARCH & FILTER BAR -->
        <form method="GET" action="{{ route('catalog') }}" style="display:flex;
flex-wrap: wrap; justify-content: center; gap:16px; margin: 0 auto 64px auto;
width: 100%; max-width: 1000px; background:hsl(var(--card)/.8); padding: 24px;
border: 4px solid var(--ink-c); box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0
var(--a3); position: relative; z-index: 100;">
            <input type="text" name="search" value="{{ request('search') }}"
placeholder="&gt; Search name..." style="flex:2; min-width: 200px; padding: 12px;
background: #000; color: #fff; border: 2px solid var(--a5); font-family:'Share
Tech Mono',monospace;">

            <select name="category" style="flex:1; min-width: 150px; padding:
12px; background: #000; color: var(--a5); border: 2px solid var(--ink-c); font-
family:'Share Tech Mono',monospace;">
                <option value="">ALL TYPES</option>
                @foreach($categories as $cat)
                    <option value="{{ $cat->name }}" {{ request('category') ==
$cat->name ? 'selected' : '' }}>{{ strtoupper($cat->name) }}</option>
                @endforeach
            </select>

            <select name="sort" style="flex:1; min-width: 150px; padding: 12px;
background: #000; color: var(--a3); border: 2px solid var(--ink-c); font-
family:'Share Tech Mono',monospace;">
                <option value="name_asc" {{ request('sort') == 'name_asc' ?
'selected' : '' }}>A-Z</option>
                <option value="name_desc" {{ request('sort') == 'name_desc' ?
'selected' : '' }}>Z-A</option>
                <option value="price_asc" {{ request('sort') == 'price_asc' ?
'selected' : '' }}>PRICE: LOW TO HIGH</option>
                <option value="price_desc" {{ request('sort') == 'price_desc' ?
'selected' : '' }}>PRICE: HIGH TO LOW</option>
            </select>

            <button type="submit" class="btn cyan sm" style="flex: 0.5; min-width:
120px;"><span class="inner">Execute</span></button>
        </form>

        <!-- THE CARD GRID -->
        <div class="features-grid" style="display: grid; grid-template-columns:
repeat(auto-fill, minmax(300px, 1fr)); gap: 40px; width: 100%; justify-items:
center; position: relative; z-index: 10;">
            @forelse($cards as $card)
                @php
                    $glow = 'shadow-brick';
                    if($card->category->name == 'Monster') $glow = 'shadow-brick-
yellow';
                    if($card->category->name == 'Spell') $glow = 'shadow-brick-
cyan';
                    if($card->category->name == 'Trap') $glow = 'shadow-brick-
magenta';
```

```
                    // Check Moataz's DB to see if the user favorited this card
                    $isWishlisted = false;
                    if(auth()->check() && $card->wishlistedBy()->where('user_id',
auth()->id())->exists()) {
                        $isWishlisted = true;

                    //[TECH LEAD FIX]: Advanced Ownership & Quantity Checks!
                    $activeListings = clone $card->listings()->where('is_active',
true)->where('quantity', '>', 0)->get();
                    $totalQuantity = $activeListings->sum('quantity');
                    $isSelling = auth()->check() && $activeListings-
>where('seller_id', auth()->id())->isNotEmpty();
                @endphp

                <div class="tcard {{ $glow }} {{ $isWishlisted ? 'wishlisted' : ''
}}" style="width: 100%; max-width: 320px;">

                    <div class="titlebar" style="display: flex; justify-content:
space-between; align-items: center; padding: 8px 15px;">
                        <div style="display: flex; align-items: center; gap:
8px;">
                            <span class="dots"><span class="d1"></span><span
class="d2"></span><span class="d3"></span></span>
                            <span class="ttl" style="font-size: 10px; font-family:
'Share Tech Mono', monospace;">&gt; {{ $card->passcode }}.bin</span>
                        </div>

                        @auth
                        <button class="btn-wishlist {{ $isWishlisted ? 'active' :
'' }}" onclick="toggleWishlist(event, {{ $card->id }})" title="Toggle Wishlist"
style="background: none; border: none; cursor: pointer; transition: all 0.3s;
color: {{ $isWishlisted ? 'var(--a1)' : 'var(--chrome-c)' }};">
                            <svg style="width: 18px; height: 18px; fill: {{
$isWishlisted ? 'var(--a1)' : 'none' }};" viewBox="0 0 24 24"
stroke="currentColor" stroke-width="2.5"><path d="M20.84 4.61a5.5 5.5 0 0 0-7.78
0L12 5.67l-1.06-1.06a5.5 5.5 0 0 0-7.78 7.78l1.06 1.06L12 21.23l8.84-8.84 1.06-
1.06a5.5 5.5 0 0 0 0-7.78z"></path></svg>
                        </button>
                        @endauth
                    </div>

                    <div class="body" style="display: flex; flex-direction:
column; align-items: center; text-align: center; padding: 24px;">

                        <!-- [TECH LEAD FIX]: "YOU OWN THIS" BADGE -->
                        @if($isSelling)
                            <div class="tag magenta" style="margin-bottom: 15px;
width: 100%; justify-content: center;">
                                <span class="label" style="color: #fff;">&gt; YOUR
LISTING ACTIVE</span>
                            </div>
                        @endif

                        <div style="position: relative; display: inline-block;">
```

```
                            <img src="{{ $card->image_url }}" alt="{{ $card->name
}}" style="width: 180px; height: auto; border: 3px solid #000; margin-bottom:
15px; box-shadow: 0 0 15px rgba(0,0,0,0.5);">

                            <!-- MARKET VALUE BADGE -->
                            <div style="position: absolute; top: -10px; right:
-15px; background: var(--a5); color: var(--ink-c); padding: 4px 8px; font-family:
'Share Tech Mono', monospace; font-weight: bold; font-size: 0.9rem; border: 2px
solid var(--ink-c); transform: skewX(-10deg); box-shadow: 4px 4px 0 var(--ink-
c);">
                                @if($card->listings_min_price)
                                    💎 {{ $card->listings_min_price }} DT
                                @else
                                    💎 N/A
                                @endif
                            </div>
                        </div>

                        <h3 style="font-size: 1.1rem; min-height: 2.5rem; display:
flex; align-items: center; margin-bottom: 5px; font-family: 'Outfit', sans-
serif;">{{ $card->name }}</h3>

                        <!-- [TECH LEAD FIX]: TOTAL QUANTITY -->
                        <p class="mono" style="font-size: 11px; color: var(--
chrome-c); margin-bottom: 5px;">QTY AVAIL: <span style="color: var(--a3); font-
weight: bold;">{{ $totalQuantity }}</span></p>

                        <p class="mono" style="font-size: 11px; color: var(--a5);
margin-bottom: 20px;">[{{ strtoupper($card->type) }}]</p>

                        <div style="width: 100%;">
                            <a href="{{ route('cards.show', $card->id) }}"
class="btn outline sm full" style="text-decoration: none; border: 2px solid var(--
a5); color: var(--a5); padding: 8px; font-family: 'Share Tech Mono';">
                                <span class="inner">Market Data</span>
                            </a>
                        </div>
                    </div>
                </div>
            @empty
                <div style="grid-column: 1/-1; text-align: center; padding:
100px;">
                    <h3 class="text-stack" style="color: var(--a1); font-family:
'Orbitron';">NO DATA FOUND</h3>
                </div>
            @endforelse
        </div>

        <div style="margin: 80px 0; display: flex; justify-content: center; width:
100%;">
            {{ $cards->links() }}
        </div>

    </div>
```

```
</section>
@endsection
```

FILE: resources/views\dashboard.blade.php

```
@extends('layouts.master')

@section('content')
<div class="container-narrow" style="min-height: 70vh; padding-top: 60px;">

    <div style="margin-bottom: 40px;">
        <span class="tag cyan-on-dark" style="margin-bottom: 15px;"><span
class="label">&gt; SYSTEM.DUELIST_LINK</span></span>
        <h2 class="h2 text-stack-sm" style="font-size: 3rem;">DUELIST <span
class="accent-c">TERMINAL</span></h2>
    </div>

    <div class="features-grid">
        <!-- 1. THE USER'S ID CARD -->
        <div class="tcard shadow-brick-cyan">
            <div class="titlebar">
                <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                <span class="ttl">&gt; user_profile.dat</span>
            </div>
            <div class="corner tri bgc-5"></div>
            <div class="body" style="padding: 30px;">
                <h3 style="color: var(--chrome-c); margin-bottom: 10px;">{{
strtoupper(Auth::user()->name) }}</h3>
                <p style="color: var(--a5); font-family: 'Share Tech Mono',
monospace; font-size: 1.1rem; margin-bottom: 5px;">
                    &gt; CALLSIGN: {{ Auth::user()->name }}
                </p>
                <p style="color: hsl(var(--chrome)/.7); font-family: 'Share Tech
Mono', monospace; margin-bottom: 5px;">
                    &gt; NETWORK_ID: {{ Auth::user()->email }}
                </p>
                <p style="color: hsl(var(--chrome)/.7); font-family: 'Share Tech
Mono', monospace; margin-bottom: 25px;">
                    &gt; CLEARANCE: {{ strtoupper(Auth::user()->role) }}
                </p>

                <a href="{{ route('profile.edit') }}" class="btn cyan sm full">
                    <span class="inner">UPDATE SECURE DATA</span>
                </a>
            </div>

            <form method="POST" action="{{ route('logout') }}" style="margin-top:
40px;">
                @csrf
                <button type="submit" style="color: var(--a1); font-family: 'Share
```

```
Tech Mono'; cursor: pointer; text-decoration: underline;">[ LOGOUT ]</button>
            </form>
        </div>

        <!-- 2. QUICK NAVIGATION MODULES -->
        <div style="display: flex; flex-direction: column; gap: 30px;">

            <!-- Link to Moataz's Inventory -->
            <div class="tcard rot-r shadow-brick-yellow">
                <div class="titlebar">
                    <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                    <span class="ttl">&gt; active_listings.exe</span>
                </div>
                <div class="corner square bgc-3"></div>
                <div class="body" style="padding: 20px;">
                    <h3 style="font-size: 1.5rem; color: var(--a3);">MY
BINDER</h3>
                    <p>Manage your cards for sale.</p>
                    <a href="{{ route('inventory.index') }}" class="btn yellow sm"
style="margin-top: 15px;"><span class="inner">OPEN BINDER</span></a>
                </div>
            </div>

            <!-- Link to Moataz's Order History -->
            <div class="tcard rot-l shadow-brick-magenta">
                <div class="titlebar">
                    <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                    <span class="ttl">&gt; transaction_log.bin</span>
                </div>
                <div class="corner circle bgc-4"></div>
                <div class="body" style="padding: 20px;">
                    <h3 style="font-size: 1.5rem; color: var(--a4);">ORDER
HISTORY</h3>
                    <p>Track your incoming and outgoing shipments.</p>
                    <a href="{{ route('orders.index') }}" class="btn magenta sm"
style="margin-top: 15px;"><span class="inner">VIEW LOGS</span></a>
                </div>
            </div>

        </div>
    </div>

</div>
@endsection
```

FILE: resources/views\show.blade.php

```
@extends('layouts.master')
```

```
@section('content')
<section class="section" style="min-height: 100vh; padding-top: 50px;">
    <div class="container-narrow">
        <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 64px;
align-items: start;">

            <!-- LEFT: Holographic Card Art -->
            <div style="position: relative;">
                <div class="tcard shadow-brick-cyan anim-float" style="width:
100%; padding: 20px; background: hsl(var(--card)/.9); max-width: 400px; margin: 0
auto;">
                    <img src="{{ $card->image_url }}" alt="{{ $card->name }}"
style="width: 100%; border: 4px solid var(--ink-c); box-shadow: 0 0 30px
rgba(0,0,0,0.8);">
                </div>
            </div>

            <!-- RIGHT: The Market Data Feed -->
            <div style="display: flex; flex-direction: column; gap: 20px;">
                <span class="tag yellow" style="width: fit-content;"><span
class="label">&gt; artifact.detected</span></span>

                <h1 class="hero-h1" style="font-size: 40px; line-height: 1;">
                    <span class="row1 text-stack">{{ $card->name }}</span>
                </h1>

                <div style="background: hsl(var(--card)/.6); border-left: 4px
solid var(--a5); padding: 20px;">
                    <p class="mono" style="color: var(--chrome-c); line-height:
1.8;">
                        &gt; TYPE: {{ $card->type }}<br>
                        &gt; CATEGORY: {{ strtoupper($card->category->name ??
'UNKNOWN') }}<br>
                        &gt; PASSCODE: {{ $card->passcode }}
                    </p>
                </div>

                <p class="lede" style="font-size: 14px;">{{ $card->description }}
</p>

                <!-- THE MARKETPLACE (Moataz's Listings) -->
                <div style="border: 4px solid var(--ink-c); padding: 24px;
background: var(--bg); box-shadow: 6px 6px 0 var(--a3);">
                    <h4 class="mono" style="color: var(--a3); margin-bottom: 16px;
font-size: 20px;">&gt; ACTIVE_SELLERS</h4>

                    <div style="display: flex; flex-direction: column; gap:
15px;">
                        @forelse($listings as $listing)
                            <div style="display: flex; justify-content: space-
between; align-items: center; border-bottom: 1px solid var(--a5); padding-bottom:
10px;">
                                <div>
                                    <span style="color: var(--a5); font-family:
```

```
'Share Tech Mono';">DUELIST: {{ $listing->seller->name }}</span><br>
                                    <span style="color: var(--chrome-c); font-
size: 12px;">COND: {{ $listing->condition }} | QTY: {{ $listing->quantity }}
</span>
                                </div>
                                <div style="display: flex; align-items: center;
gap: 15px;">
                                    <span class="font-display" style="color: var(-
-a3); font-size: 20px;">{{ $listing->price }} DT</span>

                                    <!-- OPEN CHAT WITH SELLER -->
                                    <button onclick="openChatWith({{ $listing-
>seller->id }}, '{{ addslashes($listing->seller->name) }}')" class="btn outline
sm" style="border-color: var(--a5); color: var(--a5);">
                                        <span class="inner">NEGOTIATE</span>
                                    </button>

                                    <!-- BUY BUTTON -->
                                    <form action="{{ route('cart.add') }}"
method="POST" style="margin:0;">
                                        @csrf
                                        <input type="hidden" name="listing_id"
value="{{ $listing->id }}">
                                        <button type="submit" class="btn cyan sm"
onclick="showNotification('> ADDED_TO_CART', true)"><span class="inner">BUY</span>
</button>
                                    </form>
                                </div>
                            </div>
                        @empty
                            <p class="mono" style="color: var(--a1);">&gt; NO
ACTIVE LISTINGS FOUND FOR THIS ARTIFACT.</p>
                        @endforelse
                    </div>
                </div>
            </div>
        </div>
    </div>
</section>
@endsection
```

FILE: resources/views\welcome.blade.php

```
@extends('layouts.master')

@section('content')
<section class="hero" id="top">
    <div class="float-layer" aria-hidden="true">
        <div class="shape circle bgc-4 anim-float"
style="top:10%;left:6%;width:56px;height:56px"></div>
        <div class="shape sq-rot bgc-3 anim-float-rev"
```

```
style="top:20%;left:88%;width:44px;height:44px"></div>
        <div class="shape tri bgc-5 anim-wiggle"
style="top:70%;left:4%;width:60px;height:60px"></div>
    </div>

    <span class="hero-bgword" aria-hidden="true">DUEL</span>

    <div class="container hero-grid">
        <div class="hero-copy">
            <span class="tag"><span class="dot anim-pulse-glow"></span><span
class="label">v.2026 // online</span></span>

            <h1 class="hero-h1">
                <span class="row1 text-stack">Trade Cards.</span>
                <span class="row2 text-gradient">Build Decks.</span>
                <span class="row3">Total <em>Domination.</em></span>
            </h1>

            <p class="hero-sub">&gt; The premier peer-to-peer Trading Card
marketplace. Over 14,000 cards in the database. <span class="cur anim-
blink">_</span></p>

            <div class="hero-ctas">
                <a href="/catalog" class="btn magenta lg"><span
class="inner">Enter Catalog</span></a>
            </div>
        </div>

        @if (Route::has('login'))
            <div class="h-14.5 hidden lg:block"></div>
        @endif

        <div class="hero-art">
            <div class="bg"></div>
            <div class="stripe pattern-stripes-light"></div>
            <div class="circle-r anim-pulse-glow"></div>
            <div class="square-y"></div>
            <div class="center"><div class="tri" style="clip-path:polygon(50% 0%,
0% 100%, 100% 100%); width:64px; height:64px; background:var(--a5);"></div></div>
            <div class="dot-stack"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></div>
        </div>
    </div>
</section>
@endsection
```

FILE: resources/views\wishlist.blade.php

```
@extends('layouts.master')

@section('content')
```

```
<section class="section">
    <div class="container">
        <div style="text-align: center; margin-bottom: 60px;">
            <span class="tag magenta"><span class="label">&gt;
USER_HEART_ARCHIVE</span></span>
            <h1 class="h2 text-stack-sm" style="font-size: 80px; margin: 20px
0;">FAVORITE<br><span style="color: var(--a5);">ARTIFACTS.</span></h1>
        </div>

        <div class="features-grid">
            @forelse($favorites as $card)
                <div class="tcard shadow-brick-magenta wishlisted">
                    <div class="titlebar" style="display: flex; justify-content:
space-between; padding: 8px 15px; border-bottom: 4px solid var(--ink-c);">
                        <span class="mono" style="color:var(--a4); font-size:
10px;">LOCKED_SIGNAL</span>
                        <!-- Un-heart button -->
                        <button class="btn-wishlist active"
onclick="toggleWishlist(event, {{ $card->id }})" style="background: none; border:
none; color: var(--a1); cursor: pointer;">
                            <svg style="width: 18px; height: 18px;" viewBox="0 0
24 24" fill="currentColor" stroke="currentColor" stroke-width="2.5"><path
d="M20.84 4.61a5.5 5.5 0 0 0-7.78 0L12 5.67l-1.06-1.06a5.5 5.5 0 0 0-7.78
7.78l1.06 1.06L12 21.23l8.84-8.84 1.06-1.06a5.5 5.5 0 0 0 0-7.78z"></path></svg>
                        </button>
                    </div>
                    <div class="body" style="display: flex; flex-direction:
column; align-items: center; text-align: center; padding: 24px;">
                        <img src="{{ $card->image_url }}" style="width: 180px;
border: 3px solid #000; margin-bottom: 20px;">
                        <h3 style="font-size: 1.1rem;">{{ $card->name }}</h3>
                        <a href="{{ route('cards.show', $card->id) }}" class="btn
outline sm full" style="margin-top: 15px;"><span class="inner">View Market
Data</span></a>
                    </div>
                </div>
            @empty
                <div style="grid-column: 1/-1; text-align: center; padding: 100px;
border: 2px dashed var(--a4);">
                    <p class="lede" style="color: var(--a4);">&gt; NO SIGNALS
DETECTED IN THE HEART VAULT.</p>
                </div>
            @endforelse
        </div>
    </div>
</section>
@endsection
```

FILE: `resources/views\admin\dashboard.blade.php`

FILE: resources/views\auth\confirm-password.blade.php

```
<x-guest-layout>
    <div class="mb-4 text-sm text-gray-600">
        {{ __('This is a secure area of the application. Please confirm your
password before continuing.') }}
    </div>

    <form method="POST" action="{{ route('password.confirm') }}">
        @csrf

        <!-- Password -->
        <div>
            <x-input-label for="password" :value="__('Password')" />

            <x-text-input id="password" class="block mt-1 w-full"
                            type="password"
                            name="password"
                            required autocomplete="current-password" />

            <x-input-error :messages="$errors->get('password')" class="mt-2" />
        </div>

        <div class="flex justify-end mt-4">
            <x-primary-button>
                {{ __('Confirm') }}
            </x-primary-button>
        </div>
    </form>
</x-guest-layout>
```

FILE: resources/views\auth\forgot-password.blade.php

```
<x-guest-layout>
    <div class="mb-4 text-sm text-gray-600">
        {{ __('Forgot your password? No problem. Just let us know your email
address and we will email you a password reset link that will allow you to choose
a new one.') }}
    </div>

    <!-- Session Status -->
    <x-auth-session-status class="mb-4" :status="session('status')" />

    <form method="POST" action="{{ route('password.email') }}">
```

```
        @csrf

        <!-- Email Address -->
        <div>
            <x-input-label for="email" :value="__('Email')" />
            <x-text-input id="email" class="block mt-1 w-full" type="email"
name="email" :value="old('email')" required autofocus />
            <x-input-error :messages="$errors->get('email')" class="mt-2" />
        </div>

        <div class="flex items-center justify-end mt-4">
            <x-primary-button>
                {{ __('Email Password Reset Link') }}
            </x-primary-button>
        </div>
    </form>
</x-guest-layout>
```

FILE: resources/views\auth\login.blade.php

```
@extends('layouts.master')

@section('content')
<div class="container-narrow" style="display: flex; justify-content: center;
align-items: center; min-height: 60vh;">
    <div class="tcard shadow-brick-magenta" style="width: 100%; max-width:
450px;">
        <div class="titlebar">
            <span class="dots"><span class="d1"></span><span class="d2"></span>
<span class="d3"></span></span>
            <span class="ttl">&gt; system.auth.login</span>
        </div>
        <div class="corner square bgc-4"></div>
        <div class="body" style="padding: 40px;">

            <h2 class="h2 text-stack-sm" style="font-size: 2rem; margin-bottom:
30px; text-align: center;">ACCESS <br/><span class="accent-m">VOID</span></h2>

            <!-- Session Status (Handled by Breeze) -->
            <x-auth-session-status style="color: var(--a5); margin-bottom: 15px;"
:status="session('status')" />

            <form method="POST" action="{{ route('login') }}" style="display:
flex; flex-direction: column; gap: 20px;">
                @csrf

                <!-- Email Address -->
                <div>
                    <label for="email" style="font-family: 'Share Tech Mono',
monospace; color: var(--chrome-c);">&gt; EMAIL_ADDRESS</label>
```

```
                    <input id="email" type="email" name="email" value="{{
old('email') }}" required autofocus
                            style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors->get('email')" style="color:
var(--a1); margin-top: 5px;" />
                </div>

                <!-- Password -->
                <div>
                    <label for="password" style="font-family: 'Share Tech Mono',
monospace; color: var(--chrome-c);">&gt; PASSWORD</label>
                    <input id="password" type="password" name="password" required
autocomplete="current-password"
                            style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors->get('password')"
style="color: var(--a1); margin-top: 5px;" />
                </div>

                <!-- Remember Me -->
                <div style="display: flex; align-items: center; gap: 10px;">
                    <input id="remember_me" type="checkbox" name="remember"
style="accent-color: var(--a5);">
                    <label for="remember_me" style="font-family: 'Share Tech
Mono', monospace; color: var(--chrome-c); font-size: 0.9rem;">Keep session
active</label>
                </div>

                <!-- Actions -->
                <div style="display: flex; flex-direction: column; gap: 15px;
margin-top: 10px;">
                    <button type="submit" class="btn magenta md full">
                        <span class="inner">INITIALIZE LINK</span>
                    </button>

                    @if (Route::has('password.request'))
                        <a href="{{ route('password.request') }}" style="text-
align: center; font-family: 'Share Tech Mono', monospace; color: var(--chrome-c);
font-size: 0.8rem; text-decoration: underline;">
                            &gt; Recover lost cipher?
                        </a>
                    @endif
                </div>
            </form>
        </div>
    </div>
</div>
@endsection
```

FILE: resources/views\auth\register.blade.php

```
@extends('layouts.master')

@section('content')
<div class="container-narrow" style="display: flex; justify-content: center;
align-items: center; min-height: 60vh;">
    <div class="tcard shadow-brick-cyan" style="width: 100%; max-width: 450px;">
        <div class="titlebar">
            <span class="dots"><span class="d1"></span><span class="d2"></span>
<span class="d3"></span></span>
            <span class="ttl">&gt; system.auth.register</span>
        </div>
        <div class="corner tri bgc-5"></div>
        <div class="body" style="padding: 40px;">

            <h2 class="h2 text-stack-sm" style="font-size: 2rem; margin-bottom:
30px; text-align: center;">NEW <br/><span class="accent-c">DUELIST</span></h2>

            <form method="POST" action="{{ route('register') }}" style="display:
flex; flex-direction: column; gap: 20px;">
                @csrf

                <!-- Name -->
                <div>
                    <label for="name" style="font-family: 'Share Tech Mono',
monospace; color: var(--chrome-c);">&gt; CALLSIGN (NAME)</label>
                    <input id="name" type="text" name="name" value="{{ old('name')
}}" required autofocus autocomplete="name"
                           style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors->get('name')" style="color:
var(--a1); margin-top: 5px;" />
                </div>

                <!-- Email Address -->
                <div>
                    <label for="email" style="font-family: 'Share Tech Mono',
monospace; color: var(--chrome-c);">&gt; EMAIL_ADDRESS</label>
                    <input id="email" type="email" name="email" value="{{
old('email') }}" required autocomplete="username"
                           style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors->get('email')" style="color:
var(--a1); margin-top: 5px;" />
                </div>

                <!-- Password -->
                <div>
                    <label for="password" style="font-family: 'Share Tech Mono',
```

```
monospace; color: var(--chrome-c);">&gt; PASSWORD</label>
                    <input id="password" type="password" name="password" required
autocomplete="new-password"
                           style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors->get('password')"
style="color: var(--a1); margin-top: 5px;" />
                </div>

                <!-- Confirm Password -->
                <div>
                    <label for="password_confirmation" style="font-family: 'Share
Tech Mono', monospace; color: var(--chrome-c);">&gt; VERIFY_PASSWORD</label>
                    <input id="password_confirmation" type="password"
name="password_confirmation" required autocomplete="new-password"
                           style="width: 100%; background: var(--ink-c); border:
2px solid var(--a5); color: var(--chrome-c); padding: 12px; margin-top: 5px; font-
family: 'Share Tech Mono', monospace;">
                    <x-input-error :messages="$errors-
>get('password_confirmation')" style="color: var(--a1); margin-top: 5px;" />
                </div>

                <!-- Actions -->
                <div style="display: flex; flex-direction: column; gap: 15px;
margin-top: 10px;">
                    <button type="submit" class="btn cyan md full">
                        <span class="inner">FORGE ACCOUNT</span>
                    </button>

                    <a href="{{ route('login') }}" style="text-align: center;
font-family: 'Share Tech Mono', monospace; color: var(--chrome-c); font-size:
0.8rem; text-decoration: underline;">
                        &gt; Already registered? Authenticate here.
                    </a>
                </div>
            </form>
        </div>
    </div>
</div>
@endsection
```

FILE: resources/views\auth\reset-password.blade.php

```
<x-guest-layout>
    <form method="POST" action="{{ route('password.store') }}">
        @csrf

        <!-- Password Reset Token -->
        <input type="hidden" name="token" value="{{ $request->route('token') }}">
```

```
        <!-- Email Address -->
        <div>
            <x-input-label for="email" :value="__('Email')" />
            <x-text-input id="email" class="block mt-1 w-full" type="email"
name="email" :value="old('email', $request->email)" required autofocus
autocomplete="username" />
            <x-input-error :messages="$errors->get('email')" class="mt-2" />
        </div>

        <!-- Password -->
        <div class="mt-4">
            <x-input-label for="password" :value="__('Password')" />
            <x-text-input id="password" class="block mt-1 w-full" type="password"
name="password" required autocomplete="new-password" />
            <x-input-error :messages="$errors->get('password')" class="mt-2" />
        </div>

        <!-- Confirm Password -->
        <div class="mt-4">
            <x-input-label for="password_confirmation" :value="__('Confirm
Password')" />

            <x-text-input id="password_confirmation" class="block mt-1 w-full"
                                type="password"
                                name="password_confirmation" required
autocomplete="new-password" />

            <x-input-error :messages="$errors->get('password_confirmation')"
class="mt-2" />
        </div>

        <div class="flex items-center justify-end mt-4">
            <x-primary-button>
                {{ __('Reset Password') }}
            </x-primary-button>
        </div>
    </form>
</x-guest-layout>
```

FILE: resources/views\auth\verify-email.blade.php

```
<x-guest-layout>
    <div class="mb-4 text-sm text-gray-600">
        {{ __('Thanks for signing up! Before getting started, could you verify
your email address by clicking on the link we just emailed to you? If you didn\'t
receive the email, we will gladly send you another.') }}
    </div>

    @if (session('status') == 'verification-link-sent')
        <div class="mb-4 font-medium text-sm text-green-600">
```

```
            {{ __('A new verification link has been sent to the email address you
provided during registration.') }}
        </div>
    @endif

    <div class="mt-4 flex items-center justify-between">
        <form method="POST" action="{{ route('verification.send') }}">
            @csrf

            <div>
                <x-primary-button>
                    {{ __('Resend Verification Email') }}
                </x-primary-button>
            </div>
        </form>

        <form method="POST" action="{{ route('logout') }}">
            @csrf

            <button type="submit" class="underline text-sm text-gray-600
hover:text-gray-900 rounded-md focus:outline-none focus:ring-2 focus:ring-offset-2
focus:ring-indigo-500">
                {{ __('Log Out') }}
            </button>
        </form>
    </div>
</x-guest-layout>
```

FILE: resources/views\Cards\show.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section" style="min-height: 100vh; padding-top: 50px;">
    <div class="container-narrow">
        <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 64px;
align-items: start;">

            <!-- LEFT: Holographic Card Art -->
            <div style="position: relative;">
                <div class="tcard shadow-brick-cyan anim-float" style="width:
100%; padding: 20px; background: hsl(var(--card)/.9); max-width: 400px; margin: 0
auto;">
                    <img src="{{ $card->image_url }}" alt="{{ $card->name }}"
style="width: 100%; border: 4px solid var(--ink-c); box-shadow: 0 0 30px
rgba(0,0,0,0.8);">
                </div>
            </div>

            <!-- RIGHT: The Market Data Feed -->
```

```
            <div style="display: flex; flex-direction: column; gap: 20px;">
                <span class="tag yellow" style="width: fit-content;"><span
class="label">&gt; artifact.detected</span></span>

                <h1 class="hero-h1" style="font-size: 40px; line-height: 1;">
                    <span class="row1 text-stack">{{ $card->name }}</span>
                </h1>

                <div style="background: hsl(var(--card)/.6); border-left: 4px
solid var(--a5); padding: 20px;">
                    <p class="mono" style="color: var(--chrome-c); line-height:
1.8;">
                        &gt; TYPE: {{ $card->type }}<br>
                        &gt; CATEGORY: {{ strtoupper($card->category->name ??
'UNKNOWN') }}<br>
                        &gt; PASSCODE: {{ $card->passcode }}
                    </p>
                </div>

                <p class="lede" style="font-size: 14px;">{{ $card->description }}
</p>

                <!-- THE MARKETPLACE (Moataz's Listings) -->
                <div style="border: 4px solid var(--ink-c); padding: 24px;
background: var(--bg); box-shadow: 6px 6px 0 var(--a3);">
                    <h4 class="mono" style="color: var(--a3); margin-bottom: 16px;
font-size: 20px;">&gt; ACTIVE_SELLERS</h4>

                    <div style="display: flex; flex-direction: column; gap:
15px;">
                        @forelse($listings as $listing)
                            <div style="display: flex; justify-content: space-
between; align-items: center; border-bottom: 1px solid var(--a5); padding-bottom:
10px;">
                                <div>
                                    <span style="color: var(--a5); font-family:
'Share Tech Mono';">DUELIST: {{ $listing->seller->name }}</span><br>
                                    <span style="color: var(--chrome-c); font-
size: 12px;">COND: {{ $listing->condition }} | QTY: {{ $listing->quantity }}
</span>
                                </div>

                                <div style="display: flex; align-items: center;
gap: 15px;">
                                    <span class="font-display" style="color: var(-
-a3); font-size: 20px;">{{ $listing->price }} DT</span>

                                    <!--[TECH LEAD FIX]: RESTORED NEGOTIATE BUTTON
-->
                                    @if(auth()->check() && auth()->id() !==
$listing->seller_id)
                                        <button onclick="openChatWith({{ $listing-
>seller->id }}, '{{ addslashes($listing->seller->name) }}')" class="btn outline
sm" style="border-color: var(--a5); color: var(--a5);">
```

```
                                            <span class="inner">NEGOTIATE</span>
                                        </button>
                                    @endif

                                    <!-- BUY BUTTON -->
                                    <form action="{{ route('cart.add') }}"
method="POST" style="margin:0;">
                                        @csrf
                                        <input type="hidden" name="listing_id"
value="{{ $listing->id }}">
                                        <button type="submit" class="btn cyan sm"
onclick="showNotification('> INITIATING_TRANSACTION', false)"><span
class="inner">BUY</span></button>
                                    </form>
                                </div>
                            </div>
                        @empty
                            <p class="mono" style="color: var(--a1);">&gt; NO
ACTIVE LISTINGS FOUND FOR THIS ARTIFACT.</p>
                        @endforelse
                    </div>
                </div>
            </div>
        </div>
    </div>
</section>
@endsection
```

FILE: resources/views\cart\index.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section">
    <div class="container-tight">
        <h2 class="h2 text-stack-sm">Your <span class="accent-c">Vault.</span>
</h2>

        @if(session('success'))
            <div class="tag cyan-on-dark" style="margin-bottom:20px; width:100%;
text-align:center;">{{ session('success') }}</div>
        @endif

        @if(empty($cart))
            <div class="tcard" style="padding: 40px; text-align: center;">
                <p>&gt; THE VAULT IS EMPTY. FIND CARDS IN THE CATALOG.</p>
                <a href="{{ route('catalog') }}" class="btn magenta sm"
style="margin-top:20px"><span class="inner">To Catalog</span></a>
            </div>
        @else
            <div class="tcard" style="padding: 24px;">
```

```
                @foreach($cart as $id => $item)
                    <div style="display: flex; align-items: center; justify-
content: space-between; border-bottom: 2px solid var(--ink-c); padding: 15px 0;">
                        <img src="{{ $item['image'] }}" style="width: 60px;
height: auto;">
                        <div>
                            <h3 style="font-size: 1rem;">{{ $item['name'] }}</h3>
                            <p style="font-size: 0.8rem;">Cond: {{
$item['condition'] }} | Qty: {{ $item['quantity'] }}</p>
                        </div>
                        <div style="font-family: 'Share Tech Mono';">{{
$item['price'] * $item['quantity'] }} DT</div>

                        <form action="{{ route('cart.remove') }}" method="POST">
                            @csrf @method('DELETE')
                            <input type="hidden" name="listing_id" value="{{ $id
}}">
                            <button type="submit" style="color: var(--a1);">
[REMOVE]</button>
                        </form>
                    </div>
                @endforeach

                <div style="margin-top: 30px; text-align: right;">
                    <h3 style="font-size: 1.5rem;">TOTAL: {{ $total }} DT</h3>
                    <form action="{{ route('checkout.process') }}" method="POST"
style="margin-top: 20px;">
                        @csrf
                        <button type="submit" class="btn magenta lg"><span
class="inner">Execute Checkout</span></button>
                    </form>
                </div>
            </div>
        @endif
    </div>
</section>
@endsection
```

FILE: resources/views\components\application-logo.blade.php

```
<svg viewBox="0 0 316 316" xmlns="http://www.w3.org/2000/svg" {{ $attributes }}>
    <path d="M305.8 81.125C305.77 80.995 305.69 80.885 305.65 80.755C305.56 80.525
305.49 80.285 305.37 80.075C305.29 79.935 305.17 79.815 305.07 79.685C304.94
79.515 304.83 79.325 304.68 79.175C304.55 79.045 304.39 78.955 304.25
78.845C304.09 78.715 303.95 78.575 303.77 78.475L251.32 48.275C249.97 47.495
248.31 47.495 246.96 48.275L194.51 78.475C194.33 78.575 194.19 78.725 194.03
78.845C193.89 78.955 193.73 79.045 193.6 79.175C193.45 79.325 193.34 79.515 193.21
79.685C193.11 79.815 192.99 79.935 192.91 80.075C192.79 80.285 192.71 80.525
192.63 80.755C192.58 80.875 192.51 80.995 192.48 81.125C192.38 81.495 192.33
81.875 192.33 82.265V139.625L148.62 164.795V52.575C148.62 52.185 148.57 51.805
148.47 51.435C148.44 51.305 148.36 51.195 148.32 51.065C148.23 50.835 148.16
```

```
50.595 148.04 50.385C147.96 50.245 147.84 50.125 147.74 49.995C147.61 49.825 147.5
49.635 147.35 49.485C147.22 49.355 147.06 49.265 146.92 49.155C146.76 49.025
146.62 48.885 146.44 48.785L93.99 18.585C92.64 17.805 90.98 17.805 89.63
18.585L37.18 48.785C37 48.885 36.86 49.035 36.7 49.155C36.56 49.265 36.4 49.355
36.27 49.485C36.12 49.635 36.01 49.825 35.88 49.995C35.78 50.125 35.66 50.245
35.58 50.385C35.46 50.595 35.38 50.835 35.3 51.065C35.25 51.185 35.18 51.305 35.15
51.435C35.05 51.805 35 52.185 35 52.575V232.235C35 233.795 35.84 235.245 37.19
236.025L142.1 296.425C142.33 296.555 142.58 296.635 142.82 296.725C142.93 296.765
143.04 296.835 143.16 296.865C143.53 296.965 143.9 297.015 144.28 297.015C144.66
297.015 145.03 296.965 145.4 296.865C145.5 296.835 145.59 296.775 145.69
296.745C145.95 296.655 146.21 296.565 146.45 296.435L251.36 236.035C252.72 235.255
253.55 233.815 253.55 232.245V174.885L303.81 145.945C305.17 145.165 306 143.725
306 142.155V82.265C305.95 81.875 305.89 81.495 305.8 81.125ZM144.2 227.205L100.57
202.515L146.39 176.135L196.66 147.195L240.33 172.335L208.29 190.625L144.2
227.205ZM244.75 114.995V164.795L226.39 154.225L201.03 139.625V89.825L219.39
100.395L244.75 114.995ZM249.12 57.105L292.81 82.265L249.12 107.425L205.43
82.265L249.12 57.105ZM114.49 184.425L96.13 194.995V85.305L121.49 70.705L139.85
60.135V169.815L114.49 184.425ZM91.76 27.425L135.45 52.585L91.76 77.745L48.07
52.585L91.76 27.425ZM43.67 60.135L62.03 70.705L87.39
85.305V202.545V202.555V202.565C87.39 202.735 87.44 202.895 87.46 203.055C87.49
203.265 87.49 203.485 87.55 203.695V203.705C87.6 203.875 87.69 204.035 87.76
204.195C87.84 204.375 87.89 204.575 87.99 204.745C87.99 204.745 87.99 204.755 88
204.755C88.09 204.905 88.22 205.035 88.33 205.175C88.45 205.335 88.55 205.495
88.69 205.635L88.7 205.645C88.82 205.765 88.98 205.855 89.12 205.965C89.28 206.085
89.42 206.225 89.59 206.325C89.6 206.325 89.6 206.325 89.61 206.335C89.62 206.335
89.62 206.345 89.63 206.345L139.87 234.775V285.065L43.67 229.705V60.135ZM244.75
229.705L148.58 285.075V234.775L219.8 194.115L244.75 179.875V229.705ZM297.2
139.625L253.49 164.795V114.995L278.85 100.395L297.21 89.825V139.625H297.2Z"/>
</svg>
```

FILE: resources/views\components\auth-session-status.blade.php

```
@props(['status'])

@if ($status)
    <div {{ $attributes->merge(['class' => 'font-medium text-sm text-green-600']) }}>
        {{ $status }}
    </div>
@endif
```

FILE: resources/views\components\danger-button.blade.php

```
<button {{ $attributes->merge(['type' => 'submit', 'class' => 'inline-flex items-center px-4 py-2 bg-red-600 border border-transparent rounded-md font-semibold
```

```
text-xs text-white uppercase tracking-widest hover:bg-red-500 active:bg-red-700
focus:outline-none focus:ring-2 focus:ring-red-500 focus:ring-offset-2 transition
ease-in-out duration-150']) }}>
    {{ $slot }}
</button>
```

FILE: resources/views\components\dropdown-link.blade.php

```
<a {{ $attributes->merge(['class' => 'block w-full px-4 py-2 text-start text-sm
leading-5 text-gray-700 hover:bg-gray-100 focus:outline-none focus:bg-gray-100
transition duration-150 ease-in-out']) }}>{{ $slot }}</a>
```

FILE: resources/views\components\dropdown.blade.php

```
@props(['align' => 'right', 'width' => '48', 'contentClasses' => 'py-1 bg-white'])

@php
$alignmentClasses = match ($align) {
    'left' => 'ltr:origin-top-left rtl:origin-top-right start-0',
    'top' => 'origin-top',
    default => 'ltr:origin-top-right rtl:origin-top-left end-0',
};

$width = match ($width) {
    '48' => 'w-48',
    default => $width,
};
@endphp

<div class="relative" x-data="{ open: false }" @click.outside="open = false"
@close.stop="open = false">
    <div @click="open = ! open">
        {{ $trigger }}
    </div>

    <div x-show="open"
            x-transition:enter="transition ease-out duration-200"
            x-transition:enter-start="opacity-0 scale-95"
            x-transition:enter-end="opacity-100 scale-100"
            x-transition:leave="transition ease-in duration-75"
            x-transition:leave-start="opacity-100 scale-100"
            x-transition:leave-end="opacity-0 scale-95"
            class="absolute z-50 mt-2 {{ $width }} rounded-md shadow-lg {{
$alignmentClasses }}"
            style="display: none;"
            @click="open = false">
        <div class="rounded-md ring-1 ring-black ring-opacity-5 {{ $contentClasses
```

```
}}">
            {{ $content }}
        </div>
    </div>
</div>
```

FILE: resources\views\components\input-error.blade.php

```
@props(['messages'])

@if ($messages)
    <ul {{ $attributes->merge(['class' => 'text-sm text-red-600 space-y-1']) }}>
        @foreach ((array) $messages as $message)
            <li>{{ $message }}</li>
        @endforeach
    </ul>
@endif
```

FILE: resources\views\components\input-label.blade.php

```
@props(['value'])

<label {{ $attributes->merge(['class' => 'block font-medium text-sm text-gray-
700']) }}>
    {{ $value ?? $slot }}
</label>
```

FILE: resources\views\components\modal.blade.php

```
@props([
    'name',
    'show' => false,
    'maxWidth' => '2xl'
])

@php
$maxWidth = [
    'sm' => 'sm:max-w-sm',
    'md' => 'sm:max-w-md',
    'lg' => 'sm:max-w-lg',
    'xl' => 'sm:max-w-xl',
    '2xl' => 'sm:max-w-2xl',
][$maxWidth];
```

```
@endphp

<div
    x-data="{
        show: @js($show),
        focusables() {
            // All focusable element types...
            let selector = 'a, button, input:not([type=\'hidden\']), textarea,
select, details, [tabindex]:not([tabindex=\'-1\'])'
            return [...$el.querySelectorAll(selector)]
                // All non-disabled elements...
                .filter(el => ! el.hasAttribute('disabled'))
        },
        firstFocusable() { return this.focusables()[0] },
        lastFocusable() { return this.focusables().slice(-1)[0] },
        nextFocusable() { return this.focusables()[this.nextFocusableIndex()] ||
this.firstFocusable() },
        prevFocusable() { return this.focusables()[this.prevFocusableIndex()] ||
this.lastFocusable() },
        nextFocusableIndex() { return
(this.focusables().indexOf(document.activeElement) + 1) %
(this.focusables().length + 1) },
        prevFocusableIndex() { return Math.max(0,
this.focusables().indexOf(document.activeElement)) -1 },
    }"
    x-init="$watch('show', value => {
        if (value) {
            document.body.classList.add('overflow-y-hidden');
            {{ $attributes->has('focusable') ? 'setTimeout(() =>
firstFocusable().focus(), 100)' : '' }}
        } else {
            document.body.classList.remove('overflow-y-hidden');
        }
    })"
    x-on:open-modal.window="$event.detail == '{{ $name }}' ? show = true : null"
    x-on:close-modal.window="$event.detail == '{{ $name }}' ? show = false : null"
    x-on:close.stop="show = false"
    x-on:keydown.escape.window="show = false"
    x-on:keydown.tab.prevent="$event.shiftKey || nextFocusable().focus()"
    x-on:keydown.shift.tab.prevent="prevFocusable().focus()"
    x-show="show"
    class="fixed inset-0 overflow-y-auto px-4 py-6 sm:px-0 z-50"
    style="display: {{ $show ? 'block' : 'none' }};"
>
    <div
        x-show="show"
        class="fixed inset-0 transform transition-all"
        x-on:click="show = false"
        x-transition:enter="ease-out duration-300"
        x-transition:enter-start="opacity-0"
        x-transition:enter-end="opacity-100"
        x-transition:leave="ease-in duration-200"
        x-transition:leave-start="opacity-100"
        x-transition:leave-end="opacity-0"
```

```
    >
        <div class="absolute inset-0 bg-gray-500 opacity-75"></div>
    </div>

    <div
        x-show="show"
        class="mb-6 bg-white rounded-lg overflow-hidden shadow-xl transform
transition-all sm:w-full {{ $maxWidth }} sm:mx-auto"
        x-transition:enter="ease-out duration-300"
        x-transition:enter-start="opacity-0 translate-y-4 sm:translate-y-0
sm:scale-95"
        x-transition:enter-end="opacity-100 translate-y-0 sm:scale-100"
        x-transition:leave="ease-in duration-200"
        x-transition:leave-start="opacity-100 translate-y-0 sm:scale-100"
        x-transition:leave-end="opacity-0 translate-y-4 sm:translate-y-0 sm:scale-
95"
    >
        {{ $slot }}
    </div>
</div>
```

FILE: resources/views\components\nav-link.blade.php

```
@props(['active'])

@php
$classes = ($active ?? false)
            ? 'inline-flex items-center px-1 pt-1 border-b-2 border-indigo-400
text-sm font-medium leading-5 text-gray-900 focus:outline-none focus:border-
indigo-700 transition duration-150 ease-in-out'
            : 'inline-flex items-center px-1 pt-1 border-b-2 border-transparent
text-sm font-medium leading-5 text-gray-500 hover:text-gray-700 hover:border-gray-
300 focus:outline-none focus:text-gray-700 focus:border-gray-300 transition
duration-150 ease-in-out';
@endphp

<a {{ $attributes->merge(['class' => $classes]) }}>
    {{ $slot }}
</a>
```

FILE: resources/views\components\primary-button.blade.php

```
<button {{ $attributes->merge(['type' => 'submit', 'class' => 'inline-flex items-
center px-4 py-2 bg-gray-800 border border-transparent rounded-md font-semibold
text-xs text-white uppercase tracking-widest hover:bg-gray-700 focus:bg-gray-700
active:bg-gray-900 focus:outline-none focus:ring-2 focus:ring-indigo-500
focus:ring-offset-2 transition ease-in-out duration-150']) }}>
```

```
    {{ $slot }}
</button>
```

FILE: resources/views\components\responsive-nav-link.blade.php

```
@props(['active'])

@php
$classes = ($active ?? false)
            ? 'block w-full ps-3 pe-4 py-2 border-l-4 border-indigo-400 text-start text-base font-medium text-indigo-700 bg-indigo-50 focus:outline-none focus:text-indigo-800 focus:bg-indigo-100 focus:border-indigo-700 transition duration-150 ease-in-out'
            : 'block w-full ps-3 pe-4 py-2 border-l-4 border-transparent text-start text-base font-medium text-gray-600 hover:text-gray-800 hover:bg-gray-50 hover:border-gray-300 focus:outline-none focus:text-gray-800 focus:bg-gray-50 focus:border-gray-300 transition duration-150 ease-in-out';
@endphp

<a {{ $attributes->merge(['class' => $classes]) }}>
    {{ $slot }}
</a>
```

FILE: resources/views\components\secondary-button.blade.php

```
<button {{ $attributes->merge(['type' => 'button', 'class' => 'inline-flex items-center px-4 py-2 bg-white border border-gray-300 rounded-md font-semibold text-xs text-gray-700 uppercase tracking-widest shadow-sm hover:bg-gray-50 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2 disabled:opacity-25 transition ease-in-out duration-150']) }}>
    {{ $slot }}
</button>
```

FILE: resources/views\components\text-input.blade.php

```
@props(['disabled' => false])

<input @disabled($disabled) {{ $attributes->merge(['class' => 'border-gray-300 focus:border-indigo-500 focus:ring-indigo-500 rounded-md shadow-sm']) }}>
```

FILE: resources/views\decks\builder.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section" style="padding: 20px;">
    <!-- LAYOUT GRID: Preview (300px) | Main/Extra (Center) | Library (400px) -->
    <div style="display: grid; grid-template-columns: 300px 1fr 400px; gap: 20px;
height: 80vh;">

        <!-- LEFT: PREVIEW & TOOLS -->
        <div class="tcard" style="padding: 20px; display: flex; flex-direction:
column; background: hsl(var(--card)/.9);">
            <h3 class="accent-m" style="margin-bottom:15px; font-family: 'Share
Tech Mono';">&gt; DECK: {{ strtoupper($deck->name) }}</h3>

            @if($deck->previewCard)
                <img src="{{ $deck->previewCard->image_url }}" style="width: 100%;
border: 2px solid var(--a3); box-shadow: 0 0 20px var(--a3); margin-bottom:
20px;">
            @else
                <div style="width: 100%; height: 300px; border: 2px dashed var(--
a5); display: grid; place-items: center; margin-bottom: 20px;">
                    <p class="mono">&gt; NO PREVIEW</p>
                </div>
            @endif

            <!-- IMPORT / EXPORT TOOLS -->
            <div style="border-top: 2px solid var(--ink-c); padding-top: 20px;
margin-top: auto;">
                <h4 class="mono" style="color: var(--a5); margin-bottom:
10px;">&gt; DATA_TRANSFER</h4>

                <a href="{{ route('deck.export', $deck->id) }}" class="btn cyan sm
full" style="margin-bottom: 10px;">
                    <span class="inner">⬇ EXPORT .YDK</span>
                </a>

                <form action="{{ route('deck.import', $deck->id) }}" method="POST"
enctype="multipart/form-data" style="display: flex; flex-direction: column; gap:
5px;">
                    @csrf
                    <input type="file" name="ydk_file" required style="font-
family: 'Share Tech Mono'; font-size: 10px; color: var(--chrome-c);">
                    <button type="submit" class="btn yellow sm full"><span
class="inner">⬆ IMPORT .YDK</span></button>
                </form>
            </div>
        </div>

        <!-- CENTER: MAIN & EXTRA DECK -->
        <div class="tcard" style="padding: 20px; overflow-y: auto; display: flex;
```

```
flex-direction: column; gap: 30px;">

            <!-- MAIN DECK -->
            <div>
                <h3 class="accent-c" style="margin-bottom:10px;">&gt; MAIN DECK
({{ $deck->cards->where('pivot.location', 'main')->sum('pivot.quantity') }}/60)
</h3>
                <div style="display: grid; grid-template-columns: repeat(auto-
fill, minmax(80px, 1fr)); gap: 5px;">
                    @foreach($deck->cards->where('pivot.location', 'main') as
$card)
                        <div style="position:relative; border:1px solid #444;">
                            <img src="{{ $card->image_url }}" style="width:100%;">
                            <span class="tag yellow" style="position:absolute;
bottom:0; right:0; font-size:9px; padding:1px 3px;">{{ $card->pivot->quantity }}
</span>
                            <div style="display: flex; gap: 2px;">
                                <form action="{{ route('deck.removeCard', [$deck-
>id, $card->id]) }}" method="POST" style="flex:1;">
                                    @csrf @method('DELETE')
                                    <button type="submit" class="btn magenta sm"
style="width:100%; font-size:8px; padding:0;">[X]</button>
                                </form>
                                <form action="{{ route('deck.setPreview', $deck-
>id) }}" method="POST" style="flex:1;">
                                    @csrf
                                    <input type="hidden" name="card_id" value="{{
$card->id }}">
                                    <button type="submit" class="btn yellow sm"
style="width:100%; font-size:8px; padding:0;">[P]</button>
                                </form>
                            </div>
                        </div>
                    @endforeach
                </div>
            </div>

            <!-- EXTRA DECK -->
            <div>
                <h3 class="accent-m" style="margin-bottom:10px;">&gt; EXTRA DECK
({{ $deck->cards->where('pivot.location', 'extra')->sum('pivot.quantity') }}/15)
</h3>
                <div style="display: grid; grid-template-columns: repeat(auto-
fill, minmax(80px, 1fr)); gap: 5px;">
                    @foreach($deck->cards->where('pivot.location', 'extra') as
$card)
                        <div style="position:relative; border:1px solid #444;">
                            <img src="{{ $card->image_url }}" style="width:100%;">
                            <span class="tag yellow" style="position:absolute;
bottom:0; right:0; font-size:9px; padding:1px 3px;">{{ $card->pivot->quantity }}
</span>
                        </div>
                    @endforeach
                </div>
```

```
            </div>
        </div>

        <!-- RIGHT: LIBRARY -->
        <div class="tcard" style="padding: 20px; overflow-y: auto; background:
hsl(var(--card)/.9);">
            <h3 class="accent-y" style="margin-bottom:15px;">&gt; LIBRARY</h3>
            <form action="{{ route('deck.builder', $deck->id) }}" method="GET"
style="margin-bottom: 15px;">
                <input type="text" name="library_search" value="{{
request('library_search') }}" placeholder="Search library..."
                       style="width: 100%; background:var(--bg); border:2px solid
var(--a5); padding:10px; color:white; font-family:'Share Tech Mono';">
            </form>

            <div style="display: grid; grid-template-columns: repeat(3, 1fr); gap:
5px;">
                <!-- [TECH LEAD FIX]: Limited to 50 cards to prevent memory
exhaustion -->
                @foreach(\App\Models\Card::where('name', 'like', '%' .
request('library_search') . '%')->limit(50)->get() as $card)
                    <button onclick="openSummonModal('{{ $card->id }}', '{{
addslashes($card->name) }}')"
                            style="background:none; border:none; cursor:pointer;
width:100%;">
                        <img src="{{ $card->image_url }}" title="{{ $card->name
}}" style="width:100%; border:1px solid #444;">
                    </button>
                @endforeach
            </div>
        </div>
    </div>
</section>

<!-- MODAL POPUP -->
<div id="summonModal" style="display:none; position:fixed; inset:0;
background:rgba(0,0,0,0.85); z-index:2000; place-items:center;">
    <form id="summonForm" method="POST" class="tcard" style="padding:30px;
width:300px; background:var(--bg);">
        @csrf
        <input type="hidden" name="card_id" id="modal_card_id">
        <h3 id="modal_card_name" class="accent-c" style="margin-bottom:20px;">
</h3>
        <select name="location" style="width:100%; background:var(--bg);
padding:10px; color:white; border:2px solid var(--a3);">
            <option value="main">MAIN DECK</option>
            <option value="extra">EXTRA DECK</option>
        </select>
        <button type="submit" class="btn cyan sm full" style="margin-top:20px;">
<span class="inner">CONFIRM</span></button>
        <button type="button"
onclick="document.getElementById('summonModal').style.display='none'" class="btn
magenta sm full" style="margin-top:10px;"><span class="inner">CANCEL</span>
</button>
```

```
    </form>
</div>

<script>
    function openSummonModal(cardId, cardName) {
        document.getElementById('modal_card_id').value = cardId;
        document.getElementById('modal_card_name').innerText = cardName;
        document.getElementById('summonForm').action = "{{ route('deck.addCard',
$deck->id) }}";
        document.getElementById('summonModal').style.display = 'grid';
    }
</script>
@endsection
```

FILE: resources/views\decks\index.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section">
    <div class="container-tight">
        <h2 class="h2 text-stack-sm">My <span class="accent-y">Decks.</span></h2>

        <!-- Create New Deck -->
        <form action="{{ route('deck.store') }}" method="POST" class="tcard"
style="padding: 20px; margin-bottom: 40px; background: hsl(var(--card)/.9);">
            @csrf
            <input type="text" name="name" placeholder="New Deck Name..." required
style="background:var(--bg); border:2px solid var(--a3); padding:10px;
color:white; width: 100%; margin-bottom: 10px;">
            <button type="submit" class="btn yellow sm"><span class="inner">Create
Deck</span></button>
        </form>

       <!-- List Decks -->
@foreach($decks as $d)
    <div class="tcard" style="padding: 15px; display: flex; justify-content:
space-between; align-items: center; margin-bottom: 10px;">

        <div style="display: flex; align-items: center; gap: 15px;">
            <!-- THE PREVIEW IMAGE -->
            <div style="width: 50px; height: 70px; border: 2px solid var(--a3);
overflow: hidden;">
                @if($d->previewCard)
                    <img src="{{ $d->previewCard->image_url }}" style="width:
100%; height: 100%; object-fit: cover;">
                @else
                    <div style="width: 100%; height: 100%; background: var(--ink-
c);"></div>
                @endif
            </div>
```

```
            <span class="mono" style="font-size: 1.2rem;">{{ $d->name }}</span>
        </div>

        <a href="{{ route('deck.builder', $d->id) }}" class="btn cyan sm">
            <span class="inner">Edit Deck</span>
        </a>
    </div>
@endforeach
    </div>
</section>
@endsection
```

FILE: resources/views\errors\404.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section" style="height: 80vh; display: flex; align-items: center;
justify-content: center; text-align: center;">
    <div class="container-tight">
        <div class="shadow-brick-red" style="background: var(--bg); border: 4px
solid var(--a1); padding: 60px; position: relative; overflow: hidden;">

            <!-- GLITCH EFFECT OVERLAY -->
            <div class="pattern-stripes" style="position:absolute; inset:0;
opacity:0.2; pointer-events:none;"></div>

            <h1 class="font-display anim-wiggle" style="font-size: 120px; color:
var(--a1); line-height: 1; margin: 0;">404</h1>
            <h2 class="h2 text-stack-sm" style="font-size: 30px; margin-top: 20px;
color: var(--chrome-c);">SIGNAL_LOST</h2>

            <p class="mono" style="margin-top: 32px; color: var(--a1); opacity:
0.8;">
                &gt; ERROR_CODE: 0xTCG_VOID<br>
                &gt; DESTINATION: UNREACHABLE<br>
                &gt; ACTION: RE-ESTABLISH CONNECTION
            </p>

            <div style="margin-top: 48px;">
                <a href="{{ route('catalog') }}" class="btn magenta lg">
                    <span class="inner">Return to Catalog</span>
                </a>
            </div>
        </div>
    </div>
</section>
@endsection
```

FILE: resources/views\inventory\index.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section">
    <div class="container-tight">
        <h2 class="h2 text-stack-sm">My <span class="accent-m">Binder.</span></h2>

        <!-- MOATAZ DOMAIN: Add New Listing Form -->
        <form action="{{ route('inventory.store') }}" method="POST" class="tcard"
style="padding: 24px; margin-top: 40px; background: hsl(var(--card)/.9);">
            @csrf
            <h3 style="margin-bottom: 20px; font-family: 'Share Tech Mono'; font-
size: 1rem; color: var(--a5);">&gt; LIST NEW CARD</h3>
            <div style="display: flex; flex-direction: column; gap: 20px;">

                <label style="font-family: 'Share Tech Mono'; color: var(--chrome-
c);">Select Card (From Library):</label>
                <!-- [TECH LEAD FIX]: Limited to 100 to prevent 14,000 tag memory
crash -->
                <select name="card_id" required style="background: var(--bg);
border: 2px solid var(--ink-c); padding: 10px; color: white; font-family: 'Share
Tech Mono';">
                    @foreach(\App\Models\Card::limit(100)->get() as $card)
                        <option value="{{ $card->id }}">{{ $card->name }} ({{
$card->passcode }})</option>
                    @endforeach
                </select>

                <label style="font-family: 'Share Tech Mono'; color: var(--chrome-
c);">Price (DT):</label>
                <input type="number" name="price" placeholder="Price (DT)"
step="0.01" required style="background: var(--bg); border: 2px solid var(--ink-c);
padding: 10px; color: white; font-family: 'Share Tech Mono';">

                <label style="font-family: 'Share Tech Mono'; color: var(--chrome-
c);">Condition:</label>
                <select name="condition" required style="background: var(--bg);
border: 2px solid var(--ink-c); padding: 10px; color: white; font-family: 'Share
Tech Mono';">
                    <option value="Mint">Mint</option>
                    <option value="Near Mint">Near Mint</option>
                    <option value="Lightly Played">Lightly Played</option>
                    <option value="Damaged">Damaged</option>
                </select>

                <label style="font-family: 'Share Tech Mono'; color: var(--chrome-
c);">Quantity:</label>
                <input type="number" name="quantity" value="1" min="1"
placeholder="Quantity" required style="background: var(--bg); border: 2px solid
var(--ink-c); padding: 10px; color: white; font-family: 'Share Tech Mono';">

                <button type="submit" class="btn magenta lg full"><span
```

```
class="inner">Add to Market</span></button>
            </div>
        </form>

        <!-- MOATAZ DOMAIN: Current Listings -->
        <h3 style="margin: 40px 0 20px 0; font-family: 'Share Tech Mono'; font-
size: 1.2rem; color: var(--a3);">&gt; ACTIVE LISTINGS</h3>
        @forelse($myListings as $listing)
            <div class="tcard" style="padding: 15px; display: flex; justify-
content: space-between; align-items: center; margin-bottom: 10px;">
                <span class="mono" style="color: var(--chrome-c);">{{ $listing-
>card->name }}</span>
                <span class="mono" style="color: var(--a5);">{{ $listing->price }}
DT</span>
                <form action="{{ route('inventory.destroy', $listing->id) }}"
method="POST">
                    @csrf @method('DELETE')
                    <button type="submit" style="color: var(--a1); font-family:
'Share Tech Mono'; cursor: pointer; background: none; border: none;">[REMOVE]
</button>
                </form>
            </div>
        @empty
            <div class="tcard" style="padding: 20px; text-align: center;">
                <p class="mono" style="color: var(--chrome-c); opacity: 0.7;">&gt;
Your binder is empty. Add a card to the market.</p>
            </div>
        @endforelse
    </div>
</section>
@endsection
```

FILE: resources/views\layouts\app.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
    <head>
        <meta charset="utf-8">
        <meta name="viewport" content="width=device-width, initial-scale=1">
        <meta name="csrf-token" content="{{ csrf_token() }}">

        <title>{{ config('app.name', 'Laravel') }}</title>

        <!-- Fonts -->
        <link rel="preconnect" href="https://fonts.bunny.net">
        <link href="https://fonts.bunny.net/css?
family=figtree:400,500,600&display=swap" rel="stylesheet" />

        <!-- Scripts -->
        @vite(['resources/css/app.css', 'resources/js/app.js'])
    </head>
```

```
    <body class="font-sans antialiased">
        <div class="min-h-screen bg-gray-100">
            @include('layouts.navigation')

            <!-- Page Heading -->
            @isset($header)
                <header class="bg-white shadow">
                    <div class="max-w-7xl mx-auto py-6 px-4 sm:px-6 lg:px-8">
                        {{ $header }}
                    </div>
                </header>
            @endisset

            <!-- Page Content -->
            <main>
                {{ $slot }}
            </main>
        </div>
    </body>
</html>
```

FILE: resources/views\layouts\guest.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
    <head>
        <meta charset="utf-8">
        <meta name="viewport" content="width=device-width, initial-scale=1">
        <meta name="csrf-token" content="{{ csrf_token() }}">

        <title>{{ config('app.name', 'Laravel') }}</title>

        <!-- Fonts -->
        <link rel="preconnect" href="https://fonts.bunny.net">
        <link href="https://fonts.bunny.net/css?
family=figtree:400,500,600&display=swap" rel="stylesheet" />

        <!-- Scripts -->
        @vite(['resources/css/app.css', 'resources/js/app.js'])
    </head>
    <body class="font-sans text-gray-900 antialiased">
        <div class="min-h-screen flex flex-col sm:justify-center items-center pt-6
sm:pt-0 bg-gray-100">
            <div>
                <a href="/">
                    <x-application-logo class="w-20 h-20 fill-current text-gray-
500" />
                </a>
            </div>
```

```
            <div class="w-full sm:max-w-md mt-6 px-6 py-4 bg-white shadow-md
overflow-hidden sm:rounded-lg">
                {{ $slot }}
            </div>
        </div>
    </body>
</html>
```

FILE: resources/views\layouts\master.blade.php

```
<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>The TCG Exchange | Neon Bauhaus</title>

    <link rel="preconnect" href="https://fonts.googleapis.com" />
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
    <link href="https://fonts.googleapis.com/css2?
family=Outfit:wght@400;500;700;900&family=Orbitron:wght@500;700;900&family=Share+T
ech+Mono&display=swap" rel="stylesheet" />

    <!-- Neon Bauhaus Core Styles -->
    <link rel="stylesheet" href="{{ asset('css/neon.css') }}">
    <meta name="csrf-token" content="{{ csrf_token() }}">

    @stack('styles')
</head>

<body class="scanlines">
    <!-- BACKGROUND ATMOSPHERE -->
    <div class="atmosphere" aria-hidden="true">
        <div class="atmo-sun"></div>
        <div class="atmo-grid pattern-grid-floor"></div>
        <div class="atmo-dots pattern-dots"></div>
    </div>

    <div class="page">
        <!-- THE NAVBAR -->
        <header class="nav">
            <div class="nav-inner">
                <a href="/" class="logo" aria-label="NBD home">
                    <span class="logo-shapes"><span class="s1"></span><span
class="s2"></span><span class="s3"></span></span>
                    <span class="logo-text">TCG<b>EX</b></span>
                </a>
                <nav class="nav-links">
                    <a href="{{ route('catalog') }}">&gt; CATALOG</a>
                    <a href="{{ route('wishlist.index') }}">&gt; FAVORITES</a>
```

```
                    <a href="{{ route('cart.index') }}">&gt; MY CART</a>
                    <a href="{{ route('inventory.index') }}">&gt; MY BINDER</a>
                    <a href="{{ route('decks.index') }}">&gt; MY DECKS</a>

                    @auth
                        <a href="{{ url('/dashboard') }}">&gt; DASHBOARD</a>
                    @else
                        <a href="{{ route('login') }}">&gt; LOGIN</a>
                        <a href="{{ route('register') }}">&gt; REGISTER</a>
                    @endauth
                </nav>
            </div>
        </header>

        <!-- MAIN CONTENT INJECTION -->
        <main style="min-height: 80vh; padding-top: 100px;">
            <!-- THE DOPAMINE FEEDBACK -->
            <div class="container" style="margin-top: 20px;">
                @if(session('success'))
                    <div class="tag yellow" style="width: 100%; justify-content:
center; margin-bottom: 20px;">
                        <span class="label">&gt; {{ session('success') }}</span>
                    </div>
                @endif

                @if(session('error'))
                    <div class="tag cyan-on-dark" style="width: 100%; justify-
content: center; margin-bottom: 20px; border-color: var(--a1);">
                        <span class="label" style="color: var(--a1);">&gt; {{
session('error') }}</span>
                    </div>
                @endif
            </div>

            @yield('content')
        </main>

        <!-- THE FOOTER -->
        <footer class="foot">
            <div class="foot-bar">
                <div class="foot-bar-inner" style="text-align: center; padding:
20px; color: var(--chrome-c); opacity: 0.5; font-family: 'Share Tech Mono'; width:
100%; justify-content: center;">
                    <span>&gt; © 2026 THE TCG EXCHANGE. ALL SIGNALS RESERVED.
</span>
                </div>
            </div>
        </footer>
    </div>

    <!-- THE DUELIST COMM DRAWER -->
    <div id="chatDrawer" style="position: fixed; right: -400px; top: 0; width:
350px; height: 100vh; background: var(--bg); border-left: 4px solid var(--a5); z-
index: 1000; transition: right 0.4s cubic-bezier(0.19, 1, 0.22, 1); box-shadow:
```

```
-10px 0 40px rgba(0,0,0,0.8); padding: 25px; display: flex; flex-direction:
column;">
        <div style="display: flex; justify-content: space-between; align-items:
center; border-bottom: 2px solid var(--a5); padding-bottom: 15px; margin-bottom:
20px;">
            <h3 class="font-display" style="color: var(--a5); margin: 0; font-
size: 1.2rem; letter-spacing: 2px;">&gt; DUELIST_COMM</h3>
            <button onclick="toggleChat()" style="color: var(--a1); font-family:
'Share Tech Mono', monospace; cursor: pointer; background: none; border: none;">
[X] CLOSE</button>
        </div>

        <!-- Message Container -->
        <div id="chatMessages" style="flex: 1; overflow-y: auto; display: flex;
flex-direction: column; gap: 15px; padding: 10px;" class="pattern-dots-cyan">
            <div class="tag cyan-on-dark" style="width: fit-content;"><span
class="dot"></span><span class="label">System: Encrypted channel active.</span>
</div>
        </div>

        <!-- Input Box -->
        <div style="margin-top: 20px; border-top: 2px solid var(--ink-c); padding-
top: 20px;">
            <textarea id="chatInput" placeholder="Enter message..." style="width:
100%; background: var(--ink-c); color: var(--chrome-c); border: 2px solid var(--
a4); padding: 12px; font-family: 'Share Tech Mono', monospace; resize: none;
margin-bottom: 10px;"></textarea>
            <button onclick="sendMessage()" class="btn magenta sm full"><span
class="inner">Transmit</span></button>
        </div>
    </div>

    <!-- Floating Neon Button -->
    <button onclick="toggleChat()" id="chatFab" style="position: fixed; bottom:
30px; right: 30px; width: 65px; height: 65px; border-radius: 50%; background:
var(--a5); border: 4px solid var(--ink-c); cursor: pointer; z-index: 999; display:
flex; align-items: center; justify-content: center; box-shadow: 0 0 20px var(--
a5);" class="anim-pulse-glow">
        <svg style="width: 30px; height: 30px; color: var(--ink-c);" viewBox="0 0
24 24" fill="none" stroke="currentColor" stroke-width="2.5" stroke-linecap="round"
stroke-linejoin="round"><path d="M21 15a2 2 0 0 1-2 2H7l-4 4V5a2 2 0 0 1 2-2h14a2
2 0 0 1 2 2z"></path></svg>
    </button>

    <!-- SYSTEM NOTIFICATION POPUP -->
    <div id="neon-notification" style="position: fixed; bottom: -100px; left: 50%;
transform: translateX(-50%); z-index: 9999; background: var(--bg); border: 3px
solid var(--a5); box-shadow: 0 0 20px var(--a5), 6px 6px 0 var(--ink-c); padding:
15px 30px; transition: all 0.5s cubic-bezier(0.19, 1, 0.22, 1); pointer-events:
none;">
        <div style="display: flex; align-items: center; gap: 15px;">
            <span class="dot anim-pulse-glow" style="width: 10px; height: 10px;
background: var(--a5); border-radius: 50%;"></span>
            <span class="msg" id="notification-text" style="font-family: 'Share
```

```
Tech Mono', monospace; color: var(--a5); text-transform: uppercase; letter-
spacing: 2px; font-weight: bold;">ARCHIVE_SUCCESS</span>
        </div>
    </div>

    <!-- MASTER JAVASCRIPT LOGIC -->
    <script>
        const CSRF_TOKEN = '{{ csrf_token() }}';
        const AUTH_USER_ID = '{{ auth()->id() ?? 0 }}';
        let chatPartnerId = 1; // Default to Seto Kaiba for testing

        // --- MOATAZ'S CART INTEGRATION ---
        async function addToCart(listingId) {
            try {
                let response = await fetch('/cart/add', {
                    method: 'POST',
                    headers: {
                        'Content-Type': 'application/json',
                        'X-CSRF-TOKEN': CSRF_TOKEN
                    },
                    body: JSON.stringify({ listing_id: listingId, quantity: 1 })
                });

                let data = await response.json();

                if(data.success || response.ok) {
                    showNotification("> " + (data.message ?
data.message.toUpperCase() : "ARTIFACT_ADDED_TO_CARGO"), false);
                } else {
                    showNotification("> ERROR: " + (data.message ?
data.message.toUpperCase() : "TRANSACTION_FAILED"), true);
                }
            } catch (e) {
                showNotification("> ERROR: SERVER_UNREACHABLE", true);
            }
        }

        // --- 1. NOTIFICATION & WISHLIST LOGIC ---
        function showNotification(message, vibrate = false, priority = false) {
            const toast = document.getElementById('neon-notification');
            const text = document.getElementById('notification-text');

            text.innerText = message;

            // THE COLOR SWITCH
            if (priority) {
                // High Priority: PURE RED (var(--a1))
                text.style.color = "var(--a1)";
                toast.style.borderColor = "var(--a1)";
                toast.style.boxShadow = "0 0 25px var(--a1), 6px 6px 0 var(--ink-
c)";
            } else {
                // Standard: HOT PINK (var(--a4))
                text.style.color = "var(--a4)";
```

```
                toast.style.borderColor = "var(--a4)";
                toast.style.boxShadow = "0 0 20px var(--a4), 6px 6px 0 var(--ink-
c)";
            }

            toast.style.bottom = '40px';

            if(vibrate) toast.classList.add('vibrate-alert');

            setTimeout(() => {
                toast.style.bottom = '-100px';
                toast.classList.remove('vibrate-alert');
            }, 3000);
        }

        // --- 1B. WISHLIST AJAX & ANIMATION (Sarah's True Vision) ---
        async function toggleWishlist(event, cardId) {
            event.preventDefault();
            const btn = event.currentTarget;
            const wholeCard = btn.closest('.tcard'); // Selects the entire card
container
            const svg = btn.querySelector('svg');

            try {
                const response = await fetch('/wishlist/toggle', {
                    method: 'POST',
                    headers: { 'Content-Type': 'application/json', 'X-CSRF-TOKEN':
CSRF_TOKEN },
                    body: JSON.stringify({ card_id: cardId })
                });

                if (!response.ok) throw new Error('Unauthorized');
                const data = await response.json();

                if (data.status === 'added') {
                    // 1. Fill the Heart
                    btn.classList.add('active');
                    if(svg) {
                        svg.style.fill = 'currentColor';
                        svg.style.color = '#fff';
                    }

                    if(wholeCard) {
                        // 2. Add the permanent Pink Glow
                        wholeCard.classList.add('wishlisted');
                        // 3. SHAKE THE ENTIRE CARD (Like the video!)
                        wholeCard.classList.add('vibrate-alert');
                        // Stop shaking after 400ms
                        setTimeout(() => wholeCard.classList.remove('vibrate-
alert'), 400);
                    }

                    showNotification("> ARTIFACT_SAVED_TO_HEART", true, true);
                } else {
```

```
                    // Remove everything
                    btn.classList.remove('active');
                    if(svg) {
                        svg.style.fill = 'none';
                        svg.style.color = 'var(--chrome-c)';
                    }
                    if(wholeCard) {
                        wholeCard.classList.remove('wishlisted');
                        wholeCard.classList.remove('vibrate-alert');
                    }

                    showNotification("> REMOVED_FROM_ARCHIVE", false, false);
                }
            } catch (e) {
                showNotification("> ERROR: LOGIN REQUIRED", true, true);
            }
        }

        // --- 2. CHAT UI LOGIC ---
        function toggleChat() {
            var drawer = document.getElementById('chatDrawer');
            var fab = document.getElementById('chatFab');
            if (drawer.style.right === '0px') {
                drawer.style.right = '-400px';
                fab.style.display = 'flex';
            } else {
                drawer.style.right = '0px';
                fab.style.display = 'none';
                fetchMessages();
            }
        }

        // --- DYNAMIC CHAT TARGETING ---
        function openChatWith(sellerId, sellerName) {
            chatPartnerId = sellerId; // Global variable

            // Update UI
            document.querySelector('#chatDrawer h3').innerText = '> COMM: ' +
sellerName.toUpperCase();
            document.getElementById('chatMessages').innerHTML = '<div class="tag
cyan-on-dark" style="width: fit-content;"><span class="dot"></span><span
class="label">System: Encrypted channel active with ' + sellerName + '.</span>
</div>';

            // Open drawer
            document.getElementById('chatDrawer').style.right = '0px';
            const fab = document.getElementById('chatFab');
            if(fab) fab.style.display = 'none';
        }

        // --- 3. AJAX CHAT LOGIC ---
        async function sendMessage() {
            var input = document.getElementById('chatInput');
            var box = document.getElementById('chatMessages');
```

```
            var content = input.value.trim();

            if (content === "") return;

            // --- 1. VISUAL FEEDBACK (Sarah's UI logic) ---
            const msgDiv = document.createElement('div');
            msgDiv.className = 'tag';
            msgDiv.style.alignSelf = 'flex-end';
            msgDiv.style.borderColor = 'var(--a4)'; // Hot Pink/Magenta
            msgDiv.innerHTML = '<span class="label" style="color: var(--a4);">YOU:
' + content + '</span>';
            box.appendChild(msgDiv);

            input.value = ""; // Clear input
            box.scrollTop = box.scrollHeight; // Auto-scroll

            // --- 2. TRANSMISSION (The Bridge to Moataz) ---
            try {
                const response = await fetch('/chat/send', {
                    method: 'POST',
                    headers: {
                        'Content-Type': 'application/json',
                        'X-CSRF-TOKEN': CSRF_TOKEN
                    },
                    body: JSON.stringify({
                        receiver_id: chatPartnerId, // Default chat partner
                        content: content
                    })
                });

                if (!response.ok) {
                    console.warn("System: Backend not responding. Staying in
Local-Only mode.");
                }
            } catch (e) {
                console.error("Comm Satellite Offline. Message saved to local
cache only.");
            }
        }

        async function fetchMessages() {
            try {
                const response = await fetch('/chat/fetch/' + chatPartnerId);
                if (!response.ok) return; // Exit if Moataz's backend isn't ready

                const data = await response.json();
                const box = document.getElementById('chatMessages');

                data.forEach(msg => {
                    // THE TRICK: Check if this message ID is already on the
screen
                    const existingMessage = document.getElementById('msg-' +
msg.id);
```

```
                    if (!existingMessage) {
                        const msgDiv = document.createElement('div');
                        msgDiv.id = 'msg-' + msg.id; // Give it a unique ID
                        msgDiv.className = 'tag';

                        const isMe = msg.sender_id == AUTH_USER_ID;
                        msgDiv.style.alignSelf = isMe ? 'flex-end' : 'flex-start';
                        msgDiv.style.borderColor = isMe ? 'var(--a4)' : 'var(--
a5)';

                        msgDiv.innerHTML = '<span class="label" style="color: ' +
(isMe ? 'var(--a4)' : 'var(--a5)') + ';">' +
                                            (isMe ? 'YOU' : 'OPPONENT') + ': ' +
msg.content + '</span>';

                        box.appendChild(msgDiv);
                        box.scrollTop = box.scrollHeight;
                    }
                });
            } catch (error) {
                // Librarian is asleep, leave the chalkboard alone
            }
        }

        setInterval(fetchMessages, 4000);

        // --- DYNAMIC CHAT SYSTEM ---
        function openChatWith(sellerId, sellerName) {
            chatPartnerId = sellerId;
            document.querySelector('#chatDrawer h3').innerText = '> COMM: ' +
sellerName.toUpperCase();

            // Clear old messages and open drawer
            document.getElementById('chatMessages').innerHTML = '<div class="tag
cyan-on-dark" style="width: fit-content;"><span class="dot"></span><span
class="label">System: Encrypted channel active with ' + sellerName + '.</span>
</div>';

            document.getElementById('chatDrawer').style.right = '0px';
            document.getElementById('chatFab').style.display = 'none';
            fetchMessages(); // Instantly pull history
        }
    </script>

    @stack('scripts')
</body>
</html>
```

FILE: `resources/views\layouts\navigation.blade.php`

```
<nav x-data="{ open: false }" class="bg-white border-b border-gray-100">
    <!-- Primary Navigation Menu -->
    <div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
        <div class="flex justify-between h-16">
            <div class="flex">
                <!-- Logo -->
                <div class="shrink-0 flex items-center">
                    <a href="{{ route('dashboard') }}">
                        <x-application-logo class="block h-9 w-auto fill-current
text-gray-800" />
                    </a>
                </div>

                <!-- Navigation Links -->
                <nav class="nav-links">
                    <a href="{{ route('catalog') }}">&gt; CATALOG</a>
                    <a href="{{ route('cart.index') }}">&gt; MY CART</a>
                    <a href="{{ route('inventory.index') }}">&gt; MY BINDER</a>
                    <a href="{{ route('decks.index') }}">&gt; MY DECKS</a>
                    <a href="{{ route('dashboard') }}">&gt; DASHBOARD</a>
                </nav>
                </div>
            </div>

            <!-- Settings Dropdown -->
            <div class="hidden sm:flex sm:items-center sm:ms-6">
                <x-dropdown align="right" width="48">
                    <x-slot name="trigger">
                        <button class="inline-flex items-center px-3 py-2 border
border-transparent text-sm leading-4 font-medium rounded-md text-gray-500 bg-white
hover:text-gray-700 focus:outline-none transition ease-in-out duration-150">
                            <div>{{ Auth::user()->name }}</div>

                            <div class="ms-1">
                                <svg class="fill-current h-4 w-4"
xmlns="http://www.w3.org/2000/svg" viewBox="0 0 20 20">
                                    <path fill-rule="evenodd" d="M5.293 7.293a1 1
0 011.414 0L10 10.586l3.293-3.293a1 1 0 111.414 1.414l-4 4a1 1 0 01-1.414 0l-4-4a1
1 0 010-1.414z" clip-rule="evenodd" />
                                </svg>
                            </div>
                        </button>
                    </x-slot>

                    <x-slot name="content">
                        <x-dropdown-link :href="route('profile.edit')">
                            {{ __('Profile') }}
                        </x-dropdown-link>

                        <!-- Authentication -->
                        <form method="POST" action="{{ route('logout') }}">
                            @csrf
```

```
                            <x-dropdown-link :href="route('logout')"
                                    onclick="event.preventDefault();
                                                this.closest('form').submit();">
                                {{ __('Log Out') }}
                            </x-dropdown-link>
                        </form>
                    </x-slot>
                </x-dropdown>
            </div>

            <!-- Hamburger -->
            <div class="-me-2 flex items-center sm:hidden">
                <button @click="open = ! open" class="inline-flex items-center
justify-center p-2 rounded-md text-gray-400 hover:text-gray-500 hover:bg-gray-100
focus:outline-none focus:bg-gray-100 focus:text-gray-500 transition duration-150
ease-in-out">
                    <svg class="h-6 w-6" stroke="currentColor" fill="none"
viewBox="0 0 24 24">
                        <path :class="{'hidden': open, 'inline-flex': ! open }"
class="inline-flex" stroke-linecap="round" stroke-linejoin="round" stroke-
width="2" d="M4 6h16M4 12h16M4 18h16" />
                        <path :class="{'hidden': ! open, 'inline-flex': open }"
class="hidden" stroke-linecap="round" stroke-linejoin="round" stroke-width="2"
d="M6 18L18 6M6 6l12 12" />
                    </svg>
                </button>
            </div>
        </div>
    </div>

    <!-- Responsive Navigation Menu -->
    <div :class="{'block': open, 'hidden': ! open}" class="hidden sm:hidden">
        <div class="pt-2 pb-3 space-y-1">
            <x-responsive-nav-link :href="route('dashboard')" :active="request()-
>routeIs('dashboard')">
                {{ __('Dashboard') }}
            </x-responsive-nav-link>
        </div>

        <!-- Responsive Settings Options -->
        <div class="pt-4 pb-1 border-t border-gray-200">
            <div class="px-4">
                <div class="font-medium text-base text-gray-800">{{ Auth::user()-
>name }}</div>
                <div class="font-medium text-sm text-gray-500">{{ Auth::user()-
>email }}</div>
            </div>

            <div class="mt-3 space-y-1">
                <x-responsive-nav-link :href="route('profile.edit')">
                    {{ __('Profile') }}
                </x-responsive-nav-link>
```

```
                <!-- Authentication -->
                <form method="POST" action="{{ route('logout') }}">
                    @csrf

                    <x-responsive-nav-link :href="route('logout')"
                            onclick="event.preventDefault();
                                        this.closest('form').submit();">
                        {{ __('Log Out') }}
                    </x-responsive-nav-link>
                </form>
            </div>
        </div>
    </div>
</nav>
```

FILE: resources/views\orders\index.blade.php

```
@extends('layouts.master')

@section('content')
<section class="section">
    <div class="container-tight">
        <h2 class="h2 text-stack-sm">Order <span class="accent-c">History.</span>
</h2>

        @if(session('success'))
            <div class="tag cyan-on-dark" style="margin-bottom:20px; width:100%;
text-align:center;">{{ session('success') }}</div>
        @endif

        @forelse($orders as $order)
            <div class="tcard" style="margin-bottom: 24px; padding: 24px;">
                <div style="display: flex; justify-content: space-between; align-
items: center;">
                    <div>
                        <h3 style="font-size: 1.2rem;">Order #{{ $order->uuid }}
</h3>
                        <p style="font-family:'Share Tech Mono'; opacity:
0.7;">Date: {{ $order->created_at->format('Y-m-d') }}</p>
                    </div>
                    <div class="tag {{ $order->status == 'Validée' ? 'yellow' :
($order->status == 'Annulée' ? 'red' : 'cyan-on-dark') }}">
                        <span class="label">{{ $order->status }}</span>
                    </div>
                </div>

                <div style="margin-top: 20px; border-top: 2px solid var(--ink-c);
padding-top: 15px;">
                    @foreach($order->items as $item)
                        <div style="display: flex; justify-content: space-between;
```

```
margin-bottom: 8px; font-family: 'Share Tech Mono';">
                            <span>{{ $item->listing->card->name }} (x{{ $item-
>quantity }})</span>
                            <span>{{ $item->price_locked }} DT</span>
                        </div>
                    @endforeach
                    <div style="margin-top: 15px; font-weight: bold; font-family:
'Orbitron'; border-top: 1px solid var(--ink-c); padding-top: 10px;">
                        TOTAL: {{ $order->total_price }} DT
                    </div>
                </div>
            </div>
        @empty
            <div class="tcard" style="padding: 40px; text-align: center;">
                <p>&gt; NO ORDERS FOUND. THE VAULT IS SILENT.</p>
            </div>
        @endforelse
    </div>
</section>
@endsection
```

FILE: resources/views\profile\edit.blade.php

```
@extends('layouts.master')

@section('content')
<div class="container-narrow" style="padding-top: 60px; padding-bottom: 60px;
text-align: center;">

    <div style="margin-bottom: 40px; display: inline-block; text-align: left;">
        <span class="tag cyan-on-dark" style="margin-bottom: 15px;"><span
class="label">&gt; SECURE_CONNECTION</span></span>
        <h2 class="h2 text-stack-sm" style="font-size: 3rem;">DATA <span
class="accent-m">FORGE</span></h2>
    </div>

    <div style="display: flex; flex-direction: column; gap: 40px; align-items:
center;">

        <!-- PROFILE INFORMATION FORM -->
        <div class="tcard shadow-brick-cyan">
            <div class="titlebar">
                <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                <span class="ttl">&gt; update_profile.exe</span>
            </div>
            <div class="corner square bgc-5"></div>
            <div class="body" style="padding: 30px; background: var(--ink-c);">
                <!-- We include the default Breeze form, but force text to be
white/neon inside it -->
                <div style="color: var(--chrome-c);">
```

```
                    @include('profile.partials.update-profile-information-form')
                </div>
            </div>
        </div>

        <!-- PASSWORD UPDATE FORM -->
        <div class="tcard shadow-brick-magenta">
            <div class="titlebar">
                <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                <span class="ttl">&gt; change_cipher.sys</span>
            </div>
            <div class="corner circle bgc-4"></div>
            <div class="body" style="padding: 30px; background: var(--ink-c);">
                <div style="color: var(--chrome-c);">
                    @include('profile.partials.update-password-form')
                </div>
            </div>
        </div>

        <!-- DELETE ACCOUNT FORM -->
        <div class="tcard shadow-brick-red">
            <div class="titlebar">
                <span class="dots"><span class="d1"></span><span class="d2">
</span><span class="d3"></span></span>
                <span class="ttl">&gt; self_destruct.bin</span>
            </div>
            <div class="corner tri bgc-1"></div>
            <div class="body" style="padding: 30px; background: var(--ink-c);">
                <div style="color: var(--chrome-c);">
                    @include('profile.partials.delete-user-form')
                </div>
            </div>
        </div>

    </div>
</div>
@endsection
```

FILE: resources/views\profile\partials\delete-user-form.blade.php

```
<section class="space-y-6" style="text-align: center;">
    <header>
        <h2 class="text-lg font-medium" style="color: var(--a1); font-size:
1.5rem; font-family: 'Orbitron', sans-serif;">
            {{ __('Delete Account') }}
        </h2>
        <p class="mt-1 text-sm" style="color: var(--chrome-c); font-family: 'Share
Tech Mono', monospace; font-size: 1rem; margin-bottom: 20px;">
            {{ __('Once your account is deleted, all of its resources and data
```

```
will be permanently deleted.') }}
        </p>
    </header>

    <div style="display: flex; justify-content: center;">
    <button class="btn outline sm" style="border-color: var(--a1); color: var(--
a1);"
        x-data=""
        x-on:click.prevent="$dispatch('open-modal', 'confirm-user-deletion')">
        <span class="inner">{{ __('INITIATE SELF DESTRUCT') }}</span>
    </button>

    </div>

    <x-modal name="confirm-user-deletion" :show="$errors->userDeletion-
>isNotEmpty()" focusable>
        <form method="post" action="{{ route('profile.destroy') }}"
style="padding: 30px; background: var(--bg); border: 4px solid var(--a1); box-
shadow: 0 0 30px rgba(255,0,0,0.5); text-align: center;">
            @csrf
            @method('delete')

            <h2 class="text-lg font-medium" style="color: var(--a1); font-size:
1.5rem; font-family: 'Orbitron', sans-serif;">
                {{ __('Are you sure you want to delete your account?') }}
            </h2>

            <p class="mt-1 text-sm" style="color: var(--chrome-c); font-family:
'Share Tech Mono', monospace; font-size: 1rem; margin-bottom: 20px; margin-top:
10px;">
                {{ __('Please enter your password to confirm you would like to
permanently delete your account.') }}
            </p>

            <div style="margin-top: 20px; display: flex; justify-content:
center;">
                <x-input-label for="password" value="{{ __('Password') }}"
class="sr-only" />

                <x-text-input
                    id="password"
                    name="password"
                    type="password"
                    style="max-width: 400px; width: 100%; padding: 12px;
background: var(--ink-c); color: var(--chrome-c); border: 2px solid var(--a1);
font-family: 'Share Tech Mono', monospace; font-size: 1.1rem;"
                    placeholder="{{ __('Password') }}"
                />

                <x-input-error :messages="$errors->userDeletion->get('password')"
style="color: var(--a1); margin-top: 10px;" />
            </div>

            <div style="margin-top: 25px; display: flex; justify-content: flex-
```

```
end; gap: 15px;">
                <button type="button" class="btn outline sm" x-
on:click="$dispatch('close')">
                    <span class="inner">{{ __('CANCEL') }}</span>
                </button>

                <button type="submit" class="btn red sm">
                    <span class="inner">{{ __('CONFIRM DELETION') }}</span>
                </button>
            </div>
        </form>
    </x-modal>
</section>
```

FILE: resources/views\profile\partials\update-password-form.blade.php

```
<style>
    .neon-input-magenta {
        width: 100%;
        max-width: 500px;
        padding: 14px 18px;
        background: rgba(0, 0, 0, 0.4);
        border: 2px solid hsl(var(--accent-4) / 0.5);
        color: var(--chrome-c);
        font-family: 'Share Tech Mono', monospace;
        font-size: 1.1rem;
        outline: none;
        transition: all 0.2s ease-in-out;
    }
    .neon-input-magenta:focus {
        border-color: var(--a4);
        box-shadow: 0 0 15px hsl(var(--accent-4) / 0.4);
        background: rgba(0, 0, 0, 0.8);
        transform: translateX(5px);
    }
</style>

<section style="text-align: center;">
    <header style="margin-bottom: 30px;">
        <h2 style="color: var(--chrome-c); font-size: 1.6rem; font-family:
'Orbitron', sans-serif; text-transform: uppercase;">
            {{ __('Update Password') }}
        </h2>
        <p style="color: var(--a4); font-family: 'Share Tech Mono', monospace;
font-size: 0.95rem; margin-top: 5px;">
            &gt; Ensure your account is using a long, random cipher to stay
secure.
        </p>
    </header>
```

```
    <form method="post" action="{{ route('password.update') }}" style="display:
flex; flex-direction: column; align-items: center; gap: 25px;">
        @csrf
        @method('put')

        <div>
            <label for="update_password_current_password" class="form-label">&gt;
CURRENT CIPHER</label>
            <input id="update_password_current_password" name="current_password"
type="password" class="neon-input-magenta" autocomplete="current-password" />
            <x-input-error :messages="$errors->updatePassword-
>get('current_password')" style="color: var(--a1);" />
        </div>

        <div>
            <label for="update_password_password" class="form-label">&gt; NEW
CIPHER</label>
            <input id="update_password_password" name="password" type="password"
class="neon-input-magenta" autocomplete="new-password" />
            <x-input-error :messages="$errors->updatePassword->get('password')"
style="color: var(--a1);" />
        </div>

        <div>
            <label for="update_password_password_confirmation" class="form-
label">&gt; CONFIRM NEW CIPHER</label>
            <input id="update_password_password_confirmation"
name="password_confirmation" type="password" class="neon-input-magenta"
autocomplete="new-password" />
            <x-input-error :messages="$errors->updatePassword-
>get('password_confirmation')" style="color: var(--a1);" />
        </div>

        <div style="display: flex; align-items: center; justify-content: center;
gap: 20px; margin-top: 10px;">
            <button class="btn magenta md"><span class="inner">{{ __('UPDATE
CIPHER') }}</span></button>

            @if (session('status') === 'password-updated')
                <p x-data="{ show: true }" x-show="show" x-transition x-
init="setTimeout(() => show = false, 2000)"
                   style="color: var(--a4); font-family: 'Share Tech Mono',
monospace; font-size: 1rem; margin: 0; text-shadow: 0 0 8px var(--a4);">
                    &gt; CIPHER SECURED.
                </p>
            @endif
        </div>
    </form>
</section>
```

FILE: resources/views\profile\partials\update-profile-information-form.blade.php

```
<style>
    .neon-input-cyan {
        width: 100%;
        max-width: 500px; /* Ergonomic constraint */
        padding: 14px 18px;
        background: rgba(0, 0, 0, 0.4);
        border: 2px solid hsl(var(--accent-5) / 0.5);
        color: var(--chrome-c);
        font-family: 'Share Tech Mono', monospace;
        font-size: 1.1rem;
        outline: none;
        transition: all 0.2s ease-in-out;
    }
    .neon-input-cyan:focus {
        border-color: var(--a5);
        box-shadow: 0 0 15px hsl(var(--accent-5) / 0.4);
        background: rgba(0, 0, 0, 0.8);
        transform: translateX(5px); /* Cyberpunk sliding effect */
    }
    .form-label {
        display: block; color: var(--chrome-c); font-family: 'Share Tech Mono',
monospace;
        font-size: 1rem; text-transform: uppercase; margin-bottom: 8px; opacity:
0.85;
    }
</style>

<section style="text-align: center;">
    <header style="margin-bottom: 30px;">
        <h2 style="color: var(--chrome-c); font-size: 1.6rem; font-family:
'Orbitron', sans-serif; text-transform: uppercase;">
            {{ __('Profile Information') }}
        </h2>
        <p style="color: var(--a5); font-family: 'Share Tech Mono', monospace;
font-size: 0.95rem; margin-top: 5px;">
            &gt; Update your account's profile information and email address.
        </p>
    </header>

    <form id="send-verification" method="post" action="{{
route('verification.send') }}">
        @csrf
    </form>

    <form method="post" action="{{ route('profile.update') }}" style="display:
flex; flex-direction: column; align-items: center; gap: 25px;">
        @csrf
        @method('patch')

        <div>
            <label for="name" class="form-label">&gt; CALLSIGN (Name)</label>
            <input id="name" name="name" type="text" class="neon-input-cyan"
```

```
value="{{ old('name', $user->name) }}" required autofocus autocomplete="name" />
            <x-input-error class="mt-2" :messages="$errors->get('name')"
style="color: var(--a1);" />
        </div>

        <div>
            <label for="email" class="form-label">&gt; NETWORK_ID (Email)</label>
            <input id="email" name="email" type="email" class="neon-input-cyan"
value="{{ old('email', $user->email) }}" required autocomplete="username" />
            <x-input-error class="mt-2" :messages="$errors->get('email')"
style="color: var(--a1);" />
        </div>

        <div style="display: flex; align-items: center; justify-content: center;
gap: 20px; margin-top: 10px;">
            <button class="btn cyan md"><span class="inner">{{ __('SAVE DATA') }}
</span></button>

            @if (session('status') === 'profile-updated')
                <p x-data="{ show: true }" x-show="show" x-transition x-
init="setTimeout(() => show = false, 2000)"
                   style="color: var(--a5); font-family: 'Share Tech Mono',
monospace; font-size: 1rem; margin: 0; text-shadow: 0 0 8px var(--a5);">
                    &gt; SAVED SUCCESSFULLY.
                </p>
            @endif
        </div>
    </form>
</section>
```

FILE: `routes\auth.php`

```
<?php

use App\Http\Controllers\Auth\AuthenticatedSessionController;
use App\Http\Controllers\Auth\ConfirmablePasswordController;
use App\Http\Controllers\Auth\EmailVerificationNotificationController;
use App\Http\Controllers\Auth\EmailVerificationPromptController;
use App\Http\Controllers\Auth\NewPasswordController;
use App\Http\Controllers\Auth\PasswordController;
use App\Http\Controllers\Auth\PasswordResetLinkController;
use App\Http\Controllers\Auth\RegisteredUserController;
use App\Http\Controllers\Auth\VerifyEmailController;
use Illuminate\Support\Facades\Route;

Route::middleware('guest')->group(function () {
    Route::get('register', [RegisteredUserController::class, 'create'])
        ->name('register');

    Route::post('register', [RegisteredUserController::class, 'store']);
```

```
    Route::get('login', [AuthenticatedSessionController::class, 'create'])
        ->name('login');

    Route::post('login', [AuthenticatedSessionController::class, 'store']);

    Route::get('forgot-password', [PasswordResetLinkController::class, 'create'])
        ->name('password.request');

    Route::post('forgot-password', [PasswordResetLinkController::class, 'store'])
        ->name('password.email');

    Route::get('reset-password/{token}', [NewPasswordController::class, 'create'])
        ->name('password.reset');

    Route::post('reset-password', [NewPasswordController::class, 'store'])
        ->name('password.store');
});

Route::middleware('auth')->group(function () {
    Route::get('verify-email', EmailVerificationPromptController::class)
        ->name('verification.notice');

    Route::get('verify-email/{id}/{hash}', VerifyEmailController::class)
        ->middleware(['signed', 'throttle:6,1'])
        ->name('verification.verify');

    Route::post('email/verification-notification',
[EmailVerificationNotificationController::class, 'store'])
        ->middleware('throttle:6,1')
        ->name('verification.send');

    Route::get('confirm-password', [ConfirmablePasswordController::class, 'show'])
        ->name('password.confirm');

    Route::post('confirm-password', [ConfirmablePasswordController::class,
'store']);

    Route::put('password', [PasswordController::class, 'update'])-
>name('password.update');

    Route::post('logout', [AuthenticatedSessionController::class, 'destroy'])
        ->name('logout');
});
```

FILE: routes\console.php

```
<?php

use Illuminate\Foundation\Inspiring;
use Illuminate\Support\Facades\Artisan;
```

```
Artisan::command('inspire', function () {
    $this->comment(Inspiring::quote());
})->purpose('Display an inspiring quote');
```

FILE: routes\web.php

```
<?php

use App\Http\Controllers\ProfileController;
use Illuminate\Support\Facades\Route;
use App\Http\Controllers\ListingController;
use App\Http\Controllers\CartController;
use App\Http\Controllers\OrderController;
use App\Http\Controllers\ReviewController;
use App\Http\Controllers\ChatController;
use App\Http\Controllers\NexusController;
use App\Http\Controllers\CatalogController;
use App\Http\Controllers\WishlistController;
use App\Http\Controllers\DeckController;

/*
|--------------------------------------------------------------------------
| Public Routes (Anyone can visit these)
|--------------------------------------------------------------------------
*/
Route::get('/', function () {
    return view('welcome');
});

// [SARAH DOMAIN: PUBLIC CATALOG & CARDS]
Route::get('/catalog', [CatalogController::class, 'index'])->name('catalog');
Route::get('/catalog/{card}', [CatalogController::class, 'show'])-
>name('cards.show');


/*
|--------------------------------------------------------------------------
| Authenticated Routes (Must be logged in to visit these)
|--------------------------------------------------------------------------
*/
Route::middleware('auth')->group(function () {

    // [RITEJ DOMAIN: PROFILE MANAGEMENT]
    Route::get('/dashboard', function () {
        return view('dashboard');
    })->name('dashboard');

    Route::get('/profile', [ProfileController::class, 'edit'])-
>name('profile.edit');
```

```
    Route::patch('/profile', [ProfileController::class, 'update'])-
>name('profile.update');
    Route::delete('/profile', [ProfileController::class, 'destroy'])-
>name('profile.destroy');

    // [SARAH DOMAIN: WISHLIST]
    Route::get('/favorites', [WishlistController::class, 'index'])-
>name('wishlist.index');
    Route::post('/wishlist/toggle', [WishlistController::class, 'toggle'])-
>name('wishlist.toggle');

    // [MOATAZ DOMAIN: INVENTORY]
    Route::get('/my-inventory', [ListingController::class, 'index'])-
>name('inventory.index');
    Route::post('/inventory/add', [ListingController::class, 'store'])-
>name('inventory.store');
    Route::delete('/inventory/{listing}', [ListingController::class, 'destroy'])-
>name('inventory.destroy');

    // [MOATAZ DOMAIN: CART]
    Route::get('/cart', [CartController::class, 'index'])->name('cart.index');
    Route::post('/cart/add', [CartController::class, 'add'])->name('cart.add');
    Route::patch('/cart/update', [CartController::class, 'update'])-
>name('cart.update');
    Route::delete('/cart/remove', [CartController::class, 'remove'])-
>name('cart.remove');

    // [MOATAZ DOMAIN: CHECKOUT & ORDERS]
    Route::post('/checkout', [OrderController::class, 'checkout'])-
>name('checkout.process');
    Route::get('/my-orders', [OrderController::class, 'index'])-
>name('orders.index');
    Route::patch('/order/{order}/status', [OrderController::class,
'updateStatus'])->name('orders.updateStatus');

    // [MOATAZ DOMAIN: REVIEWS]
    Route::post('/review/store', [ReviewController::class, 'store'])-
>name('reviews.store');

    // [MOATAZ & SARAH DOMAIN: AJAX CHAT API]
    Route::post('/chat/send', [ChatController::class, 'sendMessage'])-
>name('chat.send');
    Route::get('/chat/fetch/{receiver_id}', [ChatController::class,
'fetchMessages'])->name('chat.fetch');

    // [MOATAZ DOMAIN: DECK BUILDER]
    Route::get('/decks', [DeckController::class, 'index'])->name('decks.index');
    Route::post('/deck/create', [DeckController::class, 'store'])-
>name('deck.store');
    Route::get('/deck/{id}/builder', [DeckController::class, 'builder'])-
>name('deck.builder');
    Route::post('/deck/{id}/add', [DeckController::class, 'addCard'])-
>name('deck.addCard');
    Route::delete('/deck/{deckId}/remove/{cardId}', [DeckController::class,
```

```
'removeCard'])->name('deck.removeCard');
    Route::post('/deck/{id}/preview', [DeckController::class, 'setPreview'])-
>name('deck.setPreview');
    Route::get('/deck/{id}/export',[\App\Http\Controllers\DeckController::class,
'exportYdk'])->name('deck.export');
    Route::post('/deck/{id}/import',[\App\Http\Controllers\DeckController::class,
'importYdk'])->name('deck.import');

    // [TECH LEAD DOMAIN: THE NEXUS]
    Route::post('/nexus/upload', [NexusController::class, 'uploadYdk'])-
>name('nexus.upload');
});


/*
|--------------------------------------------------------------------------
| [RITEJ DOMAIN] Admin Secure Routes (Must be logged in AND be an Admin)
|--------------------------------------------------------------------------
*/
Route::middleware(['auth', \App\Http\Middleware\RoleMiddleware::class .
':admin'])->group(function () {
    Route::get('/admin/dashboard', function () {
        return view('admin.dashboard');
    })->name('admin.dashboard');
});

/*
|--------------------------------------------------------------------------
| Laravel Breeze Default Auth Routes (Login, Register, Password Reset)
|--------------------------------------------------------------------------
*/
require __DIR__.'/auth.php';
```

FILE: public/css\neon.css

```
/* ============================================================
   NEON BAUHAUS DOPAMINE — single-file vanilla build
   No Tailwind. No JS deps. Pure CSS + tiny inline JS.
   ============================================================ */

:root{
  --background: 260 80% 4%;
  --foreground: 0 0% 96%;
  --card: 260 60% 10%;
  --ink: 0 0% 4%;
  --chrome: 0 0% 96%;
  --accent-1: 350 95% 55%;   /* red */
  --accent-2: 220 100% 55%;  /* blue */
  --accent-3: 48 100% 55%;   /* yellow */
  --accent-4: 300 100% 55%;  /* magenta */
```

```
  --accent-5: 180 100% 55%;  /* cyan */

  --bg: hsl(var(--background));
  --fg: hsl(var(--foreground));
  --ink-c: hsl(var(--ink));
  --chrome-c: hsl(var(--chrome));
  --card-c: hsl(var(--card));
  --a1: hsl(var(--accent-1));
  --a2: hsl(var(--accent-2));
  --a3: hsl(var(--accent-3));
  --a4: hsl(var(--accent-4));
  --a5: hsl(var(--accent-5));
}

*,*::before,*::after{box-sizing:border-box;margin:0;padding:0;border:0 solid var(-
-ink-c)}
html{scroll-behavior:smooth;-webkit-text-size-adjust:100%}
body{
  background:var(--bg);
  color:var(--fg);
  font-family:'Outfit',system-ui,-apple-system,Segoe UI,Roboto,sans-serif;
  font-weight:500;
  line-height:1.5;
  overflow-x:hidden;
  min-height:100vh;
}
img,svg{display:block;max-width:100%}
button{font:inherit;color:inherit;background:none;cursor:pointer}
a{color:inherit;text-decoration:none}
ul,ol{list-style:none}
h1,h2,h3,h4,h5,h6{font-family:'Outfit',sans-serif;font-weight:900;line-height:1.1}

.font-display{font-family:'Orbitron',sans-serif}
.font-mono,.mono{font-family:'Share Tech Mono','SFMono-Regular',Menlo,monospace}

/* ===== Signature shadow: stacked neon brick ===== */
.shadow-brick         { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a3),
0 0 40px hsl(var(--accent-4)/.5);}
.shadow-brick-cyan    { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a5),
0 0 40px hsl(var(--accent-5)/.5);}
.shadow-brick-magenta { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a4),
0 0 40px hsl(var(--accent-4)/.5);}
.shadow-brick-red     { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a1),
0 0 40px hsl(var(--accent-1)/.5);}
.shadow-brick-yellow  { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a3),
0 0 40px hsl(var(--accent-3)/.6);}
.shadow-brick-blue    { box-shadow: 6px 6px 0 var(--ink-c), 12px 12px 0 var(--a2),
0 0 40px hsl(var(--accent-2)/.5);}
.shadow-brick-sm      { box-shadow: 4px 4px 0 var(--ink-c), 0 0 20px hsl(var(--
accent-4)/.4);}

.text-stack    { text-shadow: 3px 3px 0 var(--ink-c), 6px 6px 0 var(--a4), 9px 9px
0 var(--a5);}
.text-stack-sm { text-shadow: 2px 2px 0 var(--ink-c), 4px 4px 0 var(--a4);}
```

```
.text-glow-cyan{ text-shadow: 0 0 10px hsl(var(--accent-5)/.9);}

.text-gradient{
  background:linear-gradient(90deg,var(--a3),var(--a1),var(--a4),var(--a5),var(--
a3));
  background-size:300% 100%;
  -webkit-background-clip:text;background-clip:text;
  -webkit-text-fill-color:transparent;color:transparent;
  animation:gradient-shift 6s ease infinite;
}

/* ===== Patterns ===== */
.pattern-dots        { background-image: radial-gradient(hsl(var(--accent-4)/.35)
1.5px, transparent 1.5px); background-size:22px 22px;}
.pattern-dots-cyan   { background-image: radial-gradient(hsl(var(--accent-5)/.35)
1.5px, transparent 1.5px); background-size:22px 22px;}
.pattern-stripes     { background-image: repeating-linear-gradient(45deg,
transparent, transparent 12px, hsl(var(--ink)/.4) 12px, hsl(var(--ink)/.4) 14px);}
.pattern-stripes-light { background-image: repeating-linear-gradient(45deg,
transparent, transparent 12px, hsl(0 0% 100%/.18) 12px, hsl(0 0% 100%/.18) 14px);}
.pattern-grid-floor{
  background-image:
    linear-gradient(hsl(var(--accent-4)/.6) 1px, transparent 1px),
    linear-gradient(90deg, hsl(var(--accent-4)/.6) 1px, transparent 1px);
  background-size:50px 50px;
  transform: perspective(600px) rotateX(60deg) translateY(-50px) scale(2.4);
  transform-origin: top center;
  -webkit-mask-image: linear-gradient(to bottom, var(--bg) 10%, transparent 90%);
          mask-image: linear-gradient(to bottom, var(--bg) 10%, transparent 90%);
}

/* CRT scanlines + chromatic aberration */
.scanlines::before{
  content:"";position:fixed;inset:0;pointer-events:none;z-index:50;
  background: linear-gradient(hsl(0 0% 0% / 0) 50%, hsl(0 0% 0% / .18) 50%);
  background-size:100% 4px;
}
.scanlines::after{
  content:"";position:fixed;inset:0;pointer-events:none;z-index:50;
  background: linear-gradient(90deg, hsl(0 100% 50% / .04), hsl(120 100% 50% /
.02), hsl(240 100% 50% / .04));
  mix-blend-mode:screen;
}

.clip-tri{clip-path:polygon(50% 0%, 0% 100%, 100% 100%)}

/* ===== Keyframes ===== */
@keyframes float       { 0%,100%{transform:translateY(0) rotate(0)} 50%
{transform:translateY(-20px) rotate(8deg)} }
@keyframes float-rev   { 0%,100%{transform:translateY(0) rotate(0)} 50%
{transform:translateY(20px) rotate(-8deg)} }
@keyframes spin-slow   { to{ transform: rotate(360deg)} }
@keyframes wiggle      { 0%,100%{transform:rotate(-4deg)} 50%
{transform:rotate(4deg)} }
```

```
@keyframes pulse-glow  {
  0%,100% { box-shadow: 0 0 20px hsl(var(--accent-4)/.5), 0 0 40px hsl(var(--
accent-5)/.3);}
  50%     { box-shadow: 0 0 40px hsl(var(--accent-4)/.9), 0 0 80px hsl(var(--
accent-5)/.6);}
}
@keyframes gradient-shift { 0%{background-position:0% 50%} 50%{background-
position:100% 50%} 100%{background-position:0% 50%} }
@keyframes blink { 50%{opacity:0} }

.anim-float     {animation:float 6s ease-in-out infinite}
.anim-float-rev {animation:float-rev 5s ease-in-out infinite}
.anim-spin-slow {animation:spin-slow 20s linear infinite}
.anim-wiggle    {animation:wiggle 1.4s ease-in-out infinite}
.anim-pulse-glow{animation:pulse-glow 2.4s ease-in-out infinite}
.anim-blink     {animation:blink 1s steps(1) infinite;display:inline-block}

@media (prefers-reduced-motion: reduce){
  [class^="anim-"], .text-gradient { animation:none !important; }
}

/* ===== Layout primitives ===== */
.container{max-width:1280px;margin:0 auto;padding:0 24px}
.container-narrow{max-width:960px;margin:0 auto;padding:0 24px}
.container-tight{max-width:768px;margin:0 auto;padding:0 24px}

.section{position:relative;padding:96px 0;border-bottom:4px solid var(--ink-
c);overflow:hidden}
.section-border-only{position:relative;border-bottom:4px solid var(--ink-c)}
@media(min-width:768px){.section{padding:128px 0}}

/* ===== Atmosphere ===== */
.atmosphere{position:fixed;inset:0;z-index:0;overflow:hidden;pointer-events:none}
.atmo-sun{
  position:absolute;left:50%;top:35%;transform:translateX(-50%);
  width:600px;height:600px;border-radius:9999px;opacity:.3;filter:blur(100px);
  background:linear-gradient(to bottom, var(--a3), var(--a4));
}
.atmo-grid{position:absolute;left:0;right:0;bottom:0;height:70vh}
.atmo-dots{position:absolute;inset:0;opacity:.3}

.page{position:relative;z-index:10}

/* ===== NAV ===== */
.nav{
  position:fixed;top:0;left:0;right:0;z-index:40;
  background:hsl(var(--background)/.8);
  backdrop-filter:blur(12px);-webkit-backdrop-filter:blur(12px);
  border-bottom:4px solid var(--ink-c);
}
.nav-inner{max-width:1280px;margin:0 auto;padding:16px 24px;display:flex;align-
items:center;justify-content:space-between;gap:16px}
.logo{display:inline-flex;align-items:center;gap:12px}
.logo-shapes{display:inline-flex;gap:4px}
```

```
.logo-shapes>span{width:24px;height:24px;border:2px solid var(--ink-
c);transition:transform .2s}
.logo-shapes>.s1{background:var(--a1);border-radius:9999px}
.logo-shapes>.s2{background:var(--a3)}
.logo-shapes>.s3{background:var(--a5);border:0;clip-path:polygon(50% 0%, 0% 100%,
100% 100%)}
.logo:hover .s1{transform:translateY(-4px)}
.logo:hover .s2{transform:translateY(4px)}
.logo:hover .s3{transform:rotate(45deg)}
.logo-text{font-family:'Orbitron',sans-serif;font-size:20px;font-
weight:900;letter-spacing:.2em;color:var(--chrome-c)}
.logo-text b{color:var(--a4);font-weight:900}

.nav-links{display:none;gap:32px;align-items:center}
@media(min-width:900px){.nav-links{display:inline-flex}}
.nav-links a{font-family:'Share Tech Mono',monospace;font-size:14px;text-
transform:uppercase;letter-spacing:.2em;color:var(--chrome-c);transition:color
.2s,text-shadow .2s}
.nav-links a:hover{color:var(--a5);text-shadow:0 0 10px hsl(var(--accent-5)/.9)}
.nav-cta-desktop{display:none}
@media(min-width:900px){.nav-cta-desktop{display:inline-block}}

.nav-burger{display:inline-grid;place-
items:center;width:40px;height:40px;border:2px solid var(--ink-c);background:var(-
-a3);color:var(--ink-c)}
@media(min-width:900px){.nav-burger{display:none}}
.mobile-menu{display:none;border-top:4px solid var(--ink-c);background:var(--
bg);padding:24px;flex-direction:column;gap:16px}
.mobile-menu.open{display:flex}
.mobile-menu a{font-family:'Share Tech Mono',monospace;text-
transform:uppercase;letter-spacing:.2em;color:var(--chrome-c)}

/* ===== NBD Button ===== */
.btn{
  display:inline-flex;align-items:center;justify-content:center;gap:8px;
  transform:skewX(-12deg);
  border:4px solid var(--ink-c);
  font-family:'Share Tech Mono',monospace;
  text-transform:uppercase;letter-spacing:.2em;font-weight:700;
  transition:transform .2s ease-out, box-shadow .2s ease-out;
  user-select:none;border-radius:0;
}
.btn:hover{transform:skewX(0) scale(1.04)}
.btn:active{transform:translate(2px,2px) skewX(-12deg)}
.btn:focus-visible{outline:none;box-shadow:0 0 0 4px var(--ink-c), 0 0 0 8px var(-
-a5)}
.btn .inner{display:inline-flex;align-items:center;gap:8px;transform:skewX(12deg)}
.btn.sm{height:40px;padding:0 20px;font-size:12px}
.btn.md{height:48px;padding:0 28px;font-size:14px}
.btn.lg{height:64px;padding:0 40px;font-size:16px}
.btn.full{width:100%}
.btn.magenta{background:var(--a4);color:#fff;box-shadow:6px 6px 0 var(--ink-c),
12px 12px 0 var(--a4), 0 0 40px hsl(var(--accent-4)/.5)}
.btn.cyan   {background:var(--a5);color:var(--ink-c);box-shadow:6px 6px 0 var(--
```

```
ink-c), 12px 12px 0 var(--a5), 0 0 40px hsl(var(--accent-5)/.5)}
.btn.yellow {background:var(--a3);color:var(--ink-c);box-shadow:6px 6px 0 var(--
ink-c), 12px 12px 0 var(--a3), 0 0 40px hsl(var(--accent-3)/.6)}
.btn.outline{background:var(--bg);color:var(--chrome-c);box-shadow:6px 6px 0 var(-
-ink-c), 12px 12px 0 var(--a3), 0 0 40px hsl(var(--accent-4)/.5)}

/* ===== Tag chip (skewed) ===== */
.tag{
  display:inline-flex;align-items:center;gap:8px;
  padding:6px 12px;border:2px solid var(--a5);
  background:hsl(var(--background)/.6);transform:skewX(-12deg);
}
.tag>*{transform:skewX(12deg);display:inline-block}
.tag .dot{width:8px;height:8px;border-radius:9999px;background:var(--a5)}
.tag .label{font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:var(--a5)}
.tag.yellow{border-color:var(--a3)}
.tag.yellow .label{color:var(--a3)}
.tag.cyan-on-dark{background:var(--bg);border-color:var(--ink-c);color:var(--a5)}
.tag.cyan-on-dark .label{color:var(--a5)}

/* ===== HERO ===== */
.hero{padding:128px 0 96px;border-bottom:4px solid var(--ink-
c);position:relative;overflow:hidden}
.hero-bgword{position:absolute;top:-40px;left:50%;transform:translateX(-50%);font-
family:'Orbitron',sans-serif;font-weight:900;font-size:18rem;line-height:1;letter-
spacing:-.06em;color:hsl(0 0% 100% / .03);pointer-events:none;user-
select:none;white-space:nowrap}
.hero-grid{position:relative;z-index:20;display:grid;grid-template-
columns:1fr;gap:48px;align-items:center}
@media(min-width:1024px){.hero-grid{grid-template-columns:7fr 5fr}}
.hero-copy{display:flex;flex-direction:column;gap:32px}
.hero-h1{font-weight:900;text-transform:uppercase;line-height:.85;letter-
spacing:-.04em;font-size:clamp(40px, 9vw, 128px)}
.hero-h1 .row1{display:block;color:var(--chrome-c)}
.hero-h1 .row2{display:block}
.hero-h1 .row3{display:block;color:var(--chrome-c)}
.hero-h1 em{font-style:italic;font-family:'Orbitron',sans-serif;color:var(--a3)}
.hero-sub{font-family:'Share Tech Mono',monospace;font-size:18px;line-
height:1.7;color:hsl(var(--chrome)/.8);max-width:560px}
.hero-sub .cur{color:var(--a5)}
.hero-ctas{display:flex;flex-wrap:wrap;gap:24px;padding-top:8px}
.hero-meta{display:flex;flex-wrap:wrap;align-items:center;gap:24px;padding-
top:24px;font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:hsl(var(--chrome)/.6)}
.hero-meta .pip{width:4px;height:4px}
.hero-meta .pip.m{background:var(--a4)}
.hero-meta .pip.y{background:var(--a3)}

.hero-art{position:relative;height:480px}
.hero-art .bg{position:absolute;inset:0;background:var(--a2);border:4px solid
var(--ink-c);box-shadow:6px 6px 0 var(--ink-c), 12px 12px 0 var(--a4), 0 0 40px
hsl(var(--accent-4)/.5)}
.hero-art .stripe{position:absolute;inset:0;opacity:.4}
```

```
.hero-art .circle-
r{position:absolute;top:-32px;left:-32px;width:160px;height:160px;border-
radius:9999px;background:var(--a1);border:4px solid var(--ink-c)}
.hero-art .square-
y{position:absolute;top:96px;right:40px;width:176px;height:176px;background:var(--
a3);border:4px solid var(--ink-c);transform:rotate(15deg)}
.hero-art .tri-
m{position:absolute;bottom:24px;left:48px;width:144px;height:144px;background:var(
--a4);clip-path:polygon(50% 0%, 0% 100%, 100% 100%)}
.hero-art
.center{position:absolute;top:50%;left:50%;transform:translate(-50%,-50%);width:12
8px;height:128px;background:var(--chrome-c);border:4px solid var(--ink-
c);display:grid;place-items:center}
.hero-art .center .tri{width:64px;height:64px;background:var(--a5);clip-
path:polygon(50% 0%, 0% 100%, 100% 100%)}
.hero-art .dot-stack{position:absolute;bottom:-24px;right:-24px;display:flex;flex-
direction:column;gap:4px}
.hero-art .dot-stack span{width:16px;height:16px;border:2px solid var(--ink-
c);border-radius:9999px}
.hero-art .dot-stack .d1{background:var(--a1)}
.hero-art .dot-stack .d2{background:var(--a3)}
.hero-art .dot-stack .d3{background:var(--a5)}

/* Floating shapes overlay */
.float-layer{position:absolute;inset:0;z-index:10;pointer-
events:none;overflow:hidden}
.float-layer .shape{position:absolute;border:2px solid var(--ink-c)}
.float-layer .circle{border-radius:9999px}
.float-layer .tri{clip-path:polygon(50% 0%, 0% 100%, 100% 100%);border:0}
.float-layer .sq-rot{transform:rotate(12deg)}

/* ===== STATS ===== */
.stats-row{display:grid;grid-template-columns:1fr;border-bottom:4px solid var(--
ink-c)}
@media(min-width:640px){.stats-row{grid-template-columns:repeat(2,1fr)}}
@media(min-width:1024px){.stats-row{grid-template-columns:repeat(4,1fr)}}
.stat{position:relative;padding:56px 24px;overflow:hidden;border-bottom:4px solid
var(--ink-c)}
@media(min-width:640px){.stat{border-bottom:0;border-right:4px solid var(--ink-
c)}}
.stat:last-child{border-right:0;border-bottom:0}
.stat .stripes{position:absolute;inset:0;opacity:.3;pointer-events:none}
.stat
.corner{position:absolute;top:12px;right:12px;width:16px;height:16px;border:2px
solid var(--ink-c);border-radius:9999px;background:var(--bg)}
.stat .num{font-family:'Orbitron',sans-serif;font-weight:900;font-
size:clamp(40px,5vw,64px);letter-spacing:-.04em}
.stat .lbl{margin-top:12px;font-family:'Share Tech Mono',monospace;font-
size:12px;text-transform:uppercase;letter-spacing:.2em;opacity:.85}
.stat.s1{background:var(--a1);color:#fff}
.stat.s2{background:var(--a3);color:var(--ink-c)}
.stat.s3{background:var(--a2);color:#fff}
.stat.s4{background:var(--a4);color:#fff}
```

```
/* ===== Section heading ===== */
.heading-block{max-width:768px;margin-bottom:64px}
.h2{font-weight:900;text-transform:uppercase;letter-spacing:-.04em;line-
height:.9;font-size:clamp(36px,6vw,80px);color:var(--chrome-c)}
.h2 .accent-m{color:var(--a4)}
.h2 .accent-c{color:var(--a5)}
.h2 .accent-y{color:var(--a3)}
.h2 .accent-r{color:var(--a1)}
.lede{margin-top:24px;font-family:'Share Tech Mono',monospace;color:hsl(var(--
chrome)/.7);font-size:18px;max-width:560px}

/* ===== Features grid ===== */
.features-grid{display:grid;grid-template-columns:1fr;gap:40px}
@media(min-width:768px){.features-grid{grid-template-columns:repeat(2,1fr)}}
@media(min-width:1100px){.features-grid{grid-template-columns:repeat(3,1fr)}}

.tcard{
  position:relative;background:hsl(var(--card)/.8);
  backdrop-filter:blur(8px);-webkit-backdrop-filter:blur(8px);
  border:4px solid var(--ink-c);
  transition:transform .3s;
}
.tcard:hover{transform:translateY(-8px)}
.tcard.rot-r{transform:rotate(1deg)}
.tcard.rot-r:hover{transform:rotate(1deg) translateY(-8px)}
.tcard.rot-l{transform:rotate(-1deg)}
.tcard.rot-l:hover{transform:rotate(-1deg) translateY(-8px)}
.tcard .titlebar{display:flex;align-items:center;gap:12px;border-bottom:4px solid
var(--ink-c);background:hsl(var(--background)/.8);padding:8px 16px}
.tcard .dots{display:inline-flex;gap:6px}
.tcard .dots span{width:12px;height:12px;border-radius:9999px;border:1px solid
var(--ink-c)}
.tcard .dots .d1{background:var(--a1)}
.tcard .dots .d2{background:var(--a3)}
.tcard .dots .d3{background:var(--a5)}
.tcard .ttl{font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:hsl(var(--chrome)/.8)}
.tcard .corner{position:absolute;top:-14px;right:-14px;z-
index:2;width:28px;height:28px;border:2px solid var(--ink-c)}
.tcard .corner.circle{border-radius:9999px}
.tcard .corner.square{transform:rotate(45deg)}
.tcard .corner.tri{border:0;clip-path:polygon(50% 0%, 0% 100%, 100% 100%)}
.tcard .body{padding:24px}
.tcard .iconbox{display:inline-grid;place-
items:center;width:56px;height:56px;border:4px solid var(--ink-c);margin-
bottom:24px;color:var(--ink-c)}
.tcard h3{font-weight:900;text-transform:uppercase;letter-spacing:-.02em;font-
size:24px;color:var(--a5);text-shadow:0 0 10px hsl(var(--accent-5)/.9)}
.tcard p{margin-top:12px;font-family:'Share Tech Mono',monospace;font-
size:14px;line-height:1.7;color:hsl(var(--chrome)/.75)}

/* shadow color helpers */
.bgc-1{background:var(--a1)}.bgc-2{background:var(--a2)}.bgc-3{background:var(--
a3)}.bgc-4{background:var(--a4)}.bgc-5{background:var(--a5)}
```

```
/* ===== How It Works ===== */
.timeline{position:relative}
.timeline-
line{display:none;position:absolute;left:50%;top:0;bottom:0;width:4px;transform:tr
anslateX(-50%);background:var(--ink-c)}
.timeline-line::after{content:"";position:absolute;inset:0;background:linear-
gradient(to bottom, var(--a4), var(--a5), var(--a3));opacity:.8}
@media(min-width:768px){.timeline-line{display:block}}

.steps{display:flex;flex-direction:column;gap:64px}
.step{display:grid;grid-template-columns:1fr;gap:32px;align-items:center}
@media(min-width:768px){.step{grid-template-columns:1fr 1fr}}
.step .copy{position:relative}
.step .num{display:inline-block;font-family:'Orbitron',sans-serif;font-
weight:900;font-size:clamp(56px,7vw,96px);line-height:1;color:var(--ink-
c);border:4px solid var(--ink-c);padding:0 16px;box-shadow:4px 4px 0 var(--ink-c),
0 0 20px hsl(var(--accent-4)/.4)}
.step h3{margin-top:24px;font-weight:900;text-transform:uppercase;letter-
spacing:-.02em;font-size:30px;color:var(--chrome-c)}
.step p{margin-top:12px;font-family:'Share Tech Mono',monospace;color:hsl(var(--
chrome)/.7);max-width:420px}
.step .pin{display:none;justify-content:center}
@media(min-width:768px){.step .pin{display:flex}}
.step .pin .mark{width:48px;height:48px;border:4px solid var(--ink-c)}
.step.left .copy{text-align:left;padding-right:0}
.step.right .copy{text-align:left;padding-left:0}
@media(min-width:768px){
  .step.left .copy{text-align:right;padding-right:64px}
  .step.right .copy{text-align:left;padding-left:64px;order:2}
  .step.right .pin{order:1}
}

/* ===== Pricing ===== */
.pricing-grid{display:grid;grid-template-columns:1fr;gap:40px;align-items:start}
@media(min-width:900px){.pricing-grid{grid-template-columns:repeat(3,1fr)}}
.tier{
  position:relative;background:hsl(var(--card)/.8);color:var(--chrome-c);
  border:4px solid var(--ink-c);padding:32px;
  transition:transform .3s;
}
.tier:hover{transform:translateY(-8px)}
.tier.rot-l{transform:rotate(-1deg)}
.tier.rot-l:hover{transform:rotate(-1deg) translateY(-8px)}
.tier.rot-r{transform:rotate(1deg)}
.tier.rot-r:hover{transform:rotate(1deg) translateY(-8px)}
.tier.featured{background:var(--a4);color:#fff}
@media(min-width:900px)
{.tier.featured{transform:translateY(-24px)}.tier.featured:hover{transform:transla
teY(-32px)}}
.tier
.corner{position:absolute;top:-16px;right:-16px;width:40px;height:40px;border:2px
solid var(--ink-c)}
.tier .corner.circle{border-radius:9999px;background:var(--a4)}
```

```
.tier .corner.tri-c{border:0;clip-path:polygon(50% 0%, 0% 100%, 100%
100%);background:var(--a5)}
.tier .corner.tri-y{border:0;clip-path:polygon(50% 0%, 0% 100%, 100%
100%);background:var(--a3)}
.tier .badge{position:absolute;top:-16px;left:24px;background:var(--
a3);color:var(--ink-c);border:2px solid var(--ink-c);padding:4px 12px;font-
family:'Share Tech Mono',monospace;font-size:12px;text-transform:uppercase;letter-
spacing:.2em;transform:skewX(-12deg)}
.tier .badge>span{display:inline-block;transform:skewX(12deg)}
.tier h3{font-weight:900;text-transform:uppercase;letter-spacing:-.02em;font-
size:30px}
.tier .price{margin-top:24px;display:flex;align-items:baseline;gap:8px}
.tier .price .v{font-family:'Orbitron',sans-serif;font-weight:900;font-
size:60px;letter-spacing:-.04em}
.tier .price .s{font-family:'Share Tech Mono',monospace;font-size:14px;text-
transform:uppercase;opacity:.7}
.tier ul{margin-top:32px;display:flex;flex-direction:column;gap:12px}
.tier li{display:flex;align-items:flex-start;gap:12px;font-family:'Share Tech
Mono',monospace;font-size:14px}
.tier li .chk{margin-top:2px;display:grid;place-
items:center;width:20px;height:20px;border-radius:9999px;border:2px solid var(--
ink-c);background:var(--a5);color:var(--ink-c);flex-shrink:0}
.tier.featured li .chk{background:var(--a3)}
.tier li span:last-child{color:hsl(var(--chrome)/.85)}
.tier.featured li span:last-child{color:hsl(0 0% 100% / .9)}
.tier .cta-wrap{margin-top:32px}

/* ===== FAQ ===== */
.faq-list{display:flex;flex-direction:column;gap:24px}
.faq{border:4px solid var(--ink-c);background:hsl(var(--card)/.8);box-shadow:4px
4px 0 var(--ink-c), 0 0 20px hsl(var(--accent-4)/.4);transition:background .25s}
.faq.open{background:var(--a1)}
.faq button{display:flex;align-items:center;justify-content:space-
between;gap:16px;width:100%;padding:20px 24px;text-align:left}
.faq button .q{font-weight:900;text-transform:uppercase;letter-
spacing:-.01em;font-size:18px;color:var(--chrome-c)}
.faq.open button .q{color:#fff}
.faq button .chev{width:24px;height:24px;color:var(--a5);transition:transform .3s,
color .3s;flex-shrink:0}
.faq.open button .chev{transform:rotate(180deg);color:#fff}
.faq .panel{display:none;border-top:4px solid var(--ink-c);background:var(--
a3);color:var(--ink-c);padding:20px 24px}
.faq.open .panel{display:block}
.faq .panel p{font-family:'Share Tech Mono',monospace;font-size:15px;line-
height:1.7}
@media(min-width:640px){.faq button .q{font-size:20px}}

/* ===== Final CTA ===== */
.cta{position:relative;background:var(--a3);color:var(--ink-
c);overflow:hidden;border-bottom:4px solid var(--ink-c)}
.cta .sh1{position:absolute;top:-64px;left:-64px;width:288px;height:288px;border-
radius:9999px;background:var(--a1);border:4px solid var(--ink-c);opacity:.9}
.cta
.sh2{position:absolute;bottom:-80px;right:-40px;width:320px;height:320px;backgroun
```

```
d:var(--a2);border:4px solid var(--ink-c);transform:rotate(20deg)}
.cta
.sh3{position:absolute;top:40px;right:33%;width:96px;height:96px;background:var(--
a4);clip-path:polygon(50% 0%, 0% 100%, 100% 100%)}
.cta .sh4{position:absolute;bottom:48px;left:33%;width:64px;height:64px;border-
radius:9999px;background:var(--a5);border:4px solid var(--ink-c)}
.cta .stripes{position:absolute;inset:0;opacity:.2;pointer-events:none}
.cta .inner{position:relative;text-align:center;padding:112px 24px;max-
width:768px;margin:0 auto}
.cta h2{font-weight:900;text-transform:uppercase;line-height:.85;letter-
spacing:-.04em;font-size:clamp(40px,7vw,96px)}
.cta h2 em{font-style:italic}
.cta p{margin-top:24px;font-family:'Share Tech Mono',monospace;font-size:18px;max-
width:520px;margin-inline:auto}
.cta .btnrow{margin-top:40px;display:flex;flex-wrap:wrap;justify-
content:center;gap:24px}

/* ===== Footer ===== */
footer{background:var(--ink-c);color:var(--chrome-c);position:relative}
.foot-grid{max-width:1280px;margin:0 auto;padding:80px 24px;display:grid;grid-
template-columns:1fr;gap:48px}
@media(min-width:768px){.foot-grid{grid-template-columns:5fr 2fr 2fr 2fr 1fr}}
.foot-tag{display:flex;gap:8px}
.foot-tag span{width:12px;height:12px;border:1px solid hsl(var(--chrome)/.5)}
.foot-tag .t1{background:var(--a1);border-radius:9999px}
.foot-tag .t2{background:var(--a3)}
.foot-tag .t3{background:var(--a5);border:0;clip-path:polygon(50% 0%, 0% 100%,
100% 100%)}
.foot-tag .t4{background:var(--a4);border-radius:9999px}
.foot-tag .t5{background:var(--a2)}
.foot h4{font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:var(--a5);margin-bottom:16px}
.foot ul{display:flex;flex-direction:column;gap:8px}
.foot li a{font-family:'Share Tech Mono',monospace;font-size:14px;color:hsl(var(--
chrome)/.7);transition:color .2s}
.foot li a:hover{color:var(--a3)}
.foot .top{font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:hsl(var(--chrome)/.6)}
.foot .top:hover{color:var(--a4)}
.foot-bar{border-top:2px solid hsl(var(--chrome)/.2)}
.foot-bar-inner{max-width:1280px;margin:0 auto;padding:20px
24px;display:flex;flex-wrap:wrap;align-items:center;justify-content:space-
between;gap:16px;font-family:'Share Tech Mono',monospace;font-size:12px;text-
transform:uppercase;letter-spacing:.2em;color:hsl(var(--chrome)/.5)}
.foot-bar-inner .sig{display:inline-flex;align-items:center;gap:8px}
.foot-bar-inner .sig .d{width:8px;height:8px;border-radius:9999px;background:var(-
-a5)}
.foot p.intro{font-family:'Share Tech Mono',monospace;font-
size:14px;color:hsl(var(--chrome)/.6);max-width:380px;margin-block:24px}

/* utility */
.hide-mobile{display:none}
@media(min-width:768px){.hide-mobile{display:initial}}
```

```
/* SVG icon */
.ico{width:18px;height:18px;stroke:currentColor;stroke-width:2.5;fill:none;stroke-
linecap:round;stroke-linejoin:round}
.ico-lg{width:28px;height:28px}
.ico-sm{width:14px;height:14px;stroke-width:3}
/* Centers the cards within the main container */
.features-grid {
    display: grid;
    grid-template-columns: repeat(auto-fit, minmax(320px, 1fr)); /* Responsive
columns */
    gap: 40px;
    justify-content: center; /* THE FIX: Centers the grid itself */
    justify-items: center;  /* THE FIX: Centers cards within their grid cells */
    width: 100%;
}

/* Centers everything inside the card body */
.tcard .body {
    padding: 24px;
    display: flex;
    flex-direction: column;
    align-items: center;    /* THE FIX: Horizontal center for all items */
    text-align: center;      /* THE FIX: Centers the text */
}

/* Ensure images don't lean left */
.tcard .body img {
    margin: 0 auto 20px auto;
    display: block;
}
```