

# Resource request from native Android applications

## Overview

To create and configure an Android native project, first follow the [Configuring a native Android application with the MobileFirst Platform SDK \(../../hello-world/configuring-a-native-android-application-with-the-mfp-sdk/\)](#) tutorial.

MobileFirst applications can access resources using the `WLResourceRequest` REST API. This tutorial explains how to use the `WLResourceRequest` API with an HTTP adapter.

## Initializing WLClient

1. Create an instance of the `WLClient` class.

The `WLClient` instance requires a reference to the activity in which it is running.

```
WLClient client = WLClient.createInstance(context);
```

2. To establish a connection to the MobileFirst Server instance, use the `connect` method by specifying the `MyConnectListener` class instance as a parameter.

The `WLClient` instance tries to connect to the MobileFirst Server according to the properties of the `wlclient.properties` file.

After the connection is established, it invokes one of the methods of the `MyConnectListener` class.

3. Specify that the `MyConnectListener` class implements the `WLResponseListener` interface.

```
public class MyConnectListener implements WLResponseListener {
```

The `WLResponseListener` interface defines two methods:

- `public void onSuccess (WLResponse response) { }`
- `public void onFailure (WLFailResponse response) { }`

4. Use these methods to process connection success or connection failure.

## Invoking an adapter procedure

After the connection is established with a MobileFirst Server instance, you can use the `WLResourceRequest` class to invoke adapter procedures or call any REST resources.

1. Define the URI of the resource. For a JavaScript HTTP adapter:

```
/adapters/{AdapterName}/{ProcedureName}
```

```
URI adapterPath = new URI("/adapters/RSSReader/getFeed");
```

2. Create a `WLResourceRequest` object and choose the HTTP Method (GET, POST, etc).

```
WLResourceRequest request = new WLResourceRequest(adapterPath,WLResourceRequest.GET);
```

3. Add the required parameters.

- For JavaScript-based adapters, use the `params` parameter name to set an array of parameters.

```
request.setQueryParameter("params",["MobileFirst_Platform"]);
```

- For Java adapters or other resources, you can use `setQueryParameter` for each parameter.

```
request.setQueryParameter("param1","value1");  
request.setQueryParameter("param2","value2");
```

- Trigger the request with `.send()`.

Specify a `MyInvokeListener` class instance as a parameter.

You learn how to define this class instance in the next section.

```
request.send(new MyInvokeListener());
```

Other signatures, which are not covered in this tutorial, exist for the `send` method. Those signatures enable you to set parameters in the body instead of the query, or to handle the response with a delegate instead of a completion handler. See the user documentation to learn more.

## Receiving a procedure response

After the procedure invocation is completed, the framework calls one of the methods of the `MyInvokeListener` class.

1. Specify that the `MyInvokeListener` class implements the `WLResponseListener` interface.

```
public class MyInvokeListener implements WLResponseListener {
```

The `WLClient` instance invokes the `onSuccess` and `onFailure` methods.

If the procedure invocation is successful, the `onSuccess` method of `MyInvokeListener` is invoked.

2. Use that method to get the data that is retrieved from the adapter. The `response` object contains the

response data.

You can use its methods and properties to retrieve the required information.

```
public void onSuccess(WLResponse response) {  
    String responseText = response.getResponseText();  
    AndroidNativeApp.updateTextView("Adapter Procedure Invoked Successfully\n" +  
responseText);  
}  
  
public void onFailure(WLFailResponse response) {  
    String responseText = response.getResponseText();  
    AndroidNativeApp.updateTextView("Failed to Invoke Adapter Procedure\n" + responseText);  
}
```

## Sample application

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/InvokingAdapterProcedures>) the MobileFirst project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/InvokingAdapterProceduresAndroid>) the Native project.

- The InvokingAdapterProcedures project contains a MobileFirst Native API to deploy to your MobileFirst Server instance.
- The InvokingAdapterProceduresAndroid project contains a native Android application that uses a MobileFirst native API library to communicate with MobileFirst Server.
- Make sure to update the `wlclient.properties` file in the native Android project with the required server settings.

