

Tag and Broadcast Notifications in Native Android Applications

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/7.1/notifications/push-notifications-overview/push-notifications-native-android-applications/tag-based-notifications-in-native-android-applications.html>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

Overview

Prerequisite: Make sure that you read the Push notifications in native Android applications (../) tutorial first.

Tag notifications are notification messages that are targeted to all the devices that are subscribed to a particular tag.

Tags represent topics of interest to the user and provide the ability to receive notifications according to the chosen interest.

Broadcast notifications are a form of tag push notifications that are targeted to all subscribed devices.

Broadcast notifications are enabled by default for any push-enabled MobileFirst application by a subscription to a reserved `Push.all` tag (auto-created for every device). Broadcast notifications can be disabled by unsubscribing from the reserved `Push.all` tag.

Agenda

- Notifications configuration
- Notifications API
- Sample application

Notifications configuration

Tag Notifications configuration

Setting up tags

Tags are defined in the `application-descriptor.xml` file:

```

<nativeAndroidApp xmlns="http://www.worklight.com/native-android-descriptor"
id="NativeAndroidTagNotifications" platformVersion="7.1.0.00.20150312-0731" version="1.0">
<pushSender key="API_KEY" senderId="PROJECT_NUMBER"/>
...
...
...
<tags>>
  <tag>
    <name>my tag 1</name>
    <description>About my tag 1</description>
  </tag>
  <tag>
    <name>my tag 2</name>
    <description>About my tag 2</description>
  </tag>
</tags>

```

Notifications API

API methods for tag notifications

Client-side API

- `WLPush.subscribeTag(tagName,options)` - Subscribes the device to the specified tag name
- `WLPush.unsubscribeTag(tagName,options)` - Unsubscribes the device from the specified tag name
- `WLPush.isTagSubscribed(tagName)` - Returns whether the device is subscribed to a specified tag name

Common API methods for tag and broadcast notifications

Client-side API

- `WLNotificationListener`
Defines the callback method to be notified when the notification arrives.
- `client.getPush().setWLNotificationListener(listener)`
This method sets the implementation class of the `WLNotificationListener` interface.
- `client.getPush().setOnReadyToSubscribeListener(listener)`
This method registers a listener to be used for push notifications. This listener should implement the `onReadyToSubscribe()` method.
- The `onMessage(props,payload)` method of `WLNotificationListener` is called when a push notification is received by the device.
 - **props** - A JSON block that contains the notifications properties of the platform.
 - **payload** - A JSON block that contains other data that is sent from MobileFirst Server. The JSON block also contains the tag name for tag-based or broadcast notification. The tag name appears in the "tag" element. For broadcast notification, the default tag name is `Push.ALL`.

Server-side API

```
WL.Server.sendMessage(applicationId,notificationOptions)
```

This method submits a notification that is based on the specified target parameters.

- `applicationId` - (mandatory) The name of the MobileFirst application
- `notificationOptions` - (mandatory) A JSON block containing message properties

For a full list of message properties, refer to the `WL.Server.sendMessage` API in the API reference of user documentation

Sample application

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/TagNotifications/tree/release71>) the MobileFirst project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/TagNotificationsAndroid/tree/release71>) the Native project.

- The `TagNotifications` project contains a MobileFirst native API that you can deploy to your MobileFirst Server instance.
- The `TagNotificationsAndroid` project contains a native android application that uses a MobileFirst native API library to subscribe to push notifications and receive notifications from GCM.
- Make sure to update the `wlclient.properties` file in the native project with the relevant server settings.



Sending a notification

To test the application is able to receive a push notification you can perform one of the following:

1. From MobileFirst Studio, right-click the adapter folder, select **Call MobileFirst Adapter** and:
 - If selecting the "sendBroadcastNotification" procedure, provide the application ID and notification text in quotation marks.
 - If selecting the "sendTagNotification" procedure, provide the application ID, notification text and tag name in quotation marks.
 - The application ID can be determined from the `id` attribute in `application-descriptor.xml`:

```
<application ... id="NativeAndroidTagNotifications" ...>
```

2. If using the CLI:

```
$ mfp adapter call  
[?] Which endpoint do you want to use? PushAdapter/sendBroadcastNotification  
[?] Enter the comma-separated parameters: "NativeAndroidTagNotifications","hello"  
[?] How should the procedure be called? GET
```

Or:

```
$ mfp adapter call  
[?] Which endpoint do you want to use? PushAdapter/sendTagNotification<  
[?] Enter the comma-separated parameters: "NativeAndroidTagNotifications","hello","sample-tag1, sample-tag2"<  
[?] How should the procedure be called? GET
```