

# Event source-based notifications in native Windows 8 applications

## Overview

Event source notifications are notification messages that are targeted to devices with a user subscription.

To learn more about the architecture and terminology of push notifications in IBM MobileFirst™ Platform Foundation, see the “Event source-based notifications in hybrid applications (../push-notifications-hybrid-applications/event-source-based-notifications/)” tutorial.

For more information about setting up push notifications in native Windows 8 applications, see the “Push notifications in native Windows 8 applications (../)” tutorial.

Go to:

- Notification API - Server-side
- Notification API - Client-side
- Sample application

## Notification API: Server-side

### Creating an event source

Create a notification event source in the adapter JavaScript™ code at a global level (outside any JavaScript function).

```
WL.Server.createEventSource({
  name: 'PushEventSource',
  onDeviceSubscribe: 'deviceSubscribeFunc',
  onDeviceUnsubscribe: 'deviceUnsubscribeFunc',
  securityTest: 'PushApplication-strong-mobile-securityTest'
});
```

- **name** – A name by which the event source is referenced.
- **onDeviceSubscribe** – An adapter function that is called when the request for user subscription is received.
- **onDeviceUnsubscribe** – An adapter function that is called when the request for user unsubscription is received.
- **securityTest** – A security test from the `authenticationConfig.xml` file, which is used to protect the event source.

### Sending a notification

Notifications can be either polled from, or pushed by, the back-end system. In this example, a `submitNotifications()` adapter function is invoked by a back-end system as an external API to send notifications.

```
function submitNotification(userId, notificationText) {
    var userSubscription = WL.Server.getUserNotificationSubscription('PushAdapter.PushEventSource', userId);
    if (userSubscription === null) {
        return { result: "No subscription found for user :: " + userId };
    }
    var badgeDigit = 1;
    var notification = WL.Server.createDefaultNotification(notificationText, badgeDigit, {custom:"data"});
    WL.Server.notifyAllDevices(userSubscription, notification);
    return {
        result: "Notification sent to user :: " + userId
    };
}
```

## Notification API - Client-side

The first step is to create an instance of the `WLClient` class:

```
WLClient client = WLClient.getInstance();
```

You derive all push notification operations from the `WLPush` class.

`getPush` – Use this method to retrieve an instance of the `WLPush` class from the `WLClient` instance.

```
WLPush push = client.getPush();
```

`WLOnReadyToSubscribeListener` – When connecting to MobileFirst Server, the application attempts to register itself with the Google Cloud Messaging (GCM) server to receive push notifications.

```
OnReadyToSubscribeListener myOnReadyListener = new OnReadyToSubscribeListener();
push.onReadyToSubscribeListener = myOnReadyListener;
```

The `onReadyToSubscribe` method of `WLOnReadyToSubscribeListener` is called when the registration is complete.

```
public void onReadyToSubscribe()
{...}
```

## WLPush.registerEventSourceCallback

To register an alias on a particular event source, use the `WLPush.registerEventSourceCallback` method.

The API takes the following arguments:

- `alias` - An alias name.
- `Adaptername` - Adapter in which the event source is defined.
- `EventSourceName` - The event source on which the alias is called.

Example:

```
WLClient.getInstance().getPush().registerEventSourceCallback("myPush", "PushAdapter", "PushEventSource", this);
```

Typically, this method is called in the `onReadyToSubscribe` callback function.

```
public void onReadyToSubscribe()  
{  
    WLClient.getInstance().getPush().registerEventSourceCallback("myPush", "PushAdapter", "PushEventSource", this);  
}
```

## Subscribing to push notification

To set up subscription to push notification, use the `WLPush.subscribe(alias, pushOptions, responseListener)` API.

The API takes the following arguments:

- `alias` – The alias to which the device must subscribe.
- `pushOptions` – An object of type `WLPushOptions`.
- `responseListener` – An object of type `WLResponseListener`, which is called when subscription completes.

Example:

```
WLPush push = WLClient.getInstance().getPush();  
MySubscribeListener mySubListener = new MySubscribeListener();  
push.subscribe("myPush", null, mySubListener);
```

`MySubscribeListener` implements `WLResponseListener` and provides the following callback functions:

- `onSuccess` – Called when subscription succeeds.
- `onFailure` – Called when subscription fails.

## Unsubscribing from push notifications

To set up unsubscription from push notification, use the `WLPush.unsubscribe(alias, responseListener)` API.

The API takes the following arguments:

- `alias` – The alias to which the device has subscribed.
- `responseListener` – An object of type `WLResponseListener`, which is called when unsubscription completes.

Example:

```
WLPush push = WLClient.getInstance().getPush();  
MyUnsubscribeListener myUnsubListener = new MyUnsubscribeListener();  
push.unsubscribe("myPush", myUnsubListener);
```

MyUnsubscribeListener implements WLResponseListener and provides the following callback functions:

onSuccess – Called when unsubscription succeeds.

onFailure – Called when unsubscription fails.

## Additional client-side API methods

isSubscribed() - Indicates whether the device is subscribed to push notifications.

```
WLClient.getInstance().getPush().isSubscribed("myPush");
```

## Receiving a push notification

When a push notification is received, the onReceive method is called on an WLEventSourceListener instance.

```
class OnReadyToSubscribeListener : WLOnReadyToSubscribeListener, WLEventSourceListener{...}
```

The WLEventSourceListener instance is registered during the registerEventSourceCallback callback.

```
WLClient.getInstance().getPush().registerEventSourceCallback("myPush", "PushAdapter", "PushEventSource", this);
```

The onReceive method displays the received notification on the screen.

```
public void onReceive(String props, String payload)  
{  
    Debug.WriteLine("Props: " + props);  
    Debug.WriteLine("Payload: " + payload);  
}
```

## Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v700/PushNotificationsNativeProject.zip>)  
the Studio project.

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v700/Windows8NativePushProject.zip>)  
the Native project.

The sample contains two projects:

- The PushNotificationsNativeProject.zip file contains a **MobileFirst native API** that you can

deploy to your MobileFirst Server instance.

- The `Windows8NativePushProject.zip` file contains a **native Windows 8 application** that uses a MobileFirst native API library to subscribe to push notifications and receive notifications from Windows Notification Services (WNS).

Make sure to update the `wlclient.properties` file in `Windows8NativePushProject` with the relevant server settings.