Cordova end-to-end demonstration

Overview

The purpose of this demonstration is to experience an end-to-end flow:

- 1. A scaffold application an application that is pre-bundled with the MobileFirst client SDK, is registered and downloaded from the MobileFirst Operations Console.
- 2. An new or provided adapter is deployed to the MobileFirst Operations Console.
- 3. The application logic is changed to make a resource request.

End result:

- Successfully pinging the MobileFirst Server.
- · Successfully retrieving data using a MobileFirst Adapter.

Prerequisites:

- Xcode for iOS, Android Studio for Android or Visual Studio 2013/2015 for Windows 8.1 Universal / Windows 10 UWP
- Cordova 6.0.0 CLI (v6.1.0 is not supported)
- Optional. MobileFirst CLI (download (file:///home/travis/build/MFPSamples/DevCenter/_site/downloads))
- Optional. Stand-alone MobileFirst Server (download (file:////home/travis/build/MFPSamples/DevCenter/_site/downloads))

1. Starting the MobileFirst Server


If a remote server was already set-up, skip this step.

From a **Command-line** window, navigate to the server's folder and run the command: ./run.sh in Mac and Linux or run.cmd in Windows.


2. Creating and registering an application

In a browser window, open the MobileFirst Operations Console by loading the URL: http://your-server-host:server-port/mfpconsole. If running locally, use: http://localhost:9080/mfpconsole (http://localhost:9080/mfpconsole). The username/password are admin/admin.

- Click the New button next to Applications
 - Select a platform: Android, iOS, Windows
 - Enter com.ibm.mfpstartercordova as the application identifier
 - Enter 1.0.0 as the version value
 - Click on Register application



2. Click on the Get Starter Code tile and select to download the Cordova application scaffold.



3. Editing application logic

- 1. Open the Cordova project in your code editor of choice.
- 2. Select the **www/js/index.js** file and paste the following code snippet, replacing the existing WLAuthorizationManager.obtainAccessToken() function:

```
WLAuthorizationManager.obtainAccessToken()
.then (
  function(accessToken) {
    var statusText = document.getElementById("statusText");
    statusText.innerHTML = "Obtained Access Token Successfully";
    var resourceRequest = new WLResourceRequest(
       "/adapters/javaAdapter/users/world",
       WLResourceRequest.GET
    );
    resourceRequest.send().then(
       function(response) {
         // Will display "Hello world" in an alert dialog.
         alert("Success: " + response.responseText);
       },
       function(response) {
         alert ("Failure: " + response.errorMsg);
    );
  },
  function(error) {
    var statusText = document.getElementById("statusText");
    statusText.innerHTML = "Failed to obtain access token: " + JSON.stringify(error);
  }
);
```

4. Creating an adapter

Download this prepared .adapter artifact (../javaAdapter.adapter) and deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action.

Alternatively, click the **New** button next to **Adapters**.


1. Select the **Actions** → **Download sample** option. Download the "Hello World" **Java** adapter sample.

If Maven and MobileFirst CLI are not installed, follow the on-screen **Set up your development environment** instructions.

2. From a **Command-line** window, navigate to the adapter's Maven project root folder and run the command:

```
mfpdev adapter build
```

3. When the build finishes, deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action. The adapter can be found in the **[adapter]/target** folder.



5. Testing the application

- 1. From a **Command-line** window, navigate to the Cordova project's root folder.
- 2. Run the command: cordova platform add ios/android/windows to add a platform.
- 3. In the Cordova project, select the config.xml file and edit the

 <mfp:server ... url=" "/> value with
 the IP address of the MobileFirst Server.
 Alternatively, if you have installed the
 MobileFirst Develper CLI then navigate to
 the project root folder and run the
 command mfpdev app register. If a
 remote server is used instead of a local
 server, first use the command mfpdev
 server add to add it.
- 4. Run the command: cordova run.

If a device is connected, the application will be installed and launched in the device,

Otherwise the Simulator or Emulator will be used.



Results

- Clicking the Ping MobileFirst Server button will display Connected to MobileFirst Server.
- If the application was able to connect to the MobileFirst Server, a resource request call using the deployed Java adapter will take place.

The adapter response is then displayed in an alert.

Next steps

Learn more on using adapters in applications, and how to integrate additional services such as Push Notifications, using the MobileFirst security framework and more:

- Review the Using the MobileFirst Platform Foundation (../../using-the-mfpf-sdk/) tutorials
- Review the Adapters development (../../adapters/) tutorials
- Review the Authentication and security tutorials (../../authentication-and-security/)
- Review the Notifications tutorials (../../notifications/)
- Review All Tutorials (../../all-tutorials)