

# Adapter-based authentication in native Windows Phone 8 applications

## Overview

This tutorial illustrates the native Windows Phone 8 client-side authentication components for adapter-based authentication.

**Prerequisite:** Make sure that you read Adapter-based authentication (../) first.

## Creating the client-side authentication components

Create a native Windows Phone 8 application and add the MobileFirst native APIs as explained in the documentation.

### CustomAdapterChallengeHandler

Create a CustomAdapterChallengeHandler class as a subclass of ChallengeHandler.

Your CustomAdapterChallengeHandler class must implement the isCustomResponse and handleChallenge methods.

- The isCustomResponse method checks every custom response received from MobileFirst Server to verify whether this is the expected challenge.

Copy

```
public override bool isCustomResponse(WLResponse response) {
    if (response == null ||
        response.getResponseJSON() == null ||
        response.getResponseText() == null ||
        response.getResponseJSON()["authRequired"] == null ||
        String.Compare(response.getResponseJSON()["authRequired"].ToString(), "false", StringComparison.OrdinalIgnoreCase) == 0)
    {
        return false;
    }
    return true;
}
```

- The handleChallenge method is called after the isCustomResponse method returns true. Use this method to present the login form. Different approaches are available.

Copy

```
public override void handleChallenge(JObject challenge)
{
    Deployment.Current.Dispatcher.BeginInvoke(() =>
    {
        MainPage._this.NavigationService.Navigate(new Uri("/LoginPage.xaml", UriKind.Relative))
    });
}
```

From the login form, credentials are passed to the CustomAdapterChallengeHandler class. The submitAdapterAuthentication() method is used to send input data to the authenticator.

Copy

```
public void submitLogin(string userName, string password)
{
    object[] parameters = new object[] { userName, password };
    WLProcedureInvocationData invocationData = new WLProcedureInvocationData("NativeAdapterBasedAdapter", "submitAuthentification");
    invocationData.setParameters(parameters);
    WLRequestOptions options = new WLRequestOptions();
    submitAdapterAuthentication(invocationData, options);
}
```

## MainPage

Within the MainPage class, connect to MobileFirst Server, register your challengeHandler, and invoke the protected adapter procedure.

The procedure invocation triggers MobileFirst Server to send a challenge that will trigger the challenge handler.

Copy

```
WLClient client;
client = WLClient.getInstance();
challengeHandler = new WindowsChallengeHandler();
client.registerChallengeHandler((BaseChallengeHandler<JsonObject>)challengeHandler)
;
client.connect(new MyConnectResponseListener(this))
```

Because the native API is not protected by a defined security test, no login form is presented during server connection. Invoke the protected adapter procedure. The login form is presented by the challengeHandler.

Copy

```
WLProcedureInvocationData invokeData = new WLProcedureInvocationData("NativeAdapterBasedAdapter", "getSecretData");
WLRequestOptions options = new WLRequestOptions();
client.invokeProcedure(invokeData, new MyResponseListener(this), options);
```

## Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v700/NativeAdapterBasedAuthProject.zip>)  
the Studio project.

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v700/WP8NativeAdapterBasedAuthProject.zip>)  
the Native project.

