

Adapters overview

Overview

This tutorial presents how to develop server-side code (adapters) that is used to transfer and retrieve information from back-end systems to client applications and cloud services. MobileFirst Server processes the information and handles security. You can write adapters in JavaScript or Java.

This tutorial covers the following topics:

- Benefits of using adapters
- JavaScript adapters
- Java adapters
- Creating adapters
- Deploying adapters
- Testing adapters
- Tutorials to follow next



Benefits of using adapters

Universality

- Adapters support multiple integration technologies and back-end information systems.

Read-only and transactional capabilities

- Adapters support read-only and transactional access modes to back-end systems.

Fast development

- Adapters use simple XML syntax and are easily configured with JavaScript API or Java API.

Security

- Adapters use flexible authentication facilities to create connections with back-end systems.
- Adapters offer control over the identity of the connected user.

Transparency

- Data that is retrieved from back-end applications is exposed in a uniform manner, regardless of the adapter type.

Benefits specific to Java adapters

- Ability to fully control the URL structure, the content types, the request and response headers, content and encoding
- Easy and fast development and testing by using MobileFirst Studio or the command-line interface (CLI)
- Ability to test the adapter without MobileFirst Studio or CLI, by using a 3rd-party tool such as Postman
- Easy and fast deployment to a running MobileFirst Server instance with no compromise on performance and no downtime
- Security integration with the MobileFirst security model with no additional customization, by using simple annotations in the source code

JavaScript adapters

JavaScript adapters provide templates for connection to various back-ends, such as HTTP, SQL, Cast Iron, SAP JCo, and SAP Netweaver. JavaScript adapters also provide a service discovery wizard, which you can use to autogenerate adapters for connecting to WSDL services and more.

Learn more about JavaScript adapters ([../javascript-adapters/](#))

Java adapters

Java adapters expose a full REST API to the client and are written in Java. This type of adapters is based on the JAX-RS specification (<https://jax-rs-spec.java.net/nonav/2.0-rev-a/apidocs/index.html>).

In Java adapters, it is up to the developer to define the returned content and its format, as well as the URL structure of each resource.

Learn more about Java adapters ([../java-adapter/](#))

Creating adapters

CLI

From the project's directory, use `mfp add adapter` and follow the interactive instructions.

Studio

1. In Eclipse, click the MobileFirst icon that is located in the toolbar and select **MobileFirst Adapter**.



2. Select a MobileFirst project and an adapter type. This generates the template of the adapters.



3. Select an adapter type and type an adapter name. Applications use this name to access the adapter.
4. Click **Finish**.

Deploying adapters

CLI

In the terminal, go to the adapter's directory: `$ cd adapters/TestAdapt/`.
Use `mfp push` to build and deploy the current adapter.

Studio

1. Select an adapter to deploy.
2. Right-click the adapter and select **Run As > Deploy MobileFirst Adapter**.



MobileFirst Studio archives the adapter code and deploys it to the MobileFirst Server instance. You can see the deployed adapter in the MobileFirst Console ([../hello-world/introduction-to-mobilefirst-platform-operations-console/](#)).



Testing adapters

CLI

To run a procedure test, make sure your adapter is built and deployed, then use `$ mfp adapter call`. Follow the interactive instructions.

Studio

To test adapter procedures, you can use MobileFirst Studio.

To run a procedure test:

1. Select **Run As > Call MobileFirst Procedure**.



2. Select the procedure that you want to test.
3. Enter key values and click **Run**.

JavaScript adapters

A screenshot of a macOS-style dialog box titled 'Call MobileFirst Procedure'. It contains the following elements:

- 'Adapter Name' field: HelloWorldAdapter
- 'Procedure name' dropdown: getStories (interest)
- 'REST Call Type' dropdown: GET
- Two tabs: 'Procedure Arguments' (active) and 'Headers'.
- A table with two columns: 'Key' and 'Value'. It has three empty rows for data entry.
- 'Load' button to the right of the table.
- 'Save' button below the table.
- 'Run' and 'Cancel' buttons at the bottom right.

Java adapters

Call MobileFirst Procedure

Adapter Name : HelloWorldAdapter

Procedure name : /HelloWorld/adapters/HelloWorldAdapter/users

REST Call Type : GET

Path Parameters Query Parameters Body Parameters Headers

Key	Value

Load

Save

Run Cancel

In Postman

MobileFirst adapters are available via a REST interface. This means that if you know the URL of a resource/procedure, you can use HTTP tools such as Postman to test requests and pass URL parameters, path parameters, body parameters or headers as you see fit.

The URL to access your adapter procedure is:

`/ {project-context} /adapters/ {adapter-name} / {procedure-name}`

When using Java adapters, parameters can be passed in the URL, body, form, etc, depending on how you configured your adapter.

When using JavaScript adapters, parameters are passed as `params=[a,b,c,d]`, in other words, a JavaScript procedure receives only **one** parameter called `params` which needs to be an array of ordered, unnamed values. This parameter can either be in the URL (GET) or in the body (POST) using Content-Type: `application/x-www-form-urlencoded`.

If your resource is protected by a security test, the request prompts you to provide a valid authorization header. Note that by default, MobileFirst uses a simple security scope even if you did not specify any. So unless you specifically disabled security, the endpoint is always protected.

For you to work around this during your development stage, the development version of the MobileFirst server includes a test token endpoint.

To receive a Test Token, make an HTTP POST request to `http(s)://{server_ip}:`

{server_port}/{project_name}/authorization/v1/testtoken with your HTTP client (Postman).

You receive a JSON object with a temporary valid authorization token:

```
{
  "Authorization": "Bearer eyJhbGciOiJSUzI1NiIsImpwYlI6eyJhbGciOiJSU0EiLCJleHAiOiJBUEUFC
liwibW9kljoiQU0wRGQ3eEFkdjZILXlnTDdyOHFDTGRFLTnJmM2FPZUlx2UtkpBMHVadXcyc
khoWFozV1ZDZUtleJWY0NPWXNRTi1tUUsWbWZ6NV8zby1ldjBVWXda1NPd0JCbDFFaHFJ
d1ZE09pZWcySk1HbDBFWHNQWmZrTlpJLUhVNG9NaWktVHJOTHp..."
}
```

In your next requests to your adapter endpoints, add an HTTP header with the name "Authorization" and the value you received previously (starting with Bearer).

The security framework now skips any security challenges protecting your resource.

The screenshot displays the Postman application interface. At the top, there are tabs for authentication methods: Normal, Basic Auth, Digest Auth, OAuth 1.0, and OAuth 2.0. The 'Normal' tab is selected. Below the tabs, the URL bar shows 'http://localhost:10080/Adapters/adapters/JavaAdapter/nathan' and the method is set to 'GET'. The 'Headers' tab is active, showing a single header: 'Authorization: Bearer eyJhbGciOiJSUzI1NiIsImpwYlI6eyJhbGciOiJSU0EiLCJleHAiOiJBUEUFCliwibW9kljoiQU0wRGQ3eEFkdjZILXlnTDdyOHFDTGRFLTnJmM2FPZUlx2UtkpBMHVadXcyckhoWFozV1ZDZUtleJWY0NPWXNRTi1tUUsWbWZ6NV8zby1ldjBVWXda1NPd0JCbDFFaHFJd1ZE09pZWcySk1HbDBFWHNQWmZrTlpJLUhVNG9NaWktVHJOTHp...'. Below the headers, there are buttons for 'Add preset', 'Manage presets', 'Send', 'Save', 'Preview', 'Pre-request script', 'Tests', 'Add to collection', and a red 'Reset' button. The 'Body' tab is selected, showing the response 'Hello nathan'. The status bar at the bottom indicates 'STATUS 200 OK' and 'TIME 52 ms'. There are also buttons for 'Pretty', 'Raw', 'Preview', and 'Copy'.

For more information about JavaScript and Java adapters, see the topic about "MobileFirst adapters overview" in the user documentation.

Tutorials to follow next

Follow the tutorials in the server-side development section (../) to learn more about HTTP, SQL, Cast Iron, and JMS JavaScript adapters, Java adapters, invoking adapter procedures from hybrid and native applications, advanced adapter usage and more.

