

# Invoking adapter procedures from native Windows Phone 8 applications

## Overview

To create and configure a Windows Phone 8 native project, first follow the "Creating your first Native WP8 MobileFirst application (../../hello-world/creating-first-native-windows-phone-8-mobilefirst-application/)" tutorial.

## Initializing WLClient

```
WLClient client = WLClient.getInstance();
```

1. To establish a connection to MobileFirst Server, use the `connect` method by specifying the `MyConnectResponseListener` class instance as a parameter.

```
client.connect(new MyConnectResponseListener(this));
```

The `WLClient` instance tries to connect to the MobileFirst Server instance according to the properties of the `wlclient.properties` file.

After the connection is established, it invokes one of the methods of the `MyConnectResponseListener` class.

2. Specify that the `MyConnectResponseListener` class implements the `WLResponseListener` interface.

```
public class MyConnectResponseListener : WLResponseListener
```

The `WLResponseListener` interface defines two methods:

- `public void onSuccess (WLResponse response) { }`
- `public void onFailure (WLFailResponse response) { }`

3. Use the previous methods to process connection success or connection failure.

## Invoking an adapter procedure

After the connection is established with a MobileFirst Server instance, you can use the `WLClient` instance to invoke adapter procedures.

1. Create a `WLProcedureInvocationData` object with the adapter and procedure names.
2. Add the required parameters as an object array and set request options (for example: Invocation Context).
3. Get the existing `WLClient` instance and use it to invoke an adapter procedure.
4. Specify the `MyInvokeListener` class instance as a parameter.

```
WLProcedureInvocationData invocationData = new WLProcedureInvocationData("RSSReader", "getStories");
invocationData.setParameters(new Object[]{});
String myContextObject = "InvokingAdapterProceduresWP8";
WLRequestOptions options = new WLRequestOptions();
options.setInvocationContext(myContextObject);
WLClient.getInstance().invokeProcedure(invocationData, new MyInvokeListener(this), options);<br />
```

## Receiving a procedure response

After the procedure invocation is completed, the `WLClient` instance calls one of the methods of the `MyInvokeListener` class.

As before, you must specify that the `MyInvokeListener` class implements the `WLResponseListener` interface.

```
using IBM.Worklight;
namespace InvokingAdapterProceduresWP8{
    public class MyInvokeListener : WLResponseListener
    {
    {
```

The `onSuccess` and `onFailure` methods are invoked by the `WLClient`. The response object contains the response data. You can use its methods and properties to retrieve the required information.

```
public void onSuccess(WLResponse response)
{
    WLProcedureInvocationResult invocationResponse = ((WLProcedureInvocationResult) response)
;
    JObject items;
    try
    {
        items = invocationResponse.getResponseJSON();
        Deployment.Current.Dispatcher.BeginInvoke(() =>
        {
            myMainPage.AddTextToReceivedTextBlock("Response Success: " + items.ToString());
        });
    }
    catch (JsonReaderException e)
    {
        Deployment.Current.Dispatcher.BeginInvoke(() =>
        {
            myMainPage.AddTextToReceivedTextBlock("JSONException : " + e.Message);
        });
    }
}
public void onFailure(WLFailResponse response)
{
    Deployment.Current.Dispatcher.BeginInvoke(() =>
    {
        myMainPage.AddTextToReceivedTextBlock("Response failed: " + response.ToString());
    });
}
```

## Sample application

The sample contains two projects:

- The **InvokingAdapterProceduresNativeProject.zip** file contains a MobileFirst Native API to deploy to MobileFirst Server.
- The **InvokingAdapterProceduresWP8project.zip** file contains a native Windows Phone 8 application that uses a MobileFirst native API library to communicate with a MobileFirst Server instance.

Make sure to update the **wlclient.properties** file in **InvokingAdapterProceduresWP8** with the relevant server settings.

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/InvokingAdapterProceduresNativeProject.zip>)  
the Studio project.

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/InvokingAdapterProceduresWP8Project.zip>)  
the Native project.

# Hello Worklight

Connect

Invoke

Invoking Procedure...

Response Success: {

"statusCode": 200,

"errors": [],

"isSuccessful": true,

"statusReason": "OK",

"rss": {

"channel": {

"pubDate": "Mon, 02 Jun 2014 07:01:24

EDT",

"title": "CNN.com - Top Stories",

"description": "CNN.com delivers up-to-the-minute news and information on the latest top stories, weather, entertainment, politics and more.",

"item": [

{

2014-06-02 07:01:24

