

Adapters Overview

Overview

Adapters (server-side code) are used to transfer and retrieve information from back-end systems to client applications and cloud services. MobileFirst Server processes the information and handles security. Each adapter has its own isolated sandbox, which runs without knowing about or interrupting other adapter sandboxes. That said, adapters can still communicate with one another by calling API which makes "adapter mashup ([../advanced-adapter-usage-mashup](#))" possible. You can write adapters in JavaScript or Java.



Benefits of using adapters

Universality

- Adapters support multiple integration technologies and back-end information systems.

Read-only and transactional capabilities

- Adapters support read-only and transactional access modes to back-end systems.

Fast development

- Adapters use simple XML syntax and are easily configured with JavaScript API or Java API.

Security

- Adapters use flexible authentication facilities to create connections with back-end systems.
- Adapters offer control over the identity of the connected user.

Transparency

- Data that is retrieved from back-end applications is exposed in a uniform manner, regardless of the adapter type.

Benefits specific to Java adapters

- Ability to fully control the URL structure, the content types, the request and response headers, content and encoding

- Easy and fast development and testing by using the command-line interface (CLI)
- Ability to test the adapter by using a 3rd-party tool such as Postman
- Easy and fast deployment to a running MobileFirst Server instance with no compromise on performance and no downtime
- Security integration with the MobileFirst security model with no additional customization, by using simple annotations in the source code

JavaScript adapters

JavaScript adapters provide templates for connection to various back-ends, such as HTTP, SQL, Cast Iron, SAP JCo, and SAP Netweaver.

JavaScript adapter provides a set of services, called procedures. Mobile apps invoke procedures by issuing Ajax requests. The procedure retrieves information from the back-end application that returns data in some format:

- If this format is JSON, the MobileFirst Server keeps the data intact.
- Otherwise, the MobileFirst Server automatically converts it to JSON. Alternatively, you can provide an XSL transformation to convert the data to JSON. In this case, the returned content type from the back end must be XML. Then, you can use an XSLT to filter the data.

The JavaScript implementation of the procedure receives the JSON data, performs any additional processing, and returns it to the calling app.

UPDATE THE IMAGE



For more information see the topic about "MobileFirst adapters overview" in the user documentation.