

JSONStore in iOS applications

Prerequisites

- Read the JSONStore parent tutorial (../)
- Make sure the MobileFirst Native SDK was added to the Xcode project. Follow the Adding the MobileFirst Foundation SDK to iOS applications (../../adding-the-mfpf-sdk/ios/) tutorial.

Jump to:

- Adding JSONStore
- Basic Usage
- Advanced Usage
- Sample application

Adding JSONStore

1. Add the following to the existing `podfile`, located at the root of the Xcode project:

```
pod 'IBMMobileFirstPlatformFoundationJSONStore'
```

2. From a **Command-line** window, navigate to the root of the Xcode project and run the command:

```
pod install
```

 - note that this action may take a while.

Whenever you want to use JSONStore, make sure that you import the JSONStore header:
Objective-C:

```
#import <IBMMobileFirstPlatformFoundationJSONStore/IBMMobileFirstPlatformFoundationJSONStore.h>
```

Swift:

```
import IBMMobileFirstPlatformFoundationJSONStore
```

Basic Usage

Open

Use `openCollections` to open one or more JSONStore collections.

Starting or provisioning a collections means creating the persistent storage that contains the collection and documents, if it does not exists.

If the persistent storage is encrypted and a correct password is passed, the necessary security procedures to make the data accessible are run.

For optional features that you can enable at initialization time, see **Security, Multiple User Support** and **MobileFirst Adapter Integration** in the second part of this tutorial.

```
let collection:JSONStoreCollection = JSONStoreCollection(name: "people")
```

```
collection.setSearchField("name", withType: JSONStore_String)  
collection.setSearchField("age", withType: JSONStore_Integer)
```

```
do {  
    try JSONStore.sharedInstance().openCollections([collection], withOptions: nil)  
} catch let error as NSError {  
    // handle error  
}
```

Get

Use `getCollectionWithName` to create an accessor to the collection. You must call `openCollections` before you call `getCollectionWithName`.

```
let collectionName:String = "people"  
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)
```

The variable `collection` can now be used to perform operations on the `people` collection such as `add`, `find`, and `replace`.

Add

Use `addData` to store data as documents inside a collection.

```
let collectionName:String = "people"  
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)  
  
let data = ["name" : "yoel", "age" : 23]  
  
do {  
    try collection.addData([data], andMarkDirty: true, withOptions: nil)  
} catch let error as NSError {  
    // handle error  
}
```

Find

Use `findWithQueryParts` to locate a document inside a collection by using a query. Use `findAllWithOptions` to retrieve all the documents inside a collection. Use `findWithIds` to search by the document unique identifier.

```

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

let options:JSONStoreQueryOptions = JSONStoreQueryOptions()
// returns a maximum of 10 documents, default: returns every document
options.limit = 10

let query:JSONStoreQueryPart = JSONStoreQueryPart()
query.searchField("name", like: "yoel")

do {
    let results:NSArray = try collection.findWithQueryParts([query], andOptions: options)
} catch let error as NSError {
    // handle error
}

```

Replace

Use `replaceDocuments` to modify documents inside a collection. The field that you use to perform the replacement is `_id`, the document unique identifier.

```

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

var document:Dictionary<String, AnyObject> = Dictionary()
document["name"] = "chevy"
document["age"] = 23

var replacement:Dictionary<String, AnyObject> = Dictionary()
replacement["_id"] = 1
replacement["json"] = document

do {
    try collection.replaceDocuments([replacement], andMarkDirty: true)
} catch let error as NSError {
    // handle error
}

```

This examples assumes that the document `{_id: 1, json: {name: 'yoel', age: 23} }` is in the collection.

Remove

Use `removeWithIds` to delete a document from a collection. Documents are not erased from the collection until you call `markDocumentClean`. For more information, see the **MobileFirst Adapter Integration** section later in this tutorial.

```

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

do {
    try collection.removeWithIds([1], andMarkDirty: true)
} catch let error as NSError {
    // handle error
}

```

Remove Collection

Use `removeCollection` to delete all the documents that are stored inside a collection. This operation is similar to dropping a table in database terms.

```

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

do {
    try collection.removeCollection()
} catch let error as NSError {
    // handle error
}

```

Destroy

Use `destroyData` to remove the following data:

- All documents
- All collections
- All Stores - See **Multiple User Support** later in this tutorial
- All JSONStore metadata and security artifacts - See **Security** later in this tutorial

```

do {
    try JSONStore.sharedInstance().destroyData()
} catch let error as NSError {
    // handle error
}

```

Advanced Usage

Security

You can secure all the collections in a store by passing a `JSONStoreOpenOptions` object with a password to the `openCollections` function. If no password is passed, the documents of all the collections in the store are not encrypted.

Some security metadata is stored in the keychain (iOS).

The store is encrypted with a 256-bit Advanced Encryption Standard (AES) key. All keys are strengthened with Password-Based Key Derivation Function 2 (PBKDF2).

Use `closeAllCollections` to lock access to all the collections until you call `openCollections` again. If

you think of `openCollections` as a login function you can think of `closeAllCollections` as the corresponding logout function.

Use `changeCurrentPassword` to change the password.

```
let collection:JSONStoreCollection = JSONStoreCollection(name: "people")
collection.setSearchField("name", withType: JSONStore_String)
collection.setSearchField("age", withType: JSONStore_Integer)

let options:JSONStoreOpenOptions = JSONStoreOpenOptions()
options.password = "123"

do {
    try JSONStore.sharedInstance().openCollections([collection], withOptions: options)
} catch let error as NSError {
    // handle error
}
```

Multiple User Support

You can create multiple stores that contain different collections in a single MobileFirst application. The `openCollections` function can take an options object with a username. If no username is given, the default username is "jsonstore".

```
let collection:JSONStoreCollection = JSONStoreCollection(name: "people")
collection.setSearchField("name", withType: JSONStore_String)
collection.setSearchField("age", withType: JSONStore_Integer)

let options:JSONStoreOpenOptions = JSONStoreOpenOptions()
options.username = "yoel"

do {
    try JSONStore.sharedInstance().openCollections([collection], withOptions: options)
} catch let error as NSError {
    // handle error
}
```

MobileFirst Adapter Integration

This section assumes that you are familiar with MobileFirst adapters. MobileFirst Adapter Integration is optional and provides ways to send data from a collection to an adapter and get data from an adapter into a collection.

You can achieve these goals by using functions such as `WLResourceRequest`.

Adapter Implementation

Create a MobileFirst adapter and name it "**People**". Define its procedures `addPerson`, `getPeople`, `pushPeople`, `removePerson`, and `replacePerson`.

```

function getPeople() {
    var data = { peopleList : [{name: 'chevy', age: 23}, {name: 'yoel', age: 23}] };
    WL.Logger.debug('Adapter: people, procedure: getPeople called. ');
    WL.Logger.debug('Sending data: ' + JSON.stringify(data));
    return data;
}
function pushPeople(data) {
    WL.Logger.debug('Adapter: people, procedure: pushPeople called. ');
    WL.Logger.debug('Got data from JSONStore to ADD: ' + data);
    return;
}
function addPerson(data) {
    WL.Logger.debug('Adapter: people, procedure: addPerson called. ');
    WL.Logger.debug('Got data from JSONStore to ADD: ' + data);
    return;
}
function removePerson(data) {
    WL.Logger.debug('Adapter: people, procedure: removePerson called. ');
    WL.Logger.debug('Got data from JSONStore to REMOVE: ' + data);
    return;
}
function replacePerson(data) {
    WL.Logger.debug('Adapter: people, procedure: replacePerson called. ');
    WL.Logger.debug('Got data from JSONStore to REPLACE: ' + data);
    return;
}

```

Load data from MobileFirst Adapter

To load data from a MobileFirst Adapter use `WLResourceRequest`.

```

// Start - LoadFromAdapter
class LoadFromAdapter: NSObject, WLDelegate {
    func onSuccess(response: WLResponse!) {
        let responsePayload: NSDictionary = response.getResponseJson()
        let people: NSArray = responsePayload.objectForKey("peopleList") as! NSArray
        // handle success
    }

    func onFailure(response: WLFailResponse!) {
        // handle failure
    }
}
// End - LoadFromAdapter

let pull = WLResourceRequest(URL: NSURL(string: "/adapters/People/getPeople"), method: "GET")

let loadDelegate: LoadFromAdapter = LoadFromAdapter()
pull.sendWithDelegate(loadDelegate)

```

Get Push Required (Dirty Documents)

Calling `allDirty` returns an array of so called "dirty documents", which are documents that have local modifications that do not exist on the back-end system.

```

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

do {
    let dirtyDocs:NSArray = try collection.allDirty()
} catch let error as NSError {
    // handle error
}

```

To prevent JSONStore from marking the documents as "dirty", pass the option `andMarkDirty:false` to `add`, `replace`, and `remove`.

Push changes

To push changes to a MobileFirst adapter, call the `allDirty` to get a list of documents with modifications and then use `WLResourceRequest`. After the data is sent and a successful response is received make sure you call `markDocumentsClean`.

```

// Start - PushToAdapter
class PushToAdapter: NSObject, WLDelegate {
    func onSuccess(response: WLResponse!) {
        // handle success
    }

    func onFailure(response: WLFailResponse!) {
        // handle failure
    }
}
// End - PushToAdapter

let collectionName:String = "people"
let collection:JSONStoreCollection = JSONStore.sharedInstance().getCollectionWithName(collectionName)

do {
    let dirtyDocs:NSArray = try collection.allDirty()
    let pushData:NSData = NSKeyedArchiver.archivedDataWithRootObject(dirtyDocs)

    let push = WLResourceRequest(URL: NSURL(string: "/adapters/People/pushPeople"), method: "POST")

    let pushDelegate:PushToAdapter = PushToAdapter()
    push.sendWithData(pushData, delegate: pushDelegate)

} catch let error as NSError {
    // handle error
}

```

Sample application

The JSONStoreSwift project contains a native iOS Swift application that utilizes the JSONStore API set.

Included is a JavaScript adapter Maven project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/JSONStoreSwift/tree/release80>) the Native iOS project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/JSONStoreAdapter/tree/release80>) the adapter Maven project.

Sample usage

Follow the sample's README.md file for instructions.

