

Application Authenticity Protection in Native Android applications

This is a continuation of the Application Authenticity Protection (../) tutorial.

Adding required files

From the MobileFirst project's Native API folder, copy the following folders to your native's project lib folder: armabi, armabi-v7a, mips, x86.

application-descriptor.xml

Adding the security test

Modify the application-descriptor.xml file of your application.

Add the *securityTest* attribute to the Android or iPhone/iPad environment element. For example:

```
<iphone bundleId="com.worklight.MyBankApp" applicationId="MyBankApp" securityTest="customTests" version="1.0">
```

Adding the public signing key

Extract the public signing key of the certificate that is used to sign application bundle (apk file).

- If building the application for distribution (production), extract the public key from the certificate that is used to sign the production ready application.
- If building an application in the development environment, the default public key that is supplied by the Android SDK can be used. The development certificate can be found in a keystore that is in a **{user-home}/.android/debug.keystore** file.


The public signing key can be extracted either manually or by using the wizard that MobileFirst Studio provides.

To use the wizard:

- Right-click the Android NativeAPI folder and select **Extract public signing key**.
- Specify the location and the password of a keystore file, and click **Load Keystore**. The default password for debug.keystore is "android".
- Set the **Key alias** and click **Next**.
- A dialog opens that displays the public key.
- Click **Finish** to automatically paste the public signing key to the relevant section of the application-descriptor.xml file.



Add the Application package name by using the Application Descriptor Editor (design view):



Take the Application package name value from the package attribute of the *manifest* node in the **AndroidManifest.xml**.

If you decide to change the value to another, verify that you change it in both locations.

The application-descriptor.xml file can also be edited directly to add the *packageName*:

```
<android version="1.0" securityTest="customTests">
  <worklightSettings include="false"/>
  <security>
    <encryptWebResources enabled="false"/>
    <testWebResourcesChecksum enabled="false"
      ignoreFileExtensions="png, jpg, jpeg, gif, mp4, mp3"/>
  >
    <publicSigningKey>MIGfM ...</publicSigningKey>
    <packageName>com.MyBankApp</packageName>
  </security>
</android>
```