

Setting up the MobileFirst development environment

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/setting-up-your-development-environment/mobilefirst-development-environment.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

Overview

The IBM MobileFirst Platform Foundation components can be installed either separately via online repositories, or downloaded bundled together for offline installation using the Development Kit Installer.

This tutorial expands on the components of IBM MobileFirst Platform Foundation and the setup needed to get started with the MobileFirst Development environment.

Jump to:

- Development Kit
- MobileFirst Platform Foundation components
- Applications and Adapters Development
- Tutorials to follow next

Development Kit

The development kit provides a ready-for-development environment with minimal configuration needed.

The Development Kit consists of: MobileFirst Server, MobileFirst Developer Command-line Interface (CLI), MobileFirst Operations Console and the MobileFirst client SDKs.

MobileFirst Platform Foundation Development Kit Installer

The Installer can be downloaded ahead of time and be used for "offline situations", where Internet connectivity is not available. The Installer pre-packages the MobileFirst Server, The MobileFirst Developer CLI and the MobileFirst client SDKs for manual installation.

To download the installer, visit the downloads (file:///home/travis/build/MFPSamples/DevCenter/_site/downloads/) page.

MobileFirst Platform Foundation components

MobileFirst Server

As part of the Development Kit, the MobileFirst Server is provided pre-deployed on a WebSphere Liberty profile application server. The server is pre-configured with an "mfp" runtime and uses a filesystem-based Apache Derby database.

To download and install the MobileFirst Server, visit the downloads (</downloads/>) page. If using MobileFirst Server on IBM Containers, see the Using Foundation Tile ([../ibm-containers/](https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/using-foundation-tile-on-ibm-containers/)) tutorial.

In the server directory, available are the following scripts:

- `console.[sh|cmd]`: Open the local MobileFirst Console

- `run . [sh|cmd]` : Run the local MobileFirst Server with trailing Liberty Server messages
 - Add the `-bg` flag to run the process in the background
- `start . [sh|cmd]` : Run the local MobileFirst Server in the background
- `stop . [sh|cmd]` : Stop the current local MobileFirst Server instance

Adding the MobileFirst Server to Eclipse

The MobileFirst Server can be integrated into the Eclipse IDE, allowing to quickly starting and stopping of the development server.

1. From the **Servers** view in Eclipse, select **New → Server**.
2. If an IBM folder option does not exist, click on "Download additional server adapters".
3. Select **WebSphere Application Server Liberty Tools** and follow the on-screen instructions.
4. From the **Servers** view in Eclipse, select **New → Server**.
5. Select **IBM → WebSphere Application Server Liberty**.
6. Provide a server **name** and **hostname** and click **Next**.
7. Provide the path to the server's root directory, and select a JRE version to use.
8. Click **Next** followed by clicking **Finish**.

MobileFirst Operations Console

The MobileFirst Server's Operations Console exposes the following functionalities.

A developer can:

- Register and deploy applications and adapters
- Optionally download native/Cordova application and adapter starter code templates
- Configure an application's authentication and security properties
- Manage applications:
 - Application Authenticity
 - Push Notifications
 - Direct Update
 - Remote Disable/Notify
- Generate DevOps scripts for continuous integration workflows and faster development cycles
- and more

Learn more about the MobileFirst Operations Console in the Using the MobileFirst Platform Operations Console (../quick-start/console/) tutorial.

MobileFirst Command-line Interface

The IBM MobileFirst command-line interface (CLI) tool enables developers to:

- Manage MobileFirst Servers
- Register and configure applications
- Create, build, deploy and test adapters

To download and install the MobileFirst Developer CLI, visit the downloads (/downloads/) page. Learn more about the various CLI commands in the Using CLI to manage MobileFirst artifacts (../using-the-mfpf-sdk/using-cli-to-manage-mobilefirst-artifacts/) tutorial.

MobileFirst Platform Foundation client and server SDKs & APIs

MobileFirst Platform Foundation provides client-side SDKs for Cordova applications as well as for Native platforms (iOS, Android and Windows 8.1 Universal & Windows 10 UWP). Server-side APIs for adapter development are available as well.

- To use the MobileFirst client SDKs, visit the Adding the MobileFirst Platform Foundation SDK ([../adding-the-mfpf-sdk/](#)) tutorials category.
- To use the MobileFirst server-side APIs, visit the Adapters ([../adapters/](#)) tutorials category.

Manual installation

If the MobileFirst SDKs were downloaded as part of the MobileFirst Platform Foundation Development Kit Installer, visit the user documentation (http://www-01.ibm.com/support/knowledgecenter/SSHS8R_8.0.0/wl_welcome.html) for setup instructions.

Applications and adapters development

You can use your preferred code editor, such as Atom.io, Visual Studio Code, Eclipse, IntelliJ and others, to implement applications and adapters.

For adapters development, refer to the Adapters ([../adapters/](#)) category as well as to the Developing Adapters in IDEs ([../adapters/developing-adapters](#)) and testing and debugging adapters ([../adapters/testing-and-debugging-adapters](#)) tutorials.

Note: API auto-completion is available only in Typescript-supporting editors.

Tutorials to follow next

Visit the All Tutorials ([../all-tutorials/](#)) page and select a tutorials category to follow next.