

# The Application Center console

## Overview

With the Application Center console, you can manage the repository of the Application Center and your applications.

The Application Center console is a web application to manage the repository of the Application Center. The Application Center repository is the central location where you store the mobile applications that can be installed on mobile devices.

Use the Application Center console to:

- Upload applications that are written for these operating systems: Android, iOS, Windows 8 (Windows Store packages only), or Windows Phone 8.
- Manage several different versions of mobile applications.
- Review the feedback of testers of mobile applications.
- Define the users who have the rights to list and install an application on the mobile devices.
- Track which applications are installed on which devices.

### Notes:

- Only users with the administrator role can log in to the Application Center console.
- Multicultural support: the user interface of the Application Center console has not been translated.

### Jump to

- Starting the Application Center console
- Troubleshooting a corrupted login page (Apache Tomcat)
- Troubleshooting a corrupted login page in Safari browsers
- Application Management
- Adding a mobile application
- Adding an application from a public app store
- Application properties
- Editing application properties
- Upgrading a mobile application in MobileFirst Server and the Application Center
- Downloading an application file

In the Application Center console, you can see reviews about mobile application versions sent by users.

- User and group management
- Access control
- Managing access control
- Device Management
- Application enrollment tokens in Windows 8 Universal
- Signing out of the Application Center console

## Starting the Application Center console

You can start the Application Center with your web browser and log in if you have the administrator role.

1. Start a web browser session on your desktop.
2. Contact your system administrator to obtain the address and port of the server where the Application Center is installed.
3. Enter the following URL: `http://server/appcenterconsole`
4. Where **server** is the address and port of the server where the Application Center is installed:  
`http://localhost:9080/appcenterconsole`

Log in to the Application Center console. Contact your system administrator to get your credentials so that you can log in to the Application Center console.



**Note:** Only users with the administrator role can log in to the Application Center console.

## Troubleshooting a corrupted login page (Apache Tomcat)

You can recover from a corrupted login page of the Application Center console when the Application Center is running in Apache Tomcat.

When the Application Center is running in Apache Tomcat, the use of a wrong user name or password might corrupt the login page of the Application Center console.

When you try to log in to the console with an incorrect user name or an incorrect password, you receive an error message. When you correct the user name or password, instead of a successful login, you have one of the following errors; the message depends on your web browser.

- The same error message as before
- The message **The connection was reset**
- The message **The time allowed for login exceeded**

The behavior is linked to the management by Apache Tomcat of the `j_securitycheck` servlet. This behavior is specific to Apache Tomcat and does not occur in any of the WebSphere Application Server profiles.

The workaround is to click the refresh button of the browser to refresh the web page after a login failure. Then, enter the correct credentials.

## Troubleshooting a corrupted login page in Safari browsers

You can recover from a corrupted login page of the Application Center console when you use the Safari browser.

When the Application Center console is open in a Safari browser, you might navigate away from the console. When you come back to the console, you might see the login page. Even though you enter the correct login details, you see the following message instead of a successful login: **HTTP Status 404 - appcenterconsole/j\_securitycheck**.

The behavior is linked to a caching problem in the Safari browser.

The workaround is to trigger a forced reload when you see the login page without entered or autocompleted credentials. Here is how to trigger a forced reload:

- On a Mac computer, press Shift + the **Refresh** button.
- On an iPad or iPhone device: Double-click the refresh button or clean the cache by closing Safari: you double-click the home button and then swipe Safari away.

## Application Management

You can use Application Management to add new applications and versions and to manage those applications. The Application Center enables you to add new applications and versions and to manage those applications.

Click **Applications** to access Application Management.

## Application Center installed on WebSphere Application Server Liberty profile or on Apache Tomcat

Installations of the Application Center on these application servers, during installation of IBM MobileFirst Foundation with the IBM Installation Manager package, have two different users defined that you can use to get started.

- User with login **demo** and password **demo**
- User with login **appcenteradmin** and password **admin**

## WebSphere Application Server full profile

If you installed the Application Center on WebSphere Application Server full profile, one user named appcenteradmin is created by default with the password indicated by the installer.

The screenshot displays the Application Center console interface. The top navigation bar includes tabs for 'Application Center', 'Applications', 'Devices', and 'Users / Groups'. The 'Applications' tab is selected. The header also shows a user greeting 'Welcome demo' with a 'Sign out' link, a settings icon, and the IBM logo. Below the navigation bar, the breadcrumb 'You are in: Applications' is visible. The main section is titled 'Application Management' and includes a search bar. Underneath, the 'Available Applications' section features an 'Add Application' button. A table lists the available applications, showing one entry: 'AppMan Sample' for iOS, provided by 'AppMan', with 'Access control: unrestricted', version '1.0', and a date of '10/24/13'. It also shows a star rating of 0. The table is paginated, showing '1 of 1' items on 'Page 1'. At the bottom, there are controls for showing rows (5, 10, 20, 50, or all rows), a 'Jump to page' selector set to 1 of 1, and 'Previous' and 'Next' navigation links.

## Adding a mobile application

You can add applications to the repository on the server by using the Application Center console. These applications can then be installed on mobile devices by using the mobile client.

In the Applications view, you can add applications to Application Center. Initially the list of applications is empty and you must upload an application file. Application files are described in this procedure.

To add an application to make it available for installation on mobile devices:

1. Click **Add Application**.
2. Click **Upload**.
3. Select the application file to upload to the Application Center repository.

### Android

The application file name extension is .apk.

### iOS

The application file name extension is .ipa for normal iOS applications.

### Windows Phone 8

The application file name extension is .xap. The application must be signed with a company account. The application enrollment token for this company account must be made available to Windows Phone 8 devices before the application can be installed on the devices. See Application enrollment tokens in Windows 8 Universal for details.

### Windows 8

The application is provided as a Windows Store package; the file extension is .appx.

Windows Store .appx packages can depend on one or more Windows component library app packages, also known as "framework" packages. MobileFirst hybrid applications for Windows 8 depend on the Microsoft.WinJS framework package. When you use Microsoft Visual Studio to generate the application package, the dependencies packages are also generated and packaged as separate .appx files. To successfully install such applications by using the mobile client, you must upload the application .appx package and any other dependency package onto the Application Center server. When you upload a dependency package, it appears as inactive in the Application Center console. This behavior is expected, so that the framework package does not appear as an installable application in the client. Later, when a user installs an application, the mobile client checks whether the dependency is already installed on the device. If the dependency package is not installed, the client automatically retrieves the dependency package from the Application Center server and installs it on the device. For more information about dependencies, see Dependencies (<http://msdn.microsoft.com/library/windows/apps/hh464929.aspx#dependencies>) in the Windows developer documentation about packages and deployment of applications.

4. Click **Next** to access the properties to complete the definition of the application.
5. Complete the properties to define the application. See Application properties for information about how to complete property values.
6. Click **Finish**.


Application Center

Applications

Devices

Users / Groups

Welcome demo  
Sign out



IBM

You are in: Applications > Add an application

## Application Management

### Add an application

#### Application Details

Package, Version and Label must be set in the uploaded application package and cannot be modified afterwards.

Package:	AppMan
	Identifies the application
Internal Version:	1.0
	Internal version number used to compare versions
Commercial Version:	No value set
	Version displayed on the mobile device
* Label:	AppMan Sample
	Label of the application as defined by the developer
External URL:	ibmappctr://show-app?id=AppMan
	URL to open the Application Center mobile client on this application.
Author:	demo
	User who has uploaded this application
Description:	
	(2048 characters maximum)
Minimal OS Version:	3.1
	The application runs on devices with OS at least this version
Device Family:	iphone
	The application runs on devices from this device family
Recommended:	<input type="checkbox"/>
	This application will be listed as a recommended application on the mobile device
Installer:	<input type="checkbox"/>
	Indicates whether this application is an installer
Active:	<input checked="" type="checkbox"/>
	An active application can be installed on a device
Ready for production:	<input type="checkbox"/>
	Indicates whether this application is ready for production
Instrumented	No
	Indicates whether this application is instrumented for IBM MobileFirst Platform Test Workbench

Previous

Done

Cancel

## Adding an application from a public app store

Application Center supports adding to the catalog applications that are stored in third-party application stores, such as Google play or Apple iTunes.

Applications from third-party app stores appear in the Application Center catalog like any other application, but users are directed to the corresponding public app store to install the application. You add an application from a public app store in the console, in the same place where you add an application that was created within your own enterprise. See [Adding a mobile application](#).

**Note:** Currently, the Application Center supports only Google Play and Apple iTunes. Windows Phone Store and Windows Store are not yet supported.

Instead of the application executable file, you must provide a URL to the third-party application store where the application is stored. To find the correct application link more easily, the console provides direct links in the **Add an application** page to the supported third-party application store websites.

The Google play store address is <https://play.google.com/store/apps> (<https://play.google.com/store/apps>).

The Apple iTunes store address is <https://linkmaker.itunes.apple.com/> (<https://linkmaker.itunes.apple.com/>); use the linkmaker site rather than the iTunes site, because you can search this site for all kinds of iTunes items, including songs, podcasts, and other items that are supported by Apple. Only selecting iOS applications provides you with compatible links to create application links.

1. Click the URL of the public app store that you want to browse.
2. Copy the URL of the application in the third-party app store to the **Application URL** text field in the **Add an application** page of the Application Center console.
  - o **Google Play:**
    - Select an application in the store.
    - Click the detail page of the application.
    - Copy the address bar URL.
  - o **Apple iTunes:**
    - When the list of items is returned in the search result, select the item that you want.
    - At the bottom of the selected application, click **Direct Link** to open the application details page.
    - Copy the address bar URL.

**Note:** Do not copy the **Direct Link** to the Application Center. **Direct Link** is a URL with redirection, you will need to get the URL it redirects to.
3. When the application link is in the **Application URL** text field of the console, click **Next** to validate the creation of the application link.
  - o If the validation is unsuccessful, an error message is displayed in the **Add an application** page. You can either try another link or cancel the attempt to create the current link.
  - o If the validation is successful, this action displays the application properties. You can then modify the application description in the application properties before you move to the next step.

You are in: [Applications](#) > Add an application

# Application Management

## Add an application

### Application Details

Package, Version and Label must be set in the uploaded application package and cannot be modified afterwards.

Package:	com.ibm.android.sametime <small>Identifies the application</small>
* Label:	<input type="text" value="IBM Sametime"/> <small>Label of the application as defined by the developer</small>
Author:	admin <small>User who has uploaded this application</small>
Vendor:	IBM Collaboration Solutions <small>Vendor who has created this application</small>
Description:	<div><p>IBM Sametime for Android provides access to IBM's award-winning platform for Social Communications on today's hottest Android devices, now with phone and tablet support. **** REQUIREMENT: The IBM Sametime Mobile Client for Android devices does not connect directly to a Sametime Community Server. The Sametime 8.5.2 IFR 1 Proxy Server must be deployed in your infrastructure environment in order for the Android Sametime client to work. Check with your IT department to see if this is the case. You will need to obtain the Sametime proxy server address and port to configure the client. After installing the application enter the proxy server address in the server field in the format :, then enter your Sametime credentials and select the Next button. Features: - Support for IBM SmartCloud - Support for Android phones and tablets - ...</p></div> <div>(2048 characters maximum)</div>
Active:	<input checked="" type="checkbox"/> <small>An active application can be installed on a device</small>

Previous

Done

Cancel

4. Click **Done** to create the application link.

This action makes the application available to the corresponding version of the Application Center mobile client. A small link icon appears on the application icon to show that this application is stored in a public app store and is different from a binary app.



Application Center
Applications
Devices
Users / Groups

Welcome demo
Sign out

You are in: Applications

# Application Management


Search

## Available Applications

Add Application

1 of 1
Page 1
Previous
Next

Sort by: Label ^ OS Update Date
Filter: Show all applications



**IBM Sametime**  
Android  
com.ibm.android.sametime  
Access control: **unrestricted**

Show: 5 10 20 50 All rows
Jump to page 1 of 1
Previous
Next

## Application properties

Applications have their own sets of properties, which depend on the operating system on the mobile device and cannot be edited. Applications also have a common property and editable properties.

The values of the following fields are taken from the application and you cannot edit them.

- **Package.**
- **Internal Version.**
- **Commercial Version.**
- **Label.**
- **External URL**; this property is supported for applications that run on Android, iOS, and Windows Phone 8.

## Properties of Android applications

For more information about the following properties, see the Android SDK documentation.

- **Package** is the package name of the application; **package** attribute of the manifest element in the manifest file of the application.
- **Internal Version** is the internal version identification of the application; **android:versionCode** attribute of the **manifest** element in the manifest file of the application.
- **Commercial Version** is the published version of the application.
- **Label** is the label of the application; **android:label** attribute of the application element in the **manifest** file of the application.
- **External URL** is a URL that you can use to have the mobile client of the Application Center started automatically in the Details view of the latest version of the current application.

## Properties of iOS applications

For more information about the following properties, see the iOS SDK documentation.

- **Package** is the company identifier and the product name; **CFBundleIdentifier** key.
- **Internal Version** is the build number of the application; **CFBundleVersion** key of the application.
- **Commercial Version** is the published version of the application.
- **Label** is the label of the application; **CFBundleDisplayName** key of the application.
- **External URL** is a URL that you can use to have the mobile client of the Application Center started automatically in the Details view of the latest version of the current application.

## Properties of Windows Phone 8 applications

For more information about the following properties, see the Windows Phone documentation.

- **Package** is the product identifier of the application; **ProductID** attribute of the App element in the manifest file of the application.
- **Internal Version** is the version identification of the application; **Version** attribute of the App element in the manifest file of the

application.

- **Commercial Version**, like **Internal Version**, is the version of the application.
- **Label()** is the title of the application; **Title** attribute of the **App** element in the manifest file of the application.
- **Vendor** is the vendor who created the application; **Publisher** attribute of the **App** element in the manifest file of the application.
- **External URL** is a URL that you can use to have the mobile client of the Application Center started automatically in the Details view of the latest version of the current application.
- **Commercial Version**, like **Internal Version**, is the version of the application.

## Properties of Windows Store applications

For more information about the following properties, see the Windows Store documentation about application development.

- **Package** is the product identifier of the application; **Package** name attribute in the manifest file of the application.
- **Internal Version** is the version identification of the application; **Version** attribute in the manifest file of the application.
- **Commercial Version**, like **Internal Version**, is the version of the application.
- **Label** is the title of the application; **Package** display name attribute in the manifest file of the application.
- **Vendor** is the vendor who created the application; **Publisher** attribute in the manifest file of the application.

## Common property: Author

The **Author** field is read-only. It displays the **username** attribute of the user who uploads the application.

## Editable properties

You can edit the following fields:

### Description

Use this field to describe the application to the mobile user.

### Recommended

Select **Recommended** to indicate that you encourage users to install this application. Recommended applications appear as a special list in the mobile client.

### Installer

For the Administrator only: This property indicates that the application is used to install other applications on the mobile device and send feedback on an application from the mobile device to the Application Center. Usually only one application is qualified as **Installer** and is called the mobile client. This application is documented in The mobile client (../mobile-client).

### Active

Select **Active** to indicate that an application can be installed on a mobile device.

- If you do not select **Active**, the mobile user does not see the application in the list of available applications that is displayed on the device and the application is inactive.
- In the list of available applications in Application Management, if **Show inactive** is selected, the application is disabled. If **Show inactive** is not selected, the application does not appear in the list of available applications.

### Ready for production

Select **Ready for production** to indicate that an application is ready to be deployed in a production environment and is therefore suitable to be managed by Tivoli Endpoint Manager through its application store. Applications for which this property is selected are the only ones that are flagged to Tivoli Endpoint Manager.

## Editing application properties

You can edit the properties of an application in the list of uploaded applications.

To edit the properties of an uploaded application:

1. Select **Applications** to see the list of uploaded applications: Available Applications.
2. Click the version of the application to edit the properties: Application Details.
3. Edit any of the editable properties that you want. See Application properties for details about these properties. The name of the current application file is shown after the properties.

**Important:** If you want to update the file, it must belong to the same package and be the same version number. If either of these properties is not the same you must go back to the application list and add the new version first.

4. Click **OK** to save your changes and return to Available Applications or **Apply** to save and keep Application Details open.



You are in: Applications > Application properties



# AppMan Sample (iOS)

## Version 1.0

- Properties
- Reviews

## Edit application properties

### Application Details

Package, Version and Label must be set in the uploaded application package and cannot be modified afterwards.

Package:	AppMan	Identifies the application
Internal Version:	1.0	Internal version number used to compare versions
Commercial Version:	No value set	Version displayed on the mobile device
* Label:	<input type="text" value="AppMan Sample"/>	Label of the application as defined by the developer
External URL:	ibmappctr://show-app?id=AppMan	URL to open the Application Center mobile client on this application.
Author:	demo	User who has uploaded this application
Description:	<input type="text"/>	(2048 characters maximum)
Minimal OS Version:	3.1	The application runs on devices with OS at least this version
Device Family:	iphone	The application runs on devices from this device family
Recommended:	<input type="checkbox"/>	This application will be listed as a recommended application on the mobile device
Installer:	<input type="checkbox"/>	Indicates whether this application is an installer
Active:	<input checked="" type="checkbox"/>	An active application can be installed on a device
Ready for production:	<input type="checkbox"/>	Indicates whether this application is ready for production
Instrumented	No	Indicates whether this application is instrumented for IBM Mobile Test Workbench for Worklight

### Application File

Define an application file with an ipa extension for an iOS application to update the application.

Current:	appman.ipa
New file:	<input type="text"/> <input type="button" value="Upload..."/>

OK

Cancel

Apply

Delete

## Upgrading a mobile application in MobileFirst Server and the Application Center

You can easily upgrade deployed mobile applications by using a combination of MobileFirst Operations Console and the Application Center.

The mobile client of the Application Center must be installed on the mobile device. The HelloWorld application must be installed on the mobile device and must connect to MobileFirst Server when the application is running.

You can use this procedure to update Android, iOS, and Windows Phone applications that have been deployed on MobileFirst Server and also in the Application Center. In this task, the application HelloWorld version 1.0 is already deployed on MobileFirst Server and in the Application Center.

HelloWorld version 2.0 is released and you would like users of version 1.0 to upgrade to the later version. To deploy the new version of the application:

1. Deploy HelloWorld 2.0 in the Application Center. See Adding a mobile application.
2. From the Application Details page, copy the setting of the external URL.


### Application Details

Package, Version and Label must be set in the uploaded application package and cannot be modified afterwards.


Package:	com.HelloWorld
	Identifies the application
Internal Version:	2
	Internal version number used to compare versions
Commercial Version:	2.0
	Version displayed on the mobile device
* Label:	<input type="text" value="HelloWorld"/>
	Label of the application as defined by the developer
External URL:	<input type="text" value="ibmappctr://show-app?id=com.HelloWorld"/>
	URL to open the Application Center mobile client on this application.

3. When the external URL is copied to the clipboard, open the MobileFirst Operations Console.
4. Change the access rule of HelloWorld version 1.0 to "Access Disabled".
5. Paste the external URL into the URL field.

Running the client: When a mobile device connects to MobileFirst Server to try to run HelloWorld version 1.0, the device user is requested to upgrade the version of the application.



6. Click **Upgrade** to open the Application Center client. When the login details are correctly completed, you access the Details page of HelloWorld version 2.0 directly.



## Downloading an application file

You can download the file of an application registered in the Application Center.

1. Select **Applications** to see the list of uploaded applications: **Available Applications**.
2. Tap the version of the application under **Application Details**.
3. Tap the file name in the "Application File" section.

## Viewing application reviews

In the Application Center console, you can see reviews about mobile application versions sent by users.


Users of mobile applications can write a review, which includes a rating and a comment, and submit the review through the Application Center client. Reviews are available in the Application Center console and the client. Individual reviews are always associated with a particular version of an application.

To view reviews from mobile users or testers about an application version:

1. Select **Applications** to see the list of uploaded applications: **Available Applications**.
2. Select the version of the application.
3. In the menu, select **Reviews**.

The rating is an average of the ratings in all recorded reviews. It consists of one to five stars, where one star represents the lowest level of appreciation and five stars represent the highest level of appreciation. The client cannot send a zero star rating.

The average rating gives an indication of how the application satisfies the intended use of the application.

4. Click the two arrow heads  to expand the comment that is part of the review and to view the details of the mobile device where the review is generated.

For example, the comment can give the reason for submitting the review, such as failure to install. If you want to delete the review, click the trash can icon to the right of the review that you want to delete.

## User and group management

You can use users and groups to define who has access to some features of the Application Center, such as installing applications on mobile devices.

Use users and groups in the definition of access control lists (ACL).

### Managing registered users

To manage registered users, click the **Users/Groups** tab and select **Registered users**. You obtain a list of registered users of the Application Center that includes:

- Mobile client users
- Console users
- Local group members
- Members of an access control list

You are in: Users/Groups > Users

## User and Group Management

User Groups

Registered Users

### Registered Users

Registered users of the Application center: mobile users, console users, local group members or members of access control list.

Register user...

1 of 1	Page 1	Previous	Next
Sort by: Name ^			
 demo	demo		
Show: 10   20   50   100   All items	Jump to page 1 of 1	Previous	Next

If the Application Center is connected to an LDAP repository, you cannot edit the user display names. If the repository is not LDAP, you can change a user display name by selecting it and editing it.

To register new users, click **Register User**, enter the login name and the display name, and click **OK**.

To unregister a user, click the trash icon next to the user name.

- Removing feedback given by the user
- Removing the user from the access control lists
- Removing the user from local groups

**Note:** When you unregister a user, the user is not removed from the application server or the LDAP repository.

### Managing local groups

To manage local groups, click the **Users/Groups** tab and select **User group**.

To create a local group, click **Create group**. Enter the name of the new group and click **OK**.

If the Application Center is connected to an LDAP repository, the search includes local groups as well as the groups defined in the LDAP repository. If the repository is not LDAP, only local groups are available to the search.

You are in: Users/Groups > Groups

## User and Group Management

User Groups

Registered Users

### User Groups

Groups defined in Application Center that are available when defining access control lists.

Create group...

1 of 1	Page 1	Previous	Next
Sort by: Name ^			
 <b>New Group</b>	Edit members		
Show: 10   20   50   100   All items	Jump to page 1 of 1	Previous	Next

To delete a group, click the trash icon next to the group name. The group is also removed from the access control lists.  
To add or remove members of a group, click the **Edit members** link of the group.

The screenshot shows the 'Users / Groups' tab in the Application Center. The breadcrumb trail is 'You are in: Users/Groups > Group Members'. The main heading is '"New Group" group members'. Below this is a search bar with 'demo' entered and an 'Add' button. A dropdown menu shows 'demo (demo)' selected. Below the search bar is a table with 0 of 0 members. The table has a 'Sort by: Name' dropdown. Below the table is a 'No member...' message. At the bottom, there is a pagination bar with 'Show: 10 | 20 | 50 | 100 | All items', 'Jump to page 0 of 0', and 'Previous | Next' links.

To add a new member, search for the user by entering the user display name, select the user, and click **Add**.

If the Application Center is connected to an LDAP repository, the search for the user is performed in the LDAP repository. If the repository is not LDAP, the search is performed in the list of registered users.

To remove a member from a group, click the cross icon to the right of the user name.

## Access control

You can decide whether installation of an application on mobile devices is open to any users or whether you want to restrict the ability to install an application.

Installation of applications on a mobile device can be limited to specific users or available to any users.

Access control is defined at the application level and not at the version level.

By default, after an application is uploaded, any user has the right to install the application on a mobile device.

The current access control for an application is displayed in Available Applications for each application. The unrestricted or restricted access status for installation is shown as a link to the page for editing access control.

Installation rights are only about the installation of the application on the mobile device. If access control is not enabled, everybody has access to the application.

## Managing access control

You can add or remove access for users or groups to install an application on mobile devices.

You can edit access control:

1. In Application Management under Available Applications, click the unrestricted or restricted state of Installation of an application.



2. Select **Access control enabled** to enable access control.
3. Add users or groups to the access list.

To add a single user or group, enter a name, select the entry in the matching entries found, and click **Add**.

If the Application Center is connected to an LDAP repository, you can search for users and groups in the repository as well as locally defined groups. If the repository is not LDAP, you can search only local groups and registered users. Local groups are exclusively defined in the **Users/Groups** tab. When you use the Liberty profile federated registry, you can only search for users by using the login name; the result is limited to a maximum of 15 users and 15 groups (instead of 50 users and 50 groups).

To register a user at the same time as you add the user to the access list, enter the name and click **Add**. Then you must specify the login name and the display name of the user.



To add all the users of an application, click **Add users from application** and select the appropriate application.  
To remove access from a user or group, click the cross icon on the right of the name.

Application Center

Applications

Devices

Users / Groups

Welcome demo  
Sign out

You are in: Applications > Access control list

AppMan Sample (iOS)

Installation Access Control

The users with permission to install this application on their devices.

☒ Access control enabled

Add

Import access control from application...

Select an existing user or register a new one.

1 of 1

Page 1

Previous

Next

Sort by: Name ^

demo

demo

Show: 10 | 20 | 50 | 100 | All items

Jump to page 1 of 1

Previous

Next

## Device Management

You can see the devices that connected to the Application Center from the Application Center mobile client and their properties.

**Device Management** shows under the **Registered Devices** the list of devices that have connected to the Application Center at least once from the Application Center mobile client.

Application Center

Applications

Devices

Users / Groups

Welcome demo  
Sign out

You are in: Devices

Device Management

Search

Registered Devices

1 of 1

Page 1

Previous

Next

Sort by: User Name | Device Name ^ | OS | Manufacturer | Model | Update Date

Demo's phone

demo | Apple iPhone 5S | 7.0 | Updated on 10/24/13

Show: 5 | 10 | 20 | 50 | All items

Jump to page 1 of 1

Previous

Next

## Device properties

Click a device in the list of devices to view the properties of the device or the applications installed on that device.

You are in: [Devices](#) > Properties



## Demo's phone

### Properties

Installed Applications

### Device Properties

* Name:	<input type="text" value="Demo's phone"/>
	<small>Name of the device</small>
Owner Name:	demo
Manufacturer:	Apple
Model:	iPhone 5S
Operating System:	iOS
Family:	iphone
Unique Identifier:	myDeviceId

Select **Properties** to view the device properties.

#### Name

The name of the device. You can edit this property.

**Note:** on iOS, the user can define this name in the settings of the device in Settings > General > Information > Name. The same name is displayed on iTunes.

#### User Name

The name of the first user who logged into the device.

#### Manufacturer

The manufacturer of the device.

#### Model

The model identifier.

#### Operating System

The operating system of the mobile device.

#### Unique identifier

The unique identifier of the mobile device.

If you edit the device name, click **OK** to save the name and return to Registered Devices or **Apply** to save and keep Edit Device Properties open.

### Applications installed on device

Select **Applications installed on device** to list all the applications installed on the device.



▼ Search 🔍



AppMan  
1.0

Show: 5 10 20 50 All items Jump to page 1 of 1 Previous Next

## Open issue

Privacy	( <a href="https://twitter.com/ibmmobiledev">https://twitter.com/ibmmobiledev</a> )	( <a href="https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/issues/new">https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/issues/new</a> )
( <a href="http://www.ibm.com/privacy/us/en/">http://www.ibm.com/privacy/us/en/</a> )	YouTube	
Terms of use	( <a href="https://www.youtube.com/channel/UCz1t4jKznci2Qusu97Q">https://www.youtube.com/channel/UCz1t4jKznci2Qusu97Q</a> )	Contribute
( <a href="file:///home/travis/build/MFPSamples/DevCenter/Cite/links/of-use/">file:///home/travis/build/MFPSamples/DevCenter/Cite/links/of-use/</a> )	Git Hub	( <a href="https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/blob/master/contributing.m">https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/blob/master/contributing.m</a>
Third party notice	( <a href="https://github.com/MobileFirst-Platform-Developer-Center">https://github.com/MobileFirst-Platform-Developer-Center</a> )	Report abuse
( <a href="file:///home/travis/build/MFPSamples/DevCenter/Platform-Developer-party-notice/">file:///home/travis/build/MFPSamples/DevCenter/Platform-Developer-party-notice/</a> )		( <a href="https://www.ibm.com/developerworks/commu">https://www.ibm.com/developerworks/commu</a>