

# Android end-to-end demonstration

fork and edit tutorial (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/>) | report issue (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/issues/new>)

## Overview

The purpose of this demonstration is to experience an end-to-end flow where an application and an adapter are registered using the MobileFirst Operations Console, an "skeleton" Android Studio project is downloaded and edited to call the adapter, and the result is printed to the log - verifying a successful connection with the MobileFirst Server.

### Prerequisites:

- Android Studio
- MobileFirst Developer CLI (download  
([file:///home/travis/build/MFPSamples/DevCenter/\\_site/downloads](file:///home/travis/build/MFPSamples/DevCenter/_site/downloads)))
- *Optional*. Stand-alone MobileFirst Server (download  
([file:///home/travis/build/MFPSamples/DevCenter/\\_site/downloads](file:///home/travis/build/MFPSamples/DevCenter/_site/downloads)))

## 1. Starting the MobileFirst Server

If a remote server was already set-up, skip this step.

From a **Command-line** window, navigate to the server's **scripts** folder and run the command: `./start.sh` in Mac and Linux or `start.cmd` in Windows.

## 2. Creating an application

In a browser window, open the MobileFirst Operations Console by loading the URL: `http://your-server-host:server-port/mfpconsole`. If running locally, use: `http://localhost:9080/mfpconsole` (`http://localhost:9080/mfpconsole`). The username/password are `admin/admin`.

1. Click on the "Create new" button next to **Applications** and select the desired *platform*, *identifier* and *version* values.



2. Click on the **Get Starter Code** tile and select to download the Android Starter Code.



### 3. Editing application logic

1. Open the Android Studio project.
2. Select the **app/java/com/mfp/sample/MainActivity.java** file and:
  - Add the following imports:

```
import com.worklight.wlclient.api.*;
import java.net.URI;
import android.util.Log;
```

- Paste the following code snippet, inside the `protected void onCreate()` function:

```

WLClient client = WLClient.createInstance(this);
URI adapterPath = null;
try {
    adapterPath = new URI("/adapters/javaAdapter/users/world");
} catch (URISyntaxException e) {
    e.printStackTrace();
}

WLResourceRequest request = new WLResourceRequest(adapterPath, WLResourceRequest.GET);
request.send(new WLResponseListener() {
    @Override
    public void onSuccess(WLResponse wlResponse) {
        // Will print "Hello world" in LogCat.
        Log.i("MobileFirst Quick Start", "Success: " + wlResponse.getResponseText());
    }

    @Override
    public void onFailure(WLFailResponse wlFailResponse) {
        Log.i("MobileFirst Quick Start", "Failure: " + wlFailResponse.getErrorMsg());
    }
});

```

## 4. Creating an adapter

1. Click on the "Create new" button next to **Adapters** and download the **Java** adapter sample.

If Maven and the MobileFirst Developer CLI are not installed, follow the on-screen **Setting up your environment** instructions to install.

The screenshot displays the MobileFirst Operations Console interface. On the left, a sidebar contains navigation links: Dashboard, Runtimes, mfp, Settings, Applications, Adapters, Devices, Client Logs, and Error Log. The 'Adapters' section is highlighted, showing a 'Create new' button. The main content area is titled 'Create a new Adapter' and includes a 'Deploy Adapter' button. Below the title, a message states 'It seems like you don't have any adapters, lets get started'. A section titled 'Follow these steps to set up an adapter' lists five steps: 1. Setting up your environment, 2. Start with a sample adapter, 3. In your IDE of choice, edit the adapter code - REST end points and adapter descriptor, 4. Build and package, and 5. Upload adapter. Step 2 is expanded, showing options for 'Console', 'CLI', and 'Maven', with a placeholder for console output.



- From a **Command-line** window, navigate to the adapter's Maven project root folder and run the command:

```
mfpdev adapter build
```

- When the build finishes, run the command:

```
mfpdev adapter deploy
```

If using a remote MobileFirst Server, run the command:

```
mfpdev adapter deploy Replace-with-remote-server-name
```

## 5. Testing the application

- In Android Studio, select the **[project]/app/src/main/assets/mfpclient.properties** file and edit the **host** property with the IP address of the MobileFirst Server.
- Click on the **Run App** button.

The adapter response is then printed in Android Studio's LogCat view.



## Next steps

Learn more on using adapters in applications, and how to integrate additional services such as Push Notifications, using the MobileFirst security framework and more:

- [Review the Server-side development tutorials \(../adapters/\)](#)
- [Review the Authentication and security tutorials \(../authentication-and-security/\)](#)
- [Review the Notifications tutorials \(../notifications/\)](#)
- [Review All Tutorials \(../all-tutorials\)](#)