

# Form-based authentication in native Android applications

## Overview

This tutorial illustrates the native Android client-side authentication components for form-based authentication. Make sure you read [Form-based authentication \(../\)](#) first.

## Creating the client-side authentication components

Create a native Android application and add the MobileFirst native APIs following the documentation.

Add an Activity, `LoginFormBasedAuth`, that will handle and present the login form.

Remember to add this Activity to the `AndroidManifest.xml` file as well.

## MyChallengeHandler

Create a `MyChallengeHandler` class as a subclass of `ChallengeHandler`.

`MyChallengeHandler` should implement `isCustomResponse` which checks every custom response received from MobileFirst Server to see if this is the challenge we are expecting.

```
public boolean isCustomResponse(WLResponse response) {  
    if (response == null || response.getResponseText() == null ||  
        response.getResponseText().indexOf("_security_check") == -1)  
    {  
        return false;  
    }  
    return true;  
}
```

`handleChallenge` is called after the `isCustomResponse` method returned true.

Here we use this method to present our login form.

```
public void handleChallenge(WLResponse response){  
    if (!isCustomResponse(response)) {  
        submitSuccess(response);  
    } else {  
        cachedResponse = response;  
        Intent login = new Intent(parentActivity,  
            LoginFormBasedAuth.class);  
        parentActivity.startActivityForResult(login, 1);  
    }  
}
```

`submitLogin` is called by the login form. If the user asked to abort this action we use `submitFailure()` method, otherwise we use `submitLoginForm()` method to send our input data to the authenticator.

```

public void submitLogin(int resultCode, String userName, String password, boolean back){
    if (resultCode != Activity.RESULT_OK || back) {
        submitFailure(cachedResponse);
    } else {
        HashMap<String, String> params = new HashMap<String, String>();
        params.put("_username", userName);
        params.put("_password", password);
        submitLoginForm("/_security_check", params, null, 0, "post");
    }
}

```

## Main Activity

In the Main Activity class connect to MobileFirst server, register your challengeHandler and invoke the protected adapter procedure.

The procedure invocation will trigger MobileFirst server to send a challenge that will trigger our challengeHandler.

```

final WLClient client = WLClient.createInstance(this);
client.connect(new MyConnectionListener());
challengeHandler = new AndroidChallengeHandler(this, realm);
client.registerChallengeHandler(challengeHandler);
invokeBtn = (Button) findViewById(R.id.invoke);
invokeBtn.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View v) {
        //setMainText("Invoking...");
        WLProcedureInvocationData invocationData = new WLProcedureInvocationData("DummyAdapter",
"getSecretData");
        WLRequestOptions options = new WLRequestOptions();
        options.setTimeout(30000);
        client.invokeProcedure(invocationData, new MyResponseListener(), options);
    }
});

```

## Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/NativeFormBasedAuthProject.zip>) the Studio project.

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/AndroidNativeFormBasedAuthProject.zip>) the Native project.

