

# Distributing mobile applications with IBM Application Center

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/moving-to-production/app-center.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

## Overview

IBM MobileFirst Platform Application Center is a **repository of mobile applications** similar to public app stores but focused on the needs of an organization or a team. It is a private app store.

Application Center facilitates sharing mobile applications:

- You can **share feedback and rating** information.
- You can use access control lists to limit who can install applications.

Application Center works with MobileFirst apps and non-MobileFirst apps, and supports any **iOS, Android, BlackBerry 6/7** and **Windows/Phone 8.x** applications.

You can use Application Center in different contexts. For example:

- As an enterprise app store across an organization.
- During development to distribute applications within a team.

**Note: to build the iOS AppCenter Installer application, MobileFirst 7.1 is required**

Jump to:

- **Installing and configuring**
- **Preparing mobile clients**
- **Managing applications in the Application Center console**
- **The Application Center mobile client**
- **Deploying applications from MobileFirst Studio**
- **Application Center command-line tools**

## Installing and configuring

Application Center is installed as part of the installation of MobileFirst Server with IBM Installation Manager.

**Prerequisite:** Before you install Application Center, you must have installed an application server and a database:

- **Application server:** Tomcat or WebSphere® Application Server full profile or Liberty profile
- **Database:** DB2®, Oracle, or MySQL

If you do not have a database installed, the installation process can also install an Apache Derby database. However, using the Derby database is not recommended for production scenarios.

1. IBM Installation Manager guides you through the installation of Application Center with choices of database and application server. For more information

For more information, see the topic about installing MobileFirst Server, in the user documentation.

Because iOS 7.1 supports only the https protocol, the Application Center server must be secured with SSL (at least with TLS v.1) if you plan to distribute apps for devices that run iOS 7.1 or later. Self-signed certificates are not recommended, but can be used for testing purpose, provided that self-signed CA certificates are distributed to devices.

For more information, see the topic about configuring Secure Sockets Layer (SSL), in the user documentation.

2. After Application Center is installed with IBM Installation Manager, open the console:

`http://localhost:9080/appcenterconsole`

3. Log in with this user/password combination: demo/demo
4. At this point, you can configure user authentication. For example, you can connect to an LDAP repository.

For more information, see the topic about configuring the Application Center after installation, in the user documentation.

5. Prepare the mobile client for Android, iOS, BlackBerry 6/7, and Windows Phone 8, as explained in Preparing mobile clients ([http://ibm.biz/knowctr#SSHS8R\\_8.0.0/com.ibm.worklight.installconfig.doc/appcenter/c\\_configuration\\_of\\_the\\_applicati.html](http://ibm.biz/knowctr#SSHS8R_8.0.0/com.ibm.worklight.installconfig.doc/appcenter/c_configuration_of_the_applicati.html)).

The mobile client is the mobile application that you use to browse the catalog and install the application.

**Note:** For a production installation, consider to install the Application Center by running the provided Ant tasks: it enables you to decouple updates to the server from updates to the Application Center. For more information, see the user documentation.

## Preparing mobile clients

### For Android phones and tablets

The mobile client is delivered as a compiled application (APK) and is located at `install_dir/ApplicationCenter/installer/IBMAApplicationCenter.apk`

### For iPad and iPhone

1. Compile and sign the client application provided in source code. This is mandatory.
2. In MobileFirst Studio, open the IBMAppCenter Project at: `install_dir/ApplicationCenter/installer`
3. Use Run As > Run on MobileFirst Development Server to build the project.
4. Use Xcode to build and sign the application with your Apple iOS Enterprise profile.  
You can either open the resulting native project (in `iphone/native`) manually in Xcode, or right-click the iPhone folder and select Run As > Xcode project (which will generate the project and then open it in Xcode).

### For Blackberry

- To build the BlackBerry version, you must have the BlackBerry Eclipse IDE (or Eclipse with the BlackBerry Java™ plug-in) with the BlackBerry SDK 6.0. The application also runs on BlackBerry OS 7 when compiled with BlackBerry SDK 6.0.

A BlackBerry project is provided in: `install_dir/ApplicationCenter/installer/IBMAppCenterBlackBerry6`

### For Windows Phone 8

1. Register a company account with Microsoft.  
Application Center manages only company applications that are signed with the company certificate that comes with your company account.
2. The Windows Phone version of the mobile client is included at:  
`install_dir/ApplicationCenter/installer/IBMAApplicationCenterUnsigned.xap`
  - Make sure that also the Application Center mobile client is signed with this company certificate.
  - To install company applications on a device, first enroll the device with the company by installing a company enrollment token.

For more information about company accounts and enrollment tokens, see the Microsoft Developer website > Company app distribution for Windows Phone ([http://msdn.microsoft.com/library/windows/apps/jj206943\(v=vs.105\).aspx](http://msdn.microsoft.com/library/windows/apps/jj206943(v=vs.105).aspx)) page

For more information about how to sign Windows Phone mobile client applications, see the Microsoft Developer website (<http://dev.windows.com/en-us/develop>).

**Important:** You cannot use the unsigned `.xap` file directly. Before you can install it on a device, you must first sign it with your company certificate, which you obtained from Symantec or Microsoft.

### For Windows Store Apps for Windows 8.1 Pro

- The `install_dir/ApplicationCenter/installer/IBMAApplicationCenterWindowsStore.zip` file contains the executable of the Application Center client. Distribute this file to the client computer and unzip it. It contains the executable program.

- Installing a Windows Store app (a file of type `appx`) without using Microsoft Windows Store is called *sideloading* an app. To sideload an app, you must comply with the prerequisites in [Prepare to sideload apps](https://technet.microsoft.com/fr-fr/library/dn613842.aspx). The Windows 8.1.1 update simplifies the prerequisites for sideloading. For more information, see Sideload Store Apps to Windows 8.1.1 Devices (<http://blogs.msdn.com/b/micham/archive/2014/05/30/sideload-store-apps-to-windows-8-1-devices.aspx>).

## Managing applications in the Application Center console



Use the Application Center console to manage applications in the catalog in the following ways:

- Add and remove applications
- Manage versions of applications
- Look at the details of an application
- Restrict the access of an application to specific users or groups of users
- Read the reviews for each application
- Review registered users and devices

## Adding new applications to the store

### Add an application

#### Application File

Upload an application file with file extension apk, ipa, xap, appx or zip.

Application file:  Upload...

To add new applications to the Store:

1. Open the Application Center console.
2. Click Add application.
3. Select an application file:
  - `.ipa` : iOS
  - `.apk` : Android
  - `.zip` : BlackBerry 6/7
  - `.xap` : Windows Phone 8.x

- .appx : Windows Store 8.x

- Click Next.

In the Application Details views, you can review the information about the new application and enter further information such as the description. You can return to this view later for all applications in the catalog.

## Application Management

### Add an application

#### Application Details

Package, Version and Label must be set in the uploaded application package and cannot be modified afterwards.

Package:	com.clickgamer.AngryBirds	Identifies the application
* Label:	<input type="text" value="Angry Birds"/>	Label of the application as defined by the developer
External URL:	ibmappctr://show-app?id=com.clickgamer.AngryBirds	URL to open the Application Center mobile client on this application.
Author:	demo	User who has uploaded this application
Vendor:	Rovio Entertainment Ltd	Vendor who has created this application
Description:	<input type="text"/>	(2048 characters maximum)
Active:	<input checked="" type="checkbox"/>	An active application can be installed on a device
Instrumented	No	Indicates whether this application is instrumented for IBM MobileFirst Platform Test Workbench

- Click Done to finish the task.

The new application is added to the store.

## Installation Access Control

The users with permission to install this application on their devices.

☒ Access control enabled

Select an existing user or register a new one.

1 of 1 Page 1

Sort by: Name ^

 demo	demo
--	------

Show: 10 | 20 | 50 | 100 | All items

By default, an application can be installed by any authorized user of the store.

## Restricting access to a group of users

To restrict access to a group of users:

1. In the catalog view, click the unrestricted link that is next to the application name. The Installation Access Control page opens.
2. Select Access control enabled. You can now enter the list of users or groups that are authorized to install the application.
3. If you have configured LDAP, add users and groups that are defined in the LDAP repository.

You can also add applications from public app stores such as Google Play or Apple App Store by entering their URLs.

## The Application Center mobile client

The App Center mobile client is a mobile application to manage the applications on the device. With the mobile client, you can:

- List all applications from the catalog (for which you have access rights).
- List the favorite applications.
- Install an application or upgrade to a new version.
- Provide feedback and five-star rating for an application.

## Adding mobile client applications to the catalog

You must add Application Center mobile client applications to the catalog.

1. Open the Application Center console.
2. Click the Add Application button to add the mobile client `.apk`, `.ipa`, `.zip`, or `.xap` file.
3. Click Next to open the Application Details page.
4. In the Application Details page, select Installer to indicate that this application is a mobile client.
5. Click Done to add the Application Center app to the catalog.

The Application Center client for Windows 8.1 Pro does not need to be added to the catalog. This client is a regular Windows `.exe` program contained in the `install_dir\ApplicationCenter\installer\IBMApplicationCenterWindowsStore.zip` file. You can simply copy it to the client computer.

## Windows Phone 8

On Windows Phone 8, you must also install the enrollment token that you received with your company account to the Application Center console, so that users can enroll their devices. You use the Application Center Settings page, which you can open through the gear icon.

## Application Center Settings



Before you can install the mobile client, you must enroll the device with the company by installing the enrollment token:

1. Open the web browser on the device.
2. Enter the URL: `http://hostname:9080/appcenterconsole/installers.html`
3. Enter the user name and password.
4. Click Tokens to open the list of enrollment tokens.
5. Select the company in the list. The details of the company account are displayed.
6. Click Add Company Account. Your device is enrolled.

## Installing the mobile client on the mobile device

To install the mobile client on the mobile device:



1. Open the web browser on the device.
2. Enter the URL: `http://hostname:9080/appcenterconsole/installers.html`
3. Enter the user name and password.
4. Select the Application Center application to start the installation.

On Android devices, you must open the Android Download application and select IBM App Center for installation.

## Logging in to the mobile client

To log in to the mobile client:

1. Enter your credentials for access to the server.
2. Enter the host name or IP address of the server.
3. In the Server port field, enter the port number if it is not the default one ( 9080 ).
4. In the Application context field, enter the context: `applicationcenter` .

## Application Center mobile client views

- The Catalog view displays the list of available applications.
- Selecting an application opens the Details view on the application. You can install applications from the Details view. You can also mark applications as favorites by using the star icon in the Details View.



- The Favorites view lists the favorite applications. This list is available on all the devices of a particular user.
- The Updates view lists all available updates. In the Updates view, you can navigate to the Details view. You can select a newer version of the application or take the latest available version. If Application Center is configured to send push notifications, you might be notified of updates by push notification messages.

From the mobile client, you can rate the application and send a review. Reviews can be viewed on the console or on the mobile device.



## Application Center command-line tools

The `install_dir/ApplicationCenter/tools` directory contains all the files that are required to use the command-line tool or Ant tasks to manage the applications in the store:

- `applicationcenterdeploytool.jar`: the upload command-line tool.

- `json4jar` : the library for the JSON format that is required by the upload tool.
- `build.xml` : a sample Ant script that you can use to upload a single file or a sequence of files to Application Center.
- `acdeploytool.sh` and `acdeploytool.bat` : Simple scripts to call Java with the `applicationcenterdeploytool.jar` file.

For example, to deploy an application `app.apk` file to the store in `localhost:9080/applicationcenter` with user ID `demo` and password `demo`, write:

```
Java com.ibm.appcenter.Upload -s http://localhost:9080 -c applicationcenter -u demo -p demo app.apk
```