

Overview of client technologies

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/6.3/advanced-client-side-development/overview-client-technologies.html>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

IBM MobileFirst Platform Foundation includes and supports various technologies to help you develop a mobile application.

Each technology has its advantages and disadvantages. You must know which tool to use in any situation.

The following tutorial provides an overview of these technologies.

Each technology is then further covered in later tutorials.

MobileFirst supports both native (Objective-C, Java, etc) applications and Hybrid Web-Based applications.

Full Native Development

If your app requires the full power of the environment, you can develop it purely in native code.

This approach is also useful when you are deploying existing native apps on the MobileFirst Server.

The platform supplies a native MobileFirst Client API to manage authentication and back-end access, and to benefit from more server functionality.

For more information, see various tutorials on development native applications for MobileFirst.

Hybrid Web-Based Development

You can choose to develop your MobileFirst application as a Hybrid, web-based application.

MobileFirst Hybrid apps are developed by using standard web technologies:

- A single HTML file.
- JavaScript.
- Style sheets and images.

MobileFirst apps use the MobileFirst API to access backend data and server functionality.

Some controls are common to most hybrid environments. Examples: modal pop-ups, loading screens and tab bars.

MobileFirst provides a JavaScript API to invoke these controls regardless of the environment, and automatically renders them in a native way for each platform.

For more information, see the Common UI Controls (../common-ui-controls/) tutorial.

Environment-specific code



To achieve maximum adaptation to a specific environment, web resources can be optimized specifically for it.

For example, an iPhone environment requires an iPhone specific look and feel that can be achieved by extending CSS or JavaScript files.

MobileFirst eases the code maintenance of multiple-environment optimization.

For more information, see the [Optimizing your application for various environments \(../../client-side-development-basics/optimizing-application-various-environments/\)](#) tutorial.

Skins



Skins provide support for multiple form factors in a single executable file for devices of the same OS family. Skins are a sub-variant of an environment.

Skins are packaged together in one app.

The decision on which skin to use is made automatically at run time.

For more information, see the [Supporting multiple form factors by using skins \(../supporting-multiple-form-factors-using-skins/\)](#) tutorial.

Cordova APIs

Cordova (<http://cordova.apache.org/>) is an open source development framework that is based on JavaScript for building multiplatform mobile apps.

The MobileFirst Framework uses the Cordova library. MobileFirst exposes the Cordova APIs so that developers can access native device functions through those services.

For more information, see the [Apache Cordova overview \(../../adding-native-functionality/apache-cordova-overview/\)](#) tutorial.

Cordova Plugins

The Cordova plug-in is an abstraction that allows native components to be called by using a JavaScript API. With custom plug-ins, you can add native functions such as an encryption library or computational components and call them using JavaScript.

By default, a plug-in must be implemented for each supported environment (for example, iPhone).

Various Cordova plug-ins exist on the market.

For more information, see the [Adding native functionality to hybrid applications \(../../adding-native-functionality/\)](#) tutorial.

Native UI

MobileFirst provides different ways to augment web applications with native pages.

Users can navigate freely between web and native pages, share data between pages, and share a single server session

For example, contact details can be accessed by using the Apache Cordova API. However, if your application can use the contact application in the device use the Native Page API.

For more information, see the Adding native functionality to hybrid applications ([../adding-native-functionality/](#)) tutorials.

You can also modify the native project generated by MobileFirst to write your own custom native code. See [Android – Adding native UI elements to hybrid applications](#) ([../adding-native-functionality/android-adding-native-ui-elements-hybrid-applications/](#)) and [iOS – Adding native UI elements to hybrid applications](#) ([../adding-native-functionality/ios-adding-native-ui-elements-hybrid-applications/](#)).

Multi-page techniques

Applications with multiple pages can be built in two ways:

- A single HTML file that contains all app pages. Pages are *divs* that become hidden or shown at run time.
- A separate HTML file for each application page.

The first option is better for small apps but is less scalable.

For more information, see the Building a multipage application ([../client-side-development-basics/building-multi-page-application/](#)) tutorial.

Offline Access

MobileFirst apps work in concert with the MobileFirst Server.

In offline mode, developers can detect app connectivity failures and determine the best course of action.

Developers can define custom application behavior for offline and online status.

For more information, see the Working offline ([../working-offline/](#)) tutorial.