

Windows Phone 8 - Using native pages

Overview

In this tutorial, integration of native and web "pages" in a Windows Phone 8 application will be explained by using the `WL.NativePage.show()` API to open a native page from JavaScript. With this method, data can be sent from JavaScript to the opened native page, and specify a callback to call after the native page closes.

Connecting to the plugin from the JavaScript code

As a first step, `WL.NativePage.show()` needs to be implemented in order to open the native page:

```
1 function openNativePage(){
2     var params = {
3         nameParam : $('#nameInput').val()
4     };
5     WL.NativePage.show(nativePageClassName, backFromNativePage, params);
6 }
```

- `nativePageClassName`: The name of a native Windows Phone 8 UIViewController instance to start.
- `backFromNativePage`: A callback function to call when the native page closes.
- `params`: optional custom parameters object to pass to the native code.

To handle the callback function:

```
1 function backFromNativePage(data){
2     alert("Received phone number is: " + data.phoneNumber);
3 }
```

- `backFromNativePage(data)`: After the native closes, it can pass data back to the web part of an application.

Creating a native page

For WP8, the native page must be implemented as a Windows Phone User Control, or extend an existing one.

Step 1

In the new User Control, add `using Cordova.Extension.Commands;` to the `.cs` file, and use the same package and class name as in the `WL.NativePage` API call in the JavaScript:

```
using Cordova.Extension.Commands;
using Newtonsoft.Json;

namespace NativePagesInHybridApp
{
    public partial class HelloNative : UserControl
    {
```

Step 2

To retrieve custom data parameters that are passed from the web view, the `WLNativePage.Data` method should be used. In the below example, the data is sent as a JSON string. For this purpose, the external `JSON.NET` library is used to convert the incoming JSON string to a native dictionary. For more information, see <http://json.codeplex.com/> (<http://json.codeplex.com/>)

```
InitializeComponent();
    if (WLNativePage.Data != null) {
        Dictionary<string, string> data = JsonConvert.DeserializeObject<Dictionary<string, string>>(NameReceivedTextBlock.Text = "Hello " + data["nameParam"]);
        tb_returnValue.Text = "1234567890";
    }

```

Returning control to the web view

When the native page needs to switch back to the web view, it calls the `WLNativePage.backFromNative` method. Data can be passed back to the web view as parameters to the call:

C#:

```
void DoneButton_Click(object sender, RoutedEventArgs e) {
    Dictionary<string, string> data = new Dictionary<string, string> {
        { "phoneNumber", tb_returnValue.Text }
    };

    string json = JsonConvert.SerializeObject(data, Formatting.Indented);
    WLNativePage.backFromNative(this, json);
}

```

JavaScript:

```
1 function backFromNativePage(data){
2     alert("Received phone number is: " + data.phoneNumber);
3 }

```

Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/UsingNativePagesInHybridAppsProject.zip>) the Studio project.

