Resource request from native Android applications

fork and edit tutorial (https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/7.1/server-side-development/invoking-adapter-procedures-native-android-applications.html) | report issue (https://github.ibm.com/MFPSamples/DevCenter/issues/new)

Overview

To create and configure an Android native project, first follow the Configuring a native Android application with the MobileFirst Platform SDK (../../hello-world/configuring-a-native-android-application-with-the-mfp-sdk/) tutorial.

MobileFirst applications can access resources using the `WLResourceRequest` REST API.
This tutorial explains how to use the `WLResourceRequest` API with an HTTP adapter.

Initializing WLClient

1. Create an instance of the `WLClient` class.
   The `WLClient` instance requires a reference to the activity in which it is running.

   ```
   WLClient client = WLClient.createInstance(context);
   ```

2. To establish a connection to the MobileFirst Server instance, use the `connect` method by specifying the `MyConnectListener` class instance as a parameter.
   The `WLClient` instance tries to connect to the MobileFirst Server according to the properties of the `wlclient.properties` file.
   After the connection is established, it invokes one of the methods of the `MyConnectListener` class.
3. Specify that the `MyConnectListener` class implements the `WLResponseListener` interface.

   ```
   public class MyConnectListener implements WLResponseListener {
   ```

   The `WLResponseListener` interface defines two methods:
   - `public void onSuccess (WLResponse response) { }`
   - `public void onFailure (WLFailResponse response) { }`
4. Use these methods to process connection success or connection failure.

Invoking an adapter procedure

After the connection is established with a MobileFirst Server instance, you can use the `WLResourceRequest` class to invoke adapter procedures or call any REST resources.

1. Define the URI of the resource. For a JavaScript HTTP adapter:
   `/adapters/{AdapterName}/{ProcedureName}`

   ```
   URI adapterPath = new URI("/adapters/RSSReader/getFeed");
   ```

2. Create a `WLResourceRequest` object and choose the HTPP Method (GET, POST, etc).

```
WLResourceRequest request = new WLResourceRequest(adapterPath,WLResourceRequest.GET);
```

3. Add the required parameters.
   - For JavaScript-based adapters, use the `params` parameter name to set an array of parameters.

     ```
     request.setQueryParameter("params","['MobileFirst_Platform']");
     ```

   - For Java adapters or other resources, you can use `setQueryParameter` for each parameter.

     ```
     request.setQueryParameter("param1","value1");
     request.setQueryParameter("param2","value2");
     ```

   - Trigger the request with `.send()`.
     Specify a `MyInvokeListener` class instance as a parameter.
     You learn how to define this class instance in the next section.

     ```
     request.send(new MyInvokeListener());
     ```

     Other signatures, which are not covered in this tutorial, exist for the `send` method. Those signatures enable you to set parameters in the body instead of the query, or to handle the response with a delegate instead of a completion handler. See the user documentation to learn more.

Receiving a procedure response

After the procedure invocation is completed, the framework calls one of the methods of the `MyInvokeListener` class.

1. Specify that the `MyInvokeListener` class implements the `WLResponseListener` interface.

   ```
   public class MyInvokeListener implements WLResponseListener {
   ```

   The `WLClient` instance invokes the `onSuccess` and `onFailure` methods.
   If the procedure invocation is successful, the `onSuccess` method of `MyInvokeListener` is invoked.
2. Use that method to get the data that is retrieved from the adapter. The `response` object contains the response data.
   You can use its methods and properties to retrieve the required information.

```
public void onSuccess(WLResponse response) {
    String responseText = response.getResponseText();
    AndroidNativeApp.updateTextView("Adapter Procedure Invoked Successfuly\n" + responseTex
t);
}

public void onFailure(WLFailResponse response) {
    String responseText = response.getResponseText();
    AndroidNativeApp.updateTextView("Failed to Invoke Adapter Procedure\n" + responseText);
}
```

Sample application

Click to download (https://github.com/MobileFirst-Platform-Developer-Center/InvokingAdapterProcedures/tree/release71) the MobileFirst project.

Click to download (https://github.com/MobileFirst-Platform-Developer-Center/InvokingAdapterProceduresAndroid/tree/release71) the Native project.

– The `InvokingAdapterProcedures` project contains a MobileFirst Native API to deploy to your MobileFirst Server instance.
– The `InvokingAdapterProceduresAndroid` project contains a native Android application that uses a MobileFirst native API library to communicate with MobileFirst Server.
- Make sure to update the `wlclient.properties` file in the native Android project with the required server settings.

80% 13:33
1. Connect
2. Invoke Procedure
Adapter Procedure Invoked Successfuly
*-secure-
{"responseID":"6","statusCode":200,"Items":[{"pubDate":
Thu, 08 Nov 2012 06:08:00 EDT","title":"Google Shopper
adds push notifications, new UI and more with 3.0
update","link":"http:\/\/www.engadget.
com\/2012\/11\/08\/google-shooper-update-ui-push-
notification-sales\/","creator":"Alexis Santos"},
{"pubDate":"Thu, 08 Nov 2012 05:31:00 EDT","title":"Jam
with Chrome: Google reinvents browser-based band
practice (video)","link":"http:\/\/www.engadget.
com\/2012\/11\/08\/jam-with-chrome\/","creator":
Daniel Cooper"},{"pubDate":"Thu, 08 Nov 2012 04:54:00
EDT","title":"Sandvine: Netflix up to 29 percent of North
American internet traffic, YouTube is fast on the rise",
link":"http:\/\/www.engadget.com\/2012\/11\/08\/
sandvine-netflix-29-percent-of-north-american-
internet-traffic\/","creator":"Jon Fingas"},{"pubDate":
Thu, 08 Nov 2012 04:21:00 EDT","title":"Amazon Kindle
Paperwhite update optimizes your Manga mania, offers
quicker settings","link":"http:\/\/www.engadget.
com\/2012\/11\/08\/amazon-kindle-paperwhite-
update-optimizes-your-manga-mania\/","creator":"Jon
Fingas"},{"pubDate":"Thu, 08 Nov 2012 03:01:00 EDT",
title":"Timbuk2 Power Commute carries your gadgets,
keeps 'em charged for $199 (hands-on)","link":"http:\/\/
www.engadget.com\/2012\/11\/08\/timbuk2-power-
commute-hands-on\/","creator":"Michael Gorman"},
{"pubDate":"Thu, 08 Nov 2012 03:00:00 EDT","title":
Angry Birds Star Wars adds sci-fi flavor to bird flinging,
available today, we go hands-on","link":"http:\/\/www.