

iOS - Implementing Cordova plug-ins

Overview

In some cases, developers of a MobileFirst application might have to use a specific third-party native library or a device function that is not yet available in Apache Cordova.

With Apache Cordova, developers can create an Apache Cordova plug-in, which means that they create custom native code blocks, and then call these code blocks in their applications by using JavaScript.

This tutorial demonstrates how to create and integrate a simple Apache Cordova plug-in for iOS, in the following topics:

- Creating a plug-in
- Declaring a plug-in
- Implementing `cordova.exec()` in JavaScript
- Implementing the Objective-C code of a Cordova plug-in
- Sample application

Note: In Cordova-based applications, developers must check for the `deviceready` event before they use the Cordova API set. In a MobileFirst application, however, this check is done internally.

Instead of implementing this check, you can place implementation code in the `wlCommonInit()` function in the `common\js\main.js` file.

Creating a plug-in

1. Declare the plug-in in the `config.xml` file.
2. Use the `cordova.exec()` API in the JavaScript code.
3. Create the plug-in class that will run natively in iOS.

The plug-in performs the required action and calls a JavaScript callback method that is specified during the call to `cordova.exec()` method.



Declaring a plug-in

You must declare the plug-in in the project, so that Cordova can detect it.

To declare the plug-in, add a reference to the `config.xml` file, located in the native folder of the iOS environment.

```
1 <feature name="sayHelloPlugin">
2   <param name="ios-package" value="sayHelloPlugin" />
3 </feature>
```

Implementing cordova.exec() in JavaScript

From the JavaScript code of the application, use the `cordova.exec()` method to call the Cordova plug-in:

```
1 function sayHello() {
2   var name = $("#NameInput").val();
3   cordova.exec(sayHelloSuccess, sayHelloFailure, "SayHelloPlugin", "sayHello", [name]);
4 }
```

`sayHelloSuccess` - Success callback

`sayHelloFailure` - Failure callback

`SayHelloPlugin` - Plug-in name as declared in the `config.xml` file

`sayHello` - Action name

`[name]` - Parameters array

The plug-in calls the success and failure callbacks.

```
1 function sayHelloSuccess(data) {
2   WL.SimpleDialog.show(
3     "Response from plug-in", data,
4     [{text: "OK", handler: function() {WL.Logger.debug("Ok button pressed");}}]
5   );
6 }
7
8 function sayHelloFailure(data){
9   WL.SimpleDialog.show(
10    "Response from plug-in", data,
11    [{text: "OK", handler: function() {WL.Logger.debug("Ok button pressed");}}]
12  );
13 }
```

Implementing the Objective-C code of a Cordova plug-in

After you have declared the plug-in and the JavaScript implementation is ready, you can implement the Cordova plug-in.

Prerequisite: Ensure that the project is built in Eclipse and opened in the Xcode IDE.

Step 1

1. Add a new Cocoa Touch Class file, make sure that it is a subclass of `UIViewController`, and save it in the `Classes` folder of the Xcode project.
2. Import the `Cordova/CDV.h` header file and inherit the `CDVPlugin` class.
3. Declare the `SayHelloPlugin` signature.

```
1 | #import <Foundation/Foundation.h>
2 | #import <Cordova/CDV.h>
3 |
4 | @interface SayHelloPlugin : CDVPlugin
5 | - (void)sayHello:(CDVInvokedUrlCommand*)command;
6 | @end
```

Step 2

1. Implement the method. The `command` argument contains references to the parameters that are sent from JavaScript and callbacks:

```
1 | #import "SayHelloPlugin.h"
2 | @implementation SayHelloPlugin
3 | - (void)sayHello:(CDVInvokedUrlCommand*)command {
```

2. Write this statement to retrieve the parameters that are sent from JavaScript.

```
1 | NSString *responseString = [NSString stringWithFormat:@"Hello %@", [command.arguments o
```



3. The `pluginResult` object is created with data retrieved from JavaScript. The `CDVCommandStatus` parameter defines whether the plug-in call was successful or not.

```
1 | CDVPluginResult *pluginResult = [CDVPluginResult resultWithStatus:CDVCommandStatus_OK m
```



4. Use the `sendPluginResult` method to return a response back to JavaScript (invoke callback).

```
1 | [self.commandDelegate sendPluginResult:pluginResult callbackId:command.callbackId];
2 |
3 | }
4 | @end
```

Important note:

If you work with existing `.m` and `.h` files, reference them while you are working in Xcode. Placing the `.m` and `.h` files only in the `iphone\native\Classes` folder in Eclipse is not sufficient, because these files are not referenced in the Xcode project unless they were added in Xcode.

Sample application

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/ApacheCordovaPlugins>) the MobileFirst project.

