

# Native iOS applications

## Overview

This tutorial is a continuation of the JSONStore Overview tutorial.

Jump to:

- Adding JSONStore
- Basic Usage
- Advanced Usage
- Sample application

## Adding JSONStore

Adding the JSONStore component to native iOS applications is accomplished using CocoaPods. First, make sure the MobileFirst Native SDK is present by following the instructions in the tutorial: [Configuring a Native iOS Application with the MobileFirst Platform SDK \(../configuring-the-mfpf-sdk/configuring-a-native-ios-application-with-the-mfp-sdk/\)](#).

Next, perform the following steps:

1. Edit the existing `podfile`, located at the root of the Xcode project. Add to the file:

```
source 'https://github.com/CocoaPods/Specs.git'
pod 'IBMMobileFirstPlatformFoundationJSONStore'
```

2. From a **Command-line** window, navigate to the root of the Xcode project and run the command: `pod install` - note that this action may take a while.

The JSONStore feature should now be available to you in the Xcode project.

## Basic Usage

### Open

Use `openCollections` to open one or more JSONStore collections.

Starting or provisioning a collections means creating the persistent storage that contains the collection and documents, if it does not exists.

If the persistent storage is encrypted and a correct password is passed, the necessary security procedures to make the data accessible are run.

For optional features that you can enable at initialization time, see **Security, Multiple User Support** and **MobileFirst Adapter Integration** in the second part of this tutorial.

```
NSError *error = nil;

JSONStoreCollection* collection = [[JSONStoreCollection alloc] initWithName:@"people"];
[collection setSearchField:@"name" withType:JSONStore_String];
[collection setSearchField:@"age" withType:JSONStore_Integer];

[[JSONStore sharedInstance] openCollections:@[collection] withOptions:nil error:error];
```

## Get

Use `getCollectionWithName` to create an accessor to the collection. You must call `openCollections` before you call `getCollectionWithName`.

```
NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName];
```

The variable `collection` can now be used to perform operations on the `people` collection such as `add`, `find`, and `replace`.

## Add

Use `addData` to store data as documents inside a collection.

```
NSError *error = nil;

NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName];

NSDictionary *data = @{@"name" : @"yoel", @"age" : @23};
[[collection addData:@[data] andMarkDirty:YES withOptions:nil error:error] intValue];
```

## Find

Use `findWithQueryParts` to locate a document inside a collection by using a query. Use `findAllWithOptions` to retrieve all the documents inside a collection. Use `findWithIds` to search by the document unique identifier.

```

NSError *error = nil;

NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName
];
//Build a query part.

JSONStoreQueryPart *query = [[JSONStoreQueryPart alloc] init];
[query searchField:@"name" like:@"yoel"];
JSONStoreQueryOptions *options = [[JSONStoreQueryOptions alloc] init];

// returns a maximum of 10 documents, default: returns every document
[options setLimit:@10];

// Count using the query part built above.
NSArray *results = [collection findWithQueryParts:@[query] andOptions:options error:error];

```

## Replace

Use `replaceDocuments` to modify documents inside a collection. The field that you use to perform the replacement is `_id`, the document unique identifier.

```

NSError *error = nil;

NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName
];

//Replacing name 'carlos' with name 'carlitos'.<br />
NSDictionary *replacement = @{@"_id": @1, @"json" : @{@"name" : @"chevy", @"age" : @23}};
[collection replaceDocuments:@[replacement] andMarkDirty:YES error:error];

```

This examples assumes that the document `{_id: 1, json: {name: 'yoel', age: 23} }` is in the collection.

## Remove

Use `removeWithIds` to delete a document from a collection. Documents are not erased from the collection until you call `markDocumentClean`. For more information, see the **MobileFirst Adapter Integration** section later in this tutorial.

```

NSError *error = nil;

NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName
];
[collection removeWithIds:@[@1] andMarkDirty:YES error:error];

```

## Remove Collection

Use `removeCollectionWithError` to delete all the documents that are stored inside a collection. This operation is similar to dropping a table in database terms.

```
NSError *error = nil;

NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName];
BOOL removeCollectionWorked = [collection removeCollectionWithError:error];
```

## Destroy

Use `destroyDataAndReturnError` to remove the following data:

- All documents
- All collections
- All Stores - See **Multiple User Support** later in this tutorial
- All JSONStore metadata and security artifacts - See **Security** later in this tutorial

```
NSError *error = nil;
[[JSONStore sharedInstance] destroyDataAndReturnError:error];
```

## Advanced Usage

### Security

You can secure all the collections in a store by passing a `JSONStoreOpenOptions` object with a password to the `openCollections` function. If no password is passed, the documents of all the collections in the store are not encrypted.

Some security metadata is stored in the keychain (iOS).

The store is encrypted with a 256-bit Advanced Encryption Standard (AES) key. All keys are strengthened with Password-Based Key Derivation Function 2 (PBKDF2).

Use `closeAllCollectionsAndReturnError` to lock access to all the collections until you call `openCollections` again. If you think of `openCollections` as a login function you can think of `closeAllCollectionsAndReturnError` as the corresponding logout function.

Use `changeCurrentPassword` to change the password.

```
NSError *error = nil;

JSONStoreCollection *collection = [[JSONStoreCollection alloc] initWithName:@"people"];
[collection setSearchField:@"name" withType:JSONStore_String];
[collection setSearchField:@"age" withType:JSONStore_Integer];

JSONStoreOpenOptions *options = [JSONStoreOpenOptions new];
[options setPassword:@"123"];
[[JSONStore sharedInstance] openCollections:@[collection] withOptions:options error:error];
```

### Multiple User Support

You can create multiple stores that contain different collections in a single MobileFirst application. The `openCollections` function can take an options object with a username. If no username is given, the default username is "jsonstore".

```
NSError *error = nil;
```

```
JSONStoreCollection *collection = [[JSONStoreCollection alloc] initWithName:@"people"];  
[collection setSearchField:@"name" withType:JSONStore_String];  
[collection setSearchField:@"age" withType:JSONStore_Integer];
```

```
JSONStoreOpenOptions *options = [JSONStoreOpenOptions new];  
[options setUsername:@"yoel"];  
[[JSONStore sharedInstance] openCollections:@[collection] withOptions:options error:error];
```

## MobileFirst Adapter Integration

This section assumes that you are familiar with MobileFirst adapters. MobileFirst Adapter Integration is optional and provides ways to send data from a collection to an adapter and get data from an adapter into a collection.

You can achieve these goals by using functions such as `WLClient invokeProcedure` or your own instance of an `NSURLConnection` if you need more flexibility.

### Adapter Implementation

Create a MobileFirst adapter and name it **"People"**. Define its procedures `addPerson`, `getPeople`, `pushPeople`, `removePerson`, and `replacePerson`.

```
function getPeople() {  
    var data = { peopleList : [{name: 'chevy', age: 23}, {name: 'yoel', age: 23}] };  
    WL.Logger.debug('Adapter: people, procedure: getPeople called.');
```

```
    WL.Logger.debug('Sending data: ' + JSON.stringify(data));  
    return data;  
}  
function pushPeople(data) {  
    WL.Logger.debug('Adapter: people, procedure: pushPeople called.');
```

```
    WL.Logger.debug('Got data from JSONStore to ADD: ' + data);  
    return;  
}  
function addPerson(data) {  
    WL.Logger.debug('Adapter: people, procedure: addPerson called.');
```

```
    WL.Logger.debug('Got data from JSONStore to ADD: ' + data);  
    return;  
}  
function removePerson(data) {  
    WL.Logger.debug('Adapter: people, procedure: removePerson called.');
```

```
    WL.Logger.debug('Got data from JSONStore to REMOVE: ' + data);  
    return;  
}  
function replacePerson(data) {  
    WL.Logger.debug('Adapter: people, procedure: replacePerson called.');
```

```
    WL.Logger.debug('Got data from JSONStore to REPLACE: ' + data);  
    return;  
}
```

### Load data from MobileFirst Adapter

To load data from a MobileFirst Adapter use `WLClient invokeProcedure`.

```

// Start - LoadFromAdapter
@interface LoadFromAdapter : NSObject<WLDelegate>
@end

@implementation LoadFromAdapter
-(void)onSuccess:(WLResponse *)response {
    NSArray *loadedDocuments = [[response getResponseJson] objectForKey:@"peopleList"];
    // handle success
}

-(void)onFailure:(WLFailResponse *)response {
    // handle success
}
@end
// End - LoadFromAdapter

NSError *error = nil;
WLProcedureInvocationData *invocationData = [[WLProcedureInvocationData alloc] initWithAdapterName
:@ "People" procedureName:@"getPeople"];

LoadFromAdapter *loadDelegate = [[LoadFromAdapter alloc] init];
WLClient *client = [[WLClient sharedInstance] init];
[client invokeProcedure:invocationData withDelegate:loadDelegate];

```

## Get Push Required (Dirty Documents)

Calling `allDirtyAndReturnError` returns an array of so called "dirty documents", which are documents that have local modifications that do not exist on the back-end system.

```

NSError* error = nil;
NSString *collectionName = @"people";
JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName
];
NSArray *dirtyDocs = [collection allDirtyAndReturnError:error];

```

To prevent JSONStore from marking the documents as "dirty", pass the option `andMarkDirty:NO` to `add`, `replace`, and `remove`.

## Push changes

To push changes to a MobileFirst adapter, call the `findAllDirtyDocuments` to get a list of documents with modifications and then use `WLClient invokeProcedure`. After the data is sent and a successful response is received make sure you call `markDocumentsClean`.

```

// Start - PushToAdapter
@interface PushToAdapter :NSObject<WLDelegate>
@end

@implementation PushToAdapter
-(void)onSuccess:(WLResponse *)response {
    // handle success
}

-(void)onFailure:(WLFailResponse *)response {
    // handle failure
}
@end
// End - PushToAdapter

NSError* error = nil;
NSString *collectionName = @"people";

JSONStoreCollection *collection = [[JSONStore sharedInstance] getCollectionWithName:collectionName
];
NSArray *dirtyDocs = [collection allDirtyAndReturnError:error];

WLProcedureInvocationData *invocationData = [[WLProcedureInvocationData alloc] initWithAdapterName
:@"People" procedureName:@"pushPeople"];
[invocationData setParameters:[dirtyDocs]];

PushToAdapter *pushDelegate = [[PushToAdapter alloc] init];
WLClient *client = [[WLClient sharedInstance] init];
[client invokeProcedure:invocationData withDelegate:pushDelegate];

```

## Sample application

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/JSONStoreObjC>) the Native iOS project.



Initialize (Login/Open)

Close All (Logout)

Destroy Everythng

Remove Collection

Add Data

Find By Name (Fuzzy Search)

Find By Age (Exact Search)

Collection initialized