

Custom Authenticator and Login Module in hybrid applications

This is a continuation of Custom Authenticator and Login Module (../).

Creating client-side authentication components

The application consists of two main *div* elements:

The *AppDiv* element is used to display the application content.

The *AuthDiv* element is used for authentication forms.

When authentication is required, the application hides *AppDiv* and shows *AuthDiv*. When authentication is complete, it does the opposite.

AppDiv

Copy

```
<div id="AppDiv"><br />
  <input type="button" id="getSecretDataButton" value="Call protected adapter proc" onclick="getSecretData()" />
  <input type="button" class="appButton" value="Logout" onclick="WL.Client.logout('CustomAuthenticatorRealm',{onSuccess:
WL.Client.reloadApp})" />
  <div id="ResponseDiv"></div>
</div>
```

Buttons are used to call the *getSecretData* procedure and to log out.

AuthDiv

Copy

```
<br />
<div id="AuthDiv" style="display: none">
  <p id="AuthInfo"></p><br />
  <div id="loginForm"><br />
    <input type="text" id="AuthUsername" placeholder="Enter username" />
    <br/>
    <br/>
    <input type="password" id="AuthPassword" placeholder="Enter password" />
    <br/>
    <input type="button" id="AuthSubmitButton" class="formButton" value="Login" />
    <input type="button" id="AuthCancelButton" class="formButton" value="Cancel" /
  >
</div>
</div>
```

AuthDiv is styled with *display:none* because it must not be displayed before the server requests the authentication.

Challenge Handler

Use *WL.Client.createChallengeHandler* to create a challenge handler object. Supply a realm name as a parameter.

Copy

```
var customAuthenticatorRealmChallengeHandler = WL.Client.createChallengeHandler("CustomAuthenticatorRealm");
```

The *isCustomResponse* function of the challenge handler is called each time a response is received from the server.

It is used to detect whether the response contains data that is related to this challenge handler. It must return **true** or **false**.

Copy

```
customAuthenticatorRealmChallengeHandler.isCustomResponse = function(response) {}
```

If *isCustomResponse* returns true, the framework calls the *handleChallenge* function. This function is used to perform required actions, such as hide application screen and show login screen.

Copy

```
customAuthenticatorRealmChallengeHandler.handleChallenge = function(response){}
```

In addition to the methods that the developer must implement, the challenge handler contains functionality that the developer might want to use:

- *submitLoginForm* to send collected credentials to a specific URL. The developer can also specify request parameters, headers, and callback.
- *submitSuccess* to notify the framework that the authentication finished successfully. The framework then automatically issues the original request that triggered the authentication.
- *submitFailure* to notify the framework that the authentication completed with a failure. The framework then disposes of the original request that triggered the authentication

Note: Attach each of these functions to its object. For example: *myChallengeHandler.submitSuccess()*

isCustomResponse

If the challenge JSON block contains the *authStatus* property, return *true*, otherwise return *false*.

Copy

```
customAuthenticatorRealmChallengeHandler.isCustomResponse = function(response) {  
  if (!response || !response.responseJSON) {  
    return false;  
  }  
  if (response.responseJSON.authStatus)  
    return true;  
  else  
    return false;  
};
```

handleChallenge

If the *authStatus* property equals “required”, show the login form, clean up the password input field, and display the error message if applicable.

if *authStatus* equals “complete”, hide the login screen, return to the application, and notify the framework that

authentication completed successfully.

Copy

```
customAuthenticatorRealmChallengeHandler.handleChallenge = function(response){
  var authStatus = response.responseJSON.authStatus;
  if (authStatus == "required"){
    $('#AppDiv').hide();
    $('#AuthDiv').show();
    $('#AuthInfo').empty();
    $('#AuthPassword').val("");
    if (response.responseJSON.errorMessage){
      $('#AuthInfo').html(response.responseJSON.errorMessage);
    }
  } else if (authStatus == "complete"){
    $('#AppDiv').show();
    $('#AuthDiv').hide();
    customAuthenticatorRealmChallengeHandler.submitSuccess();
  }
};
```

Clicking the **login** button triggers the function that collects the user name and password from HTML input fields and submits them to server. You can set request headers here and specify callback functions.

Copy

```
$('#AuthSubmitButton').bind('click', function () {
  var reqURL = '/my_custom_auth_request_url';
  var options = {};
  options.parameters = {
    username : $('#AuthUsername').val(),
    password : $('#AuthPassword').val()
  };
  options.headers = {};
  customAuthenticatorRealmChallengeHandler.submitLoginForm(reqURL, options, customAuthenticatorRealmChallengeHandler.submitLoginFormCallback);
});
```

Clicking the **cancel** button hides *AuthDiv*, shows *AppDiv* and notifies the framework that authentication failed.

Copy

```
$('#AuthCancelButton').bind('click', function () {
  $('#AppDiv').show();
  $('#AuthDiv').hide();
  customAuthenticatorRealmChallengeHandler.submitFailure();
});
```

The **submitLoginFormCallback** function checks the response for the containing server challenge once again. If the challenge is found, the *handleChallenge* function is called again.

Copy

```
customAuthenticatorRealmChallengeHandler.submitLoginFormCallback = function(response) {  
    var isLoginFormResponse = customAuthenticatorRealmChallengeHandler.isCustomResponse(response)  
    ;  
    if (isLoginFormResponse){  
        customAuthenticatorRealmChallengeHandler.handleChallenge(response);  
    }  
};
```

Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v700/CustomLoginModuleHybridProject.zip>)
the Studio project.

