

Application Authenticity

Overview

By issuing an HTTP request, an entity can access to corporate HTTP services (APIs) that IBM MobileFirst Foundation Server provides access to. The predefined application-authenticity security check (../) ensures that an application that tries to connect to a MobileFirst Server instance is the authentic one and was not tampered with or modified by a third-party attacker.

To enable application authenticity, you can either follow the on-screen instructions in the **MobileFirst Operations Console** → **[your-application]** → **Authenticity**, or review the information below.

Availability

- Application authenticity is available in all supported platforms (iOS, Android, Windows 8.1 Universal, Windows 10 UWP) in both Cordova and native applications.

Limitations

- Application authenticity does not support **Bitcode** in iOS. Therefore, before using application authenticity, disable Bitcode in the Xcode project properties.

Jump to:

- Application Authenticity flow
- Enabling Application Authenticity
- Configuring Application Authenticity

Application Authenticity Flow

By default, the application-authenticity security check is run during the application's runtime registration to MobileFirst Server, which occurs the first time an instance of the application attempts to connect to the server.

After an application has passed the authenticity challenge, an authenticity scope is granted. For as long as the token is valid, the authenticity challenge does not occur again. See [Configuring application authenticity](#) to learn how to customize this behavior.



The challenge token in the diagram is processed by compiled native code, so that third-party attackers cannot see the logic of this processing.

Enabling Application Authenticity

For application authenticity to be enabled in your Cordova or native application, the application binary file must be signed by using the mfp-app-authenticity tool. Eligible binary files are: `ipa` for iOS, `apk` for Android, and `appx` for Windows 8.1 Universal & Windows 10 UWP.

1. Download the mfp-app-authenticity tool from the **MobileFirst Operations Console** → **Download Center**.
2. Open a **Command-line** window and run the command: `java -jar path-to-mfp-app-authenticity.jar path-to-binary-file`

For example:

```
java -jar /Users/your-username/Desktop/mfp-app-authenticity.jar /Users/your-username/Desktop/MyBankApp.ipa
```

This command generates an `.authenticity_data` file, called `MyBankApp.authenticity_data`, next to the `MyBankApp.ipa` file.

3. Open the MobileFirst Operations Console in your favorite browser.
4. Select your application from the navigation sidebar and click on the **Authenticity** menu item.
5. Click on **Upload Authenticity File** to upload the `.authenticity_data` file.

When the `.authenticity_data` file is uploaded, application authenticity is enabled.

MobileFirst Operations Console

Home > mfp > RememberMeSwift > iOS 1.0

RememberMeSwift iOS v 1.0 | com.sample.RememberMeSwift

Management **Authenticity** Security Log Filters Configuration Files

Application-Authenticity Validation

The MobileFirst application-authenticity validation protects against unlawful attempts by fake or tampered applications to access your protected resources (APIs).

Upload an application-authenticity file to enable application-authenticity validation, and protect MobileFirst Server against fake or tampered applications that identify as your application. For more information, see the guide on this page.

Status: **Disabled** Upload Authenticity File

Follow these steps to enable MobileFirst application-authenticity validation: [Hide guide](#)

- 1 Get the MobileFirst application-authenticity Java tool.
You can download the MobileFirst application-authenticity Java tool, `mfp-app-authenticity-tool.jar`, from the [Download Center](#).
- 2 Generate an application-authenticity file.
- 3 Deploy the generated application-authenticity file to MobileFirst Server.

Disabling Application Authenticity

To disable application authenticity, click the **Delete Authenticity File** button.

Configuring Application Authenticity

You can configure the predefined application-authenticity security check with the following property:

- `expirationSec`: Defaults to 3600 seconds / 1 hour. Defines the duration until the authenticity token expires.

After an authenticity check has completed, it does not occur again until the token has expired based on the set value.

To configure the `expirationSec` property:

1. Load the MobileFirst Operations Console, navigate to **[your application] → Security → Security Check Configurations**, and click on **Create New**.
2. Search for the `appAuthenticity` scope element.
3. Set a new value in seconds.

Dashboard

mfp runtime

Applications (1) New

RememberMeSwift

Versions (1)

IOS (latest)

App Settings

Push

Adapters (0) New

No adapter is deployed.

Runtime Settings

Error Log

Devices

Download Center

Home > mfp > RememberMeSwift > IOS 1.0

Actions

ManagementAuthenticitySecurityLog FiltersConfiguration Files

Mandatory Application Scope

Configure a mandatory application scope to define an authorization logic that will be applied to each application attempt at accessing a protected resource. You can include in the scope any predefined or custom security checks, or mapped scope elements.

Add to Scope

Configure Security-Check Properties

Security Check *
appAuthenticity

Expiration Period, Successful State (seconds) *
3600

Expiration period for a successful security-check state, in seconds

OKCancel

No m
Get s

Security
Configure

No custom security-check configurations currently exist for this application.
Get started by clicking New.

New