

iOS end-to-end demonstration

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/quick-start/ios/index.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

Overview

The purpose of this demonstration is to experience an end-to-end flow where an application and an adapter are registered using the MobileFirst Operations Console, an "skeleton" Xcode project is downloaded and edited to call the adapter, and the result is printed to the log - verifying a successful connection with the MobileFirst Server.

Prerequisites:

- Xcode
- MobileFirst Developer CLI (download (file:///home/travis/build/MFPSamples/DevCenter/_site/downloads))
- *Optional.* Stand-alone MobileFirst Server (download (file:///home/travis/build/MFPSamples/DevCenter/_site/downloads))

1. Starting the MobileFirst Server

If a remote server was already set-up, skip this step.

From a **Command-line** window, navigate to the server's folder and run the command: `./run.sh`.

2. Creating an application

In a browser window, open the MobileFirst Operations Console by loading the URL: `http://your-server-host:server-port/mfpconsole`. If running locally, use: `http://localhost:9080/mfpconsole` (`http://localhost:9080/mfpconsole`). The username/password are `admin/admin`.

1. Click on the "New" button next to **Applications** and select the desired *platform*, *identifier* and *version* values.

The screenshot shows the MobileFirst Operations Console interface. On the left is a sidebar with navigation links: Dashboard, Runtimes, Applications (with a 'New' button), Adapters (with a 'New' button), Settings, Devices, and Error Log. The main content area is titled 'Register an Application' and contains the following fields: 'Application Name' (text input), 'Optional display name of the Application' (text input), 'Choose Platform' (radio buttons for Android, iOS (selected), and Windows), 'Bundle ID' (text input with a red asterisk, labeled 'Application Identifier; case sensitive'), and 'Version' (text input with a red asterisk, labeled 'Application Version'). At the bottom of the form is a blue 'Register application' button. The top of the console shows the title 'MobileFirst Operations Console', a user profile 'Hello, admin', and an 'Analytics Console' link.

2. Click on the **Get Starter Code** tile and select to download the iOS Starter Code.



3. Editing application logic

1. Open the Xcode project project by double-clicking the **.xcworkspace** file.
2. Select the **[project-root]/ViewController.m/swift** file and paste the following code snippet, replacing the existing `viewDidLoad()` function:

In Objective-C:

```
- (void)viewDidLoad {
    [super viewDidLoad];

    NSURL* url = [NSURL URLWithString:@"~/adapters/javaAdapter/users/world"];
    WLResourceRequest* request = [WLResourceRequest requestWithURL:url method:WLHttpMethodGet];

    [request sendWithCompletionHandler:^(WLResponse *response, NSError *error) {
        if (error != nil){
            NSLog(@"Failure: %@",error.description);
        }
        else if (response != nil){
            // Will print "Hello world" in the Xcode Console.
            NSLog(@"Success: %@",response.responseText);
        }
    }];
}
```

In Swift:

```
override func viewDidLoad() {
    super.viewDidLoad()

    let url = NSURL(string: "~/adapters/javaAdapter/users/world")
    let request = WLResourceRequest(URL: url, method: WLHttpMethodGet)

    request.sendWithCompletionHandler { (WLResponse response, NSError error) -> Void in
        if (error != nil){
            NSLog("Failure: " + error.description)
        }
        else if (response != nil){
            NSLog("Success: " + response.responseText)
        }
    }
}
```

4. Creating an adapter

1. Click on the "New" button next to **Adapters**
 - Select the **Actions** → **Download sample** option. Download the **Java** adapter sample.

- From a **Command-line** window, navigate to the adapter's Maven project root folder and run the command:

- When the build finishes, deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action. The adapter can be found in the **[adapter]/target** folder.
- Alternatively, download this prepared .adapter artifact and deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action.

5. Testing the application

- The adapter response is then printed in the Xcode Console.

```
MyApplication
Date = "Tue, 19 Jan 2016 06:14:40 GMT";
"Transfer-Encoding" = Identity;
"X-Powered-By" = "Servlet/3.1.1";
}
Response Data:
{"access_token": "eyJhbGciOiJIUzI1NiIsInp1diIeyI6eyIjOiJFbGVJRklubQ=="
JySghVwJNIXVKtLSZVEUGLj09ZCzIFOLWIRSztBznolzXnVLWFMFZdzhU893QKJsMuvocUL3vKR3T2LLZJKtUDsMEVYcIbaZmOwkktSFU80blpaSLuckSMelJAx0lTHZMDLOTDVB63NMVTKEHXNZLQ8twadJXCGLTBTJTJNFuRghINZDMRW95BURUVeFKUlw9omMLuSSo8ZNJHW
VZWVVq7Q203JOVVLWS9nj2LYbeXkgeLopDUccZCHZHUHwDpCkSRHLWDVduhIVrWCNEdrTBhQMNUHwIawla3rs3ojluNBElwaia3kjl0YJ2J2mZouXmakiOTtLIlny8MBDZLTksZQUHTWEZNGRLNWGU80TC3in19_eyp3Ck10d1j1bz8uw8dzImncISnN1y16t8m
52mkayfRJdJmKlyls5FzICStimhw5SpmdmubZCziwIZ2owijOnQJZ2gShjqepYALCJiz29zc3EEL39_r96Ad4UhuysY5f_67CX7W3P7NP_psgmLVnkzujY_BxldcdctIJq8nF8m8d183KL8BFHFnQdy3vb_wqb9sqioYnpAIXZ
ITrcxyVWNno30qYm1j7l6seqeLMpDKuJrFPalIPb720h=84RXZPE4B64j0KMGSQDLd6T1Q652JCgrLCP20snQg=36pvcVkuW5XSQ30Q2ufyabbkFN5_6VEAMer4Y8rJD8mlVCfrFSZgb3bbd2E4Z1LDW6KuXy7YnGH6JDKKKXkj1vm3BL1DNdcz_w
4vkypjr7mXLr6szExHG84gy8BMWG2Ba7jFNgLKdd3g","token_type": "Bearer", "expires_in": 3599, "scope": ""}
Status code=200
2016-01-19 08:14:40 410 MyApplication[93738:36590517] [OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper start]
in WLAFHTTPSessionManagerWrapper.m:372 : Starting the request with URL http://:9808/mfp/api/adapters/javaAdapter/users/world
2016-01-19 08:14:40 440 MyApplication[93738:36590517] [OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper
requestFinished:responseObject:] in WLAFHTTPSessionManagerWrapper.m:388 : Request Success
2016-01-19 08:14:40 448 MyApplication[93738:36590517] [OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper
requestFinished:responseObject:] in WLAFHTTPSessionManagerWrapper.m:391 : Response Status Code 200
2016-01-19 08:14:40 448 MyApplication[93738:36590517] --[WLAFHTTPSessionManagerWrapper requestFinished:responseObject:] [Line 393] Response Content : Hello world
2016-01-19 08:14:40 441 MyApplication[93738:36590517] Adapter invocation response: Hello world
```

Note: Xcode 7 enables Application Transport Security (ATS)

(https://developer.apple.com/library/ios/releasenotes/General/WhatsNewIniOS/Articles/iOS9.html#//apple_ref/doc/uid/TP40016198-SW14) by default.

To complete the tutorial, disable ATS (<http://iosdevtips.co/post/121756573323/ios-9-xcode-7-http-connect-server-error>).

1. In Xcode, right-click the **[project]/info.plist** file → **Open As** → **Source Code**
2. Paste the following:

```
<key>NSAppTransportSecurity</key>
<dict>
  <key>NSAllowsArbitraryLoads</key>
  <true/>
</dict>
```

3. Press the **Play** button.

Next steps

Learn more on using adapters in applications, and how to integrate additional services such as Push Notifications, using the MobileFirst security framework and more:

- Review the Server-side development tutorials ([../adapters/](#))
- Review the Authentication and security tutorials ([../authentication-and-security/](#))
- Review the Notifications tutorials ([../notifications/](#))
- Review All Tutorials ([../all-tutorials](#))