

Previewing your application on BlackBerry 10

Overview

In this tutorial the following topics will be covered. As a pre-requisite, make sure to read the "Previewing your application's web resources" tutorial.

- Preview the application in the BlackBerry Ripple Emulator
- Run the application in a physical device or simulator


Preview the application in the BlackBerry Ripple Emulator

To be able to preview the application in the Ripple Emulator, Ripple must first be installed. Ripple is a Chrome extension that can be downloaded and installed from the Chrome Web Store. Once Ripple is installed, follow the below steps.

1. Preview the BlackBerry environment from the MobileFirst Console by clicking on the "eye" icon and then click on **Open Simple Preview** .

Mobile Browser Simulator

The Mobile Browser Simulator displays mobile web pages in a variety of mobile browser sizes and shapes.



1. Enable Ripple by clicking on **Enable** from the extension's menu in Chrome.
2. If you get the following screen, choose **BlackBerry 10 WebWorks (1.0.0)** to proceed with previewing the application.



The page will auto-refresh and the environment's web resources will be displayed in the Ripple Emulator:



Run the application in a physical device or simulator



Before proceeding, you must have the BlackBerry WebWorks SDK installed. For more information, see the *Setting up your BlackBerry 10 development environment* tutorial. In Ripple, on the right menu, click **Build**,

and then click **Settings...** at the bottom. Next, enter the following details:



The screenshot shows a 'Settings' dialog box with a dark theme. The 'Package' tab is selected. It contains three sections: 'Build', 'Sign', and 'Launch'. The 'Build' section has five fields: 'SDK Path', 'Project Root', 'Archive Name', 'Output Folder', and a checkbox for 'Enable Remote Web Inspector'. The 'Sign' section has two fields: 'Signing Password' and 'Bundle Number'. The 'Launch' section has three fields: 'Target' (with a dropdown menu showing 'Simulator'), 'Device IP', and 'Device Password'.

Section	Field	Type
Build	SDK Path	Text Input
	Project Root	Text Input
	Archive Name	Text Input
	Output Folder	Text Input
	Enable Remote Web Inspector	Checkbox
Sign	Signing Password	Text Input
	Bundle Number	Text Input
Launch	Target	Dropdown (Simulator)
	Device IP	Text Input
	Device Password	Text Input

- **SDK Path:** Path where BlackBerry WebWorks SDK is installed
- **Project root:** The root folder of your project. To find the root folder, right-click the native folder in your Eclipse blackberry environment and select **Properties**.
- **Archive Name:** The name for your archive.
- **Output Folder:** The folder where to output the application. Specify a folder outside your project.
- **Password:** Sign you app with a BlackBerry 10 developer certificate to run it on a BlackBerry 10 handset. Specify your certificate password here. Signing is NOT required to run the application in the BlackBerry 10 Simulator.
- **Launch:** The Device IP address can be found by using either the BlackBerry Desktop Manager, or in the device settings.

After the package settings are defined, open the Ripple menu in Chrome and click on **start services**. Then select one of the Packaging options.