

# Logging in MobileFirst hybrid applications (JavaScript)

fork and edit tutorial (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/#fork-destination-box>) | report issue (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/issues/new>)

## Logging example for hybrid applications (JavaScript)

### Outputs to a browser JavaScript console, LogCat, or Xcode console

```
var MathUtils = function(){
  var logger = WL.Logger.create({pkg: 'MathUtils'});
  var sum = function(a, b){
    var sum = a + b;
    logger.debug('sum called with args ' + a + ' and ' + b + '. Returning ' + sum)
  };
  return sum;
}();
```

## API calls for specific tasks

**Log capture is enabled by default. To turn log capture on or off:**

```
WL.Logger.config({capture: false})
```

**The default capture level is DEBUG in development and FATAL in production. To control the capture level (verbosity):**

```
WL.Logger.config({level: 'FATAL'})
```

**Log sending is enabled by default. To turn automatic log sending on or off:**

```
WL.Logger.config({autoSendLogs: false})
```

For more information about the WL.Logger API

([http://engtest01w.francelab.fr.ibm.com:9090/support/knowledgecenter/SSHS8R\\_7.0.0/com.ibm.worklight.apiref.doc/html/refjavascript-client/html/WL.Logger.html](http://engtest01w.francelab.fr.ibm.com:9090/support/knowledgecenter/SSHS8R_7.0.0/com.ibm.worklight.apiref.doc/html/refjavascript-client/html/WL.Logger.html)), see the Reference part of the user documentation.