

# Resource request from Cordova applications

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/using-the-mfpf-sdk/resource-request-from-cordova-applications/index.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

## Overview

MobileFirst applications can access resources using the `WLResourceRequest` REST API. The REST API works with all adapters and external resources.

### Prerequisites:

- Ensure you have added the MobileFirst Platform SDK (`../../adding-the-mfpf-sdk/cordova`) to your Cordova application.
- Learn how to create adapters (`../../adapters/adapters-overview/`).

## WLResourceRequest

The `WLResourceRequest` class handles resource requests to adapters or external resources.

Create a `WLResourceRequest` object and specify the path to the resource and the HTTP method. Available methods are: `WLHttpMethodGet`, `WLHttpMethodPost`, `WLHttpMethodPut` and `WLHttpMethodDelete`.

```
var resourceRequest = new WLResourceRequest(
    "/adapters/JavaAdapter/users",
    WLResourceRequest.GET
);
```

- For **JavaScript adapters**, use `/adapters/{AdapterName}/{procedureName}`
- For **Java adapters**, use `/adapters/{AdapterName}/{path}`. The `path` depends on how you defined your `@Path` annotations in your Java code. This would also include any `@PathParam` you used.
- To access resources outside of the project, use the full URL as per the requirements of the external server.
- **timeout**: Optional, request timeout in milliseconds

## Sending the request

Request the resource by using the `send()` method.

The `send()` method takes an optional parameter to set a body to the HTTP request, which could be a JSON object or a simple string.

```
resourceRequest.send().then(
    onSuccess,
    onFailure
)
```

Using JavaScript **promises**, you can define `onSuccess` and `onFailure` functions.

## setQueryParameter

By using the `setQueryParameter` method, you can include query (URL) parameters in the REST request.

- In JavaScript adapters, which use ordered nameless parameters, pass an array of parameters with the name `params`:

```
resourceRequest.setQueryParameter("params", "[param1', 'param2']");
```

- In Java adapters or external resources, use `setQueryParameter` for each parameter:

```
resourceRequest.setQueryParameter("param1", "value1");  
resourceRequest.setQueryParameter("param2", "value2");
```

## setHeader

By using the `setHeader` method, you can set a new HTTP header or replace an existing header with the same name in the REST request.

```
resourceRequest.setHeader("Header-Name", "value");
```

## sendFormParameters(json)

To send URL-encoded form parameters, use the `sendFormParameters(json)` method instead. This method converts the JSON to a URL encoded string, sets the `content-type` to `application/x-www-form-urlencoded`, and sets it as the HTTP body.

For more information about `WLResourceRequest`, see the API reference in the user documentation.

## The response

Both the `onSuccess` and `onFailure` callbacks receive a `response` object. The `response` object contains the response data and you can use its properties to retrieve the required information. Commonly used properties are `responseText`, `responseJSON` (JSON object, if the response is in JSON) and `status` (the HTTP status of the response).

In case of request failure, the `response` object also contains a `errorMsg` property.

Depending if using a Java or JavaScript adapter, the response may contain other properties such as `responseHeaders`, `responseTime`, `statusCode`, `statusReason`, and `totalTime`.

```

{
  "responseHeaders": {
    "Content-Type": "application/json",
    "X-Powered-By": "Servlet/3.1",
    "Content-Length": "86",
    "Date": "Mon, 15 Feb 2016 21:12:08 GMT"
  },
  "status": 200,
  "responseText": "{\"height\":\"184\",\"last\":\"Doe\",\"Date\":\"1984-12-12\",\"age\":31,\"middle\":\"C\",\"first\"
:\nJohn\n\"}",
  "responseJSON": {
    "height": "184",
    "last": "Doe",
    "Date": "1984-12-12",
    "age": 31,
    "middle": "C",
    "first": "John"
  },
  "invocationContext": null
}

```

## Handling the response

The response object is received by the `onSuccess` and `onFailure` callback functions. For example:

```

onSuccess: function(response) {
  resultText = "Successfully called the resource: " + response.responseText;
},

onFailure: function(response) {
  resultText = "Failed to call the resource:" + response.errorMsg;
}

```

## For more information

For more information about `WLResourceRequest`, refer to the user documentation.

## Sample application

The ResourceRequestCordova project contains a Cordova application that makes a resource request using a Java adapter.

The adapter Maven project contains the Java adapter to be used during the resource request call.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/ResourceRequestCordova/tree/release80>) the Cordova project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/Adapters/tree/release80>) the adapter Maven project.

## Sample usage

1. From the command line, navigate to the project's root folder.
2. Ensure the sample is registered in the MobileFirst Server by running the command:  
`mfpdev app register`.
3. Add a platform by running the `cordova platform add` command.
4. The sample uses the `JavaAdapter` contained in the Adapters Maven project. Use either Maven or MobileFirst Developer CLI to build and deploy the adapter (`../../adapters/creating-adapters/`).
5. To test or debug an adapter, see the testing and debugging adapters (`../../adapters/testing-and-debugging-adapters`) tutorial.
6. Run the Cordova application by running the `cordova run` command.

