

Invoking adapter procedures from hybrid client applications

Overview

MobileFirst applications can adapt procedures to communicate with any data source without being subjected to same-origin constraints.

Basic API

Adapter procedures can be called from the client-side JavaScript:

```
1 WL.Client.invokeProcedure(invocationData, options);
```

invocationData

The first step to invoke an adapter procedure in JavaScript is to create an `invocationData` object. The `invocationData` object is used to provide invocation configuration and procedure parameters. It consists of a JSON block of properties.

```
1 var invocationData = {  
2   adapter : 'RSSReader',  
3   procedure : 'getFeedsFiltered',  
4   parameters : []  
5 };
```

The properties are:

- **adapter** (mandatory): A string that contains the name of the adapter as specified in the adapter XML file.
- **procedure** (mandatory): The procedure name as defined in the XML file.
- **parameters** (mandatory): An array of parameters that are passed to the back-end JavaScript™ procedure. Leave this property empty if no parameters are required.

Options

The second step is to define failure and success behaviors in the `options` object.

```
1 var options = {  
2   onSuccess : loadFeedsSuccess,  
3   onFailure : loadFeedsFailure,  
4   invocationContext: {}  
5 };
```

The `options` object must be passed for all asynchronous calls to MobileFirst Server.

onSuccess

The `onSuccess` function is to be invoked on successful completion of the asynchronous call.

The response typically contains the following properties:

- **invocationContext**: The `invocationContext` object that was originally passed in the `options` object, or undefined if no `invocationContext` object was passed
- **status**: The HTTP response status
- **invocationResult**: An object that contains the data that is returned by the invoked procedure, and additional information about the procedure invocation.

onFailure

The `onFailure` function is to be invoked on failure.

It includes both server-side and client-side errors (such as server connection failure or timed out calls).

The response typically contains the following properties:

- **invocationContext**: The `invocationContext` object that was originally passed in the `options` object, or undefined if no `invocationContext` object was passed.
- **status**: The HTTP response status
- **invocationResult**: An object that contains the data that is returned by the invoked procedure, and additional information about the procedure invocation.

invocationContext

`invocationContext` is an optional parameter. It is an object that is returned to the success and failure handlers.

The `invocationContext` object is used to preserve the context of the calling asynchronous service upon return from the service.

Invocation Results

`invocationResult` is a JSON object that is returned. It contains the data and more information about the procedure invocation.

The object is returned to a corresponding success/failure handler.

```
1  {
2    "errors": [],
3    "info": [],
4    "warnings": [],
5    "isSuccessful": true,
6    "responseHeaders": {
7      "Cache-Control": "no-cache, must-revalidate, post-check=0, pre-check=0"
8    },
9    "responseTime": 491,
10   "statusCode": 200,
11   "statusReason": "OK",
12   "totalTime": 592,
13   "Items": [{
14     "creator": "Jon Fingas",
15     "link": "http://www.engadget.com/2014/11/10/harvard-used-cameras-to-check-attendance/?ncid=rss_truncated",
16     "pubDate": "Mon, 10 Nov 2014 02:21:00 -0500",
17     "title": "Harvard used cameras to track attendance without telling students"
18   }, {
19     "creator": "Jon Fingas",
20     "link": "http://www.engadget.com/2014/11/10/bmw-ev-charging-street-lights/?ncid=rss_truncated",
21     "pubDate": "Mon, 10 Nov 2014 00:10:00 -0500",
22     "title": "BMW's new street lights will charge your electric car"
23   }, {
24     "creator": "Daniel Cooper",
25     "link": "http://www.engadget.com/2014/11/09/hwyc-lumia-925/?ncid=rss_truncated",
26     "pubDate": "Sun, 09 Nov 2014 22:43:00 -0500",
27     "title": "How would you change Nokia's Lumia 925?"
28   }]
29 }
```

`errors`, `info`, and `warnings` are optional arrays of strings that contain messages.

The `isSuccessful` property is set to `true` if the procedure invocation succeeded (even if no data was retrieved), to `false` otherwise.

The response can contain other metadata such as `responseHeaders`, `responseTime`, `statusCode`, `statusReason`, and `totalTime`.

The rest of the invocation result depends on what was retrieved from the back-end system. In this example, the `Items` element is a JSON representation of the XML code that was received from the back-end, after applying the rules in the XSL file.

```
1 function loadFeedsSuccess(result){
2     WL.Logger.debug("Feed retrieve success");
3     if (result.invocationResult.Items.length>0)
4         displayFeeds(result.invocationResult.Items);
5 }
```

Sample application

Click to download

(<http://public.dhe.ibm.com/software/products/en/MobileFirstPlatform/docs/v630/InvokingAdapterProceduresHybridProject.zip>)
the Studio project.

The attached sample uses the HTTP adapter created in the HTTP Adapter tutorial ([../http-adapter-communicating-http-back-end-systems/](#)).

