

Accelerating application development by reusing resources

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/7.0/advanced-topics/accelerating-application-development-reusing-resources.html>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

Overview

- Configuring application components and project template preferences
- Application components
 - Creating application components
 - Adding application components
 - Removing application components
- MobileFirst project templates
 - Creating MobileFirst project templates
 - Adding MobileFirst project templates

Configuring application components and project template preferences

To add application components or MobileFirst project templates, you must identify a download folder.

The download folder must contain only the application components or the MobileFirst project template archives.

Set the download folder in **Preferences > MobileFirst > Templates and Components > Download Folder**.



Application components

An application component is a reusable library that developers can add to their applications. It can be a client-side library or a server runtime block.

Application components must be downloaded in the **Download folder** that is specified in the **Window > Preferences > MobileFirst** menu.

Application components support only MobileFirst hybrid projects.

Creating application components

To create application components, you make sure that a MobileFirst hybrid project exists and you select the resources that you want to include.

Note: Only *hybrid* projects can be used to create application components.

The created application component is in archive format.

1. Right-click the MobileFirst hybrid project and select **Create Application Component**.



A wizard guides you through the process of creating the application component. For more information about this wizard, see the user documentation.

2. In the first page of the wizard, enter metadata information for the application component.

The screenshot shows the first step of the 'Create Application Component' wizard. The title bar reads 'Create Application Component'. The main heading is 'Create Application Component' with the instruction 'Provide the application component metadata information.' Below this, there are several input fields: 'ID' with the value 'MyComponent-9a83-4694-aa9b-f822d11054f2', 'Name' with 'My Component', 'Author' with 'IBM', 'Version' with '1.0.0', and a 'Description' text area containing 'This is a sample application component.' There is an 'Image' field with a placeholder icon and a 'Browse ...' button. At the bottom, an 'Application' dropdown menu is set to 'HelloApp'. The bottom of the window features a help icon, '< Back' button, 'Next >' button, 'Cancel' button, and 'Finish' button.

3. In the next page of the wizard, select the files that you want to include in the application component archive.

The screenshot shows the second step of the 'Create Application Component' wizard. The title bar reads 'Create Application Component'. The main heading is 'Create Application Component' with the instruction 'Provide the application component files and destination.' Below this, there is a section 'Select the files to archive:' with two panes. The left pane shows a file tree with 'HelloWorld' expanded, containing 'adapters', 'apps', 'HelloApp' (expanded), 'common', 'legal', 'externalServerLibraries', 'server', and 'services'. The right pane shows 'index.html' selected with a checkmark. Below the panes, the 'Component archive:' field is set to '/Users/user1/Documents/MyComponent.wlc' with a 'Browse ...' button. The bottom of the window features a help icon, '< Back' button, 'Next >' button, 'Cancel' button, and 'Finish' button.

After the application component archive is created, if you want to add more optional hooks to enable automation when the application component is used, refer to the topic about adding hooks to an application component, in the user documentation.

Adding application components

You can add application components only to MobileFirst hybrid applications.

1. Before adding any application component, open an existing hybrid project or create one.
Basic information about the application components is displayed.
The application components are loaded from the configured **Download folder**.
2. Right-click the MobileFirst hybrid project and select **Add/Remove Application Components**.



The application components are scanned in the Download folder.

Only valid application components are displayed in the Add and Remove Application Components wizard.

Each component is displayed along with the Thumbnail, Name, Author and Version, next to a checkbox.

The application components that you select are installed in the target MobileFirst project.



The addition status of the application component is displayed after the activity is completed.
The component resources are marked with the unique ID of the application component.



3. Ensure that the required MobileFirst environments are created before you add the application component, otherwise error messages are displayed.

If the required Android SDK is not installed on the hosting MobileFirst Studio, the appropriate message is displayed.

If the contents of the application components or the MobileFirst applications are renamed, the linkage with the application component is broken.

The application component files are read-only and you cannot modify them.



Removing application components


1. Right-click a MobileFirst hybrid project and select **Add/Remove Application Component**.
2. Select the application that you want to remove.
Marks in the **In Use** column indicate the installed application components for this particular MobileFirst hybrid project.
3. Clear the marks next to the application components that you want to remove.



When you remove application components, you are prompted to confirm whether to roll back the resource to its original content. For example, if you remove a `UserPermission` element, you are prompted to confirm the removal.

The removal status of the application component is displayed after the removal activity is done.

On successful removal of the application components, the original contents of the MobileFirst hybrid project resources are restored.



MobileFirst project templates

By using MobileFirst project templates, you can develop applications faster by not having to start from scratch.

You can use MobileFirst project templates to provide value-added services; you can add elements that are consistent with the look-and-feel of your brand.


MobileFirst project templates are of hybrid type only.

MobileFirst project templates that are created from a more recent version of IBM MobileFirst Platform Foundation are not supported in previous versions.

Creating MobileFirst project templates

You can export MobileFirst hybrid projects as templates for reusability.

1. Right-click a MobileFirst project and click **Export > IBM MobileFirst > MobileFirst Project Template**.



2. On the Export page, enter basic information for the MobileFirst project template, such as **Template name**, **Author**, **Description**, **Thumbnail**, and **Template archive**.

Valid extensions for Template archives are `.zip` and `.wlt`.

All the fields are mandatory in this wizard.

The Template archive is created at the selected location.

The structure of the Template archive is described in the documentation.



The screenshot shows a macOS-style dialog box titled "Export" with a subtitle "IBM MobileFirst Platform Project Template Export". Below the subtitle is the instruction "Export the MobileFirst project resources to a template to share." The dialog contains several input fields: "Template name:" with the value "Hello World Template", "Author:" with the value "IBM", and "Description:" with the value "This is a sample template". There is a "Thumbnail:" section with a small icon and a "Browse ..." button. The "Template archive:" section shows a dropdown menu with the selected path "/Users/user1/IBM/templates/Hello World Template.zip" and another "Browse ..." button. At the bottom, there is a help icon, and four buttons: "< Back", "Next >", "Cancel", and "Finish".

Adding MobileFirst project templates

Use the **Shared Templates** option to create a MobileFirst project from a template.

1. Click the **Create a MobileFirst Artifact** icon on the toolbar. For more information, see the user documentation.
2. In the **Name** field, provide a name for the MobileFirst project.
3. From the **Project Templates** list, click **Shared Templates**.
4. Click **Next**.



The MobileFirst project templates are loaded from the configured Download folder (as explained in Configuring application components and project template preferences).

5. Provide an application name.
6. Select a MobileFirst project template.

A MobileFirst hybrid project is created with the contents of the MobileFirst project template archive.





7. To view the FIXME tags, if any, click **Project > Properties > General > Editors > Structured Text Editors > Task Tags**.

1. Click **Enable searching for Task Tags**.
2. Click **Apply > OK**.
3. A **Task** tab is visible with the Tasks to be done.

Problems Console Servers Tasks

2 items

	Description	Resource	Path	Location	Type
	FIXME: Update the template configuration	main.js	/ProjectFromTempl...	line 16	JavaScript Task
	FIXME: Update index.html content	index.html	/ProjectFromTempl...	line 21	HTML Task