

Using Analytics REST API

Overview

MobileFirst Foundation Operational Analytics provides REST APIs to help developers with importing (POST) and exporting (GET) analytics data.

Jump to:

- [Analytics REST API](#)
- [Try It Out on Swagger Docs](#)

Analytics REST API

To use the analytics REST API:

Base URL

`/analytics-service/rest`

Example

`https://example.com:9080/analytics-service/v3/applogs`

REST API Method	Endpoint	Description
Application Logs (POST)	<code>/v3/applogs</code>	Creates a new application log.
Application Session (POST)	<code>/v3/appsession</code>	Creates an application session or updates an existing one when reporting with the same appSessionID.
Bulk (POST)	<code>/v3/bulk</code>	Reports events in bulk.
Custom Chart (GET)	<code>/v3/customchart</code>	Exports all custom chart definitions.
Custom Chart (POST)	<code>/v3/customchart/import</code>	Imports a list of custom charts.
Custom Data (POST)	<code>/v3/customdata</code>	Creates new custom data.
Device (POST)	<code>/v3/device</code>	Creates or updates a device.
Export Data (GET)	<code>/v3/export</code>	Exports data to the specified data format.
Network Transaction (POST)	<code>/v3/networktransaction</code>	Creates a new network transaction.
Server Log (POST)	<code>/v3/serverlog</code>	Creates a new server log.
User (POST)	<code>/v3/user</code>	Creates a new user.

Try it out on Swagger docs

Try out the analytics REST API on Swagger Docs.

In a MobileFirst Server configuration with Analytics enabled, visit: `<ipaddress>:<port>/analytics-service`.

**WARNING:**

Do not use a production datastore name for "x-mfp-analytics-api-key", as it could interfere with production data.

Application Session	Show/Hide	List Operations	Expand Operations
Bulk	Show/Hide	List Operations	Expand Operations
Client Logs	Show/Hide	List Operations	Expand Operations
Custom Chart	Show/Hide	List Operations	Expand Operations
Custom Data	Show/Hide	List Operations	Expand Operations
Device	Show/Hide	List Operations	Expand Operations
Export Data	Show/Hide	List Operations	Expand Operations
Network Transaction	Show/Hide	List Operations	Expand Operations
Server Log	Show/Hide	List Operations	Expand Operations
User	Show/Hide	List Operations	Expand Operations

[BASE URL: /analytics-service/rest]

By clicking on **Expand Operations**, you can see the implementation notes, parameters, and response messages for each method.

Warning: Any data that you send by using **Try it out!** might interfere with data already in the data store. If you are not specifically trying to send data to your production environment, use a test name for the `x-mfp-analytics-api-key`.

Client Logs

Show/HideList OperationsExpand Operations

POST/v3/clientlogsCreates a new Client Log

Implementation Notes

An Client Log is any debug log from the user's application

Parameters

Parameter	Value	Description	Parameter Type	Data Type
body	(required)	body	Model	Example Value
<div>Parameter content type: application/json</div>		<pre>{ "logs": [{ "timestamp": "2016-07-18T05:24:03.358Z", "timezone": "60", "file": "Main.swift", "level": "ERROR", "line": "234", "message": "Something normal happened.", "sourceClass": "string", "method": "takePicture", "locationName": "string" }] }</pre>		
x-mfp-analytics-api-key	TestIndex	Index name of the datastore.	header	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
202	Client Log created		
400	Invalid Client Log supplied	Model	Example Value

Last modified on