Logging in MobileFirst hybrid applications (JavaScript)

Logging example for hybrid applications (JavaScript)

Outputs to a browser JavaScript console, LogCat, or Xcode console

```
var MathUtils = function() {
   var logger = WL.Logger.create({pkg: 'MathUtils'});
   var sum = function(a, b) {
      var sum = a + b;
      logger.debug('sum called with args ' + a + ' and ' + b + '. Returning ' + sum)
;
   return sum;
};
}();
```

API calls for specific tasks

Log capture is enabled by default. To turn log capture on or off:

```
WL.Logger.config({capture: false})
```

The default capture level is DEBUG in development and FATAL in production. To control the capture level (verbosity):

```
WL.Logger.config({level: 'FATAL'})
```

Log sending is enabled by default. To turn automatic log sending on or off:

```
WL.Logger.config({autoSendLogs: false})
```

For more information about WL.Logger API, see the API reference in the user documentation

Last modified on

IBM	Social	Site
Legal notices	Facebook	RSS feed
(file:////home/travis/build/MFPSamples/DevCenter/(https://egodw.facebook.com/ibmmolail/effest/platfore/flyravis/build/MFPSamples/DevCe		
notices/)	Twitter	Open issue
Privacy	(https://twitter.com/ibmmobiledev)	(https://github.com/MobileFirst-
(http://www.ibm.com/privacy/us/en/)	YouTube	Platform-Developer-
Terms of use	(https://www.youtube.com/channel.UCenter/DevCenter/issues/new)	
(file:////home/travis/build/MFPSamples/DevCente	er <u>C</u> īgi te⁄ijteatKis nci2Qusu97Q)	Contribute
of-use/)	GitHub	(https://github.com/MobileFirst-
Third party notice	(https://github.com/MobileFirst-	Platform-Developer-
(file:////home/travis/build/MFPSamples/DevCente	er .P.lsitfe/thir© eveloper-	Center/DevCenter/blob/master/contributing.m
party-notice/)	Center)	Report abuse
		(https://www.ibm.com/developerworks/commi